

Proposed Residential Development at Lot No. 4822 in D.D.104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

Environmental Noise Impact Assessment

Prepared for: Glory Queen Limited

Prepared by: Westwood Hong & Associates Limited

Report No.: **22610-N2**

Date: **16 July 2025**


Ir K. K. Iu FHKIOA, MIOA, MCIBSE, MHKIE, MASA, APEC Engineer

FMOIA, MIEAust, MHKIQEP, C Eng, RPE, CPEng

Ms Kit Wong BEng, MHKIEIA

Mr Samuel Lee BSc

Westwood Hong & Associates Ltd





CONTENTS

AIN	MS	1
SUN	MMARY	1
1.	INTRODUCTION	2
2.	SITE LOCATION & BUILDING LAYOUT	2
SITE	E LOCATION	2
DEV	/ELOPMENT LAYOUT	2
3.	NOISE CRITERIA	4
	AD TRAFFIC NOISE CRITERION	
4.	SITE SURVEYS	6
DAT	TES	6
	TRUMENTATION	
FIXE	ED NOISE SOURCES IN THE VICINITY	6
5.	NOISE MITIGATION MEASURES	13
Acc	DUSTIC FIN	13
6.	ROAD TRAFFIC NOISE IMPACT ASSESSMENT	13
TRA	AFFIC FORECAST	13
	THODOLOGY OF ROAD TRAFFIC NOISE IMPACT ASSESSMENT	
PRE	DICTED ROAD TRAFFIC NOISE LEVELS (BASE SCENARIO)	14
7.	NOISE IMPACT ASSESSMENT FOR FIXED NOISE SOURCES	15
Nois	SE ASSESSMENT POINTS FOR FIXED NOISE SOURCES ASSESSMENT	15
Мет	THODOLOGY OF NOISE IMPACT ASSESSMENT FROM FIXED NOISE SOURCES	15
	L OF IDENTIFIED FIXED NOISE SOURCES	
PRE	DICTED NOISE LEVELS FROM FIXED NOISE SOURCES (BASE SCENARIO)	18
8.	POTENTIAL NOISE IMPACT FROM FIXED NOISE SOURCES IN THE PROP	
DEV	VELOPMENT	19
PLA	NNED FIXED NOISE SOURCES WITHIN THE PROPOSED DEVELOPMENT	19
CUM	MULATIVE NOISE IMPACT DUE TO ALL FIXED NOISE SOURCES	19
9.	NOISE IMPACTS FOR THE KINDERGARTEN	20
Roa	AD TRAFFIC NOISE IMPACT FOR KINDERGARTEN	20
FIXE	ED NOISE IMPACT FOR KINDERGARTEN	20
10.	CONCLUSION	21
11	DEFEDENCES	22

FIGURES

Figure 1: Site Location

Figure 2: Measurement Location

Figure 3: Identified Fixed Noise Sources

Figure 4: Computer Plot of Road Scheme (with Year 2046 traffic forecast)

Figure 5: Noise Mitigation Measures for Fixed Noise Sources

APPENDICES

Appendix 1: Architectural Drawings

Appendix 2: Year 2046 Traffic Forecast (MVA Asia Ltd.)

Appendix 3: Predicted Façade Noise Levels for Road Traffic Noise

Appendix 4: Measurement Results and SWL Calculations

Appendix 5: Fixed Noise Sources Assessment for The Proposed Development

Appendix 6: Cumulative Fixed Noise Sources Calculation
Appendix 7: Predicted Noise Levels for Kindergarten

AIMS

To assess noise impacts on the proposed residential development at Lot no. 4822 in D.D.104 and adjoining Government Land, Kam Pok Road, Mai Po, Yuen Long.

The project site is designated for residential use under a "R(D)" zoning. It was previously approved by Town Planning Board (TPB) for house development under a planning application (Application No. A/YL-MP/287). A NIA report was previously submitted to TPB and has been partially discharged the relevant planning condition under that planning application. The NIA report has identified and addressed the potential noise impacts on the project site.

This rezoning application aims to increase the domestic plot ratio to 1.5 with 1,303 flat units. The proposed Development comprises of 5 residential blocks with 16 residential storeys, and one 2-storey facility compound for clubhouse, kindergarten and Neighbourhood Elderly Centre (NEC) uses.

This NIA reveals any noise impacts and recommend appropriate noise mitigation measures for the proposed Development, whenever appropriate; and also to avoid noise impact by adjusting building layout. The adopted noise mitigation measures are as per the Hong Kong Planning Standards & Guidelines (HKPSG).

SUMMARY

All the residential flats (i.e. 100%) are designed within the 70dB(A) noise criterion, adverse road traffic noise impacts are not anticipated.

Fixed noise sources assessment were conducted based on the site survey of the industrial sites in the vicinity. With the provision of acoustic fins, the proposed scheme will comply with the noise limit set out in the HKPSG.

After considering the cumulative noise impact (the proposed plant rooms and clubhouse) in the proposed Development, all representative NSRs will comply with the stipulated noise criteria.

Noise assessments for the kindergarten were conducted and no adverse road traffic noise and fixed noise impacts are anticipated.

1. INTRODUCTION

- 1.1 Westwood Hong & Associates Ltd (WHA) has been commissioned to conduct a Noise Impact Assessment (NIA) for the proposed Development. Figure 1 shows the location of the proposed Development.
- 1.2 This environmental noise impact assessment report supports the Rezoning Application for the proposed Development.
- 1.3 This report is prepared based on MLP in Appendix 1 and Year 2046 Traffic Forecast in Appendix 2.
- 1.4 This report comprises the following assessments:-
 - Road traffic noise affecting the proposed Development
 - Fixed noise sources affecting the proposed Development
 - Noise impact from fixed noise sources of the proposed Development

2. SITE LOCATION & BUILDING LAYOUT

Site Location

- 2.1 The project site is bounded by Fung Chuk Road to the north and Ha Chuk Yuen Road to the east, Kam Pok Road to the west and Ha San Wai Road to the south (Figure 1).
- 2.2 The residential developments in the vicinity of the project site are Fairview Park, Villa Camellia, Helene Terrace and 3-storey village dwellings in Ha San Wai and the Yau Pok Road Light Public Housing (Figure 1).

Development Layout

- 2.3 The proposed Development comprises a total of 5 residential blocks with 16 residential storeys, a 2-storey facility compound for clubhouse, kindergarten and NEC uses. The building layouts are shown in Appendix 1. The development parameters are summarised in Table 2.1 below.
- 2.4 The clubhouse and NEC would be equipped with central air-conditioning and would not rely on opened windows for ventilation. The proposed Development will not give rise to an adverse noise impact on existing or planned NSRs.

 Table 2.1
 Development Parameters of the Proposed Development

•	Parameters	
Zoning	"Residential (Group D)" zone on Approved Mai Po & Fairview Park Outline Zoning Plan No. S/YL-MP/8	
Site Area	Private land: 37,702m ² Government land: 168 m ²	
Number of Residential Units	1,303	
Number of Residential Storeys	16 residential storeys	
Height of Building	59.85mPD	
Use	 5 residential blocks 6-classroom kindergarten, a Neighbourhood Elderly Centre (NEC) and a clubhouse 	
Completion Year	2031	
Name of Applicant	Glory Queen Limited	

3. NOISE CRITERIA

Road Traffic Noise Criterion

- 3.1 According to the HKPSG^[1], road traffic noise criterion for domestic premises is 70dB(A) L10(1 hour) at the external facades for the hour having the peak traffic flow. The noise criterion applied to the domestic premises which rely on opened windows for ventilation.
- 3.2 For the education institutions including kindergartens, road traffic noise criterion is 65dB(A) L10(1 hour) at the external facades for the hour having the peak traffic flow. The noise criterion applied to the kindergarten which rely on opened windows for ventilation.

Noise Criteria for Fixed Noise Sources

3.3 The proposed Development is located within a low density residential area, not being affected by any Influencing Factor (IF). With reference to the "Technical Memorandum for the Assessment of Noise from Places other than Domestic Premises, Public Places or Construction Sites" (IND – DP)^[2], an Area Sensitivity Rating (ASR) of "A" was assumed for the proposed Development. The Acceptable Noise Levels (ANLs) are shown in Table 3.1.

Table 3.1 ANLs for Day, Evening and Night-Time Periods

	ANLs, ASR "A"
Time Period	Leq (30 mins)
Day (0700 to 1900 hours) and evening (1900 to 2300 hours)	60dB(A)
Night (2300 to 0700 hours)	50dB(A)

Note: In any event, the ASR and the ANLs adopted in this report are only indicative and they are used for assessment only. It should be noted that the noise from fixed noise sources is controlled under section 13 of the Noise Control Ordinance. Therefore, the ASRs and ANLs determined in this report shall not prejudice the Noise Control Authority's discretion to determine noise impact due to fixed noise sources on the basis of prevailing legislation and practices being in force, and taking account of contemporary conditions/ situations of adjoining land uses. The assessment of noise impacts due to fixed noise sources in this report shall not bind the Noise Control Authority in the context of law enforcement against any of the noise from fixed noise sources being assessed.

3.4 The noise criteria for the design of noise sensitive developments near fixed noise sources shall refer to the IND – TM. Therefore, the assessment criteria for existing fixed noise sources in the vicinity of the proposed Development should refer to the ANLs in Table 3.1

- 3.5 The HKPSG also states that in order to plan for a better environment, all planned fixed noise sources should be so located and designed that when assessed in accordance with the TM, the level of the intruding noise at the façade of the nearest sensitive use should be at least 5dB(A) below the appropriate ANL shown in Table 2 of the IND TM or, in the case of the background being 5dB(A) lower than the ANL, should not be higher than the background.
- 3.6 Site measurements were made at the eastern site boundary on 30 April 2025, the prevailing background noise levels are summarised in Table 3.2 below. The measurement locations are provided in Figure 2.

Table 3.2 Prevailing Background Noise Measurement Details and Results

1 10 10 10 2 2 10 10 10 10 10 10 10 10 10 10 10 10 10						
Noise Sensitive Receiver	Date	Personnel	Weather	Field Observations	Measurement Results, dB(A), L90 (1 hour)	
Loc 1, Eastern site boundary	30 April 2025	Mr. Samuel Lee	Sunny, calm	Mainly community noise	Daytime: 56 Night-time: 52 (Façade)	

3.7 The prevailing background noise levels of the identified noise sensitive receivers were higher than ANL – 5dB(A). Therefore, the ANL – 5dB(A) are used as the criteria for noise from planned fixed sources (i.e. 55dB(A) for daytime, and 45dB(A) for night-time).

4. SITE SURVEYS

Dates

4.1 Site surveys were conducted on 30 April 2025, 4 September 2024, 8 March 2023, 1 June, 18 & 26 May, 4 April and 31 March 2022, 15 December & 12 August 2021, 13 August, 26 July & 22 May 2019, 13 November & 14 September 2018, 23 June 2017, 31 August 2016, 4 July 2014, 12 September 2013, 10 February 2012 and 6 January 2010.

Instrumentation

4.2 The instruments used by WHA for the surveys comply with International Electrotechnical Commission Publications 651:1979 (Type 1) and 804:1985 (Type 1). They are listed in Table 4.1 below.

Table 4.1 Instruments Used for the Noise Surveys

Tubic iii	differences esca for the rouse surveys
Manufacturer	Туре
0 0 11:	Precision Integrating Sound Level Meter
Ono Sokki	(LA-5111 (Serial No.: 04100820))
Ono Sokki	Foam Windshield
D 1 177	Noise Calibrator Type 4231
Bruel and Kjaer	(Serial No.: 2699245)

- 4.3 The sound level meter was calibrated before use and further checks on completion of the survey, and confirmed that the calibration levels from before and after the noise measurement agree to within 1.0dB.
- 4.4 The site measurements including measurement equipment, calibration procedure, measurement methodology and weather conditions were conducted in accordance with the IND TM.

Fixed Noise Sources in the Vicinity

4.5 The study area for the fixed noise sources impact assessment is 300m. The identified fixed noise sources are summarised in Tables 4.2 and 4.3 and illustrated in Figure 3. Detailed discussion on the fixed noise source impact is given in Section 7. The operation of the industrial sites in the approved NIA report and the current observations are provided in Table 4.2. The photos of the identified fixed noise sources are provided in Appendix 4.

Table 4.2 Updated Observations for the Identified Fixed Noise Sources in Approved NIA Report

Source ID	Factory	Operation (in approved NIA report during S16)	Operation (in approved NIA report of discharge approval condition)	Current Observation
A-1		Operating noise of the warehouse	No change	No operation in the warehouse
A-2	Fan	Loading and unloading using forklift	No operation of forklift was observed	No operation of forklift was observed
A-3	Keung Kee	Movement of Lorry	No change	No operation of lorry was observed
A-4		Lifting of precast units using a lorry with crane	No operation of the lorry with crane was observed	No operation of the lorry with crane was observed
B-1	Shing Fat	Loading and unloading using forklift	No operation of the godown	The godown no longer exists
B-2	Logistics ("the godown")	Movement of lorry	No operation of the godown	The godown no longer exists
С	Chuk Yuen Floodwater Pumping Station	Operating noise	No change	No change

Table 4.3 Identified Existing Fixed Noise Sources

Labit	Table 4.5 Identified Existing Fixed Noise Sources				
ID	Site	Identified Industrial Activities [1]	Location of Fixed Noise Sources	Operating Hours [2]	
A	Fan Keung Kee	It is a storage yard of precast units. The industrial activities are loading / unloading of the precast units by using a lorry with crane, forklift and lorry. An operating noise (put down hand tools, fixing noise) was also observed inside the sheltered warehouse. The noise measurements were conducted at 5 – 10m distances from the noise sources, detailed noise measurement results are provided in Appendix 4. There was no industrial noise observed during the recent site survey.	on ground level	9:00am – 6:00pm.	
В	Shing Fat Logistics ("the godown")	It is a godown, with industrial activities of loading/unloading by a forklift and lorry. All the industrial activities were conducted inside the godown building. Many site surveys have been made, the operations of the godown were similar. However, the recent site survey revealed that the godown no longer exists. For conservative purpose, the previous noise measurements would be adopted in the assessment, with detailed measurement results provided in Appendix 4.	Inside the building, on ground level	8:30am – 5:30pm.	

ID	Site	Identified Industrial Activities [1]	Location of Fixed Noise Sources	Operating Hours [2]
C	Chuk Yuen Floodwater Pumping Station	This pumping station is a completed enclosed structure, which managed by Drainage Services Department (DSD). It is designed for the discharge of collected rainwater during an exceptionally heavy rainfall, i.e. it will only operate under extreme condition when there is a threat of flooding in the area under extreme storm event. No industrial noise was observed during all site surveys.	Inside the building, on ground level	24 hours
D	Construct-ion	It is the construction site of Yau Pok Road Light Public Housing. No industrial noise was observed during recent site survey.	on ground level	8:30am – 6:00pm.
E	Hung Fai	It is a temporary structure with office use. No industrial noise was observed during site surveys.	Inside the building, on ground level	9:00am – 6:00pm.
F	Open Storage	It is a storage yard of construction materials and parking use. No industrial noise was observed during site surveys.	on ground level	8:30am – 5:30pm.
G	Wai Kwong Luen Logistic Company	A warehouse is constructed with a temporary structure with steel cover, it is used for parking and office, no industrial noise was observed during site surveys.	Inside the building, on ground level	8:00am – 5:30pm.
Н	Kin Tak car repairing workshop	The workshop renamed as "Kin Tak" during recent survey, and no industrial noise was observed. For the previous workshop, the major daytime industrial activities are including fixing / replacement / disassembly / assembly of car components. The noise measurements were conducted by placing with measurement equipment (i.e. the sound level meter mounted on a stand at 1.2m height) directly towards the most noisy noise source (i.e. assembly of car components inside the building, by a pneumatic screwdriver, from a distance of 8m). The detailed noise measurements are provided in Appendix 4.	Inside the building, on ground level	9:00am – 6:00pm
J	Sun Chun Car Shop	The major daytime industrial activities are including fixing / replacement / disassembly / assembly of car components and car washing. The noise measurements were conducted by placing with measurement equipment (i.e. the sound level meter mounted on a stand at 1.2m height) directly towards the most noisy noise source (i.e. assembly of car components inside the building, by a pneumatic screwdriver, from a distance of 9m). The recent site survey revealed that the industrial activities were similar as the previous. The detailed noise measurements are provided in Appendix 4.	Inside the building, on ground level	9:00am – 6:00pm

ID	Site	Identified Industrial Activities [1]	Location of Fixed Noise Sources	Operating Hours [2]
K	Akina Auto Center	No industrial noise was observed during the recent site survey. According to the previous observation, the major daytime industrial activities are including fixing / replacement / disassembly / assembly of car components and car washing. The noise measurements were conducted by placing with measurement equipment (i.e. the sound level meter mounted on a stand at 1.2m height) directly towards the most noisy noise source (i.e. assembly of car components inside the building, by a pneumatic screwdriver, from a distance of 8m). The detailed noise measurements are provided in Appendix 4.	Inside the building, on ground level	9:00am – 6:00pm
L	Vacant	The previous retail shop no longer exists.	-	-
M	Vacant	The previous Chin Hung car repairing workshop no longer exist.	-	-
N	Sun Hing car repairing workshop	No industrial noise was observed during the recent site survey. According to the previous observation, the major daytime industrial activities are including fixing / replacement / disassembly / assembly of car components and car washing. The noise measurements were conducted by placing with measurement equipment (i.e. the sound level meter mounted on a stand at 1.2m height) directly towards the most noisy noise source (i.e. assembly of car components inside the building, by a pneumatic screwdriver, from a distance of 8m). The detailed noise measurements are provided in Appendix 4.	Inside the building, on ground level	9:00am – 6:00pm
P	Classic Motor Service Limited	It is for office use only, no industrial noise was observed during site surveys.	Inside the building, on ground level	9:00am – 6:00pm
Q	Lung Yee car repairing workshop	The major daytime industrial activities are including fixing / replacement / disassembly / assembly of car components and car washing. The noise measurements were conducted by placing with measurement equipment (i.e. the sound level meter mounted on a stand at 1.2m height) directly towards the most noisy noise source (i.e. assembly of car components inside the building, by a pneumatic screwdriver, from a distance of 5m). The recent site survey revealed that the industrial activities were similar as the previous. The detailed noise measurements are provided in Appendix 4.	Inside the building, on ground level	9:00am – 6:00pm

ID	Site	Identified Industrial Activities [1]	Location of Fixed Noise Sources	Operating Hours [2]
R	Hing Lee car repairing workshop	The major daytime industrial activities are including fixing / replacement / disassembly / assembly of car components and car washing. The noise measurements were conducted by placing with measurement equipment (i.e. the sound level meter mounted on a stand at 1.2m height) directly towards the most noisy noise source (i.e. assembly of car components inside the building, by a pneumatic screwdriver, from a distance of 5m). The recent site survey revealed that the industrial activities were similar as the previous. The detailed noise measurements are provided in Appendix 4.	Inside the building, on ground level	9:00am – 6:00pm
S	Wing Tai Tyre	No industrial noise was observed during the recent site survey. According to the previous observation, the major daytime industrial activities are including fixing tyre. The noise measurements were conducted by placing with measurement equipment (i.e. the sound level meter mounted on a stand at 1.2m height) directly towards the noise source (i.e. fixing tyre by a pneumatic screwdriver, from a distance of 5m). The detailed noise measurements are provided in Appendix 4.	Inside the building, on ground level	9:00am – 6:00pm
Т	Petrol Filling Station	No industrial noise was observed during site surveys.	On ground level	24 hours
U	Alicar Fairview Workshop	It is a self-car washing centre. No mechanical washing machine is provided. The centre provides a space with simply washing tools to the driver. Washing and waxing were observed during site surveys. Site surveys have revealed that the busiest time were $1600 - 1800$. Water pump noise was observed and noise of compressed air gun, vacuum cleaner and water jetting were also observed, which were the major industrial noise sources. The noise measurements were conducted by placing with measurement equipment (i.e. the sound level meter mounted on a stand at 1.2m height) directly towards these noise sources from a distance of 10m. The detailed noise measurements are provided in Appendix 4. The recent site survey revealed that the industrial activities were similar as the previous. Only half of the washing bays were occupied during the noise measurements. As a conservative approach, a correction of $+3dB(A)$ to the SWL will be considered in the fixed noise assessment in Section 7.	On ground level, with temporary structure	24 hours
V	Vacant	The previous Ka Fu car repairing workshop no longer exists.	-	-

ID	Site	Identified Industrial Activities [1]	Location of Fixed Noise Sources	Operating Hours [2]
W	Fugro warehouse	No industrial noise was observed during the recent site survey. According to the previous observation, it is a warehouse for storage use of the construction materials and equipment. Loading and unloading was observed during site surveys. The noise measurements were conducted at 1.2m height directly towards the noise sources (i.e. loading and unloading, from a distance of 3m). The detailed noise measurements are provided in Appendix 4.	Inside the building, on ground level	8:00am – 5:00pm
Y	Temporary structure with office use	It is a temporary structure with office use. A condenser was observed under the steel cover. The noise measurements were conducted at 1.2m height directly towards the noise sources (i.e. condenser, from a distance of 2m). The recent site survey revealed that the industrial activities were similar as the previous. The detailed noise measurements are provided in Appendix 4.	On ground level	8:30am – 5:00pm
Z	Open Storage	It is a storage yard of construction material and containers. No industrial noise was observed during site surveys.	On ground level	9:00am – 5:00pm
AA	Car repairing workshop	The workshop was closed during a few times of site survey, no industrial noise was observed. The recent site survey revealed that the workshop has been opened but without industrial noise.	On ground level	9:00am – 6:00pm
AB	Open yard for construct- ion materials	It is a storage yard of construction material (pipes, steel plates). A lorry with crane was observed, but no operation.	On ground level	9:00am – 6:00pm
AC	Top 1 Car Audio Workshop	Audio installation workshop, no industrial noise was observed during site survey.	On ground level	9:00am – 6:00pm
AD	EV-Pro HK	Car repairing workshop, but no industrial noise was observed during site survey.	On ground level	9:00am – 6:00pm
AE	KUAIFU	Office use only, no industrial noise was observed during site survey.	On ground level	9:00am – 6:00pm
AF	Xinyi Auto- mobile Glass Co. Ltd.	Office use only, no industrial noise was observed during site survey.	On ground level	9:00am – 6:00pm No night- time operation

Noted:

- The operation of the identified fixed noise sources were observed during site surveys and confirmed with the staffs.
- [2] The operating hours of the identified fixed noise sources were advised from the staffs of each site, and confirmed by night-time site survey.

4.6 According to the latest OZP, there is a proposed temporary Car Testing Centre located to the south of the proposed Development under the Planning Application A/YL-MP/308-2, a planned car trading use under the Planning Application A/YL-MP/334, and a temporary vehicle repair workshop with ancillary office and storage use under the Planning Application A/YL-MP/366. For conservatism, these proposed industrial uses will be considered in the fixed noise sources assessment, with details summarized in Table 4.4 below.

Table 4.4 Planned Fixed Noise Sources

			Location of	
Source ID	Site	Industrial Activity	Fixed Noise Sources	Operating Hours
ВВ	Car Testing Centre	The operation is assumed to be similar with car repairing workshop. The maximum allowable SWL is adopted in the fixed noise assessment in Section 7.	On ground level	According to the approval condition, the lot can not have operation between 5:30pm – 8:30am. No night-time operation is assumed.
CC	Car Trading Use	The operation is assumed to be similar with car repairing workshop. The maximum allowable SWL is adopted in the fixed noise assessment in Section 7.	On ground level	According to the approval condition, the lot can not have operation between 7:00pm – 9:00am. No night-time operation is assumed.
DD	Vehicle Repair Workshop with Ancillary Office and Storage use	The operation is assumed to be similar with car repairing workshop. The maximum allowable SWL is adopted in the fixed noise assessment in Section 7.	On ground level	According to the approval condition, the lot can not have operation between 6:00pm – 10:00am. No night-time operation is assumed.

4.7 Other than the identified fixed noise sources above, the results of the above site surveys have confirmed that there are no other major fixed noise sources in the vicinity of the project site. All the fixed noise sources within the assessment area are identified and considered in the assessment.

5. NOISE MITIGATION MEASURES

5.1 There are a number of fixed noise sources identified at the vicinity of the project site and potential fixed noise impact is envisaged. The following noise mitigation measures are incorporated in the design to alleviate the anticipated impact due to surrounding fixed noise sources.

Acoustic Fin

5.2 1.5m Acoustic Fins are proposed at T1 in order to minimize the line of sight from the flat units to the identified fixed noise sources. It is noted that the erection of vertical acoustic fins near NSRs would induce potential noise reflection effects, Sound Absorptive Material (SAM) is proposed at such surface and tip of the vertical acoustic fins. The location of acoustic fins are illustrated in Figure 5.

6. ROAD TRAFFIC NOISE IMPACT ASSESSMENT

6.1 The noise prediction was conducted by employing the WS Atkins RoadNoise 2000^[3] computer software.

Traffic Forecast

- 6.2 The anticipated occupation year of the proposed Development is 2031, the maximum traffic in 15 years after occupation of the proposed Development (i.e. 2031+15=2046) has been adopted for the purpose of the road traffic noise assessment.
- 6.3 The traffic forecast for Year 2046 was provided by the Traffic Consultant (MVA Asia Ltd.) as shown in Appendix 2. The definition of heavy vehicle in the U.K. Department of Transport's "Calculation of Road Traffic Noise" (CRTN)^[4] was adopted. Review of the data indicates that the AM peak is in general higher than the PM peak. Therefore, the set of AM peak traffic data is employed for the assessment, representing the worst-case scenario.

Noise Assessment Points for Road Traffic Noise Assessment

All noise sensitive rooms (e.g. living and dining rooms, bedrooms / master bedrooms) are assigned with a noise assessment point. The locations of assessment points are illustrated in Appendix 3. The clubhouse and NEC will be equipped with central air-conditioning and would not rely on opened windows for ventilation. No adverse noise impact is anticipated for these two uses.

6.5 The assessment points are taken at the height of 1.2m above each residential floor and 1m away from the façade of openable windows of the noise sensitive rooms.

Methodology of Road Traffic Noise Impact Assessment

- 6.6 The study area of the road traffic noise assessment would be 300m from the site boundary. The roads within the study area are included in the assessment. In this assessment, all roads are assumed to be of impervious surface.
- 6.7 The road traffic noise levels at the proposed Development were assessed based on the predicted traffic flows in Year 2046 and in accordance with the procedures given in the CRTN. The predicted road traffic noise levels at the building facades include a 2.5dB(A) facade reflection and correction factors for gradient, distance, view angle, barriers and road surface material.

Predicted Road Traffic Noise Levels (Base Scenario)

6.8 The predicted road traffic noise levels are presented in Appendix 3 for all Noise Sensitive Receivers (NSRs) of the proposed Development. Road traffic noise levels at all residential flats (i.e. 100%) will be complied with the 70dB(A) noise criterion. Noise mitigation measures are not required.

7. NOISE IMPACT ASSESSMENT FOR FIXED NOISE SOURCES

7.1 The identified fixed noise sources in the vicinity of the project site are summarised in Table 4.3.

Noise Assessment Points for Fixed Noise Sources Assessment

- 7.2 With consideration of location of the identified fixed noise sources, representative assessment points of worst affected (with shortest distance to the fixed noise sources) are assigned for the fixed noise sources assessment. The location of the assessment points are illustrated in Appendix 5.
- 7.3 The assessment points are taken at the height of 1.2m above each residential floor and 1m away from the façade of openable windows in the noise sensitive rooms.

Methodology of Noise Impact Assessment from Fixed Noise Sources

- 7.4 For the Source IDs A and B, the site areas are relatively large, it is assumed that the identified fixed noise sources are located at the notional source position in order to represent a worst-case scenario, instead of locating at the exact locations as observed onsite. For Source ID C, the location of the noise emission point is assumed to be at the noise emitting louvres. For other fixed noise sources, the noise emission point is placed at the nearest site boundary to the represented NSR of the proposed Development.
- 7.5 Although it is unlikely that all the identified fixed noise sources will be in operation simultaneously, to be conservative, it has been assumed that all the identified fixed noise sources are in operation at the same time, which also represents a worst-case scenario. Fixed noise sources are assumed to operate continuously instead of occasionally as observed on-site and all fixed noise sources are regarded as point source.
- 7.6 According to standard acoustic principle, a negative correction of 10dB(A) can be applied if the noise sources are totally screened by a substantial barrier such that none will be visible when viewed from any window, door or other opening in any façade of the NSR.
- 7.7 To predict the noise levels at the future noise sensitive uses, the following correction factors have been accounted for:
 - Distance correction: based on the slant distance between the identified fixed noise sources and the NSR, the distance correction is projected based on standard acoustic principle for point source;

- Façade correction: a +3dB(A) correction is applied to account for noise reflection from façade; and
- Barrier correction: The barrier attenuation is based on standard acoustic principle
- 7.8 Corrected Noise Level (CNL) at the NSRs in the proposed Development can be calculated by applying the above corrections to the measured Sound Power Level (SWL) of the fixed noise sources in accordance with the following formula:

$$CNL = SWL + C_{Lsr} + C_{fac} + C_{bar}$$

Where.

CNL is the corrected noise level at the NSR in dB(A)

C_{Lsr} is the distance correction in dB(A) in accordance with standard acoustic principle

C_{fac} is façade correction, +3 dB(A)

C_{bar} is the barrier correction in dB(A) in accordance with standard acoustic principle

SWL of Identified Fixed Noise Sources

- 7.9 On-site noise measurements were made to investigate the existing fixed noise sources. Sound Pressure Levels (SPLs) obtained during survey were then converted to SWLs with reference to basic acoustic principle. The SPLs at NSRs were calculated based on the distance attenuation, tonality correction, impulsiveness correction, intermittency correction, barrier correction and façade correction. No tonality correction, impulsiveness correction, intermittency correction is applied to the fixed noise sources based on site observation and measurements.
- 7.10 According to the approved EIA report of the Chuk Yuen Floodwater Pumping Station (Source ID: C) under the "Main Drainage Channels for Ngau Tam Mei, Yuen Long and Kam Tin" Project, SPL immediately outside the louvre at the pumping station is 79dB(A). Thus, SWL of 79dB(A) is adopted for the pumping station.
- 7.11 Site measurements for the fixed noise sources were conducted from year 2014 to 2025 (Section 4.1). A comparison is made for year 2014 to 2025 and the maximum values are selected as for the use of the worst-case scenario. Detailed measurement data for years 2014 2025 are provided in Appendix 4. The fixed noise assessment has already taken the noisiest activities into account for all of the identified fixed noise sources.
- 7.12 According to the recent site survey findings, some fixed noise sources were not in operation (refer to Tables 4.2 and 4.3). For conservative purpose, the operation of the industrial sites and SWLs of the fixed noise sources adopted in the previous approved NIA report or referenced to other identified fixed noise sources with similar use have been adopted in this assessment.

7.13 The pattern of operation, type and number of plants for the identified fixed noise sources are summarised in Table 7.1. The locations of fixed noise sources are shown in Figure 3.

Table 7.1 SWLs of Fixed Noise Sources

Table 7.	.1 SWLs of Fixed Noise Sources							
Source ID	Industrial Site	Fixed Noise Source Item		No.				
A-1		Operation noise from warehouse		1				
A-2	Fan Keung Kee	Loading and unloading using forklift		1				
A-3	Tan Keung Kee	Moving in/ out of lorry		1				
A-4		Lifting of precast units using a lorry with crane		1				
B-1	The godown	Loading and unloading using forklift		1				
B-2	The godown	Moving in/ out of lorry	99	1				
C	Chuk Yuen Floodwater Pumping Station	Operation noise	79	1				
Н	Kam Wing car repairing workshop	Noise of pneumatic screwdriver	93	1				
J	Sun Chun Car Shop	Noise of pneumatic screwdriver	95	1				
K	Akina Auto Center	Noise of pneumatic screwdriver	93	1				
N	Sun Hing car repairing workshop	Noise of pneumatic screwdriver	92	1				
Q	Lung Yee car repairing workshop	Noise of pneumatic screwdriver	92	1				
R	Hing Lee car repairing workshop	Noise of pneumatic screwdriver		1				
S	Wing Tai Tyre	Noise of pneumatic screwdriver		1				
U	Alicar Fairview Workshop	Water pump noise, noise from compressed air gun, vacuum cleaner and water jetting		1				
W	Fugro warehouse	Loading and unloading	90	1				
Y	Office	Condenser	92	1				
Z	Open storage	Operation of open storage assumed (referenced to Source ID: A)	102	1				
AA	Car repairing workshop	Noise of Pneumatic screwdriver assumed (referenced to Source ID: J)	95	1				
AB	Open yard for construction materials	Operation of open storage assumed (referenced to Source ID: A)	102	1				
AC	Top 1 Car Audio Workshop	Noise of Pneumatic screwdriver assumed (referenced to Source ID: J)	95	1				
AD	EV-Pro HK	Noise of Pneumatic screwdriver assumed (referenced to Source ID: J)		1				
BB	Planned Car Testing Centre	Maximum allowable SWL		1				
СС	Planned Car Trading Use	Maximum allowable SWL		1				
DD	Planned Vehicle Repair Workshop	Maximum allowable SWL		1				
		· · · · · · · · · · · · · · · · · · ·						

Note:-

- [1] The SWL of Noise Source U is 98dB(A). Referring to Table 4.3 correction of +3dB(A) has been considered. Hence, SWL of 101dB(A) is adopted in the calculation
- [2] The nearest NSR to the Noise Source BB is Helena Terrace, with 28m distance. Considering that noise criteria of ANL-5 (i.e. 55dB(A) during day time) is adopted in Helena Terrace, the maximum allowable SWL of Noise Source BB is 92dB(A).
- [3] The nearest NSR to the Noise Source CC is Helena Terrace, with 12m distance. Considering that noise criteria of ANL-5 (i.e. 55dB(A) during day time) is adopted in Helena Terrace, the maximum allowable SWL of Noise Source CC is 85dB(A).
- [4] The nearest NSR to the Noise Source DD is Meister House, with 25m distance. Considering that noise criteria of ANL-5 (i.e. 55dB(A) during day time) is adopted in Meister House, the maximum allowable SWL of Noise Source DD is 91dB(A).

Predicted Noise Levels from Fixed Noise Sources (Base Scenario)

7.14 The predicted façade noise levels from fixed noise sources at the representative NSRs are in the range of 49 – 60dB(A) Leq(30min) during day and evening time periods, and in the range of 36 – 47dB(A) Leq(30min) during night-time period. These predicted noise levels are within the stipulated noise limits as mentioned in Section 3. The predicted noise levels is summarised in Table 7.2. The summary of the predicted noise levels is given in Appendix 5.

Table 7.2 Predicted Façade Noise Level from Fixed Noise Sources

	Day and Evening Time Periods		Night-time Period			
Representative NSRs	Maximum Predicted Façade Noise Level, dB(A)	Noise Criteria, dB(A)	Maximum Predicted Façade Noise Level, dB(A)	Noise Criteria, dB(A)	Compliance	
NSR 112	58	60	37	50	Yes	
NSR 122	60	60	37	50	Yes	
NSR 125	60	60	38	50	Yes	
NSR 126	58	60	47	50	Yes	
NSR 139	57	60	47	50	Yes	
NSR 150	56	60	46	50	Yes	
NSR 226	57	60	36	50	Yes	
NSR 227	53	60	36	50	Yes	
NSR 501	55	60	43	50	Yes	
NSR 520	56	60	44	50	Yes	
NSR 601	49	60	40	50	Yes	

8. POTENTIAL NOISE IMPACT FROM FIXED NOISE SOURCES IN THE PROPOSED DEVELOPMENT

- 8.1 The planned fixed noise sources such as the E&M plant rooms and ventilating systems of the clubhouses, the noise impact would be in accordance with HKPSG standard (i.e. ANL 5dB(A) as mentioned in Section 3). As mentioned in Section 3.6, the prevailing background noise levels of the identified noise sensitive receivers were higher than ANL 5dB(A). Therefore, the ANL 5dB(A) has been used as the criteria for noise from planned fixed sources (i.e. 55dB(A) for daytime, and 45dB(A) for nighttime).
- 8.2 For the design of plant noise control treatment, the noise emanating from plantrooms and from the fresh air intake and discharge air grilles shall be controlled to 45dB(A) Leq(30min), measured at 1m from the nearest NSRs. Provisions shall be made to control the plant noise by suitable silencers, acoustic louvres, vibration isolators and enclosures in order to meet the ANL 5dB limit.

Planned Fixed Noise Sources within the Proposed Development

8.3 The planned fixed noise sources included E&M plant rooms and the ventilation systems of clubhouse. These noise sources will be housed. Standard noise treatment such as acoustic enclosure to pump motors, plant room sound absorptive treatment, silencers and vibration isolation shall be deployed in detailed design stage to avoid noise nuisance. The Project Proponent has guaranteed that all of the planned fixed noise sources associated with the proposed Development would be designed to meet the requirements of the HKPSG.

Cumulative Noise Impact due to All Fixed Noise Sources

8.4 The cumulative noise impact has been considered for the planned fixed noise sources in the proposed Development and other existing fixed noise sources in the neighbourhood (refers to Table 7.1). The results indicate that the cumulative noise levels for the representative NSRs would comply with the stipulated noise criteria (Appendix 6).

9. NOISE IMPACTS FOR THE KINDERGARTEN

9.1 A 1-storey 6-classroom kindergarten will be semi-detached to the clubhouse, which will subject to road traffic noise and fixed noise sources. The openable window of classrooms is designed facing west. The office and ancillary facilities of the kindergarten will be equipped with central air-conditioning and will not rely on opened windows for ventilation.

Road Traffic Noise Impact for Kindergarten

9.2 The predicted road traffic noise levels will be in the range of 56 – 58dB(A), which comply with the noise criteria (i.e. 65dB(A). The noise results are provided in Appendix 7.

Fixed Noise Impact for Kindergarten


9.3 The openable window of classrooms is designed facing west, which without line of sight to the major fixed noise sources (i.e. the adjoining open storage, Source ID: A). The predicted façade noise level from fixed noise sources is 52 dB(A) Leq(30min) during day and evening time and 46dB(A) Leq(30min) during night-time period. Hence, these predicted noise levels are within the stipulated noise limits as mentioned in Section 3. No noise mitigation measure is required. The noise results are provided in Appendix 7.

10. CONCLUSION


- 10.1 The proposed Development was reviewed and the road traffic noise, fixed noise sources, and in-estate planned plant noise were assessed. All the residential flats (i.e. 100%) will be within the stipulated noise criteria with the adopted acoustic fins and appropriate mitigation measures.
- 10.2 The cumulative noise impacts have been taken into account for consideration. The results have indicated that the cumulative noise levels for the representative NSRs will comply with the stipulated noise criteria.
- 10.3 Noise assessments for the kindergarten were conducted. The predicted noise levels indicate that the kindergarten will have no adverse road traffic noise and fixed noise impacts.

11. REFERENCES

- [1] "Hong Kong Planning Standards & Guidelines" of March 2014 of Hong Kong Government.
- [2] "Technical Memorandum for the Assessment of Noise from Places Other Than Domestic Premises, Public Places or Construction Sites" (IND TM) issued under the Noise Control Ordinance.
- [3] "RoadNoise 2000" Computer Software of WS Atkins Noise and Vibration, England.
- [4] "Calculation of Road Traffic Noise" of the Department of Transport, Welsh Office, UK.







Westwood Hong & Associates Ltd


PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Measurement Location


FIGURE



PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

Identified Fixed Noise Sources



Westwood Hong & Associates Ltd


PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Computer Plot of Noise Prediction Model

FIGURE



Westwood Hong & Associates Ltd

PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:


Noise Mitigation Measures for Fixed Noise Sources


FIGURE


APPENDIX 1


ARCHITECTURAL DRAWINGS

Report: 22610-N1










SECTION S1-S1



SECTION S2-S2


SECTION S3-S3



G/F PLAN




TYPICAL S.A. EFF.: 91.93%









TYPICAL S.A. EFF.: 92.84%



1/F PLAN



G/F PLAN



TYPICAL S.A. EFF.: 90.45%




1/F PLAN



G/F PLAN



TYPICAL S.A. EFF.: 89.46%







TYPICAL S.A. EFF.: 92.92%

APPENDIX 2

YEAR 2046 TRAFFIC FORECAST


Report: 22610-N1

Year 2046 Peak-Hour Traffic Forecast

			AM Pe	eak	PM P	eak
Ref.	Road Name	Direction	Traffic Flow (veh/hr) ⁽²⁾	HV% ⁽³⁾	Traffic Flow (veh/hr) ⁽²⁾	HV% ⁽³⁾
Α	Fairview Park Boulevard	Two-way	1600	17%	1650	16%
В	Castle Peak Road - Tam Mi	Two-way	1300	25%	1050	27%
С	Unnamed Road	Two-way	50	38%	50	16%
D	Ha San Wai Road	Two-way	100	38%	100	16%
Е	Kam Pok Road	Two-way	350	19%	250	13%
F	Kam Pok Road	Two-way	250	35%	300	25%
G	Yau Pok Road	SB	50	14%	50	20%
Н	Kam Pok Road	Two-way	250	18%	200	19%
1	Yau Pok Road	NB	50	7%	50	17%
J	Ha Chuk Yuen Road	Two-way	50	35%	50	26%
K	Fung Chuk Road	Two-way	100	20%	50	7%
	Unnamed Vehicular Bridge	Two-way				
L	(south)		50	15%	50	18%
М	Kam Pok Road	Two-way	300	16%	250	16%
N	Yau Pok Road	NB	50	7%	50	17%

Remarks:


- (1) Refer to **Drawing 1**;
- (2) Traffic flows rounded up to the nearest 50;
- (3) Heavy vehicles include all categories of motor vehicles except private car, taxi and motorcycle.



APPENDIX 3

PREDICTED FAÇADE NOISE LEVELS FOR ROAD TRAFFIC NOISE

Report: 22610-N1




PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

Location of Assessment Point for Road Traffic Noise Assessment – Tower 1 and Tower 2

A3-1



PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

Location of Assessment Point for Road Traffic Noise Assessment – Tower 3 – Tower 6

A3-2

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (Unmitigated)

	Receiver								Towe	er 1															
Level	101	102	103	104	105	106	107	108	109	110	111	112	113	114	115	116	117	118	119	120	121	122	123	124	125
G/F			62.4	60.2	59.3	58.5	58.0	57.6	57.1	56.8	56.3	56.7	56.4	56.2	56.0	55.8	55.7	55.8	54.8	54.7	54.7	55.1	56.0	57.3	59.2
1/F	67.2	67.1	62.4	60.3	59.3	58.6	58.0	57.6	57.2	56.9	56.4	56.8	56.5	56.3	56.1	56.0	55.9	55.9	55.0	54.9	54.9	55.3	56.2	57.4	59.3
T.P.																									
3/F	67.1	67.0	62.4	60.4	59.5	58.8	58.3	57.9	57.6	57.3	56.9	57.3	57.1	56.9	56.8	56.7	56.6	56.7	55.9	55.9	56.0	56.4	57.1	58.2	59.8
4/F	67.1	67.0	62.6	60.7	59.9	59.3	58.9	58.6	58.3	58.1	57.8	58.2	58.1	58.0	57.9	57.9	57.9	58.0	57.5	57.5	57.7	57.9	58.5	59.4	60.8
5/F	66.9	67.0	62.8	61.0	60.3	59.8	59.5	59.3	59.0	58.8	58.6	58.9	58.8	58.7	58.7	58.7	58.7	58.7	58.3	58.3	58.4	58.7	59.2	59.9	61.1
6/F	66.9	66.9	62.9	61.1	60.5	60.1	59.7	59.5	59.3	59.1	58.9	59.2	59.1	59.0	58.9	58.9	58.8	58.9	58.5	58.5	58.6	58.8	59.3	59.9	61.2
7/F	66.8	66.8	62.8	61.1	60.5	60.1	59.7	59.5	59.3	59.2	58.9	59.2	59.1	59.0	59.0	58.9	58.9	58.9	58.5	58.5	58.6	58.8	59.3	59.9	61.3
8/F	66.6	66.7	62.8	61.1	60.5	60.0	59.7	59.5	59.3	59.1	58.9	59.2	59.1	59.0	58.9	58.9	58.9	58.9	58.5	58.5	58.6	58.8	59.3	59.9	61.4
9/F	66.5	66.6	62.7	61.0	60.4	59.9	59.6	59.5	59.2	59.1	58.8	59.1	59.0	58.9	58.9	58.9	58.8	58.9	58.5	58.5	58.6	58.8	59.3	59.9	61.5
10/F	66.5	66.5	62.6	60.9	60.3	59.9	59.6	59.4	59.2	59.1	58.8	59.1	59.0	58.9	58.9	58.8	58.8	58.9	58.5	58.5	58.6	58.8	59.3	59.9	61.6
11/F	66.4	66.4	62.5	60.8	60.2	59.8	59.5	59.3	59.2	59.0	58.8	59.1	59.0	58.9	58.9	58.8	58.8	58.9	58.5	58.5	58.6	58.8	59.3	59.9	61.6
12/F	66.2	66.3	62.4	60.7	60.2	59.8	59.5	59.3	59.1	59.0	58.7	59.1	58.9	58.9	58.8	58.8	58.8	58.9	58.5	58.6	58.6	58.9	59.3	59.9	61.6
13/F	66.1	66.2	62.4	60.7	60.1	59.7	59.4	59.3	59.1	58.9	58.7	59.1	58.9	58.9	58.8	58.8	58.8	58.9	58.5	58.6	58.6	58.9	59.3	59.9	61.6
14/F	66.1	66.1	62.2	60.6	60.0	59.6	59.4	59.2	59.0	58.9	58.7	59.0	58.9	58.9	58.8	58.8	58.8	58.9	58.5	58.6	58.7	58.9	59.3	60.0	61.7
15/F	65.9	66.0	62.2	60.5	60.0	59.6	59.4	59.2	59.0	58.9	58.7	59.0	58.9	58.8	58.8	58.8	58.8	58.9	58.5	58.6	58.7	58.9	59.3	60.0	61.7
16/F	65.8	65.9	62.1	60.4	59.9	59.5	59.3	59.1	59.0	58.9	58.7	59.0	58.9	58.9	58.8	58.8	58.8	58.9	58.6	58.7	58.8	59.0	59.4	60.0	61.8

RCT610-4, Table Page 1 of 10

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (<u>Unmitigated</u>)

														Tower 1												
Level	126	127	128	129	130	131	132	133	134	135	136	137	138	139	140	141	142	143	144	145	146	147	148	149	150	151
G/F																										
1/F	67.4	67.3	67.3	67.4	67.3	67.4	67.4	67.4	67.4	67.5				67.5	67.6	67.6	67.6	67.7	67.7	67.7	67.8	67.8	68.0	68.2	68.5	68.0
T.P.																										
3/F	67.4	67.3	67.3	67.3	67.3	67.3	67.4	67.4	67.4	67.4	67.3	67.4	67.4	67.5	67.5	67.6	67.6	67.6	67.7	67.7	67.7	67.7	67.9	68.1	68.4	67.9
4/F	67.4	67.2	67.3	67.3	67.2	67.3	67.3	67.3	67.4	67.4	67.3	67.4	67.4	67.5	67.5	67.5	67.6	67.6	67.7	67.6	67.7	67.7	67.9	68.0	68.3	67.9
5/F	67.4	67.2	67.2	67.2	67.2	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.5	67.5	67.5	67.5	67.6	67.6	67.6	67.6	67.6	67.9	68.0	68.3	67.8
6/F	67.3	67.2	67.2	67.2	67.2	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.4	67.4	67.5	67.5	67.5	67.6	67.5	67.6	67.6	67.8	67.9	68.2	67.7
7/F	67.4	67.2	67.2	67.2	67.2	67.2	67.3	67.3	67.3	67.3	67.2	67.3	67.3	67.4	67.4	67.4	67.5	67.5	67.5	67.5	67.5	67.5	67.7	67.8	68.1	67.6
8/F	67.4	67.2	67.2	67.2	67.2	67.2	67.3	67.3	67.3	67.3	67.3	67.3	67.3	67.4	67.4	67.4	67.4	67.4	67.5	67.5	67.5	67.5	67.7	67.8	68.1	67.5
9/F	67.3	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.3	67.3	67.2	67.2	67.2	67.3	67.4	67.4	67.4	67.4	67.5	67.4	67.5	67.5	67.6	67.8	68.0	67.4
10/F	67.3	67.1	67.2	67.2	67.1	67.2	67.2	67.2	67.2	67.3	67.2	67.2	67.2	67.3	67.3	67.4	67.4	67.4	67.4	67.4	67.4	67.4	67.6	67.7	68.0	67.3
11/F	67.3	67.1	67.1	67.1	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.3	67.3	67.3	67.4	67.4	67.4	67.4	67.4	67.4	67.5	67.6	67.9	67.3
12/F	67.3	67.1	67.1	67.1	67.1	67.1	67.2	67.1	67.2	67.2	67.1	67.2	67.2	67.2	67.3	67.3	67.3	67.3	67.4	67.3	67.3	67.4	67.5	67.6	67.8	67.1
13/F	67.3	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.2	67.2	67.1	67.2	67.1	67.2	67.2	67.3	67.3	67.3	67.4	67.3	67.3	67.3	67.5	67.6	67.8	67.0
14/F	67.3	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.2	67.2	67.2	67.2	67.2	67.3	67.2	67.2	67.3	67.4	67.5	67.7	67.0
15/F	67.3	67.1	67.1	67.1	67.0	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.2	67.2	67.2	67.2	67.2	67.3	67.2	67.2	67.2	67.4	67.5	67.7	66.8
16/F	67.3	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.1	67.0	67.1	67.1	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.2	67.3	67.4	67.6	66.8

RCT610-4, Table Page 2 of 10

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (Unmitigated)

												-	Tower 2												
Level	201	202	203	204	205	206	207	208	209	210	211	212	213	214	215	216	217	218	219	220	221	222	223	224	225
G/F			59.5	58.2	58.0	58.0	57.9	57.9	57.9	57.9	57.8	57.8	57.8	57.7	57.6	57.4	57.1	57.0	57.0	56.7	56.5	56.3	56.3	56.3	56.2
1/F	62.7	62.6	59.6	58.3	58.2	58.1	58.0	58.0	58.0	58.0	58.0	57.9	57.9	57.9	57.7	57.5	57.3	57.2	57.1	56.9	56.7	56.5	56.5	56.5	56.4
T.P.																									
3/F	62.6	62.6	59.7	58.5	58.4	58.3	58.3	58.2	58.2	58.2	58.2	58.2	58.2	58.1	58.0	57.8	57.6	57.6	57.5	57.4	57.2	57.0	57.0	57.0	57.0
4/F	62.6	62.6	59.9	58.8	58.7	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.6	58.5	58.5	58.4	58.3	58.2	58.2	58.1	58.0	57.9	57.9	57.8	57.8
5/F	62.5	62.7	60.3	59.3	59.2	59.1	59.1	59.1	59.1	59.2	59.2	59.2	59.2	59.1	59.1	59.1	59.0	59.0	58.9	58.9	58.9	58.8	58.8	58.7	58.7
6/F	62.4	62.7	60.5	59.6	59.5	59.4	59.4	59.4	59.4	59.5	59.5	59.5	59.5	59.5	59.5	59.5	59.4	59.4	59.3	59.3	59.3	59.2	59.2	59.1	59.1
7/F	62.4	62.7	60.6	59.7	59.6	59.6	59.6	59.6	59.6	59.7	59.7	59.7	59.7	59.6	59.6	59.6	59.5	59.5	59.5	59.4	59.4	59.4	59.3	59.2	59.2
8/F	62.3	62.6	60.7	59.8	59.7	59.7	59.7	59.7	59.7	59.8	59.8	59.7	59.7	59.7	59.7	59.7	59.6	59.6	59.5	59.5	59.5	59.4	59.3	59.2	59.2
9/F	62.2	62.5	60.7	59.9	59.8	59.8	59.8	59.7	59.8	59.8	59.8	59.8	59.8	59.7	59.7	59.7	59.6	59.6	59.6	59.5	59.5	59.4	59.4	59.2	59.2
10/F	62.1	62.5	60.7	59.9	59.8	59.8	59.8	59.8	59.8	59.9	59.9	59.8	59.8	59.8	59.8	59.8	59.7	59.7	59.6	59.6	59.5	59.5	59.4	59.2	59.2
11/F	62.0	62.4	60.7	60.0	59.9	59.9	59.8	59.8	59.8	59.9	59.9	59.9	59.9	59.8	59.8	59.8	59.7	59.7	59.7	59.7	59.6	59.5	59.4	59.2	59.2
12/F	61.9	62.3	60.7	60.0	59.9	59.9	59.9	59.9	59.9	60.0	59.9	60.0	59.9	59.9	59.9	59.9	59.8	59.8	59.8	59.7	59.7	59.5	59.4	59.2	59.1
13/F	61.8	62.2	60.7	60.0	60.0	60.0	59.9	59.9	59.9	60.0	60.0	60.0	60.0	60.0	59.9	59.9	59.8	59.9	59.8	59.8	59.7	59.6	59.4	59.2	59.1
14/F	61.7	62.1	60.8	60.1	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	60.0	59.9	59.9	59.9	59.8	59.7	59.6	59.4	59.2	59.1
15/F	61.6	62.1	60.8	60.1	60.1	60.0	60.0	60.0	60.0	60.1	60.1	60.1	60.0	60.0	60.0	60.0	59.9	59.9	59.9	59.8	59.8	59.6	59.4	59.2	59.2
16/F	61.5	62.0	60.8	60.2	60.1	60.1	60.1	60.0	60.0	60.1	60.1	60.1	60.1	60.0	60.0	60.0	59.9	59.9	59.9	59.9	59.8	59.6	59.5	59.2	59.2

RCT610-4, Table Page 3 of 10

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (Unmitigated)

															Tower 2													
Level	226	227	228	229	230	231	232	233	234	235	236	237	238	239	240	241	242	243	244	245	246	247	248	249	250	251	252	253
G/F	57.2																											
1/F	57.4	67.0	67.0	67.0	67.0	67.0	67.1	67.1	67.1	67.0	67.0	66.8	66.8					66.7	66.7	66.8	66.7	66.7	66.7	66.6	66.6	66.6	66.6	66.5
T.P.																												
3/F	57.8	66.9	66.9	66.9	66.9	67.0	67.0	67.0	67.0	66.9	66.9	66.8	66.7	66.7	66.7	66.6	66.6	66.6	66.5	66.6	66.6	66.6	66.6	66.5	66.5	66.5	66.5	66.4
4/F	58.5	66.9	66.9	66.8	66.8	66.9	66.9	66.9	66.9	66.8	66.8	66.7	66.7	66.6	66.6	66.6	66.5	66.5	66.5	66.6	66.5	66.5	66.5	66.5	66.4	66.4	66.4	66.4
5/F	59.2	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.8	66.7	66.7	66.6	66.6	66.5	66.5	66.5	66.4	66.4	66.4	66.5	66.5	66.4	66.4	66.4	66.4	66.4	66.3	66.3
6/F	59.5	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.7	66.6	66.5	66.5	66.4	66.4	66.4	66.3	66.3	66.3	66.4	66.4	66.3	66.3	66.3	66.2	66.2	66.2	66.2
7/F	59.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.6	66.5	66.5	66.4	66.4	66.3	66.3	66.3	66.2	66.2	66.2	66.3	66.3	66.2	66.2	66.2	66.1	66.2	66.1	66.1
8/F	59.7	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.5	66.4	66.4	66.3	66.3	66.2	66.2	66.2	66.2	66.1	66.1	66.2	66.2	66.1	66.1	66.1	66.0	66.0	66.0	66.0
9/F	59.6	66.4	66.4	66.4	66.4	66.4	66.4	66.4	66.4	66.4	66.3	66.2	66.2	66.1	66.1	66.1	66.0	66.0	66.0	66.1	66.0	66.0	66.0	66.0	65.9	65.9	65.9	65.9
10/F	59.6	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.3	66.2	66.2	66.1	66.1	66.0	66.0	66.0	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.8	65.8	65.8	65.8
11/F	59.6	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.2	66.1	66.1	66.0	66.0	65.9	65.9	65.8	65.8	65.8	65.8	65.8	65.8	65.8	65.7	65.7	65.7	65.7	65.7	65.7
12/F	59.6	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.1	66.0	66.0	65.9	65.9	65.8	65.8	65.8	65.7	65.7	65.7	65.7	65.7	65.7	65.6	65.6	65.6	65.6	65.6	65.6
13/F	59.6	66.1	66.0	66.0		66.0	66.0	66.0	65.9	65.9	65.9	65.8	65.8	65.7	65.7	65.7	65.6	65.6	65.6	65.6	65.6	65.6	65.5	65.5	65.5	65.5	65.5	65.4
14/F	59.6	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.9	65.8	65.8	65.7	65.6	65.6	65.6	65.5	65.5	65.5	65.5	65.5	65.5	65.5	65.4	65.4	65.4	65.4	65.3	65.3
15/F	59.6	65.9	65.9	65.8	65.8	65.8	65.8	65.8	65.8	65.7	65.7	65.6	65.6	65.5	65.5	65.5	65.4	65.4	65.4	65.4	65.4	65.4	65.3	65.3	65.3	65.3	65.3	65.2
16/F	59.6	65.8	65.8	65.7	65.7	65.7	65.7	65.7	65.7	65.6	65.6	65.5	65.5	65.4	65.4	65.4	65.3	65.3	65.3	65.3	65.3	65.3	65.2	65.2	65.2	65.2	65.2	65.1

RCT610-4, Table Page 4 of 10

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (<u>Unmitigated</u>)

										Tower 3										-
Level	301	302	303	304	305	306	307	308	309	310	311	312	313	314	315	316	317	318	319	320
G/F																				
1/F	63.0	62.8	62.7	62.7	62.6	62.6	62.6					62.6	62.6	62.6	62.6	62.6	62.5	62.3	62.3	62.3
T.P.																				
3/F	62.9	62.7	62.6	62.6	62.5	62.5	62.5	62.5	62.5	62.4	62.4	62.5	62.5	62.5	62.5	62.4	62.4	62.2	62.2	62.2
4/F	62.8	62.6	62.5	62.5	62.5	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.4	62.3	62.2	62.1	62.1
5/F	62.7	62.5	62.4	62.4	62.4	62.4	62.3	62.3	62.3	62.3	62.3	62.4	62.4	62.3	62.3	62.3	62.3	62.1	62.1	62.1
6/F	62.7	62.4	62.4	62.4	62.3	62.3	62.3	62.3	62.3	62.3	62.2	62.3	62.3	62.3	62.3	62.3	62.2	62.1	62.1	62.1
7/F	62.6	62.4	62.3	62.3	62.3	62.3	62.3	62.2	62.3	62.2	62.2	62.3	62.3	62.3	62.3	62.3	62.3	62.1	62.1	62.1
8/F	62.6	62.4	62.3	62.3	62.3	62.3	62.3	62.2	62.2	62.2	62.2	62.3	62.3	62.3	62.3	62.3	62.3	62.1	62.1	62.1
9/F	62.6	62.3	62.3	62.3	62.3	62.2	62.2	62.2	62.2	62.2	62.2	62.3	62.2	62.2	62.2	62.2	62.2	62.1	62.1	62.1
10/F	62.5	62.3	62.2	62.2	62.2	62.2	62.1	62.1	62.1	62.1	62.1	62.2	62.2	62.2	62.2	62.2	62.2	62.1	62.1	62.0
11/F	62.4	62.2	62.1	62.2	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.2	62.2	62.2	62.2	62.2	62.1	62.0	62.0	62.0
12/F	62.4	62.2	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.1	62.0	62.0	62.0
13/F	62.4	62.1	62.1	62.1	62.1	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.1	62.0	62.1	62.1	62.0	61.9	61.9	61.9
14/F	62.3	62.1	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	62.0	61.9	61.9	61.9
15/F	62.3	62.0	62.0	62.0	62.0	62.0	61.9	61.9	61.9	61.9	61.9	62.0	62.0	62.0	62.0	62.0	62.0	61.9	61.9	61.9
16/F	62.3	62.0	61.9	62.0	61.9	61.9	61.9	61.9	61.9	61.9	61.9	62.0	62.0	62.0	62.0	62.0	61.9	61.8	61.9	61.9

RCT610-4, Table Page 5 of 10

RCT610-4, Table Page 6 of 10

Job No. : 22610 Job Title : Kam Pok Road

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (<u>Unmitigated</u>)

										Tower 3									
Level	321	322	323	324	325	326	327	328	329	330	331	332	333	334	335	336	337	338	339
G/F	60.6	60.6	60.6	60.6	60.6	60.7	60.6	60.7	60.7	60.7	60.6	60.6	60.6	60.5	60.3	60.3	60.2	60.2	60.6
1/F	60.7	60.6	60.7	60.7	60.7	60.7	60.7	60.8	60.7	60.8	60.7	60.7	60.7	60.6	60.4	60.3	60.3	60.3	60.7
T.P.																			
3/F	60.7	60.6	60.7	60.7	60.7	60.7	60.7	60.8	60.7	60.7	60.7	60.7	60.7	60.6	60.4	60.3	60.3	60.3	60.7
4/F	60.7	60.6	60.6	60.7	60.7	60.7	60.7	60.8	60.7	60.7	60.7	60.7	60.7	60.6	60.4	60.3	60.3	60.3	60.7
5/F	60.7	60.6	60.6	60.6	60.7	60.7	60.7	60.8	60.7	60.7	60.7	60.7	60.7	60.6	60.4	60.3	60.3	60.3	60.6
6/F	60.8	60.6	60.6	60.6	60.7	60.7	60.6	60.7	60.7	60.7	60.6	60.7	60.6	60.5	60.4	60.3	60.3	60.3	60.6
7/F	60.8	60.5	60.6	60.6	60.6	60.6	60.6	60.7	60.7	60.7	60.6	60.7	60.6	60.5	60.3	60.3	60.2	60.3	60.5
8/F	60.9	60.5	60.6	60.5	60.6	60.6	60.6	60.7	60.6	60.7	60.6	60.6	60.6	60.5	60.3	60.2	60.2	60.2	60.5
9/F	60.9	60.5	60.5	60.5	60.5	60.5	60.6	60.6	60.6	60.6	60.6	60.6	60.5	60.5	60.3	60.2	60.2	60.2	60.5
10/F	60.9	60.4	60.5	60.5	60.5	60.5	60.5	60.6	60.6	60.6	60.6	60.6	60.5	60.5	60.3	60.2	60.2	60.2	60.4
11/F	60.9	60.4	60.4	60.5	60.5	60.5	60.5	60.6	60.6	60.5	60.5	60.5	60.4	60.4	60.2	60.2	60.1	60.1	60.4
12/F	60.8	60.4	60.4	60.4	60.5	60.4	60.5	60.5	60.5	60.5	60.5	60.5	60.4	60.4	60.2	60.1	60.1	60.1	60.4
13/F	60.8	60.3	60.3	60.4	60.4	60.4	60.4	60.5	60.5	60.4	60.5	60.5	60.4	60.4	60.2	60.1	60.1	60.0	60.4
14/F	60.8	60.3	60.3	60.4	60.3	60.4	60.4	60.4	60.5	60.4	60.4	60.4	60.4	60.3	60.1	60.1	60.1	60.0	60.3
15/F	60.7	60.2	60.2	60.3	60.4	60.3	60.3	60.4	60.4	60.4	60.4	60.4	60.3	60.3	60.1	60.0	60.0	60.0	60.3
16/F	60.7	60.2	60.2	60.3	60.3	60.3	60.3	60.4	60.4	60.3	60.4	60.3	60.3	60.3	60.0	60.0	60.0	60.0	60.2

Westwood Hong & Associates Ltd.

RCT610-4, Table Page 7 of 10

Job No. : 22610 Job Title : Kam Pok Road

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (Unmitigated)

										Tower 5								
Level	501	502	503	504	505	506	507	508	509	510	511	512	513	514	515	516	517	518
G/F																		
1/F	62.8	62.4	61.8	62.4	62.2	62.1	62.0	61.9	61.8	61.4	61.4				62.0	62.1	62.2	62.1
T.P.																		
3/F	62.8	62.3	61.7	62.3	62.1	62.0	61.9	61.8	61.8	61.3	61.4	61.8	61.9	62.0	62.0	62.1	62.1	62.0
4/F	62.7	62.3	61.7	62.3	62.1	62.0	61.9	61.8	61.8	61.3	61.3	61.8	61.9	61.9	62.0	62.0	62.1	62.0
5/F	62.7	62.2	61.7	62.2	62.0	61.9	61.8	61.8	61.7	61.3	61.3	61.8	61.9	61.9	62.0	62.0	62.1	62.0
6/F	62.6	62.2	61.6	62.2	62.0	61.9	61.8	61.8	61.7	61.3	61.3	61.8	61.8	61.9	61.9	62.0	62.1	61.9
7/F	62.5	62.1	61.6	62.1	61.9	61.9	61.8	61.7	61.7	61.2	61.3	61.7	61.8	61.8	61.9	61.9	62.0	61.9
8/F	62.5	62.0	61.5	62.0	61.9	61.8	61.7	61.7	61.6	61.2	61.2	61.7	61.8	61.8	61.9	61.9	61.9	61.8
9/F	62.4	62.0	61.4	62.0	61.9	61.8	61.7	61.6	61.6	61.2	61.2	61.6	61.7	61.8	61.8	61.9	61.9	61.8
10/F	62.3	61.9	61.4	61.9	61.8	61.7	61.6	61.6	61.5	61.1	61.1	61.6	61.7	61.7	61.8	61.8	61.9	61.8
11/F	62.3	61.8	61.3	61.9	61.7	61.7	61.6	61.5	61.5	61.1	61.1	61.6	61.6	61.6	61.7	61.8	61.8	61.7
12/F	62.2	61.8	61.2	61.8	61.7	61.6	61.5	61.5	61.5	61.0	61.1	61.5	61.6	61.6	61.7	61.7	61.8	61.7
13/F	62.2	61.7	61.2	61.8	61.6	61.6	61.5	61.4	61.4	61.0	61.0	61.5	61.5	61.6	61.6	61.7	61.7	61.6
14/F	62.1	61.7	61.1	61.7	61.6	61.5	61.5	61.4	61.4	60.9	61.0	61.4	61.5	61.6	61.6	61.7	61.7	61.6
15/F	62.0	61.6	61.1	61.7	61.5	61.5	61.4	61.3	61.3	60.9	61.0	61.4	61.5	61.5	61.6	61.6	61.7	61.6
16/F	62.0	61.6	61.0	61.6	61.5	61.4	61.4	61.3	61.3	60.9	60.9	61.4	61.5	61.5	61.6	61.6	61.7	61.6

Westwood Hong & Associates Ltd.

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (Unmitigated)

									Tower 5								
Level	519	520	521	522	523	524	525	526	527	528	529	530	531	532	533	534	535
G/F			60.7	60.0	60.0	60.5	60.6	60.7	60.7	60.7	60.8	60.9	60.7	60.7	60.7	61.0	61.5
1/F	62.2	62.3	60.9	60.2	60.1	60.7	60.7	60.8	60.9	60.8	60.9	61.0	60.8	60.8	60.8	61.0	61.6
T.P.																	
3/F	62.1	62.3	60.9	60.2	60.1	60.6	60.7	60.8	60.9	60.9	60.9	61.0	60.9	60.8	60.8	61.0	61.6
4/F	62.1	62.2	60.9	60.2	60.1	60.6	60.7	60.8	60.9	60.9	60.9	61.0	60.9	60.8	60.8	61.0	61.5
5/F	62.1	62.2	60.9	60.2	60.1	60.6	60.7	60.8	60.8	60.9	60.9	60.9	60.8	60.8	60.8	61.0	61.5
6/F	62.0	62.1	60.9	60.2	60.1	60.6	60.7	60.8	60.8	60.8	60.9	60.9	60.8	60.8	60.7	60.9	61.5
7/F	62.0	62.1	60.8	60.1	60.1	60.6	60.6	60.8	60.8	60.8	60.8	60.9	60.8	60.7	60.7	60.9	61.4
8/F	62.0	62.0	60.8	60.1	60.1	60.5	60.6	60.7	60.7	60.8	60.8	60.9	60.7	60.7	60.7	60.9	61.4
9/F	61.9	62.0	60.8	60.1	60.0	60.5	60.6	60.7	60.7	60.8	60.8	60.8	60.7	60.7	60.6	60.8	61.3
10/F	61.9	61.9	60.8	60.0	60.0	60.5	60.6	60.7	60.7	60.7	60.8	60.8	60.6	60.6	60.6	60.8	61.3
11/F	61.8	61.9	60.8	60.0	60.0	60.5	60.5	60.6	60.7	60.7	60.7	60.8	60.6	60.6	60.6	60.7	61.2
12/F	61.8	61.8	60.7	60.0	60.0	60.4	60.5	60.6	60.6	60.7	60.7	60.7	60.6	60.6	60.5	60.7	61.2
13/F	61.7	61.8	60.7	60.0	60.0	60.4	60.5	60.5	60.6	60.6	60.7	60.7	60.5	60.5	60.5	60.6	61.1
14/F	61.7	61.7	60.7	60.0	59.9	60.4	60.4	60.5	60.6	60.6	60.6	60.7	60.5	60.5	60.4	60.6	61.0
15/F	61.7	61.7	60.7	59.9	59.9	60.4	60.4	60.5	60.5	60.6	60.6	60.6	60.5	60.4	60.4	60.6	61.0
16/F	61.6	61.7	60.7	59.9	59.9	60.3	60.4	60.5	60.5	60.5	60.6	60.6	60.4	60.4	60.4	60.5	60.9

RCT610-4, Table Page 8 of 10

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (Unmitigated)

														7	ower 6															
Level	601	602	603	604	605	606	607	608	609	610	611	612	613	614	615	616	617	618	619	620	621	622	623	624	625	626	627	628	629	630
G/F			63.6	62.9	62.1	61.7	61.2	61.0	60.7	60.3	59.9	59.6	59.3	58.9	58.6	58.2	58.0	57.7	57.2	56.9	56.7	56.5	56.3	56.3	56.2	56.8	59.2			
1/F	65.7	65.9	63.6	62.8	62.1	61.7	61.3	61.0	60.7	60.3	59.9	59.6	59.3	58.9	58.5	58.2	58.0	57.7	57.2	56.9	56.7	56.5	56.3	56.3	56.2	56.9	59.3	63.7	63.9	66.7
T.P.																														
3/F	65.4	65.7	63.4	62.6	61.9	61.5	61.1	60.9	60.5	60.2	59.8	59.5	59.2	58.8	58.5	58.1	57.9	57.6	57.1	56.9	56.7	56.4	56.3	56.2	56.2	56.9	59.2	63.7	63.8	66.6
4/F	65.3	65.5	63.2	62.4	61.8	61.4	61.0	60.8	60.4	60.1	59.7	59.4	59.1	58.7	58.4	58.1	57.8	57.6	57.0	56.8	56.6	56.4	56.2	56.2	56.2	56.9	59.2	63.6	63.8	66.5
5/F	65.2	65.4	63.1	62.3	61.7	61.2	60.9	60.7	60.3	60.0	59.7	59.3	59.1	58.7	58.3	58.0	57.7	57.5	57.0	56.8	56.6	56.4	56.2	56.2	56.2	56.9	59.2	63.6	63.7	66.4
6/F	65.0	65.3	62.9	62.1	61.5	61.1	60.7	60.5	60.2	59.9	59.5	59.3	59.0	58.6	58.3	57.9	57.7	57.5	56.9	56.7	56.5	56.3	56.2	56.2	56.1	56.9	59.1	63.5	63.7	66.2
7/F	64.8	65.1	62.7	62.0	61.3	60.9	60.6	60.4	60.1	59.8	59.4	59.2	58.9	58.5	58.1	57.9	57.6	57.4	56.9	56.7	56.5	56.3	56.1	56.1	56.1	56.9	59.1	63.5	63.6	66.1
8/F	64.6	64.9	62.6	61.8	61.2	60.8	60.5	60.3	60.0	59.7	59.3	59.1	58.8	58.4	58.1	57.8	57.6	57.3	56.8	56.7	56.5	56.2	56.1	56.1	56.1	56.9	59.0	63.4	63.5	66.0
9/F	64.4	64.7	62.4	61.6	61.0	60.7	60.3	60.2	59.9	59.6	59.2	59.0	58.7	58.4	58.0	57.7	57.5	57.3	56.8	56.6	56.4	56.2	56.1	56.1	56.1	56.8	59.0	63.3	63.5	65.8
10/F	64.3	64.6	62.3	61.5	60.9	60.5	60.2	60.0	59.7	59.5	59.1	58.9	58.6	58.3	57.9	57.6	57.4	57.2	56.7	56.6	56.4	56.2	56.0	56.0	56.1	56.8	58.9	63.2	63.4	65.7
11/F	64.1	64.4	62.1	61.4	60.7	60.4	60.1	59.9	59.6	59.4	59.0	58.8	58.5	58.2	57.8	57.5	57.3	57.1	56.7	56.5	56.3	56.1	56.0	56.0	56.1	56.8	58.9	63.2	63.3	65.6
12/F	63.9	64.3	62.0	61.2	60.6	60.3	60.0	59.8	59.5	59.2	58.9	58.7	58.5	58.1	57.8	57.5	57.3	57.1	56.6	56.4	56.3	56.1	56.0	56.0	56.0	56.8	58.8	63.1	63.2	65.4
13/F	63.8	64.1	61.9	61.1	60.5	60.1	59.9	59.7	59.4	59.1	58.8	58.7	58.4	58.1	57.7	57.4	57.2	57.0	56.6	56.4	56.2	56.1	55.9	56.0	56.0	56.8	58.8	63.0	63.2	65.3
14/F	63.6	64.0	61.8	61.0	60.4	60.0	59.8	59.6	59.3	59.1	58.7	58.6	58.3	58.0	57.7	57.4	57.1	57.0	56.5	56.3	56.2	56.1	55.9	56.0	56.0	56.8	58.8	63.0	63.1	65.2
15/F	63.4	63.8	61.6	60.9	60.3	59.9	59.7	59.5	59.3	59.0	58.6	58.5	58.3	57.9	57.6	57.3	57.1	56.9	56.5	56.3	56.2	56.0	55.9	56.0	56.0	56.8	58.8	62.9	63.0	65.1
16/F	63.3	63.7	61.5	60.8	60.2	59.9	59.6	59.4	59.2	58.9	58.5	58.5	58.2	57.9	57.6	57.3	57.1	56.9	56.5	56.3	56.2	56.1	55.9	56.0	56.0	56.8	58.8	62.9	63.0	65.0

RCT610-4, Table Page 9 of 10

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (Unmitigated)

																Tower 6													
Level	631	632	633	634	635	636	637	638	639	640	641	642	643	644	645	646	647	648	649	650	651	652	653	654	655	656	657	658	659
G/F																													
1/F	66.7	66.8	66.8	66.8	66.9	66.9	66.9	66.9	66.8	66.8	66.8	66.9					66.9	66.9	66.8	66.4	67.2	67.2	67.2	67.1	67.1	67.2	67.2	67.3	67.6
T.P.																													
3/F	66.6	66.6	66.6	66.6	66.7	66.7	66.7	66.8	66.7	66.7	66.7	66.9	66.7	66.7	66.8	66.7	66.7	66.8	66.7	66.2	67.0	67.0	67.0	67.0	67.0	67.0	67.1	67.2	67.5
4/F	66.5	66.5	66.5	66.5	66.6	66.6	66.6	66.7	66.5	66.6	66.6	66.8	66.7	66.6	66.6	66.6	66.7	66.6	66.6	66.1	66.9	66.9	66.9	66.9	66.9	66.9	67.0	67.1	67.3
5/F	66.4	66.4	66.4	66.4	66.5	66.5	66.5	66.5	66.4	66.5	66.5	66.7	66.5	66.5	66.5	66.5	66.5	66.5	66.4	66.0	66.7	66.7	66.7	66.7	66.7	66.8	66.8	66.9	67.2
6/F	66.2	66.2	66.2	66.2	66.3	66.3	66.3	66.4	66.3	66.3	66.3	66.6	66.3	66.3	66.4	66.3	66.4	66.3	66.3	65.8	66.6	66.6	66.6	66.6	66.6	66.6	66.7	66.8	67.1
7/F	66.1	66.1	66.1	66.1	66.2	66.2	66.2	66.2	66.1	66.2	66.1	66.5	66.2	66.2	66.2	66.2	66.2	66.2	66.1	65.6	66.4	66.4	66.4	66.4	66.4	66.5	66.5	66.6	66.9
8/F	65.9	65.9	65.9	65.9	66.0	66.0	66.0	66.0	66.0	66.0	66.0	66.3	66.0	66.0	66.0	66.0	66.0	66.0	66.0	65.5	66.2	66.2	66.2	66.2	66.2	66.3	66.4	66.4	66.7
9/F	65.8	65.8	65.8	65.8	65.8	65.8	65.9	65.9	65.8	65.8	65.8	66.1	65.8	65.8	65.9	65.9	65.9	65.9	65.8	65.3	66.0	66.1	66.1	66.1	66.1	66.1	66.2	66.3	66.5
10/F	65.6	65.6	65.6	65.7	65.7	65.7	65.7	65.7	65.6	65.7	65.7	66.0	65.7	65.7	65.7	65.7	65.7	65.7	65.6	65.1	65.9	65.9	65.9	65.9	65.9	65.9	66.0	66.1	66.4
11/F	65.5	65.4	65.5	65.5	65.5	65.5	65.5	65.6	65.5	65.5	65.5	65.8	65.5	65.5	65.5	65.5	65.5	65.5	65.4	65.0	65.7	65.7	65.7	65.7	65.7	65.8	65.8	66.0	66.2
12/F	65.3	65.3	65.3	65.4	65.4	65.4	65.4	65.4	65.3	65.4	65.4	65.7	65.4	65.4	65.4	65.4	65.4	65.4	65.3	64.8	65.5	65.6	65.6	65.6	65.6	65.6	65.7	65.8	66.0
13/F	65.2	65.2	65.2	65.2	65.2	65.2	65.2	65.3	65.2	65.2	65.2	65.5	65.2	65.2	65.2	65.2	65.2	65.2	65.1	64.6	65.4	65.4	65.4	65.4	65.4	65.5	65.5	65.6	65.9
14/F	65.1	65.0	65.0	65.0	65.1	65.1	65.1	65.1	65.1	65.1	65.1	65.3	65.1	65.1	65.1	65.0	65.1	65.0	64.9	64.5	65.2	65.2	65.2	65.2	65.3	65.3	65.4	65.5	65.7
15/F	64.9	64.9	64.9	64.9	64.9	65.0	65.0	65.0	64.9	65.0	64.9	65.2	64.9	64.9	64.9	64.9	64.9	64.9	64.8	64.3	65.1	65.1	65.1	65.1	65.1	65.2	65.2	65.3	65.6
16/F	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8	64.8	65.1	64.8	64.8	64.8	64.8	64.8	64.8	64.7	64.2	64.9	64.9	65.0	64.9	65.0	65.0	65.1	65.2	65.4

RCT610-4, Table Page 10 of 10

APPENDIX 4

MEASUREMENT RESULTS, SWL CALCULATIONS

Report: 22610-N1

Source ID: A (Fan Keung Kee)

Photos taken on 30 April 2025



No operation was observed during site survey

Photos taken on 31 March 2022



Photos taken on 4 April 2022



No night-time operation

Photo taken in 2016



Lorry with crane was observed

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: B (Shing Fat Logistics "the godown")

Photos taken on 30 April 2025



The godown no longer exists, without any operation.

Photos taken on 31 March 2022



The godown was closed and no longer exists, without any operation.

Photos taken on 4 April 2022



No night-time operation

Photo taken in 2017





Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: C (Chuk Yuen Floodwater Pumping Station)

Photos taken on 30 April 2025



Photos taken on 31 March 2022

Photos taken on 4 April 2022





Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: D (Construction Site)

Photos taken on 30 April 2025



Construction site of Yau Pok Road Light Public Housing

Photos taken on 26 May 2022



Storage and site office use, no industrial noise observed



Photos taken on 4 April 2022



No night-time operation

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: E (Hung Fai, office use)

Photos taken on 30 April 2025



Office use, no industrial noise observed



Office use, no industrial noise observed

Photos taken on 26 May 2022



Another office adjoining Hung Fai, Grandtec Construction Limited. Office use also, no industrial noise observed



Office use, no industrial noise observed

Photos taken on 4 April 2022



No night-time operation

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: F (Open Storage, storage and parking use only)

Photos taken on 30 April 2025



The gate was closed, no industrial noise observed.

Photos taken on 31 March and 26 May 2022







Photos taken on 4 April 2022



No night-time operation

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: G (Wai Kwong Luen Logistic Company, parking and office use)

Photos taken on 30 April 2025



The gate was closed without operation, no industrial noise observation



Photos taken on 26 May 2022



Parking and office only, no industrial noise observed



Photos taken on 4 April 2022



No night-time operation

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: H (Kin Tak car repairing workshop)

Photos taken on 30 April 2025



The workshop is renamed as "Kin Tak". The gate was closed without operation, no industrial noise was observed.

Photos taken on 31 March 2022



Noise of pneumatic screwdriver was observed



With some gaps for the steel cover. The workshop is partially blocked by temporary structure on 3-sides with the opening facing south.

Photos taken on 4 April 2022



No night-time operation

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source IDs: J - M (Car repairing workshop / Shop)

Photos taken on 30 April 2025

Source ID: M Source ID: L (no longer exists)

Source ID: K

Source ID: J



Photos taken on 31 March 2022

Source ID: M Source ID: L

Source ID: K

Source ID: J



Photos taken on 31 March 2022

Photos taken on 4 April 2022





Noise of pneumatic screwdriver was observed



No night-time operation

Westwood Hong & Associates Ltd

PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source IDs: J - M (Car repairing workshop / Shop)

Photos taken on 31 March 2025

Source ID: K (Akina Auto Center)



Noise of pneumatic screwdriver was observed

Photos taken on 4 April 2022



No night-time operation

Photos taken on 30 April 2025

Source ID: L and M (Sum Mei Store and Chin Hung car repairing workshop)



The store / workshop no longer exists

Photos taken on 4 April 2022





Westwood Hong & Associates Ltd

PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: N (Sun Hing car repairing workshop)

Photos taken on 30 April 2025



service Service

No industrial noise was observed

Photos taken on 31 March 2022



Noise of pneumatic screwdriver was observed

Photos taken on 4 April 2022



No night-time operation

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: P (Classic Motor Service Ltd.)

Photos taken on 30 April 2025





Office use, no industrial noise was observed

Photos taken on 31 March 2022



Office use, no industrial noise was observed

Photos taken on 4 April 2022



No night-time operation

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: Q (Lung Yee car repairing workshop)

Photos taken on 30 April 2025



Noise of pneumatic screwdriver was observed

Photos taken on 31 March 2022





Noise of pneumatic screwdriver was observed

Photos taken on 4 April 2022



No night-time operation

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE


Source ID: R (Hing Lee car repairing workshop)

Photos taken on 30 April 2025



Noise of pneumatic screwdriver was observed

Photos taken on 31 March 2022





Noise of pneumatic screwdriver was observed

Photos taken on 4 April 2022



No night-time operation

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources


FIGURE

Source ID: S (Wing Tai Tyre)

Photos taken on 30 April 2025



Photos taken on 31 March 2022





Noise of pneumatic screwdriver was observed



No night-time operation

Source ID: T (Petro Filling Station)

Photos taken on 30 April 2025



Photos taken on 31 March 2022

Photos taken on 4 April 2022



No industrial noise was observed



No industrial noise was observed

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: U (Alicar Fairview Workshop, car washing centre)

Photos taken on 30 April 2025



Water pump noise and noise of compressed air gun, vacuum cleaner and water jetting noise were observed. All the activities were taken place under the steel plate

Photos taken on 31 March 2022 and 26 May 2022









Water pump noise and noise of compressed air gun, vacuum cleaner and water jetting noise were observed. All the activities were taken place under the steel plate

Photos taken on 4 April 2022



With night-time operation

Westwood Hong & Associates Ltd

PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: V (Ka Fu car repairing workshop)

Photos taken on 30 April 2025



The workshop closed, no longer exists

Photos taken on 31 March 2022



Noise of pneumatic screwdriver was observed

Photos taken on 4 April 2022



No night-time operation

Photos taken on 8 March 2023



The workshop closed, no longer exists

Source ID: W (Fugro warehouse, storage use)

Photos taken on 30 April 2025



No industrial noise was observed

Photos taken on 31 March 2022



Photos taken on 26 May 2022



Warehouse with storage use.
Minor Loading and unloading noise
was observed

Photos taken on 8 March 2023



No night-time operation

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE


Source ID: Y (temporary structure with office use)

Photos taken on 30 April 2025

Front Side:-



Office use. Condenser noise was observed



Condenser

Photos taken on 31 March 2022 and 26 May 2022



Office use. Condenser noise was observed



Photos taken on 4 April 2022



No night-time operation



Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: Z (open storage, storage use)

Photos taken on 30 April 2025



Photos taken on 31 March 2022 and 26 May 2022









Storage use. No industrial noise was observed

Photos taken on 4 April 2022





No night-time operation

Westwood Hong & Associates Ltd

PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: AA (car repairing workshop)

Photos taken on 30 April 2025



No industrial noise was observed.

Photos taken on 31 March 2022



Gate was closed.

Photos taken on 26 May 2022



No night-time operation

Photos taken on 8 March 2023



No industrial noise was observed.

Source ID: AB (Open yard of construction materials)

Photos taken on 30 April 2025



No industrial noise was observed

Photos taken on 26 May 2022



No industrial noise was observed.

Photos taken on 8 March 2023



Lorry with crane was observed, but without operation.

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: AC (Top 1 Car Audio Workshop)

Photos taken on 30 April 2025



Audio installation workshop. No industrial noise was observed during site survey.

Photos taken on 8 March 2023



Audio installation workshop. No industrial noise was observed during site survey.

Source ID: AD (EV-Pro HK)

Photos taken on 30 April 2025



Car repairing workshop, but no industrial noise was observed during site survey.

Photos taken on 8 March 2023



Car repairing workshop, but no industrial noise was observed during site survey.

Westwood Hong & Associates Ltd

PROJECT:

22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Source ID: AE (KUAIFU)

Photos taken on 30 April 2025



Office use only. No industrial noise was observed.

Source ID: AF (Xinyi Automobile Glass Co. Ltd.)

Photos taken on 30 April 2025



Office use only. No industrial noise was observed.

Westwood Hong & Associates Ltd

PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Identified Fixed Noise Sources

FIGURE

Job no.: 22610

Table A4-1: Measurement data for 2014 - 2025

						Year	2014	Year	2016	Year	2017	Year 2018 Year 2019		Year	2021	Year 2022		Year	2025		
Sou	ce ID	Industrial Site	Fixed Noise Source	Measurement Point	Location	Date	SPL, Leq(5min), dB(A)	Date	SPL, Leq(5min), dB(A)	Date	SPL, Leq(5min), dB(A)	Date	SPL, Leq(5min), dB(A)	Date	SPL, Leq(5min), dB(A)	Date	SPL, Leq(5min), dB(A)	Date	SPL, Leq(5min), dB(A)	Date	SPL, Leq(5min), dB(A)
	A-1	Fan Keung Kee	Operating noise	Loc A-1	10m distance from source	04-Jul-14	66	31-Aug-16	62	23-Jun-17	65	14-Sep-18	64	22-May-19	65	12-Aug-21	65	31-Mar-22	-	30-Apr-25	-
۸	A-2	Fan Keung Kee	loading and unloading using forklift	Loc A-2	5m distance from source	04-Jul-14	69	31-Aug-16	68	23-Jun-17	69	14-Sep-18	68	22-May-19	69	12-Aug-21	-	31-Mar-22	-	30-Apr-25	-
A	A-3	Fan Keung Kee	Movement of lorry	Loc A-3	8m distance from source	04-Jul-14	73	31-Aug-16	72	23-Jun-17	72	14-Sep-18	72	22-May-19	72	12-Aug-21	71	31-Mar-22	-	30-Apr-25	_
	A-4	Fan Keung Kee	lifting of precast untis using a lorry with crane	Loc A-4	10m distance from source	04-Jul-14	69	31-Aug-16	69	23-Jun-17	69	14-Sep-18	68	22-May-19	69	12-Aug-21	-	31-Mar-22	-	30-Apr-25	_
В	B-1	Shing Fat Logistics	loading and unloading using forklift	Loc B-1	10m distance from source	04-Jul-14	63	31-Aug-16	62	23-Jun-17	63	14-Sep-18	63	22-May-19	63	12-Aug-21	62	31-Mar-22	-	30-Apr-25	no longer exists
В	B-2	Shing Fat Logistics	Movement of lorry	Loc B-2	7m distance from source	04-Jul-14	74	31-Aug-16	72	23-Jun-17	73	14-Sep-18	72	22-May-19	73	12-Aug-21	73	31-Mar-22	-	30-Apr-25	no longer exists
н		Kam Wing car repairing workshop	noise of Pneumatic screwdriver	Loc H	8m distance from source													31-Mar-22	67	30-Apr-25	_
J		Sun Chun Car Shop	noise of Pneumatic screwdriver	Loc J	9m distance from source													31-Mar-22	68	30-Apr-25	66
к		Akina Auto Center	noise of Pneumatic screwdriver	Loc K	8m distance from source													31-Mar-22	67	30-Apr-25	_
М		Chin Hung Car Repairing Workshop	Air comressor noise	Loc M	8m distance from source													31-Mar-22	70	30-Apr-25	no longer exists
N		Sun Hing Car Repairing Workshop	noise of Pneumatic screwdriver	Loc N	8m distance from source													31-Mar-22	66	30-Apr-25	_
Q		Lung Yee Car Repairing Workshop	noise of Pneumatic screwdriver	Loc Q	5m distance from source													31-Mar-22	70	30-Apr-25	68
R		Hing Lee Car Repairing Workshop	noise of Pneumatic screwdriver	Loc R	5m distance from source													31-Mar-22	68	30-Apr-25	66
s		Wing Tai Tyre	noise of Pneumatic screwdriver	Loc S	5m distance from source													31-Mar-22	69	30-Apr-25	-
U		Alicar Fairview Workshop	Noise of watering jetting, compressed air gun and vacuum cleaner and pump noise	Loc U	10m distance from source													26-May-22	70	30-Apr-25	68
V		Ka Fu Car Repairing Workshop	noise of Pneumatic screwdriver	Loc V	8m distance from source													31-Mar-22	66	30-Apr-25	no longer exists
w		Fugro warehouse	loading and unloading	Loc W	3m distance from source													26-May-22	72	30-Apr-25	-
Y		Office	Condenser	Loc Y	2m distance from source													26-May-22	78	30-Apr-25	75

Remark:

The selected SPL will be adopted for calculating the SWL (a comparison is made for year 2014 to 2025 and the maximum among these values is selected in order to preserve conservatism)

Job no.: 22610

Table A4-2: Summary of Sound Power Levels of Fixed Noise Sources

Source ID	Industrial Site	Fixed Noise Sources	Measured Sound Pressure Levels, dB(A)	Measured Distance from noise source (m)	Correction to single no. of source, dB(A)	Distance Correction, dB(A)	Correction for Tonal, dB(A)	Sound Power Levels, dB(A)	Sound Power Levels adopted in the Fixed Noise Sources Assessment, dB(A)
A-1		Operating noise	66	10	0	28	0	94	
A-2	Fan Keung Kee	Loading and unloading using Forklift	69	5	0	22	0	91	102
A-3	r an Neung Nee	Movement of Lorry	73	8	0	26	0	99	102
A-4		Lifting of precast units using a lorry with crane	69	10	0	28	0	97	
B-1	China Fat Lagistics (11th a godoum 11)	Loading and unloading using Forklift	63	10	0	28	0	91	100
B-2	Shing Fat Logistics ("the godown")	Movement of Lorry	74	7	0	25	0	99	100
С	Chuk Yuen Floodwater Pumping Station	Operating noise	-		(SWL referened to EIA	report)		-	79
Н	Kam Wing car repairing workshop	Noise of Pneumatic screwdriver	67	8	0	26	0	93	93
J	Sun Chun Car Shop	Noise of Pneumatic screwdriver	68	9	0	27	0	95	95
К	Akina Auto Center	Noise of Pneumatic screwdriver	67	8	0	26	0	93	93
N	Sun Hing Car Repairing Workshop	Noise of Pneumatic screwdriver	66	8	0	26	0	92	92
Q	Lung Yee Car Repairing Workshop	Noise of Pneumatic screwdriver	70	5	0	22	0	92	92
R	Hing Lee Car Repairing Workshop	Noise of Pneumatic screwdriver	68	5	0	22	0	90	90
S	Wing Tai Tyre	Noise of Pneumatic screwdriver	69	5	0	22	0	91	91
U	Alicar Fairview Workshop	Noise of compressed air gun, water jetting and vacuum cleaner, and pump noise	70	10	0	28	0	98	101 ^[1]
w	Fugro warehouse	Loading and unloading	72	3	0	18	0	90	90
Y	Office	Condenser	78	2	0	14	0	92	92
Z	Open storage	Loading and unloading assumed	-		Referenced to Source	e ID: A		-	102
AA	Car repairing workshop	Noise of Pneumatic screwdriver assumed	-		Referenced to Source	e ID: J		-	95
АВ	Open storage of construction materials	Loading and unloading assumed	-		Referenced to Source	e ID: A		-	102
AC	Top 1 Car Audio Workshop	Noise of Pneumatic screwdriver assumed	-		Referenced to Source	e ID: J		-	95
AD	EV-Pro HK	Noise of Pneumatic screwdriver assumed	-	Referenced to Source ID: J			-	95	
ВВ	Planned car testing centre	Noise of Pneumatic screwdriver assumed	-	Maximum Allowable SWL [2]			-	92	
СС	Planned car trading use	Noise of Pneumatic screwdriver assumed	-	Maximum Allowable SWL [3]				-	85
DD Note:	Planned vehicle repair workshop with ancillary office and storage use	Noise of Pneumatic screwdriver assumed	-		Maximum Allowable S	SWL ^[4]		-	91

Only half of the washing bays were occupied during the noise measurement. As a conservative approach, a correction of +3dB(A) to the SWL will be considered in the fixed noise assessment.

The distance between the planned car testing centre and its nearest NSR (i.e. Helene Terrace) is 28m. Hence, the maximum allowable SWL of the planned car testing centre is 55+37 = 92dB(A). [2]


^[3] The distance between the planned car trading use and its nearest NSR (i.e. Helene Terrace) is 12m. Hence, the maximum allowable SWL of the planned car testing centre is 55+30 = 85dB(A).

^{]4]} The distance between the planned car trading use and its nearest NSR (i.e. Meister House) is 25m. Hence, the maximum allowable SWL of the planned car testing centre is 55+36 = 91dB(A).

APPENDIX 5

FIXED NOISE SOURCES ASSESSMENT FOR THE PROPOSED DEVELOPMENT

Report: 22610-N1




22610 PROJECT:

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

Location of Representative NSRs for Fixed Noise Sources Assessment

A5-1




22610

PROJECT:

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

Location of Fixed Noise Sources and Representative NSRs in Proposed Development

A5-2



PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

Location of Fixed Noise Sources and Representative NSRs in Proposed Development

A5-3

Job No.: 22610

Scenario: Appendix 5 - Fixed Noise Sources Assessment for the Proposed Development

Calculation of Façade Noise Levels from Fixed Noise Sources (Day and Evening Time Periods)

Westwood Hong & Associates Ltd.

		NSR 501	NSR 520	NSR 601
Noise				
Sources	х	823474	823490.6	823422.3
	Υ	837358.6	837317.4	837401.3
•	CIMIL (D(A)	102	102	100
Α	SWL dB(A) CLsr dB(A)	102 -55	102 -54	102 -57
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	47	48	35
В	SWL dB(A)	100	100	100
	CLsr dB(A)	-54	-53	-57
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	46	47	33
С	SWL dB(A) CLsr dB(A)	79 -49	79 -52	79 -43
	Cbar dB(A)	-10	-10	0
	Sub-total dB(A)	20	17	36
Н	SWL dB(A)	93	93	93
	CLsr dB(A)	-57	-57	-58
	Cbar dB(A)	-10	-10	-10
	Sub-total dB(A)	26	26	25
J	SWL dB(A)	95 -59	95 -58	95 -60
	CLsr dB(A) Cbar dB(A)	-10	-10	-10
	Sub-total dB(A)	26	27	25
К	SWL dB(A)	93	93	93
	CLsr dB(A)	-59	-58	-60
	Cbar dB(A)	-10	-10	-10
	Sub-total dB(A)	24	25	23
N	SWL dB(A) CLsr dB(A)	92 -58	92 -57	92 -59
	CLsr dB(A) Cbar dB(A)	-58 0	-57	-59 -10
	Sub-total dB(A)	34	35	23
Q	SWL dB(A)	92	92	92
	CLsr dB(A)	-61	-60	-62
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	31	32	20
R	SWL dB(A)	90 -62	90 -62	90 -63
	CLsr dB(A) Cbar dB(A)	0	0	-10
	Sub-total dB(A)	28	28	17
s	SWL dB(A)	91	91	91
	CLsr dB(A)	-63	-62	-64
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	28	29	17
U	SWL dB(A) CLsr dB(A)	101 -61	101 -60	101 -62
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	40	41	29
W	SWL dB(A)	90	90	90
	CLsr dB(A)	-60	-59	-61
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	30	31	19
Υ	SWL dB(A) CLsr dB(A)	92 -59	92 -57	92 -60
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	33	35	22
Z	SWL dB(A)	102	102	102
	CLsr dB(A)	-56	-56	-58
	Cbar dB(A)	0	0	0
•••	Sub-total dB(A)	46	46	44
AA	SWL dB(A) CLsr dB(A)	95 -57	95 -56	95 -59
	Cbar dB(A)	-57	-56	-59 -10
	Sub-total dB(A)	38	39	26
AB	SWL dB(A)	102	102	102
	CLsr dB(A)	-62	-62	-62
	Cbar dB(A)	-10	-10	-10
**	Sub-total dB(A)	30	30	30
AC	SWL dB(A)	95 -61	95 -60	95 -62
	CLsr dB(A) Cbar dB(A)	0	0	-10
	Sub-total dB(A)	34	35	23
AD	SWL dB(A)	95	95	95
	CLsr dB(A)	-63	-62	-64
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	32	33	21
ВВ	SWL dB(A)	92 -60	92 -59	92 -60
	CLsr dB(A) Cbar dB(A)	-60	-59	-10
	Sub-total dB(A)	32	33	22
СС	SWL dB(A)	85	85	85
	CLsr dB(A)	-58	-57	-59
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	27	28	16
DD	SWL dB(A)	91	91	91
	CLsr dB(A)	-62 0	-62 0	-63 -10
	Cbar dB(A) Sub-total dB(A)	29	29	18
	Cfac dB(A)	3	3	3
	CNL dB(A)	55	56	49
	Noise Criteria dB(A)	60	60	60
	Compli-ance	YES	YES	YES

ion of terms:

- the sound power level of fixed noise source, dB(A)

- the correction for slant distance between the source and the NSR, dB(A)

- the number of items of plant operating simulataneously

- the facade correction, dB(A)

- the noise reduction by barrier, dB(A), -10dB(A) if the noise sources are totally screened by substantial barrier

- the corrected noise level, dB(A) Leq (30mins)

Ind22610-2a, (Appendix S), Day and Evening A, I of 1

Job No.: 22610

Scenario: Appendix 5 - Fixed Noise Sources Assessment for the Proposed Development

Calculation of Façade Noise Levels from Fixed Noise Sources (Day and Evening Time Periods)

Westwood Hong & Associates Ltd.

No.			NSR 112	NSR 122	NSR 125	NSR 126	NSR 139	NSR 150	NSR 226	NSR 227
March 100 10										
Curr May -19			037 132.7	037 139.0			037 130.4	637 130.7		637 176.4
Char (mol.) 2 2 0 1-9 1-10 1-10 1-10 0 1-10 Submitted (mol.) 6 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 6 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 6 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 6 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-10 1-10 1-10 1-10 1-10 1-10 1-10 1-10 1-10 Char (mol.) 7 1-10 1-1	Α									
B										
Class (Sept.) -20										
Charter Char	В									
Sub-total stay)										
Carronno 12										
Cher (70)	С	SWL dB(A)								
M										
Carr district	н	1 /								
Book cost allow) 26										
Section Sect										
Clast mone 452										
Ches drop() 1-10 1-10 1-10 0 0 0 0 1-10 0 0	J									
N										
Clast drips										
Cheer driv)	K									
Sub-cent (Soc) 31 31 31 42 42 42 30 30 30										
N										
Chest critics 1-10	N	SWL dB(A)	92	92		92	92	92	92	
Sub-total allow SS S8 36 47 46 44 33 32 12 12 12 12 12 12										
Clar miles										
Clast of the Chart of the Cha	Q									
Sub-stead (a)(v) 20 27 27 37 38 35 25 25		CLsr dB(A)	-56	-55	-55	-55	-56	-57	-57	-57
R										
Clar diply 5-50										
Char disp(s) 1-10	K	- '								
Section Sect										
CLar disp										
Chart rink A -10 -	S									
Sub-total al(b) 21										
Clar (80/c) -5-8 -57 -57 -57 -57 -57 -58 -										
Char (BN)	U	SWL dB(A)								
Sub-botal col(n) 33										
W SWL (SW) 90 90 90 90 90 90 90 9										
Char Sub-total All All	w									
Sub-total (8(h)) 24 25 25 35 34 33 23 23 23 Y SWL (8(h)) 92 92 92 92 92 92 92		CLsr dB(A)			-55	-55	-56	-57	-57	
Y SWL e(HA) 92 95 95 95 95 95 95 456 458 459 458 38 48 49 40 40 10 10 10 10 10 10 10 10 10										
CLsr dis(A) -56 -55 -55 -54 -54 -54 -56 -56 -56 -57										
Char disk) 0 0 0 0 0 0 0 0 0										
SWL cs(s) 102 103		Cbar dB(A)			-10	0	0	0	0	-10
Clar (18/4) -59 -50 -55 -5										
Char dB(A)	2									
AA SWL (8(A) 95 95 95 95 95 95 95 9										
CLsr dB(A) -56 -55 -55 -55 -56 -56 -57 -57 -57 -57 Cbar dB(A) 0 0 0 0 -10 -10 -10 0 -10 Sub-total dB(A) 39 40 40 29 29 28 38 38 28 SWL dB(A) 102 102 102 102 102 102 102 102 102 102 CLsr dB(A) -58 -58 -58 -58 -57 -57 -58 -58 Cbar dB(A) -10 -10 -10 0 0 0 0 -10 0 Sub-total dB(A) 34 34 34 44 45 45 45 34 44 AC SWL dB(A) 95 95 95 95 95 95 95 9										
Cbar dB(A) 0 0 0 -10 -10 -10 -10 0 -10	AA									
Sub-total dB(A) 39										
AB SWL dB(A) 102 103 103 144 44 45 45 45 34 44 44 45 45 45 34 44 44 44 45 45 34 44 44 44 45 45 45 95 95 95 95 95 95										
Cbar dB(A)	AB	SWL dB(A)	102	102	102	102	102	102	102	102
Sub-total dB(A) 34 34 34 44 45 45 45 34 44										
AC SWL dB(A) 95 95 95 95 95 95 95 9										
CLsr dB(A) -58 -57 -57 -57 -58 -59 -59 -59 -59 Cbar dB(A) -10 -10 -10 0 0 0 0 0 0 -10 Sub-total dB(A) 27 28 28 28 38 37 36 36 26 SWL dB(A) 95 95 95 95 95 95 95 9	AC									
Sub-total dB(A) 27 28 28 38 37 36 36 26		CLsr dB(A)	-58	-57	-57	-57	-58	-59	-59	-59
AD SWL dB(A) 95 95 95 95 95 95 95 9										
CLsr dB(A) -60 -59 -59 -59 -59 -60 -60 -60 -60 Cbar dB(A) -10 -10 -10 0 0 0 0 -60 -60 -60 Sub-total dB(A) 25 26 26 26 36 36 35 35 25 SWL dB(A) 92 <t< th=""><th>AD</th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th><th></th></t<>	AD									
Cbar dB(A)	AU									
Sub-total dB(A) 25 26 26 36 36 36 35 35 25			-10	-10	-10	0	0	0	0	-10
CLsr dB(A) -53 -52 -52 -51 -52 -53 -54 -54 Cbar dB(A) -10 -10 -10 -10 50 451 0 65 85 </th <th></th> <th>Sub-total dB(A)</th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th> <th></th>		Sub-total dB(A)								
Cbar dB(A) -10 -10 -10 0 0 0 0 0 0 Sub-total dB(A) 29 30 30 41 40 39 38 38 CS SWL dB(A) 85 85 85 85 85 85 85 85 CLar dB(A) -49 -47 -47 -46 -48 -49 -50 -51 Cbar dB(A) -10 -10 -10 0 0 0 -10 -10 Sub-total dB(A) 26 28 28 39 37 36 25 24 DD SWL dB(A) 91 <	BB									
Sub-total dB(A) 29 30 30 41 40 39 38 38 38										
CC SWL dB(A) 85										
Cbar dB(A)	CC	SWL dB(A)								
Sub-total dB(A) 26 28 28 39 37 36 25 24										
SWL dB(A) 91 91 91 91 91 91 91 9										
CLsr dB(A) -59 -59 -59 -58 -59 -60 -60 -60 Cbar dB(A) -10 -10 -10 0 0 -10 -10 -10 Sub-total dB(A) 22 22 22 22 33 32 31 21 21 21 Cfac dB(A) 3 3 3 3 3 3 3 3 3 CNL dB(A) 58 60 60 58 57 56 57 53 Noise Criteria dB(A) 60 60 60 60 60 60 60	DD									
Sub-total dB(A) 22 22 22 33 32 31 21 21 Cfac dB(A) 3 5 56 57 53 56 57 53 53 50 60		CLsr dB(A)								
Cfac dB(A) 3 5 6										
CNL dB(A) 58 60 60 58 57 56 57 53 Noise Criteria dB(A) 60 60 60 60 60 60 60 60										
Noise Criteria dB(A) 60 60 60 60 60 60										
Compiliance										
		Compil-ance	YES	YES	YES	YES	YES	YES	YES	YES

Defini SWL CLsr No. Cfac Cbar CNL

tion of terms:

- the sound power level of fixed noise source, dB(A)

- the correction for slant distance between the source and the NSR, dB(A)

- the number of items of plant operating simulataneously

- the facade correction, dB(A)

- the noise reduction by barrier, dB(A), -10dB(A) if the noise sources are totally screened by substantial barrier

- the corrected noise level, dB(A) Leq (30mins)

Ind22610-2a, (Appendix S), Day and Evening B, 1 of 1

Job No.: 22610

Scenario: Appendix 5 - Fixed Noise Sources Assessment for the Proposed Development

Calculation of Façade Noise Levels from Fixed Noise Sources (Night Time Period)

Westwood Hong & Associates Ltd.

		NSR 501	NSR 520	NSR 601
Noise				
Sources	X	823474	823490.6	823422.3
	Y	837358.6	837317.4	837401.3
Α	SWL dB(A)	0	0	0
	CLsr dB(A)	-55	-54	-57
	Cbar dB(A)	0	0	-10
В	Sub-total dB(A)	0	0	0
ь	SWL dB(A) CLsr dB(A)	-54	-53	-57
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	0	0	0
С	SWL dB(A)	79	79	79
	CLsr dB(A)	-49	-52	-43
	Cbar dB(A)	-10 20	-10 17	0 36
Н	Sub-total dB(A) SWL dB(A)	0	0	0
	CLsr dB(A)	-57	-57	-58
	Cbar dB(A)	-10	-10	-10
	Sub-total dB(A)	0	0	0
J	SWL dB(A)	0	0	0
	CLsr dB(A)	-59	-58	-60
	Cbar dB(A)	-10 0	-10 0	-10 0
К	Sub-total dB(A) SWL dB(A)	0	0	0
	CLsr dB(A)	-59	-58	-60
	Cbar dB(A)	-10	-10	-10
	Sub-total dB(A)	0	0	0
N	SWL dB(A)	0	0	0
	CLsr dB(A)	-58	-57	-59 -10
	Cbar dB(A) Sub-total dB(A)	0	0	-10 0
Q	SWL dB(A)	0	0	0
	CLsr dB(A)	-61	-60	-62
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	0	0	0
R	SWL dB(A)	0	0	0
	CLsr dB(A)	-62 0	-62 0	-63 -10
	Cbar dB(A) Sub-total dB(A)	0	0	-10
s	SWL dB(A)	0	0	0
	CLsr dB(A)	-63	-62	-64
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	0	0	0
U	SWL dB(A)	101	101	101
	CLsr dB(A) Cbar dB(A)	-61 0	-60 0	-62 -10
	Sub-total dB(A)	40	41	29
w	SWL dB(A)	0	0	0
	CLsr dB(A)	-60	-59	-61
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	0	0	0
Y	SWL dB(A)	0	-57	0
	CLsr dB(A) Cbar dB(A)	-59 0	-57	-60 -10
	Sub-total dB(A)	0	0	0
z	SWL dB(A)	0	0	0
	CLsr dB(A)	-56	-56	-58
	Cbar dB(A)	0	0	0
	Sub-total dB(A)	0	0	0
AA	SWL dB(A)	-57	-56	-59
	CLsr dB(A) Cbar dB(A)	-57	-56 0	-59 -10
	Sub-total dB(A)	0	0	0
AB	SWL dB(A)	0	0	0
	CLsr dB(A)	-62	-62	-62
	Cbar dB(A)	-10	-10	-10
40	Sub-total dB(A)	0	0	0
AC	SWL dB(A)	0 -61	-60	-62
	CLsr dB(A) Cbar dB(A)	-61	-60	-62
	Sub-total dB(A)	0	0	0
AD	SWL dB(A)	0	0	0
	CLsr dB(A)	-63	-62	-64
	Cbar dB(A)	0	0	-10
PP	Sub-total dB(A)	0	0	0
ВВ	SWL dB(A)	-60	-59	-60
	CLsr dB(A) Cbar dB(A)	-60	-59	-60
	Sub-total dB(A)	0	0	0
СС	SWL dB(A)	0	0	0
	CLsr dB(A)	-58	-57	-59
	Cbar dB(A)	0	0	-10
	Sub-total dB(A)	0	0	0
DD	SWL dB(A)	0	0	0
	CLsr dB(A)	-62 0	-62 0	-63 -10
	Cbar dB(A) Sub-total dB(A)	0	0	-10
	Cfac dB(A)	3	3	3
	CNL dB(A)	43	44	40
	Noise Criteria dB(A)	50	50	50
	Compli-ance	YES		
	1		YES	YES

ion of terms:

- the sound power level of fixed noise source, dB(A)

- the correction for slant distance between the source and the NSR, dB(A)

- the number of items of plant operating simulataneously

- the facade correction, dB(A)

- the noise reduction by barrier, dB(A), -10dB(A) if the noise sources are totally screened by substantial barrier

- the corrected noise level, dB(A) Leq (30mins)

Ind22610-2a, (Appendix S), Night A, 1 of 1

Westwood Hong & Associates Ltd.

Job No.: 22610

Scenario: Appendix 5 - Fixed Noise Sources Assessment for the Proposed Development
Calculation of Façade Noise Levels from Fixed Noise Sources (Night Time Period)

		NSR 112	NSR 122	NSR 125	NSR 126	NSR 139	NSR 150	NSR 226	NSR 227
Noise									
Sources	Х	823422.1	823444	823450.3	823441.9	823414.9	823392.2	823413.9	823399.6
	Y	837152.7	837139.6	837136.1	837124	837138.4	837150.7	837176.8	837178.4
Α	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-49 0	-47 0	-46 0	-47 -10	-49 -10	-51 -10	-50 0	-51 -10
	Cbar dB(A) Sub-total dB(A)	0	0	0	-10	-10	-10	0	-10
В	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-53	-52	-52	-52	-53	-54	-53	-54
	Cbar dB(A) Sub-total dB(A)	0	0	0	-10 0	-10 0	-10 0	0	-10 0
С	SWL dB(A)	79	79	79	79	79	79	79	79
	CLsr dB(A)	-58	-58	-58	-58	-58	-58	-57	-57
	Cbar dB(A)	0 21	0 21	0 21	0 21	0 21	0 21	0 22	0 22
н	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-47	-47	-48	-46	-45	-46	-49	-48
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	0
J	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
_	CLsr dB(A)	-52	-52	-52	-51	-51	-51	-53	-53
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	0
К	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
K	CLsr dB(A)	-52	-52	-52	-51	-51	-51	-53	-53
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
	Sub-total dB(A)	0	0	0	0	0	0	0	0
N	SWL dB(A) CLsr dB(A)	0 -47	0 -46	0 -46	0 -45	0 -46	0 -48	0 -49	-50
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
	Sub-total dB(A)	0	0	0	0	0	0	0	0
Q	SWL dB(A)	0 -56	-55	-55	-55	-56	-57	-57	-57
	CLsr dB(A) Cbar dB(A)	-56 -10	-55 -10	-55 -10	-55 0	-56 0	-57	-57 -10	-57 -10
	Sub-total dB(A)	0	0	0	0	0	0	0	0
R	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A) Cbar dB(A)	-59 -10	-58 -10	-58 -10	-58 0	-59 0	-59 0	-60 -10	-60 -10
	Sub-total dB(A)	0	0	0	0	0	0	0	0
S	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-60 -10	-59 -10	-59 -10	-59 0	-59 0	-60 0	-60 -10	-60 -10
	Cbar dB(A) Sub-total dB(A)	0	0	0	0	0	0	0	0
U	SWL dB(A)	101	101	101	101	101	101	101	101
	CLsr dB(A)	-58	-57	-57	-57	-57	-58	-58	-58
	Cbar dB(A) Sub-total dB(A)	-10 33	-10 34	-10 34	0 44	0 44	0 43	-10 33	-10 33
w	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-56	-55	-55	-55	-56	-57	-57	-57
	Cbar dB(A)	-10 0	-10 0	-10 0	0	0	0	-10 0	-10 0
Y	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-56	-55	-54	-54	-56	-56	-56	-57
	Cbar dB(A)	0	0	-10	0	0	0	0	-10
Z	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
_	CLsr dB(A)	-59	-59	-58	-59	-59	-60	-59	-59
	Cbar dB(A)	0	0	0	-10	-10	-10	0	-10
AA	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
AA	CLsr dB(A)	-56	-55	-55	-56	-56	-57	-57	-57
	Cbar dB(A)	0	0	0	-10	-10	-10	0	-10
AB	Sub-total dB(A)	0	0	0	0	0	0	0	0
AB	SWL dB(A) CLsr dB(A)	0 -58	0 -58	-58	-58	-57	0 -57	-58	0 -58
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	0
	Sub-total dB(A)	0	0	0	0	0	0	0	0
AC	SWL dB(A) CLsr dB(A)	0 -58	-57	-57	-57	0 -58	0 -59	-59	0 -59
	Cbar dB(A)	-10	-10	-10	0	0	0	0	-10
	Sub-total dB(A)	0	0	0	0	0	0	0	0
AD	SWL dB(A)	-60	-59	0 -59	0 -59	0 -59	-60	-60	-60
	CLsr dB(A) Cbar dB(A)	-10	-10	-10	-59	-59	-60	-60	-10
	Sub-total dB(A)	0	0	0	0	0	0	0	0
ВВ	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A) Cbar dB(A)	-53 -10	-52 -10	-52 -10	-51 0	-52 0	-53 0	-54 0	-54 0
	Sub-total dB(A)	0	0	0	0	0	0	0	0
СС	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-49 -10	-47 -10	-47 -10	-46 0	-48 0	-49 0	-50 -10	-51 -10
	Cbar dB(A) Sub-total dB(A)	-10	-10	-10	0	0	0	-10	-10
DD	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-59	-59	-59	-58	-59	-60	-60	-60
	Cbar dB(A) Sub-total dB(A)	-10 0	-10 0	-10 0	0	0	0	-10 0	-10 0
	Cfac dB(A)	3	3	3	3	3	3	3	3
	CNL dB(A)	37	37	38	47	47	46	36	36
	Noise Criteria dB(A)	50	50	50	50	50	50	50	50
1	Compli-ance	YES							

Defin SWL CLsr No. Cfac Cbar CNL

tion of terms:

- the sound power level of fixed noise source, dB(A)

- the correction for slant distance between the source and the NSR, dB(A)

- the number of items of plant operating simulataneously

- the facade correction, dB(A)

- the noise reduction by barrier, dB(A), -10dB(A) if the noise sources are totally screened by substantial barrier

- the corrected noise level, dB(A) Leq (30mins)

Ind22610-2a, (Appendix S), Night B, 1 of 1

APPENDIX 6

CUMULATIVE FIXED NOISE SOURCES CALCULATIONS

Report: 22610-N1

Westwood Hong & Associates Ltd.

Job Title: Residential Development at Kam Pok Road

Job No.: 22610

Scenario: Appendix 6 - Cumulative Fixed Noise Sources Assessment for the Proposed Development

Calculation of Façade Noise Levels from Fixed Noise Sources (Day and Evening Time Periods)

		NSR 112	NSR 122	NSR 125	NSR 126	NSR 139	NSR 150	NSR 226	NSR 227
Noise Sources	x	823422.1	823444	823450.3	823441.9	823414.9	823392.2	823413.9	823399.6
oour ces	Y	837152.7	837139.6	837136.1	837124	837138.4	837150.7	837176.8	837178.4
A	SWL dB(A)	102	102	102	102	102	102	102	102
^	CLsr dB(A)	-49	-47	-46	-47	-49	-51	-50	-51
	Cbar dB(A)	0	0	0	-10	-10	-10	0	-10
В	Sub-total dB(A) SWL dB(A)	53 100	55 100	56 100	45 100	43 100	41 100	52 100	41 100
	CLsr dB(A)	-53	-52	-52	-52	-53	-54	-53	-54
	Cbar dB(A)	0	0	0	-10	-10	-10	0	-10
С	Sub-total dB(A) SWL dB(A)	47 79	48 79	48 79	38 79	37 79	36 79	47 79	36 79
-	CLsr dB(A)	-58	-58	-58	-58	-58	-58	-57	-57
	Cbar dB(A)	0	0	0	0	0	0	0	0
н	Sub-total dB(A) SWL dB(A)	21 93	21 93	21 93	21 93	21 93	21 93	22 93	22 93
	CLsr dB(A)	-47	-47	-48	-46	-45	-46	-49	-48
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	0
J	Sub-total dB(A) SWL dB(A)	36 95	36 95	35 95	47 95	48 95	47 95	34 95	45 95
	CLsr dB(A)	-52	-52	-52	-51	-51	-51	-53	-53
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	0
К	Sub-total dB(A) SWL dB(A)	33 93	93	93	44 93	93	93	32 93	42 93
	CLsr dB(A)	-52	-52	-52	-51	-51	-51	-53	-53
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
N	Sub-total dB(A)	31 92	31 92	31	42 92	42 92	42	30	30 92
.,	SWL dB(A) CLsr dB(A)	92 -47	92 -46	92 -46	92 -45	92 -46	92 -48	92 -49	-50
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
	Sub-total dB(A)	35	36	36	47	46	44	33	32
Q	SWL dB(A) CLsr dB(A)	92 -56	92 -55	92 -55	92 -55	92 -56	92 -57	92 -57	92 -57
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
	Sub-total dB(A)	26	27	27	37	36	35	25	25
R	SWL dB(A) CLsr dB(A)	90 -59	90 -58	90 -58	90 -58	90 -59	90 -59	90 -60	90 -60
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
	Sub-total dB(A)	21	22	22	32	31	31	20	20
S	SWL dB(A) CLsr dB(A)	91 -60	91 -59	91 -59	91 -59	91 -59	91 -60	91 -60	91 -60
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
	Sub-total dB(A)	21	22	22	32	32	31	21	21
U	SWL dB(A) CLsr dB(A)	101 -58	101 -57	101 -57	101 -57	101 -57	101 -58	101 -58	101 -58
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
	Sub-total dB(A)	33	34	34	44	44	43	33	33
w	SWL dB(A) CLsr dB(A)	90 -56	90 -55	90 -55	90 -55	90 -56	90 -57	90 -57	90 -57
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
	Sub-total dB(A)	24	25	25	35	34	33	23	23
Y	SWL dB(A) CLsr dB(A)	92 -56	92 -55	92 -54	92 -54	92 -56	92 -56	92 -56	92 -57
	Cbar dB(A)	0	0	-10	0	0	0	0	-10
	Sub-total dB(A)	36	37	28	38	36	36	36	25
z	SWL dB(A) CLsr dB(A)	102 -59	102 -59	102 -58	102 -59	102 -59	102 -60	102 -59	102 -59
	Cbar dB(A)	0	0	0	-10	-10	-10	0	-10
	Sub-total dB(A)	43	43	44	33	33	32	43	33
AA	SWL dB(A) CLsr dB(A)	95 -56	95 -55	95 -55	95 -56	95 -56	95 -57	95 -57	95 -57
	Cbar dB(A)	0	0	0	-10	-10	-10	0	-10
	Sub-total dB(A)	39	40	40	29	29	28	38	28
AB	SWL dB(A) CLsr dB(A)	102 -58	102 -58	102 -58	102 -58	102 -57	102 -57	102 -58	102 -58
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	0
	Sub-total dB(A)	34	34	34	44	45	45	34	44
AC	SWL dB(A) CLsr dB(A)	95 -58	95 -57	95 -57	95 -57	95 -58	95 -59	95 -59	95 -59
	Cbar dB(A)	-10	-10	-10	0	0	0	0	-10
AD	Sub-total dB(A)	27	28	28	38	37	36	36	26 05
AD	SWL dB(A) CLsr dB(A)	95 -60	95 -59	95 -59	95 -59	95 -59	95 -60	95 -60	95 -60
	Cbar dB(A)	-10	-10	-10	0	0	0	0	-10
P.5	Sub-total dB(A)	25	26	26	36	36	35	35	25
BB	SWL dB(A) CLsr dB(A)	92 -53	92 -52	92 -52	92 -51	92 -52	92 -53	92 -54	92 -54
	Cbar dB(A)	-10	-10	-10	0	0	0	0	0
00	Sub-total dB(A)	29	30	30	41	40	39	38	38
CC	SWL dB(A) CLsr dB(A)	85 -49	85 -47	85 -47	85 -46	85 -48	85 -49	-50	85 -51
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
	Sub-total dB(A)	26	28	28	39	37	36	25	24
DD	SWL dB(A) CLsr dB(A)	91 -59	91 -59	91 -59	91 -58	91 -59	91 -60	91 -60	91 -60
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
	Sub-total dB(A)	22	22	22	33	32	31	21	21
	Cfac dB(A)	3	3	3	3	3	3	3	3
Planned	CNL dB(A)	58	60	60	58	57	56	57	53
Noise Sources		45	45	45	45	45	45	45	45
	Cumulative CNL, dB(A)	58	60	60	58	57	57	57	54
									ļ
	Noise Criteria dB(A)	60	60	60	60	60	60	60 YES	60

orms:

- the sound power level of fixed noise source, dB(A)
- the correction for slant distance between the source and the NSR, dB(A)
- the correction for slant distance between the source and the NSR, dB(A)
- the number of litems of plant operating simulataneously
- the fixede correction, dB(A)
- the fixede correction, dB(A)
- the noise reduction by Partier, dB(A)
- the corrected noise level, dB(A) Leg (30mins)

Westwood Hong & Associates Ltd.

Job Title: Residential Development at Kam Pok Road

Job No.: 22610

Scenario: Appendix 6 - Cumulative Fixed Noise Sources Assessment for the Proposed Development

Calculation of Façade Noise Levels from Fixed Noise Sources (Night Time Period)

		NSR 112	NSR 122	NSR 125	NSR 126	NSR 139	NSR 150	NSR 226	NSR 227
Noise Sources	Х	823422.1	823444	823450.3	823441.9	823414.9	823392.2	823413.9	823399.6
	Y	837152.7	837139.6	837136.1	837124	837138.4	837150.7	837176.8	837178.4
Α	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A) Cbar dB(A)	-49 0	-47 0	-46 0	-47 -10	-49 -10	-51 -10	-50 0	-51 -10
В	Sub-total dB(A)	0	0	0	0	0	0	0	0
В	SWL dB(A) CLsr dB(A)	-53	-52	-52	-52	0 -53	-54	-53	-54
	Cbar dB(A) Sub-total dB(A)	0	0	0	-10 0	-10 0	-10 0	0	-10 0
С	SWL dB(A)	79	79	79	79	79	79	79	79
	CLsr dB(A) Cbar dB(A)	-58 0	-58 0	-58 0	-58 0	-58 0	-58 0	-57 0	-57 0
	Sub-total dB(A)	21	21	21	21	21	21	22	22
Н	SWL dB(A) CLsr dB(A)	0 -47	0 -47	0 -48	0 -46	0 -45	0 -46	0 -49	0 -48
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	0
J	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-52	-52	-52	-51	-51	-51	-53	-53
	Cbar dB(A) Sub-total dB(A)	-10 0	-10 0	-10 0	0	0	0	-10 0	0
К	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A) Cbar dB(A)	-52 -10	-52 -10	-52 -10	-51 0	-51 0	-51 0	-53 -10	-53 -10
	Sub-total dB(A)	0	0	0	0	0	0	0	0
N	SWL dB(A) CLsr dB(A)	0 -47	0 -46	0 -46	0 -45	0 -46	0 -48	0 -49	-50
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
Q	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-56	-55	-55	-55	-56	-57	-57	-57
	Cbar dB(A) Sub-total dB(A)	-10 0	-10 0	-10 0	0	0	0	-10 0	-10 0
R	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A) Cbar dB(A)	-59 -10	-58 -10	-58 -10	-58 0	-59 0	-59 0	-60 -10	-60 -10
	Sub-total dB(A)	0	0	0	0	0	0	0	0
S	SWL dB(A) CLsr dB(A)	-60	0 -59	-59	0 -59	-59	-60	-60	-60
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
U	Sub-total dB(A) SWL dB(A)	0 101							
	CLsr dB(A)	-58	-57	-57	-57	-57	-58	-58	-58
	Cbar dB(A) Sub-total dB(A)	-10 33	-10 34	-10 34	0 44	0 44	0 43	-10 33	-10 33
w	SWL dB(A)	0	0	0 -55	0	0	0	0	0
	CLsr dB(A) Cbar dB(A)	-56 -10	-55 -10	-55 -10	-55 0	-56 0	-57 0	-57 -10	-57 -10
Y	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
•	CLsr dB(A)	-56	-55	-54	-54	-56	-56	-56	-57
	Cbar dB(A) Sub-total dB(A)	0	0	-10 0	0	0	0	0	-10 0
Z	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A) Cbar dB(A)	-59 0	-59 0	-58 0	-59 -10	-59 -10	-60 -10	-59 0	-59 -10
	Sub-total dB(A)	0	0	0	0	0	0	0	0
AA	SWL dB(A) CLsr dB(A)	-56	-55	-55	-56	-56	-57	-57	-57
	Cbar dB(A)	0	0	0	-10	-10	-10	0	-10
AB	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-58	-58	-58	-58	-57	-57	-58	-58
	Cbar dB(A) Sub-total dB(A)	-10 0	-10 0	-10 0	0	0	0	-10 0	0
AC	SWL dB(A)	0 -58	0 -57	0 -57	0 -57	0	0 -59	0	0 -59
	CLsr dB(A) Cbar dB(A)	-10	-57 -10	-10	0	-58 0	0	-59 0	-10
AD	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
~	CLsr dB(A)	-60	-59	-59	-59	-59	-60	-60	-60
	Cbar dB(A) Sub-total dB(A)	-10 0	-10 0	-10 0	0	0	0	0	-10 0
ВВ	SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A) Cbar dB(A)	-53 -10	-52 -10	-52 -10	-51 0	-52 0	-53 0	-54 0	-54 0
	Sub-total dB(A)	0	0	0	0	0	0	0	0
cc	SWL dB(A) CLsr dB(A)	0 -49	0 -47	-47	0 -46	0 -48	0 -49	-50	-51
	Cbar dB(A)	-10	-10	-10	0	0	0	-10	-10
DD	Sub-total dB(A) SWL dB(A)	0	0	0	0	0	0	0	0
	CLsr dB(A)	-59	-59	-59	-58	-59	-60	-60	-60
	Cbar dB(A) Sub-total dB(A)	-10 0	-10 0	-10 0	0	0	0	-10 0	-10 0
	Cfac dB(A)	3	3	3	3	3	3	3	3
Planned	CNL dB(A)	37	37	38	47	47	46	36	36
Noise Sources		45	45	45	45	45	45	45	45
	Cumulative CNL, dB(A)	46	46	46	49	49	48	46	46
	Noise Criteria dB(A) Compli-ance	50 YES							
Definition of t			1 .20		.25	.20			


of terms:

- the sound power level of fixed noise source, dB(A)
- the correction for slant distance between the source and the NSR, dB(A)
- the number of items of plant operating simulataneously
- the fixed socrection, dB(A)
- the noise reduction by barrier, dB(A). -10dB(A) if the noise sources are lotally screened by substantial barrier
- the corrected noise level, dB(A). Let (30mins)

APPENDIX 7

PREDICTED NOISE RESULTS FOR KINDERGARTEN

Report: 22610-N1



Westwood Hong & Associates Ltd

PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

TITLE:

Location of Assessment Points for Road Traffic Noise

FIGURE


A7-1

Job No.: 22610

Job Title: Kam Pok Road

Scenario: Predicted Noise Levels, 2046 Taffic Forecast (Unmitigated), Kindergarten

	Receiver					
Level	701	702	703	704	705	706
G/F	57.6	57.3	57.0	56.8	56.5	56.2



PROJECT: 22610

Proposed Residential Development at Lot No. 4822 in D.D. 104 and Adjoining Government Land, Mai Po, Yuen Long, New Territories

Location of Assessment Points for Fixed Noise Sources

A7-2

Job Title: Residential Development at Kam Pok Road

Job No.: 22610

Scenario: Appendix 7 - Fixed Noise Sources Assessment for the Kindergarten

Calculation of Façade Noise Levels from Fixed Noise Sources

Westwood Hong & Associates Ltd.

		Day and Evening Time Periods	Night Time Period
		NSR 706	NSR 706
Noise			
Sources	X	823470.8 837191.1	823470.8 837191.1
		637191.1	837191.1
Α	SWL dB(A)	102	0
	CLsr dB(A) Cbar dB(A)	-47 -10	-47 -10
	Sub-total dB(A)	45	0
В	SWL dB(A)	100	0
	CLsr dB(A) Cbar dB(A)	-50 -10	-50 -10
	Sub-total dB(A)	40	0
С	SWL dB(A)	79	79
	CLsr dB(A) Cbar dB(A)	-57 -10	-57 -10
	Sub-total dB(A)	12	12
Н	SWL dB(A)	93	0
	CLsr dB(A) Cbar dB(A)	-51 -10	-51 -10
	Sub-total dB(A)	32	0
J	SWL dB(A)	95	0
	CLsr dB(A)	-54 -10	-54 -10
	Cbar dB(A) Sub-total dB(A)	31	0
к	SWL dB(A)	93	0
	CLsr dB(A)	-54 40	-54 40
	Cbar dB(A) Sub-total dB(A)	-10 29	-10 0
N	SWL dB(A)	92	0
	CLsr dB(A)	-51	-51
	Cbar dB(A) Sub-total dB(A)	-10 31	-10 0
Q	SWL dB(A)	92	0
	CLsr dB(A)	-56	-56
	Cbar dB(A)	-10 26	-10 0
R	Sub-total dB(A) SWL dB(A)	26 90	0
	CLsr dB(A)	-59	-59
	Cbar dB(A)	-10	-10
S	Sub-total dB(A) SWL dB(A)	21 91	0
	CLsr dB(A)	-60	-60
	Cbar dB(A)	-10	-10
U	Sub-total dB(A) SWL dB(A)	21 101	0 101
ŭ	CLsr dB(A)	-57	-57
	Cbar dB(A)	-10	-10
w	Sub-total dB(A) SWL dB(A)	34 90	34 0
**	CLsr dB(A)	-56	-56
	Cbar dB(A)	-10	-10
Y	Sub-total dB(A)	24	0
,	SWL dB(A) CLsr dB(A)	92 -55	-55
	Cbar dB(A)	-10	-10
Z	Sub-total dB(A)	27	0
2	SWL dB(A) CLsr dB(A)	102 -58	-58
	Cbar dB(A)	-10	-10
	Sub-total dB(A)	34	0
AA	SWL dB(A) CLsr dB(A)	95 -55	0 -55
	Cbar dB(A)	-10	-10
	Sub-total dB(A)	30	0
AB	SWL dB(A)	102 -59	0 -59
	CLsr dB(A) Cbar dB(A)	-59 -10	-59 -10
	Sub-total dB(A)	33	0
AC	SWL dB(A)	95 -58	0
	CLsr dB(A) Cbar dB(A)	-58 -10	-58 -10
	Sub-total dB(A)	27	0
AD	SWL dB(A)	95	0
	CLsr dB(A) Cbar dB(A)	-60 -10	-60 -10
	Sub-total dB(A)	25	0
BB	SWL dB(A)	92	0
	CLsr dB(A)	-55 -10	-55 -10
	Cbar dB(A) Sub-total dB(A)	27	0
СС	SWL dB(A)	85	0
	CLsr dB(A) Cbar dB(A)	-51 -10	-51 -10
	Sub-total dB(A)	24	0
DD	SWL dB(A)	91	0
	CLsr dB(A)	-59 -10	-59 -10
	Cbar dB(A) Sub-total dB(A)	-10 22	-10 0
	Cfac dB(A)	3	3
	CNL dB(A)	50	37
Planned Noise Sources		45	45
	Cumulative CNL, dB(A) Noise Criteria dB(A)	52 60	46 50
	Compli-ance		
	I COMPUT-ATICE	YES	YES

Items:

- the sound power level of fixed noise source, dBI(A)
- the correction for stant distance between the source and the NSR, dB(A)
- the correction for stant distance between the source and the NSR, dB(A)
- the number of limits or plaint operating simulataneously
- the facate correction, dBI(A)
- the facate correction, dBI(A)
- the noise reduction by barrier, dBI(A)
- 10dBI(A) if the noise sources are totally screened by substantial barrier
- the corrected noise level, dBI(A) Leq (30mins)