2023年 4月 2 7日

This document is received on 2.7 APR 2023.

The Town Planning Board will formally acknowledge the date of receipt of the application only upon receipt of all the required information and documents.



## APPLICATION FOR PERMISSION

### **UNDER SECTION 16 OF**

## THE TOWN PLANNING ORDINANCE

(CAP.131)

根據《城市規劃條例》(第131章) 第16條遞交的許可申請

Applicable to Proposal Only Involving Temporary Use/Development of Land and/or Building Not Exceeding 3 Years in Rural Areas or Renewal of Permission for such Temporary Use or Development\*

適用於祇涉及位於鄉郊地區土地上及/或建築物內進行為期不超過三年的臨時用途/發展或該等臨時用途/發展的許可續期的建議\*

\*Form No. S16-I should be used for other Temporary Use/Development of Land and/or Building (e.g. temporary use/developments in the Urban Area) and Renewal of Permission for such Temporary Use or Development.

\*其他土地上及/或建築物內的臨時用途/發展 (例如位於市區內的臨時用途或發展)及有關該等臨時用途/發 展的許可續期,應使用表格第 S16-I 號。

Applicant who would like to publish the <u>notice of application</u> in local newspapers to meet one of the Town Planning Board's requirements of taking reasonable steps to obtain consent of or give notification to the current land owner, please refer to the following link regarding publishing the notice in the designated newspapers: <a href="https://www.info.gov.hk/tpb/en/plan application/apply.html">https://www.info.gov.hk/tpb/en/plan application/apply.html</a>

申請人如欲在本地報章刊登<u>申請通知</u>,以採取城市規劃委員會就取得現行土地擁有人的同意或通知現行土地擁有人所指定的其中一項合理步驟,請瀏覽以下網址有關在指定的報章刊登通知: https://www.info.gov.hk/tpb/tc/plan\_application/apply.html

#### General Note and Annotation for the Form 填寫表格的一般指引及註解

- "Current land owner" means any person whose name is registered in the Land Registry as that of an owner of the land to which the application relates, as at 6 weeks before the application is made
  - 「現行土地擁有人」指在提出申請前六星期,其姓名或名稱已在土地註冊處註冊為該申請所關乎的土地的擁有人的人
- <sup>&</sup> Please attach documentary proof 請夾附證明文件
- ^ Please insert number where appropriate 請在適當地方註明編號

Please fill "NA" for inapplicable item 請在不適用的項目填寫「不適用」

Please use separate sheets if the space provided is insufficient 如所提供的空間不足,請另頁說明

Please insert a 「レ」 at the appropriate box 請在適當的方格内上加上「レ」號

For Official Use Only	Application No. 申請編號	A/TM-LTY/ 456
請勿填寫此欄	Date Received 收到日期	2 7 APR 2023

- The completed form and supporting documents (if any) should be sent to the Secretary, Town Planning Board (the Board), 15/F, North Point Government Offices, 333 Java Road, North Point, Hong Kong:
  申請人須把填妥的申請表格及其他支持申請的文件(倘有),送交香港北角渣華道 333 號北角政府合署 15 櫻城市規劃委員會(下稱「委員會」)秘書收。
- 2. Please read the "Guidance Notes" carefully before you fill in this form. The document can be downloaded from the Board's website at <a href="http://www.info.gov.hk/tpb/">http://www.info.gov.hk/tpb/</a>. It can also be obtained from the Secretariat of the Board at 15/F, North Point Government Offices, 333 Java Road, North Point, Hong Kong (Tel: 2231 4810 or 2231 4835), and the Planning Enquiry Counters of the Planning Department (Hotline: 2231 5000) (17/F, North Point Government Offices, 333 Java Road, North Point, Hong Kong and 14/F, Sha Tin Government Offices, 1 Sheung Wo Che Road, Sha Tin, New Territories). 請先細閱《申請須知》的資料單張,然後填寫此表格。該份文件可從委員會的網頁下載(網址: <a href="http://www.info.gov.hk/tpb/">http://www.info.gov.hk/tpb/</a>),亦可向委員會秘書處(香港北角渣華道 333 號北角政府合署 15 樓一電話: 2231 4810或2231 4835)及規劃署的規劃資料查詢處(熱線: 2231 5000) (香港北角渣華道 333 號北角政府合署 17 樓及新界沙田上禾盎路 1 號沙田政府合署 14 樓)索取。
- 3. This form can be downloaded from the Board's website, and obtained from the Secretariat of the Board and the Planning Enquiry Counters of the Planning Department. The form should be typed or completed in block letters. The processing of the application may be refused if the required information or the required copies are incomplete. 此表格可從委員會的網頁下載,亦可向委員會秘書處及規劃署的規劃資料查詢處索取。申請人須以打印方式或以正楷填寫表格。如果申請人所提交的資料或文件副本不齊全,委員會可拒絕處理有關申請。

### 1. Name of Applicant 申請人姓名/名稱

(□Mr. 先生 /□Mrs. 夫人 /□Miss 小姐 /□Ms. 女士 /□Company 公司 /☑Organisation 機構 ) CONSTRUCTION INDUSTRY COUNCIL (CIC)

2. Name of Authorised Agent (if applicable) 獲授權代理人姓名/名稱(如適用)

(□Mr. 先生 /□Mrs. 夫人 /□Miss 小姐 /□Ms. 女士 /□Company 公司 /□Organisation 機構)N/A

3.	Application Site 申請地點	
(a)	Full address / location / demarcation district and lot number (if applicable) 詳細地址/地點/丈量約份及地段號碼(如適用)	Government Land under Kong Sham Western Highway (next to Wong Kong Wai Road near Fuk Hang Tsuen), Lam Tei, Tuen Mun, New Territories
(b)	Site area and/or gross floor area involved 涉及的地盤面積及/或總樓面面 積	☑Site area 地盤面積 10,300 sq.m 平方米☑About 約 ☑Gross floor area 總樓面面積 1,092 sq.m 平方米☑About 約
(c)	Area of Government land included (if any) 所包括的政府土地面積(倘有)	10,300 sq.m 平方米 🛮 About 約

(d)	Name and number of the related statutory plan(s) 有關法定圖則的名稱及編號	Approved Lam Tei and Yick Yuen Outline Zoning Plan (OZP) No. S/TM-LTYY/12
(e)	Land use zone(s) involved 涉及的土地用途地帶	Area shown as 'Road'
(f)	Current use(s) 現時用途	Temporary Training Ground (Hong Kong Institute of Construction, Construction Industry Council (HKIC, CIC))  (If there are any Government, institution or community facilities, please illustrate on plan and specify the use and gross floor area) (如有任何政府、機構或社區設施、請在圖則上顯示、並註明用途及總樓面面積)
4.	"Current Land Owner" of A	pplication Site 申請地點的「現行土地擁有人」
The	applicant 申請人 —	
	is the sole "current land owner"#& (pl 是唯一的「現行土地擁有人」#& (i	ease proceed to Part 6 and attach documentary proof of ownership). 身繼續填寫第 6 部分,並夾附業權證明文件)。
		(please attach documentary proof of ownership)
Ø.	is not a "current land owner". 並不是「現行土地擁有人」"。	
Ø	The application site is entirely on Go 申請地點完全位於政府土地上(請	vernment land (please proceed to Part 6). 繼續填寫第 6 部分)。
5.	Statement on Owner's Conse 就土地擁有人的同意/通知	
(a)	根據土地註冊處截至	urrent land owner(s) " <sup>#</sup> .  年 月 日的記錄,這字由譜出來
	涉 名「現行土地	.擁有人」"。
(b)	The applicant 申請人 —  las obtained consent(s) of  已取得 名「	"current land owner(s)"。 現行土地擁有人」"的同意。
,	Details of consent of "current l	and owner(s)" dotained 取得「現行土地擁有人」 同意的詳情
	No. of 'Current Land Owner(s)' 「租行土地熔海」Land Regist	/address of premises as shown in the record of the ry where consent(s) has/have been obtained 冊處記錄已獲得同意的地段號碼/處所地址  Date of consent obtained (DD/MM/YYYY) 取得同意的日期 (日/月/年)
	Not Appl	icable
	(Pl	ce of any box above is insufficient. 如上列件何方核的空間不足,鐵足百台明)

•		"cur	rent land ov	vner(s)"#						
has n	otified	Cut		` '						
已通	知	名	「現行土地	也擁有人」	# 0			٠.		
					•					
Det	ails of the "cui	rent land o	owner(s)" "	notified E	己獲通知 	「現行土地	擁有人 」 			
	of 'Current	Lot num	ber/address	of premise	s as show	n in the rec	ord of the	Date of	f notific	ation
	id Owner(s)'	Land Res	gistry where	e notification	n(s) has/h	ave been gi	ven		M/YYYY	η ·
	現行土地擁 人」數目	根據土地	也註冊處記録	錄已發出到	通知的地段	是號碼/處戶	<b>沂地址</b>		期(日/月	
737	<u> </u>				-				•	,
			•	•						
}			· · · · · ·	<u>.</u>	<u> </u>		·	<u> </u>		
		Not Ap	plicable		•					
								- <del> </del>		
										•
1		ŀ		•			·			•
(Plea	se use separate s	heets if the	space of any	box above i	s insufficie	nt. 如上列日	何方格的	空間不足,	謝另頁部	3明)
					•				•	
	aken reasonab									
已採	取合理步驟以	人取得土地	擁有人的同	司意或向該	人發給運	知。詳情如	下:			
				, '				あら 人 YELJE	FIN	
Reas	onable Steps t									
	. •					ı 1		(DD/N	4M/YYY	'Y)#&
_	and who wast f		fo the "ours	un baci tua						,
	sent request for	or consent	to the "curr	ent land ov 句句一名「	vner(s) of 辐行士報	·	弧缆垫水	高音響		
	sent request fe	or consent	to the "curr (日/月/年)[	ent land ov 句每一名「	·····································	· ·	郵遞要求	同意書卷		
Reas	於	·	(日/月/年)[	句每一名「	現行土地	的擁有人」"	郵遞要求	同意書&	步驟	
Reas	於sonable Steps t	o Give No	(日/月/年)[ tification to	句每一名「 Owner(s)	現行土地	旗有人。"	郵遞要求 通知所採	同意書 <sup>&amp;</sup> 取的合理	步驟	
Reas	於	o Give No	(日/月/年) tification to al newspape	句每一名「 Owner(s) ers on	現行土地	·擁有人」。 <u> 作有人發出</u> (D	郵遞要求 通知 <u>所採</u> D/MM/Y	同意書 <sup>&amp;</sup> 取的合理	步驟	
Reas	於	o Give No	(日/月/年)[ tification to	句每一名「 Owner(s) ers on	現行土地	·擁有人」。 <u> 作有人發出</u> (D	郵遞要求 通知 <u>所採</u> D/MM/Y	同意書 <sup>&amp;</sup> 取的合理	步驟	
Reas	於	o Give No	(日/月/年)[ tification to al newspape (日/月/年)	句每一名「Owner(s) Owner(s) ers on 在指定報章	現行土地 向土地 京	·擁有人。	郵遞要求 通知所採 D/MM/Y	同意書 <sup>&amp;</sup> 取的合理	步驟	
Reas	於	o Give No	(日/月/年) tiffication to al newspape (日/月/年) inent positio	句每一名「Owner(s) ers on 在指定報章	現行土地 向土地 京	·擁有人。	郵遞要求 通知所採 D/MM/Y	同意書 <sup>&amp;</sup> 取的合理	步驟	
Reas	於	o Give No	(日/月/年) tiffication to al newspape (日/月/年) nent position (DD/MM/)	句每一名「Owner(s) ers on 在指定報章 on on or nea	現行土地 向土地抗 可式申請干 ar applicat	·擁有人。 作有人發出 (D 可登一次通知 ion site/pres	郵遞要求 通知所採 D/MM/Y Ti <sup>2</sup> nises on	同意書 <sup>®</sup> 取的合理: YYY) <sup>®</sup>		·
Reas	於	o Give No	(日/月/年) tiffication to al newspape (日/月/年) inent position (DD/MM/N	向每一名「Owner(s)」 ers on 在指定報章 on on or nea YYYY) 在申請地點	現行土地 向土地抗 可就申請干 ar applicat	·排有人。 <del> </del>	郵遞要求 通知所採 D/MM/Y Til <sup>®</sup> nises on 的顯明位置	同意書 <sup>®</sup> 取的合理 YYY) <sup>®</sup> 暨貼出關防	<b>冷該申</b> 講	
Reas	於	o Give No	(日/月/年) tiffication to al newspape (日/月/年) inent position (DD/MM/N	向每一名「Owner(s)」 ers on 在指定報章 on on or nea YYYY) 在申請地點	現行土地 向土地抗 可就申請干 ar applicat	·排有人。 <del> </del>	郵遞要求 通知所採 D/MM/Y Til <sup>®</sup> nises on 的顯明位置	同意書 <sup>®</sup> 取的合理 YYY) <sup>®</sup> 暨貼出關防	<b>冷該申</b> 講	
Reas	於	o Give No	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp	向每一名「Owner(s)」 ers on 在指定報章 on on or nea YYYY) 在申請地點	現行土地 向土地抗 可就申請干 ar applicat 占/申請及 owners' co	·排有人。 <del> </del>	郵遞要求 通知所採 D/MM/Y Til <sup>®</sup> nises on 的顯明位置	同意書 <sup>®</sup> 取的合理 YYY) <sup>®</sup> 暨貼出關防	<b>冷該申</b> 講	
Reas	於	o Give No	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「 Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
Reas	於	ices in localina promi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「 Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	·排有人。 <del>作有人發出</del> (D 小登一次通知 ion site/pres 医所或附近的 committee(s)	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
Reas	於	ices in localina promi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「 Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	ices in localina promi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「 Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	o Give No ices in loca in a promi relevant o ural comm	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	o Give No ices in loca in a promi relevant o ural commi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	o Give No ices in loca in a promi relevant o ural commi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	o Give No ices in loca in a promi relevant o ural commi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	o Give No ices in loca in a promi relevant o ural commi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	o Give No ices in loca in a promi relevant o ural commi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	o Give No ices in loca in a promi relevant o ural commi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	o Give No ices in loca in a promi relevant o ural commi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	o Give No ices in loca in a promi relevant o ural commi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem
	於	o Give No ices in loca in a promi relevant o ural commi	(日/月/年) tiffication to al newspape (日/月/年) inent positio (DD/MM/N (日/月/年) wners' corp ittee on	向每一名「Owner(s) ers on 在指定報章 on on or nea YYYY) <sup>&amp;</sup> 在申請地點 ooration(s)	現行土地 向土地抗 可土地抗 可就申請干 ar applicat 占/申請及 owners' co	i擁有人。	郵遞要求 通知所採 D/MM/Y nises on ウ顯明位記 /mutual ai YYY)	同意書 <sup>&amp;</sup> 取的合理: YYY) <sup>&amp;</sup> 愛貼出關防 d committ	仒該申謂 ee(s)/ma	nagem

6. Type(s) of Application	n 申請類別				
位於鄉郊地區土地上及 (For Renewal of Permissi	/或建築物內進行為期不超過 on for Temporary. Use or Develo	g Not Exceeding 3 Years in Rural Areas 三年的臨時用途/發展 oment in Rural Areas, please proceed to Part (B)) 寫(B)部分)			
	Not Applicable				
(a) Proposed use(s)/development 擬議用途/發展					
(1) 700		oposal on a layout plan) (請用平面圖說明擬議詳情)			
(b) Effective period of permission applied for 申請的許可有效期	□ year(s) 年 □ month(s) 個月	·			
(c) <u>Development Schedule</u> 發展經					
Proposed uncovered land area	<del></del> -	sq.m □About 約			
Proposed covered land area 携		sq.m □About 約			
ĺ	s/structures 擬議建築物/構築物	•			
Proposed domestic floor area					
Proposed non-domestic floor		·····sq.m □About約			
Proposed gross floor area 擬語		·····sq.m □About約			
		······sq.m □About 約 s (if applicable) 建築物/構築物的擬議高度及不同樓層			
的擬議用途 (如適用) (Please us	e separate sheets if the space below	v is insufficient) (如以下空間不足,請另頁說明)			
·		·			
		. •			
Proposed number of car parking s	spaces by types 不同種類停車位的	<b>内擬議數目</b>			
Private Car Parking Spaces 私家		•			
Motorcycle Parking Spaces 電單					
Light Goods Vehicle Parking Spa					
Medium Goods Vehicle Parking Heavy Goods Vehicle Parking Sp					
Others (Please Specify) 其他 (部		***************************************			
, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	·, · , · ,				
Proposed number of loading/unloading spaces 上落客貨車位的擬議數目					
Taxi Spaces 的士車位					
Coach Spaces 旅遊巴車位		•••••••••••••••••••••••••••••••••••••••			
Light Goods Vehicle Spaces 輕型	型貨車車位				
Medium Goods Vehicle Spaces					
Heavy Goods Vehicle Spaces 重					
Others (Please Specify) 其他 (詞	<b>育列朔)</b>				

Proposed operating hours 擬議營運時間					
the site/subject building	ss to	There is an existing access. (please indicate the street name, where appropriate) 有一條現有車路。(講註明車路名稱(如適用))  There is a proposed access. (please illustrate on plan and specify the width) 有一條擬議車路。(請在圖則顯示,並註明車路的闊度)			
	No	· 否 □			
(If necessary, please give justifications/rea	ent Propos use separa sons for no	al 擬議發展計劃的影響 te sheets to indicate the proposed measures to minimise possible adverse impacts or of providing such measures. 如需要的話,請另頁表示可盡量減少可能出現不良影			
Does the development proposal involve alteration of existing building? 擬議發展計劃是否包括現有建築	Yes 是 No 否	□ Please provide details - 請提供詳情			
	Yes 是	<ul> <li>□ (Please indicate on site plan the boundary of concerned land/pond(s), and particulars of stream diversion, the extent of filling of land/pond(s) and/or excavation of land)</li> <li>( 請用地盤平面圖顯示有關土地/池塘界線・以及河道改道、填塘、填土及/或挖土的細節及/或範圍)</li> <li>□ Diversion of stream 河道改道</li> </ul>			
Does the development proposal involve the operation on the right? 擬議發展是否涉及右列的工程?		□ Filling of pond 填塘 Area of filling 填塘面積 sq.m 平方米 □About 約 Depth of filling 填塘深度 m 米 □About 約 □ Filling of land 填土 Area of filling 填土面積 sq.m 平方米 □About 約 Depth of filling 填土厚度 m 米 □About 約 □ Excavation of land 挖土 Area of excavation 挖土面積 sq.m 平方米 □About 約			
•	No 否	Depth of excavation 挖土深度 m 米 □About 約			
) Would the development proposal cause any adverse impacts? 接議發展計劃會否造依不良影響?	On environ traffic On water On drain On slope Affected Landscap Tree Fell Visual In	Yes 會			
	the site/subject buildin是否有事路通往地有關建築物?  Impacts of Developm (If necessary, please give justifications/rea 響的措施,否則請提 Does the development proposal involve alteration of existing building? 接受包括到。  Does the development proposal involve the operation on the right? 接接对的工程?  Does the development proposal involve the operation on the right? 接接对比不可以提供的工程。  Would the development proposal cause any adverse impacts 接接不 意	Any vehicular access to the site/subject building? 是否有事路通往地盤/有關建築物?  Impacts of Development Propose (If necessary, please use separa give justifications/reasons for new endevelopment proposal involve alteration of existing building? 接接發展計劃是否包括現有建築物的改動?  Does the development proposal involve the operation on the right? 接接發展是否涉及右列的工程?  Does the development proposal involve the operation on the right? 接接發展是否涉及右列的工程?  No 否  On envir On traffic On water On drain On slope Affected Landscar Tree Fell Visual Iree Fell			

Please state measure(s) to minimise the impact(s). For tree felling, please state the number, diameter at breast height and species of the affected trees (if possible) 講註明盡量減少影響的措施。如涉及砍伐樹木,請說明受影響樹木的數目、及胸高度的樹幹直徑及品種(倘可)					
位於鄉郊地區臨時用途廢 (a) Application number to which the permission relates 與許可有關的申請編號	A/ TM-LTYY / 398				
(b) Date of approval 獲批給許可的日期					
(c) Date of expiry 許可屆滿日期					
(d) Approved use/development 已批給許可的用途/發展 (e) Approval conditions 附帶條件	Temporary Training Ground (Hong Kong Institute of Construction, Construction Industry Council (HKIC, CIC))  The permission does not have any approval condition 許可並沒有任何附帶條件  Applicant has complied with all the approval conditions 申請人已履行全部附帶條件  Applicant has not yet complied with the following approval condition(s): 申請人仍未履行下列附帶條件:  Reason(s) for non-compliance: 仍未履行的原因:				
(f) Renewal period sought 要求的續期期間	(如以上空間不足,請另頁說明) ☑ year(s) 年 □ month(s) 個月				

### 7. Justifications 理由

The applicant is invited to provide justifications in support of the application. Use separate sheets if necessary. 現譜申請人提供申請理由及支持其申請的資料。如有需要,請另頁說明)。

- (i) The demand for construction training has remained high with major infrastructure projects still in progress. The training space available within CIC's premises has also reached its ceiling. It is necessary for the CIC to continue using existing training facilities to provide continuous training to meet the demand.
- (ii) The proposed use and layout are the same with the previous approval:
- (iii) The planning conditions under previous approval have been complied with to the satisfaction of relevant Government departments.

8. Declaration 聲明				
l hereby declare that the partic 本人謹此聲明,本人就這宗	ulars given in this application。 申請提交的資料,據本人所知	are correct and true to the best of my knowledge and belief. 印及所信,均屬真實無誤。		
such materials to the Board's v	website for browsing and down	erials submitted in an application to the Board and/or to upload loading by the public free-of-charge at the Board's discretion. 斗複製及/或上載至委員會網站,供公眾免費瀏覽或下載。		
Signature 簽署		☑Applicant 申請人 / Authorised Agent 獲授權代理人		
		Senior Manager - Estates Office &		
••••••	illiam CHAN	Corporate Administration		
	ne in Block Letters	Position (if applicable)		
姓名 姓名	(請以正楷填寫)	職位 (如適用)		
Professional Qualification(s) 專業資格	☐ HKIS 香港測量師學會	/ │ HKIA 香港建築師學會 /		
	Others 其他			
on behalf of CONSTRUCTION INDUSTRY COUNCIL (CIC)				
☐ Company 公	司 / ☑ Organisation Name a	nd Chop (if applicable) 機構名稱及蓋章(如適用)		
Date 日期	17/03/2023	(DD/MM/YYYY 日/月/年)		

#### Remark 備註

The materials submitted in an application to the Board and the Board's decision on the application would be disclosed to the public. Such materials would also be uploaded to the Board's website for browsing and free downloading by the public where the Board considers appropriate.

委員會會向公眾披露申請人所遞交的申請資料和委員會對申請所作的決定。在委員會認為合適的情況下,有關申請 資料亦會上載至委員會網頁供公眾免費瀏覽及下載。

#### Warning 警告

Any person who knowingly or wilfully makes any statement or furnish any information in connection with this application, which is false in any material particular, shall be liable to an offence under the Crimes Ordinance. 任何人在明知或故意的情況下,就這宗申請提出在任何要項上是虛假的陳述或資料,即屬違反〈刑事罪行條例〉

#### Statement on Personal Data 個人資料的聲明

1. The personal data submitted to the Board in this application will be used by the Secretary of the Board and Government departments for the following purposes:

委員會就這宗申請所收到的個人資料會交給委員會秘書及政府部門,以根據〈城市規劃條例〉及相關的城市規 劃委員會規劃指引的規定作以下用途:

(a) the processing of this application which includes making available the name of the applicant for public inspection when making available this application for public inspection; and 處理這宗申請,包括公布這宗申請供公眾查閱,同時公布申請人的姓名供公眾查閱:以及

facilitating communication between the applicant and the Secretary of the Board/Government departments. 方便申請人與委員會秘書及政府部門之間進行聯絡。

- 2. The personal data provided by the applicant in this application may also be disclosed to other persons for the purposes mentioned in paragraph 1 above. 申請人就這宗申請提供的個人資料,或亦會向其他人士披露,以作上述第1段提及的用途。
- 3. An applicant has a right of access and correction with respect to his/her personal data as provided under the Personal Data (Privacy) Ordinance (Cap. 486). Request for personal data access and correction should be addressed to the Secretary of the Board at 15/F, North Point Government Offices, 333 Java Road, North Point, Hong Kong. 根據《個人資料(私隱)條例》(第 486 章)的規定,申請人有權查閱及更正其個人資料。如欲查閱及更正個人資料,應向委員會秘書提出有關要求,其地址為香港北角渣華道 333 號北角政府合署 15 樓。

6:1	LAND FANGE						
Gist of Application 申請摘要							
(Please provide details in both English and Chinese as far as possible. This part will be circulated to relevant							
consultees, uploade	consultees, uploaded to the Town Planning Board's Website for browsing and free downloading by the public and						
i deposited at the Plan	ining Enquiry Counters of the Planning Department for general information.)						
「調靈軍以英又及中   下載及存放於規劃	文填寫。此部分將會發送予相關諮詢人士、上載至城市規劃委員會網頁供公眾免費瀏覽及 署規劃資料查詢處以供一般參閱。)						
Application No.	(For Official Use Only) (請勿填寫此欄)						
申請編號							
	·						
I and and all							
Location/address	Government Land under Kong Sham Western Highway (next to Wong Kong						
位置/地址	Wai Road near Fuk Hang Tsuen), Lam Tei, Tuen Mun, New Territories						
	新界屯門藍地港深西部通道下的政府土地 (黃崗圍路旁近福亨村)						
	•						
Site area	10.000						
地盤面積	10,300 sq. m 平方米 🛭 About 約						
	   (includes Government land of 包括政府土地 10 300 sq. m 平方米 Ø About 约)						
	(includes Government land of 包括政府土地 10,300 sq. m 平方米 🗹 About 約)						
Plan	Approved Lam Tei and Yick Yuen Outline Zoning Plan No. S/TM-LTYY/12						
圖則	藍地及亦園分區計劃大綱核准圖編號 S/TM-LTYY/12						
Zoning	Area shown as 'Road'						
地帶	顯示為「道路」的地方						
<i>,</i> .							
Type of	Temporary Use/Development in Rural Areas for a Period of						
Application	位於鄉郊地區的臨時用途/發展為期						
申請類別	(上): 例如: 10m 可用您没成场别						
•	□ Year(s) 年 □ Month(s) 月						
•							
	Renewal of Planning Approval for Temporary Use/Development in Rural						
	Areas for a Period of						
	位於鄉郊地區臨時用途/發展的規劃許可續期為期						
,	☑ Year(s) 年 <u>3</u> □ Month(s) 月						
Applied use/	Temporary Training Ground (Hong Kong Institute of Construction,						
development	Construction Industry Council) for a Period of 3 Years						
申請用途/發展	臨時訓練場(建造業議會香港建造學院)(為期3年)						
,							
	<u>.</u> .						

(i)	Gross floor area and/or plot ratio		sq.m	平方米	Plot R	Ratio 地積比率
	總樓面面積及/或地積比率	Domestic 住用		□ About 約 □ Not more than 不多於		□About 約 □Not more than 不多於
		Non-domestic 非住用	1092	□ About 約 ☑ Not more than 不多於		□About 約 □Not more than 不多於
(ii)	No. of block 幢數	Domestic 住用				
		Non-domestic 非住用		. 41		
(iii)	Building height/No. of storeys 建築物高度/層數	Domestic 住用			☐ (Not	m 米 more than 不多於)
					□ (Not	Storeys(s) 層 more than 不多於)
		Non-domestic 非住用		3	Ø (Not	m 米 more than 不多於)
				1	☑ (Not	Storeys(s) 層 more than 不多於)
(iv)	Site coverage 上蓋面積			iı .	%	☑ About 約
(v)	No. of parking	Total no. of vehicle	e parking spaces	; 停車位總數		10
	spaces and loading / unloading spaces 停車位及上落客貨 車位數目	Medium Goods V	ng Spaces 電擘 icle Parking Spa 'ehicle Parking		車位	8 2
		Others (Please Sp	ecify) 其他 (記	<b>詩列明)</b>		
		Total no. of vehicl 上落客貨車位/	e loading/unload 停車處總數	ling bays/lay-bys		
	· .	Taxi Spaces 的士 Coach Spaces 旅 Light Goods Vehi Medium Goods V	遊巴車位 icle Spaces 輕勁	型貨車車位 中型貨車位		
		Heavy Goods Vel Others (Please Sp	nicle Spaces 重 ecify) 其他(記	型貨車車位 青列明)		
						•

Submitted Plans, Drawings and Documents 提交的圖則、繪圖及文件		·
	<u>Chinese</u> 中文	English 英文
Plans and Drawings 圖則及繪圖		
Master layout plan(s)/Layout plan(s) 總綱發展藍圖/布局設計圖		
Block plan(s) 樓宇位置圖		Ц
Floor plan(s) 樓宇平面圖		Ï
Sectional plan(s) 截視圖		
Elevation(s) 立視圖		. 🗆
Photomontage(s) showing the proposed development 顯示擬議發展的合成照片		П.
Master landscape plan(s)/Landscape plan(s) 園境設計總圖/園境設計圖		· 🖸
Others (please specify) 其他(請註明)	L	וצו
Site Plan, Location Plan, As-fitted drainage plan		
		•
Reports 報告書		
Planning Statement/Justifications 規劃綱領/理據		
Environmental assessment (noise, air and/or water pollutions)		· L.
環境評估(噪音、空氣及/或水的污染)	[1	□.
Traffic impact assessment (on vehicles) 就車輛的交通影響評估	П	. Li'
Traffic impact assessment (on pedestrians) 就行人的交通影響評估	H	
Visual impact assessment 視覺影響評估		
Landscape impact assessment 景觀影響評估		
Tree Survey 樹木調查		· □
Geotechnical impact assessment 土力影響評估		
Drainage impact assessment 排水影響評估	. 🗀	<b>□</b> .
Sewerage impact assessment 排污影響評估	. 🗆	n
Risk Assessment 風險評估	<b>!</b>	
Others (please specify) 其他(請註明)		لـدي
FS Certificate, Letter of compliance of approval condition (drainage, FSI)		
Note: May insert more than one 「レ」:註:可在多於一個方格內加上「レ」號	<u> </u>	

Note: The information in the Gist of Application above is provided by the applicant for easy reference of the general public. Under no circumstances will the Town Planning Board accept any liabilities for the use of the information nor any inaccuracies or discrepancies of the information provided. In case of doubt, reference should always be made to the submission of the applicant.

註: 上述申請摘要的資料是由申請人提供以方便市民大眾參考。對於所載資料在使用上的問題及文義上的歧異,城市規劃委 員會概不負責。若有任何疑問,應查閱申請人提交的文件。

屯門及元朗西規劃處 新界沙田上不量路 1 號 沙田政府合署 14 樏



#### By Post and Fax

### Planning Department

Tuen Mun and Yuen Long West District Planning Office 14/F. Sha Tin Government Offices. No.1 Shoung Wo Che Road, Sha Tin, N.T.

27 June 2022

水粥檔號 Your Reference

本習檔號 Our Reference TPB/A/TM-LTYY/398

電話號碼

Tel. No.: 2158 6286

傳真機號碼 Fax No.:

2489 9711

A.LEAD Architects Limited 8/F. The Phoenix 23 Luard Road, Wan Chai Hong Kong (Attn: Mr Esmond TAM)

Dear Sir,

### Planning Application No. A/TM-LTYY/398 Compliance with Approval Condition (k)

I refer to your submission dated 26 May 2022 for compliance with the captioned approval condition on the implementation of drainage proposal,

Relevant department has been consulted. Your submission is considered;

- $\square$ Acceptable. The captioned condition has been complied with. Please find detailed departmental comments at Appendix.
- Acceptable. Since the captioned condition requires both the submission and implementation of the proposal, it has not been fully complied with. Please proceed to implement the accepted proposal for full compliance with the approval condition.
- Not acceptable. The captioned condition has not been complied with. Please find detailed departmental comments at Appendix.

Should you have any queries on the above, please contact the undersigned.

Yours faithfully,

(Keith FUNG)

for District Planning Officer/ Tuen Mun and Yuen Long West Planning Department

c.c.

CEMN, DSD ON

Internal CTP/TPB(2) Aos6 (Attn: Mr HUI Pui Hei, William)

[Fax: 2770 4761]


A\_TM-LTYY\_398 - AC(k) - 20220627 - Compliance.doex




Appendix

The Chief Engineer/Mainland North, Drainage Services Department (CE/MN, DSD) has the following comment on the submission.

The applicant is reminded to maintain their drainage systems properly and rectify the systems if they are found to be inadequate or ineffective during operation. Also, the applicant should be reminded that the owner of the development shall also be liable for and shall indemnify claims and demands arising out of damage or nuisance caused by a failure of the systems.





屯門及元朗西規劃處 新界沙田上不登路1號 沙田政府合署 14 樓



#### By Post and Fax

### Planning Department

Tuen Mun and Yuen Long West District Planning Office 14/F., Sha Tin Government Offices, No.1 Sheung Wo Che Road, Sha Tin, N.1

20 September 2022

本函檔號 Your Reference

本署檔號 Our Reference TPB/A/TM-LTYY/398

電話號碼 Tcl No.: 2158 6286

傅真機號碼 Fax No.:

2489 9711

A.LEAD Architects Limited 8/F, The Phoenix 23 Luard Road, Wan Chai Hong Kong (Attn: Mr Esmond TAM)

Dear Sir,

### Planning Application No. A/TM-LTYY/398 Compliance with Approval Condition (n)

I refer to your submission dated 13 September 2022 for compliance with the captioned approval condition on the implementation of the fire services installation proposal.

Relevant department has been consulted. Your submission is considered:

ablaAcceptable, The captioned condition has been complied with.

Acceptable. Since the captioned condition requires both the submission and implementation of the proposal, it has not been fully complied with. Please proceed to implement the accepted proposal for full compliance with the approval condition.

Not acceptable. The captioned condition has not been complied with. Please find detailed departmental comments at Appendix.

Should you have any queries on the above, please contact the undersigned.

Yours faithfully, .

(Keith FUNG) for District Planning Officer/

Tuen Mun and Yuen Long West

Planning Department

c.c.

D of FS

(Attn: Mr WONG Ho Yin)

[Fax: 2739 8775]

Internal CTP/TPB(2)

A\_TM-LTYY\_398 - AC(n) - 20220920 - Compliance, docx



Serial No.: L001986



#### FIRE SERVICES DEPARTMENT

HONG KONG

DATE: 30/06/2022

OUR REF.: FP 19/30679

YOUR REF.:


Fire Service Installations and Equipment at:-

Government Land, Kong Sham Western Highway, Lam Tei Tuen Mun, N.T. – Short Term Tenancy No. MX18030

(T.O.P - A training ground comprising one single-storey site office, one single-storey multi purpose room and one outdoor E&M cabinet)

This certificate is issued in accordance with Section 21 of the Buildings Ordinance Subsection 6(d), and certifies that the Director of Fire Services is satisfied that the fire service installations and equipment shown on the building plans approved by him have been installed in accordance with Sub-paragraph (ii) of Paragraph (b) of Subsection (1) of Section 16 of the Buildings Ordinance and were in efficient working order and satisfactory condition at the time of their inspection on 23/06/2022.

(WONG Ka-wing)
for Director of Fire Services



F.S.172 (Rev.9/98)



Serial No.: L001995.



#### FIRE SERVICES DEPARTMENT

HONG KONG

DATE: 08/07/2022

OUR REF.: FP 19/30679

YOUR REF.:

Fire Service Installations and Equipment at:-

Government Land, Kong Sham Western Highway, Lam Tei Tuen Mun, N.T. – Short Term Tenancy No. MX18030

(T.O.P. - A training ground with one outdoor E&M cabinet)

This certificate is issued in accordance with Section 21 of the Buildings Ordinance Subsection 6(d), and certifies that the Director of Fire Services is satisfied that the fire service installations and equipment shown on the building plans approved by him have been installed in accordance with Sub-paragraph (ii) of Paragraph (b) of Subsection (1) of Section 16 of the Buildings Ordinance and were in efficient working order and satisfactory condition at the time of their inspection on 24/06/2022.

(LEE Koon-yau)
for Director of Fire Services



c.c.



# FIRE SERVICE (INSTALLATIONS AND EQUIPMENT) REGULATIONS 消防(裝置及設備)規例 (Regulation 9(1))

Serial Number	_	
10259015063		

FSD Rei			置及設備)規 gulation 9(1))		Serial N	umber
1131535631013	(第九條(1)款) CERTIFICATE OF FIRE SERVICE INSTALLATION AND EQUI			102590	15063	
		KTIFICATE OF FIRE SERV	ICE INSTALL 支置及設備證	_ATION AND EQUIP ■	MENT	
	Client 顧客姓名		· · · · · · · · · · · · · · · · · · ·	=		
Address:	iction Industry Council - Lam T	er Training Ground				同學與其名前面
	ment Land (STT no. MX 18030 :	CC 225 A CC 226	<del></del>	····································		
Kong sn	am Western Highway,Wong K	ong Wai Road, Lam Tel, Tue	en Mun, NT			
Type of Bu	illding 概字類型: Industrial 工業	Commercial 商業 Domestic	住宅 Comp	iosite 綜合 Licensed	premises 持牌億所	Institutional 社團
	ONL 1	ordance with Regulation 8(b) of the dipment which is installed in any prer st once in every 12 months,极躁消防 -名註冊水數而檢查该等消防裝置或過	Tises shar rave hubwildiren erverben			
Code 績碼 (1-35)	Type of FSI 裝 <b>資</b> 類型	Location(s)位置		on Condition 狀況評述	Completion Date 完成日期 (DD/MM/YYYY)	下次到期日
13	MFA System	STT No. MX 18030 : CS-225 & CS-226	Conform requirem	s with FSD ents	08/02/2023	07/02/2024
23	Hose Reel	Ditto	Ditto		08/02/2023	07/02/2024
Part 2 第	二部 Installation / Modification .	/ Panais / Inamastian waster #	+124 mb.ll+ ub.v	TI ALA THE TO I II.		
Code			1		<del></del>	dition Completion Date
編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置		of Work Carried out 成之工作內容	Comment on Con 狀況評述	dition 完成日期 (DD/MM/YYYY)
			<u></u>	<u> </u>		
Part 3 第	三部 Defects 損壞事項		-			
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置		Outstanding Defects 未	修缺點	Comment on Defects 缺點評述
						//
				For and	I on behalf of	
<u>_</u>			<u> </u>		1堅消防工學	有限人司
Remark (情	註			AMERICA: Authorized	N FIRE ENGINEERING	DAPANT LIMITED
•	•			Signature: 受權人簽署。		For FSD use only
Equipment	y certify that the above installations/equider in accordance with the Codes of F and Inspection, Testing and Maintenantic Codes of F	ractice for Minimum Fire Service		FSD/RC No.:	C1 /0259 RC2	Inspected
本人符此證	r by the Director of Fire Services. Defect 明以上之消防裝置及設備經試驗,證明性 守則與裝置及設備之檢查測試及保養守則	s are listed in Part 3. :能良好,符合消防邊處長不時公佈的 ]的現格,損壞耶項列於第三部,		消防處註冊號碼 Company Name: A 公司名稱 A	merican Fire Engi	neering Keylin
This	如證書涉及年檢事項 處所當眼處以供	消防處人員查核		Telephone: [ 聯絡電話	ompany Limited	Verified
prem	certificate should be displayed a ilses for FSD's inspection if any a	r prominent location of the bu innual maintenance work is in	illding or ivolved.	Date: F	0/02/2023	

F.S. 251 (Rev. 01/2012) bab9-fc6(-8694-418a-cf03-864e-19ff-1f49



10259 015063

Name of Client 顧客姓名


Construction Industry Council - Lam Tei Training Ground


## Part 1 Annual Maintenance ONLY


In accordance with Regulation 8(b) of the Fire Service (Installations and Equipment) Regulations, the owner of any fire service installation or equipment which is installed in any premises shall have such fire service installation or equipment inspected by a registered contractor at least once in every 12 months. 根據附於雙資及股價規例第八條(b)款,擁有較實在任何處所內的任何指於裝置或股價的人,須每12個日本,企業的企業的企業的企業的企業的。


ACC TO THE STORAGE STORES	at least once in every 12 months. 根據消防(裝置及設備);
第一部 只適用於年檢事項	月由一名註冊承辦商檢查該等消防裝置或設備至少一次。


213 HI	月田一名莊顺水縣的侯登該等捐防裝宜或設備至少一次。					
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置	Comment on Condition 狀況評述	Completion Date 完成日期 (DD/MM/YYYY)	Next Due Date 下次到期日 (DD/MM/YYYY)	
11	Emergency Lighting System	STT No. MX 18030 : CS-225 & CS-226	Conforms with FSD requirements	08/02/2023	07/02/2024	
12	Exit Signs	Ditto	Ditto	08/02/2023	07/02/2024	
			·			














Construction Industry Council - Lam Tei Training Ground





#### FIRE SERVICE (INSTALLATIONS AND EQUIPMENT) REGULATIONS

消防 (裝置及設備) 規例

FSD Ref.

消防虚描號

Serial Number (Regulation 9(1))

(第九條(1)款) CERTIFICATE OF FIRE SERVICE INSTALLATION AND EQUIPMENT 消防裝置及設備證書 Name of Client 顯客姓名 Construction Industry Council - Lam Tel Training Ground Government Land (STT no. MX 18030 : CS-225 & CS-226). Kong Sham Western Highway,Wong Kong Wai Road, Lam Tei, Tuen Mun, NT Type of Building 极字類型: Industrial 工業 Commercial 商業 Domestic 住宅 Composite 綜合 Licensed premises 捋牌處所 Part 1 Annual Maintenance In accordance with Regulation 8(b) of the Fire Service (Installations and Equipment) Regulations, the owner of any fire service installation or equipment which is installed in any premises shall have such fire service installation or equipment inspected by a registered contractor ONLY at least once in every 12 months. 根據消防(裝置及.後備)規例第八條(b)款,採行裝置在任何處所內的任何消防裝置或設備的人, 須持12個 第一部 只適用於年檢事項 月由一名注册水塘的检查该等消防装置或设備至少一次。 Code Completion Date Next Due Date 編碼 (1-35) 完成日期 (DD/MM/YYYY) Type of FSI 裝置類型 Location(s)位置 Comment on Condition 狀況評述 下次到期日 (DD/MM/YYYY) Conforms with FSD 23 nos. x 2 kg dry powder|STT No. MX 18030 ; 19 requirements 08/02/2023 07/02/2024 F.E. CS-225 & CS-226 (Defects see Part 3) 9 nos. x 5 kg dry powder 24 Ditto Ditto 08/02/2023 07/02/2024 Part 2 第二部 Installation / Modification / Repair / Inspection works 裝置/改裝/修理/檢查工作 Code Completion Date Nature of Work Carried out Comment on Condition 完成日期 (DD/MM/YYYY) Type of FSI 裝置類型 頯碼 Location(s)位置 完成之工作內容 狀況評述 (1-35)Part 3 第三部 Defects 損壞事項 Code Comment on Defects 編碼 (1-35) ·Type of FSI 裝置類型 Location(s)位置 Outstanding Defects 未修缺點 缺點評述 Required for Expired for hydraulic pressure test/ 23 nos. x 2 kg dry powder|STT No. MX 18030 : hydraulic pressure 24 F.E. CS-225 & CS-226 Damaged test/replacement 9 nos. x 5 kg dry powder Ditto Ditto Ditto 24 F.E. For and on beau Authorize差利堅消防工 在有限公 Remark 備註 Signal MERICAN FIRE ENGINEERING COMPANY, LINITED, FSD 受權人簽署 Name: 此名 I/We hereby certify that the above installations/equipment have been tested and found to be in efficient Inspected Authorized Signature(s) working order in accordance with the Codes of Practice for Minimum Fire Service Installations and FSD/RC No.: Equipment and Inspection, Testing and Maintenance of Installations and Equipment published from / 0216 消防處註冊號碼 time to time by the Director of Fire Services, Defects are listed in Part 3. Company Name: 本人藉此證明以上之消防裝置及設備經試驗,證明性能良好,符合消防處處長不時公佈的最低限度之消防 Key-in 公司名稱 裝置及設備守則與裝置及設備之檢查測試及保養守則的規格,損壞事項列於第三部. Chung Ping Luen 如證書涉及年檢事項,應張貼於大廈或 Telephone: 處所當眼處以供消防處人員查核 聯絡電話 Verified This certificate should be displayed at prominent location of the building or Date: 10/02/2023 premises for FSD's inspection if any annual maintenance work is involved.

F.S. 251 (Rev. 01/2012) ea2d-6b88-8c6d-08b8-3f38-ed2c-12f3-0107





Construction Industry Council - Lam Tei Training Ground


## Part 1 Annual Maintenance ONLY


In accordance with Regulation 8(b) of the Fire Service (Installations and Equipment) Regulations, the owner of any fire service installation or equipment which is installed in any premises shall have such fire service installation or equipment inspected by a registered contractor at least once in every 12 months. 根據消防(裝置及股備)規例第八條(b)款,擁有裝置在任何處所內的任何消防裝置或股備的人,須每12個月由一名註冊承辦商檢查核等消防裝置或股備部小一次。


	R 只適用於年檢事項	ce in every 12 months. 根據消防(損 Em承辦商檢查該等消防裝置或設備	b型及股份)提例统入條(n)数,擁有临界在任(	可處所內的任何消防裝置或	戏股价的人, 須每12個
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置	Comment on Condition 狀況評述	Completion Date 完成日期 (DD/MM/YYYY)	Next Due Date 下次到期日 (DD/MM/YYYY)
24	1 no. x 5 kg CO2 F.E.	STT No. MX 18030 : CS-226	Conforms with FSD requirements (Defects see Part 3)	08/02/2023	07/02/2024
24	5 nos. x 2 kg dry powder F.E.	STT No. MX 18030 : CS-226	Conforms with FSD requirements	08/02/2023	07/02/2024
24	10 nos. x 5 kg dry powder F.E.	STT No. MX 18030 : CS-225 & CS-226	Ditto	08/02/2023	07/02/2024
24	37 nos, x 5 kg CO2 F.E.	Ditto .	Ditto	08/02/2023	07/02/2024
24	11 110. X 9.7 KO ( 1)7 F F	STT No. MX 18030 : CS-225	Ditto	08/02/2023	07/02/2024














Construction Industry Council - Lam Tei Training Ground


## Part 1 Annual Maintenance ONLY


第一部 只適用於年檢專項


In accordance with Regulation 8(b) of the Fire Service (Installations and Equipment) Regulations, the owner of any fire service installation or equipment which is installed in any premises shall have such fire service installation or equipment inspected by a registered contractor at least once in every 12 months. 根據消防(裝置及設備)規例第八條(b)款,擁有裝置在任何處所內的任何消防裝置或設備的人,須每12個月由一名註冊承號商檢查該等消防裝置或設備至少一次。


Code 網碼 (1-35)	Type of FSI 裝置類型	Localion(s)位置	Comment on Condition 狀況評述	Completion Date 完成日期 (DD/MM/YYYY)	Next Due Date 下次到期日 (DD/MM/YYYY)	
25	4 nos, x sand bucket	STT No. MX 18030 : CS-225 & CS-226	Conforms with FSD requirements	08/02/2023	07/02/2024	
					<u> </u>	
-						

















Construction Industry Council - Lam Tei Training Ground


	三部 Defects 損壞事項				
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置 Outstanding Defects 未移缺點 Co		Comment on Defects 缺點評述	
24	1 no. x 5 kg CO2 F.E.	STT No. MX 18030 : CS-226	Expired for hydraulic pressure test	Required for hydraulic pressure test/replacement	
	,		·		
,		·			
Li					
















Construction Industry Council - Lam Tei Training Ground







#### Plan 1 (Location Plan)



#### Plan 2 (Site Plan)




Plan 3 (Layout Plan)




## Appendix Ia of <a href="https://example.com/RNTPC">RNTPC</a> Paper No. A/TM-LTYY/456

☐ Urge	nt 🗌 Return Receipt Requested 👚 Sign 🔲 Encrypt 🗀 Mark Subject Restricted 🗀 Expand personal&public
	{In Archive} Fw: Renewal of Planning Permission (No. A/TM-LTYY/398) Temporary Training Ground (HKIC, CIC) at Lam Tei 08/05/2023 08:55
From: To: File Ref:	Danny Hoi Hei NG/PLAND/HKSARG tpbpd/PLAND/HKSARG@PLAND
Archive:	This message is being viewed in an archive.
Forward	ded by Danny Hoi Hei NG/PLAND/HKSARG on 08/05/2023 08:55
From: To: Cc:	"dhhng@pland.gov.hk" <dhhng@pland.gov.hk></dhhng@pland.gov.hk>
Date: Subject:	05/05/2023 18:57 Renewal of Planning Permission (No. A/TM-LTYY/398) Temporary Training Ground (HKIC, CIC) at Lam Tei
before pro Best regar Ferrero Y	rds,
Ferrer \	ći O
Assistant N Office	Manager – Estates
CONSTRUC	CTION INDUSTRY COUNCIL
Tel:	Email:

☐ Urgent	☐ Return Receipt Requested ☐ Sign ☐ Encrypt ☐ Mark Subject Restricted ☐ Expand personal&publ	ic (
	Fw: Application No. A/TM-LTYY/456 - Departmental Comments 22/05/2023 08:58	
From: To:	Eva Ka Yan TAM/PLAND/HKSARG tpbpd@pland.gov.hk	
Forwarded	by Eva Ka Yan TAM/PLAND/HKSARG on 22/05/2023 08:57	
From: To: Cc:	"ekytam@pland.gov.hk" <ekytam@pland.gov.hk></ekytam@pland.gov.hk>	
Date: Subject:	19/05/2023 15:02 RE: Application No. A/TM-LTYY/456 - Departmental Comments	
Dear Ms TA	AM,	
We refer to	o your email dated 19 May 2023.	
Please find	the latest FSI proposal for your perusal.	
Thanks & re Ferrero YIP	•	
H20003-PD-020	0_FSI resubmission_210906_drawing_sign c.pdf	
Ferrer Yi		
Assistant Man Office	nager – Estates	
CONSTRUCTIO	ON INDUSTRY COUNCIL	
Tel:	Email:	





## Appendix Ic of RNTPC Paper No. A/TM-LTYY/456



RE: Planning Application No. A/TM-LTYY/456 - Departmental Comments30/05/2023 14:31

From:

To: "tpbpd@pland.gov.hk" <tpbpd@pland.gov.hk>

Cc: "dhhng@pland.gov.hk" <dhhng@pland.gov.hk>, "ekytam@pland.gov.hk"

1 Attachment



 $LTTGGC\_FS251.pdf$ 

Dear Sir/Madam,

With reference to below email.

Please find the latest FS251 for your perusal.

In addition, we confirm to maintain the existing tree planting within the Site in good condition at all times during the planning approval period.

Thanks & regards, Ferrero YIP

#### **Ferrero Yip**

Assistant Manager – Estates Office CONSTRUCTION INDUSTRY COUNCIL



Follow us







**#** 

建造業議會可持續建築大獎2023 | 立即報名 | 展示專業的可持續作業

CIC Sustainable Construction Award 2023 | Apply Now | Play a leading role in sustainable development!

The contents of this email are intended for the named addressee(s) only and may contain confidential information and/or copyrighted materials. If you are not the intended recipient or received it in error, please notify the sender immediately and then delete it. Any unauthorised use, disclosure, reproduction, copying, distribution, or other forms of dissemination of the contents is expressly prohibited. We also take no responsibility for any potential malware and viruses that might be transferred through this email.

# FIRE SERVICE (INSTALLATIONS AND EQUIPMENT) REGULATIONS 消防(装置及設備)規例 (Regulation 9(1))

Serial	Number	

30216031597

## FSD Ref.: 消防處檔號

## (第九條(1)款) CERTIFICATE OF FIRE SERVICE INSTALLATION AND EQUIPMENT


Name of 0	Client 顧客姓名	消防裝	置及設備證書	:			
	ction Industry Council - Lam Tei	Training Ground				ienus se s	evsetal
Address ±	也址		<u> </u>				약약(A) 강영(1급)
Governn	nent Land (STT no. MX 18030 : C	S-225 & CS-226),	4			<b>200</b>	
Kong Sh	am Western Highway,Wong Kor	ng Wai Road, Lam Tei, Tuer	n Mun, NT				
Type of Bu	ilding 樓字類型: Industrial 工業	Commercial 商業 Domestic (	生宅 Compo	site 綜合 Licensed pr	emises 持牌處所	Institutiona	· [13.4.30x4]   社團
	ONLY or equip	dance with Regulation 8(b) of the F ment which is installed in any prem once in every 12 months. 根據消防 注冊水辦商檢查该等消防裝置或設	ises shall have s (裝置及設備)規例	uch fire service installation	or equipment inspec	cted by a regis	tered contractor
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置	Comment o	n Condition 狀況評述 	Completion Da 完成日期 (DD/MM/YYYY	下	t Due Date 次到期日 MM/YYYY)
Part 2 第	三部 Installation / Modification / F	Repair / Inspection works 裝	置/改裝/修理	/檢查工作		,	
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置		f Work Carried out 战之工作內容	Comment on Co 狀況評述	ridition	mpletion Date 完成日期 D/MM/YYYY)
24	23 nos. x 2 kg dry powder F.E.	STT No. MX 18030 : CS-225 & CS-226	F.E. for rep	olaced	Conforms wi FSD requirer	1 1	5/03/2023
24	9 nos. x 5 kg dry powder F.E.	Ditto	Ditto		Ditto	1	5/03/2023
Part 3 第	三部 Defects 損壞事項						
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置		Dutstanding Defects 未	修缺點	1	nt on Defects 點評述
						1	
				For and 美利	on behalf of 堅消防工程	有限公	ਰੀ
	美利堅消防工程を限公司 AMERICAN FIRE ENGINEERING COMPANY LIMITED Authorized Signature: 受權人簽署 Name:						
working or Equipment time to time	by certify that the above installations/equip der in accordance with the Codes of Pra and Inspection, Testing and Maintenand e by the Director of Fire Services. Defects 問以上之消防裝置及設備經試驗,證明性能	actice for Minimum Fire Service II ce of Installations and Equipment are listed in Part 3.	nstallations and published from	姓名 FSD/RC No.: 消防處註冊號碼 Company Name:	3 / 0216 RC		Inspected
裝置及設備守則與裝置及設備之檢查測試及保養守則的規格,損壞事項列於第三部.  公司名稱  Chung Ping Luen  如證書涉及年檢事項,應張貼於大廈或						Key-in	
處所當眼處以供消防處人員查核  This certificate should be displayed at prominent location of the building or  Telephone:  White the prominent location of the building or Date:    Telephone:   White the prominent location of the building or   Date:   16/03/2023						Verified	
F.S. 251	nises for FSD's inspection if any ar (Rev. 01/2012) )-bb6e-b570-0aed-235b-ad5b-f0db						Page 1 of 3


30216031597


Name of Client 顧客姓名


Construction Industry Council - Lam Tei Training Ground


Part 2 第二部 Installation / Modification / Repair / Inspection works 裝置/改裝/修理/檢查工作							
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置	Nature of Work Carried out 完成之工作內容	Comment on Condition 狀況評述	Completion Date 完成日期 (DD/MM/YYYY)		
24	1 no. x 5 kg CO2 F.E.	STT No. MX 18030 : CS-226	F.E. for replaced	Conforms with FSD requirements	15/03/2023		














Construction Industry Council - Lam Tei Training Ground







RE: Planning Application No. A/TM-LTYY/456 - Departmental Comments05/06/2023

11:10 From:

To: "tpbpd@pland.gov.hk" <tpbpd@pland.gov.hk>

Cc: ekytam@pland.gov.hk"

<ekytam@pland.gov.hk>, "dhhng@pland.gov.hk" <dhhng@pland.gov.hk>

History

This message has been forwarded.

#### 1 Attachment



20230605 RtoC\_TD comments.pdf

Dear Sir/Madam,

With reference to below email.

Please find the attached responses to comments for your perusal.

The relevant TIA report can be downloaded at below link. https://drive.google.com/drive/folders/1toxQVIjMewotpp-ZQxUjLdJlxZ6V4h2j?usp=sharing

Thanks & regards, Ferrero YIP

## **Ferrero Yip**

Assistant Manager – Estates Office CONSTRUCTION INDUSTRY COUNCIL











建造業議會可持續建築大獎2023 | 立即報名 | 展示專業的可持續作業 CIC Sustainable Construction Award 2023 | Apply Now | Play a leading role in sustainable development!

The contents of this email are intended for the named addressee(s) only and may contain confidential information and/or copyrighted materials. If you are not the intended recipient or received it in error, please notify the sender immediately and then delete it. Any unauthorised use, disclosure, reproduction, copying, distribution, or other forms of dissemination of the contents is expressly prohibited. We also take no responsibility for any potential malware and viruses that might be transferred through this email.

# Application No. A/TM-LTYY/456 under s.16 of the Town Planning Ordinance

# **Summary of Responses to Comments (5 June 2023)**

	Comments	Responses				
	Comments from Commissioner for Transport via PlanD's email dated 1 June 2023					
a.	Please advise the number of vehicular and pedestrian	Please refer to the submitted TIA report.				
	trip generation and attraction by the subject site.					
b.	Please clarify if any shuttle service will be provided by	No shuttle service will be provided.				
	the subject site.					
c.	Please clarify the size of proposed private car and	Please refer to Figure 2.2 of the submitted TIA report.				
	motorcycle parking spaces and their locations as they	Parking space of private car: 5m x 2.5m				
	are not easily readable on the layout plan	Parking space of motorcycle: 2.4m x 1m				
d.	Please clarify the width of the proposed two vehicular	About 6m width.				
	accesses and the internal driveways of the subject					
	site.					
e.	Please supplement the swept path analysis showing	Please refer to Figure 2.3 to 2.5 of the submitted TIA				
	the vehicles (i) using the private car and motorcycle	report.				
	parking spaces, (ii) manoeuvring within the internal					
	driveway, and (iii) entering and leaving the site from					
	Wong Kong Wai Road through the proposed vehicular					
	accesses.					

f.	Please justify that the proposed parking provisions are sufficient to cater for the parking demand due to	Please refer to Section 2.4 of the submitted TIA report
	the proposed use.	
g.	It is noted that internal driveways are reserved within the subject site. Please ensure that no queuing and / or waiting of motor vehicles from the subject site onto public roads would occur and no motor vehicles shall be permitted to reverse into and out of the subject site onto adjacent public roads or Government Land.	Noted.

Appendix 6
Traffic Impact Assessment

## **Document Status Control Record**

# Proposed Training Ground in Lam Tei for the Hong Kong Institute of Construction Construction Industry Council

**Traffic Impact Assessment** 

Originating Organisation :	Prepared by:	Date: 13 February 2020
LLA Consultancy Limited Unit 610, 6/F, Island Place Tower,	Approved by:	Date: 13 February 2020
510 King's Road, North Point, Hong Kong	Revision No.: -	Date of Issue: 13 February 2020

Note: © – LLA Consultancy Limited. All rights reserved. Except for the internal use by the client for whom this document is prepared by LLA Consultancy Limited. No part of this document, which contains valuable trade secrets of a confidential nature to LLA Consultancy Limited may be (1) reproduced, stored in a retrieval system, or transmitted in any format or by any means, electronic, mechanical, photocopying, recording or otherwise; or (2) disclosed to any third party, without the prior consent of LLA Consultancy Limited.

#### 1 INTRODUCTION

#### 1.1 Background

- 1.1.1 The Construction Industry Council (CIC) intends to develop a training ground at a vacant site underneath the Kong Sham Western Highway in Lam Tei, Tuen Mun. In view of the planning context of the Site, a Section 16 planning application is required and a traffic impact assessment (TIA) to support the application is necessary.
- 1.1.2 LLA Consultancy Limited was commissioned to carry out a traffic impact assessment study to assess the potential traffic impact from the updated proposal on the traffic network in the vicinity and propose suitable mitigation measures to improve the traffic conditions, if necessary.

### 1.2 Objectives

- 1.2.1 The objectives of this study can be summarized as follows:
  - to review the existing traffic conditions in the surrounding road network;
  - to estimate the traffic generation/ attraction of the proposed training ground;
  - to project the future traffic situation in the surrounding road network;
  - to appraise the potential traffic impact of the proposed training ground; and
  - to recommend the internal transport facilities for the proposed training ground based on the operational needs.

#### 2 THE PROPOSED DEVELOPMENT

#### 2.1 The Site

- 2.1.1 The Site for the proposed training ground consists of two pieces of vacant government land under reference no. CS-225 (Part) and CS-226 (Part), separated by an existing footpath. It has a total area of about 10,300 m². It is located mainly under the existing Kong Sham Western Highway near Nai Wai Village, Lam Tei, Tuen Mun and the location of the Site is shown in **Figure 2.1**.
- 2.1.2 At present, the Site is about 500m from Castle Peak Road-Lam Tei and can be accessed via Wong Kong Wai Road. The Site can also be accessed from Castle Peak Road-Hung Shui Kiu Section via Fuk Hang Tsuen Road but the distance is comparatively longer.

### 2.2 The Proposed Training Ground

2.2.1 The proposed training ground will accommodate a total of 400 nos. of students and of 20 nos. of staff. The operating hours will be from 08:00 to 17:00 on Mondays to Fridays and 08:00 to 13:00 on Saturdays. The key development parameters are listed out in **Table 2.1**.

Table 2.1 Key Development Parameters

Item	Details
Site Area	10,300 m²
Number of Students	400
Number of Staff	20

### 2.3 Access Arrangements

- 2.3.1 The Site consists of two pieces of land and they are separated by a footpath. So, one vehicular access (6m in width) is proposed to serve each piece of land and a total of two vehicular accesses will be provided. The layout of the proposed training ground is shown in **Figure 2.2**.
- 2.3.2 Swept path analysis is conducted to demonstrate there are sufficient maneuvering spaces for vehicles maneuvering in/out of the proposed training ground (refer to **Figure 2.3**, **2.4** and **2.5**).

#### 2.4 Proposed Car parking and Loading/unloading Provisions

2.4.1 There is no specific guideline set in the Hong Kong Planning Standards and Guidelines for training grounds, the proposed car parking provision will be based on the existing provisions of other CIC training grounds as well as meeting the operational needs. **Tables 2.1** listed out the existing car parking provisions at the five existing training grounds operated by CIC.

Table 2.2 Car Parking Provisions of the Existing CIC Training Grounds – Bar Bending and Timber Formwork Training

Site	Name of Training Ground	Maximum Staff No.	Maximum Student No.	No. of Carparking Provision	No. of space / staff
1	Kwun Tong - Wai Lok Street	28	400	8	0.29
2	Tin Yuet Road	7	90	2	0.29
3	5-7 Wong Lung Hang Road, Tung Chung	6	70	2	0.33
4	Tung Chau Street, Sham Shui Po	4	60	0	0
5	Siu Lun Street, Tuen Mun	5	80	2	0.40

- 2.4.2 For all the existing CIC training grounds, the car parking spaces are solely reserved for staff use and no space is allowed for visitors and trainers. Having considered the provision rate per staff at the five existing training grounds, it is suggested to provide 8 car parking spaces, which is equivalent to the rate of 0.4 space/staff, for the proposed training ground. Also, two additional motorcycle parking spaces will also be provided to serve the possible demand.
- 2.4.3 There is no regular loading/unloading demand at the proposed training ground. The minimal loading/unloading activities can be carried out along the internal access road and will not generate a traffic queue onto the public road.

#### 3 EXISTING TRAFFIC SITUATION

#### 3.1 Existing Road Network

- 3.1.1 The Site has one frontage at Wong Kong Wai Road, which is a single track access road with various passing bays. The capacity of this type of single track access road is 100 vehicles/hour. It forms a left-in-left-out priority junction with Castle Peak Road-Lam Tei.
- 3.1.2 Castle Peak Road-Lam Tei is a district distributor road connecting Tuen Mun to Hung Shui Kui. If forms the primary access for all local developments and villages along the road.
- 3.1.3 Fuk Hang Tsuen Road is a local road connecting Castle Peak Road-Lam Tei and Lam Tei Main Street. It forms a traffic signal controlled junction with Castle Peak Road-Lam Tei.

## 3.2 Traffic Count Surveys

- 3.2.1 In order to assess the existing traffic conditions, a traffic count survey was carried out at the following locations in the vicinity of the Site on 12 September 2019 (Thursday) and 15 January 2020 (Wednesday) during the peak hour period from 07:30 to 09:30 and 16:30 to 18:30. The locations of the surveyed junctions and the area of influence (AOI) are presented in **Figure 3.1**.
  - Castle Peak Road-Lam Tei / Wong Kong Wai Road
  - Castle Peak Road Lam Tei / Fuk Hang Tsuen Road
  - Wong Kong Wai Road / Man Chat Road
  - Wong Kong Wai Road / Tat Fuk Road
  - Fuk Hang Tsuen Road / Tat Fuk Road
- 3.2.2 The identified AM and PM peak hours are 08:00 09:00 and 16:30 17:30, respectively. The recorded peak hour traffic flows are presented in **Figure 3.2**.

### 3.3 Existing Junction Capacity Assessment

3.3.1 Based on the existing traffic flows, the performance of the key junctions during the AM and PM peak hours were assessed. The results are summarized and presented in **Table 3.1** and detailed junction capacity calculation sheets are presented in **Appendix A**.

Table 3.1 Existing Junction Capacity Assessment

No.	Junction	Type/ Capacity Index <sup>(1)</sup>	AM Peak	PM Peak
А	Castle Peak Road-Lam Tei/ Wong Kong Wai Road	Priority/DFC	0.06	0.07
В	Castle Peak Road-Lam Tei/ Fuk Hang Tsuen Road	Signalized/RC	25%	32%
С	Wong Kong Wai Road / Man Chat Road	Priority/DFC	0.05	0.07
D	Wong Kong Wai Road / Tat Fuk Road	Priority/DFC	0.03	0.03
Е	Fuk Hang Tsuen Road / Tat Fuk Road	Priority/DFC	0.02	0.02

Note:

- 1) DFC = Design flow to capacity ratio for priority junction.
- (2) RC = Reserved capacity for signalized junction.

3.3.2 **Table 3.1** indicates that all junctions are performing satisfactorily during both AM and PM peak hours.

## 3.4 Existing Link Capacity Assessment

3.4.1 Being a single track access road, the Volume to Capacity (V/C) Ratios of Wong Kong Wai Road were assessed and the results are presented in **Table 3.2**.

Table 3.2 Link Capacity Assessments

			Pea	ak hour	Traffic F	low	V/C Ratio	
Road	Direction	Capacity (veh/hr)	pcu/hr		veh/hr [B]		[B] / [A]	
1.044		[A]	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak
Wong Kong Wai Road (between Site Access and Castle Peak Rd)	2-way	100	79	85	66	71	0.66	0.71

3.4.2 As shown in **Table 3.2**, the concerned section of Wong Kong Wai Road is operating with spare capacities during both AM and PM peak hours.

## 3.5 Existing Public Transport Services

3.5.1 At present, there are 13 existing bus routes and one minibus route travelling along Castle Peak Road. The details of the bus/minibus routes are shown in **Table 3.3** and the locations of various public transport services are marked on **Figure 3.3**.

Table 3.3 Existing Public Transport Routes

Mode	Route No.	Origin-Destination	Frequency (min)
Bus	53	Yuen Long Station – Tsuen Wan West Station PTI	25 – 35
	63X	Hung Shui Kiu (Hung Fuk Estate) – West Kowloon Station	12 – 30
	68A	Yuen Long (Long Ping) – Tsing Yi Station	8 – 20
	258A	Hung Shui Kiu – Lam Tin Station	07:20
	258P	Lam Tin Station – Hung Ting Road (Hung Fuk Estate)	12 – 30
	261P	Ng Lau Road (Tsing Lun Road) – Tin Ping Estate	3 per day
	960A	Central (Worldwide House) – Hung Shui Kiu (Hung Fuk Estate)	18:30
	960B	Quarry Bay (Kings Road) – Hung Shui Kiu (Hung Fuk Estate)	4 per day
	960P	Hung Shui Kiu (Hung Yuen Road) – Wan Chai North	10 per day
	960X	Hung Shui Kiu (Hung Yuen Road) – Quarry Bay (King's Road)	5 per day
	A33P	Tuen Mun Chung Uk Tsuen – Airport	07:05
	B2	Yuen Long Station – Shenzhen bay Port	10 – 20
	N969	Causeway Bay (Moreton Terrace) – Tin Shui Wai Town Centre	20 – 30
GMB	606S	Yuen Long (Fung Cheung Road) – Tsum Sha Tsui East	6 – 13

#### 4 FUTURE TRAFFIC SITUATION

#### 4.1 Design Year

4.1.1 The proposed training ground is planned to be completed by 2021. Therefore, the design year for the subsequent traffic impact assessment will be 2024, i.e. 3 years after the commencement of operation.

## 4.2 Adjacent Approved Developments

4.2.1 To estimate the future traffic flows, updated information has been obtained from available information regarding the planned and approved developments in the vicinity of the study area. Details of these developments are given in **Table 4.1**.

Table 4.1 Details of Planned and Approved Developments

Site	Ref.	Location	Use	Content
S1	DC 2016/78	Hung Shui Kiu Development	Residential	61,000 units
			Commercial	2,000,000m <sup>2</sup>
			Industrial	4,300,000m <sup>2</sup>
S2	A/TM-LTYY/249-2	Proposed Comprehensive Development Area at Lots in D.D.130, Lam Tei	Residential	126 units
S3	A/TM-LTYY/290	Proposed Flat Development at Lots in D.D.130, Lam Tei	Residential	132 units
S4	A/TM-LTYY/337	Proposed Flat at Lots in D.D.130, San Hing Road, Lam Tei	Residential	35 units
S5	LC Paper No. CB(2)350/16-17(03)	RCHE at Fuk Hang Tsuen Road, Lam Tei by Pok Oi Hospital	RCHE	1,405 beds

4.2.2 Reference was also made to the latest set of traffic generation and attraction rates published by the Transport Department for the estimation of the traffic generated by these developments. The traffic generation/attractions by these adjacent developments are taken into account in the following assessment.

#### 4.3 Future Traffic Flows

4.3.1 In order to establish the traffic growth rate in the vicinity of the Site, reference was made to the 2014 to 2018 Annual Traffic Census Reports published by Transport Department, reporting on the annual average daily traffic (AADT) flows at the counting stations in the territory. The details of the counting stations in the study area and the corresponding counts are shown in **Table 4.2**.

Table 4.2 Annual Traffic Census Data

Stn.		Road Section			AADT <sup>(1)</sup>				Avg.
No.	Road	From	То	2014	2015	2016	2017	2018	Growth%
5296	Castle Peak Road – Lingnan	Fu Tei Road	Lam Tei Int	8,860	8,790 (-0.8%)	9,150 (4.1%)	9,010 (-1.5%)	10,030 (11.3%)	3.1%
6604	Lam Tei Main Street	Castle Peak Road - Lam Tei	Fuk Hang Tsuen Road	890	1,060 (19.1%)	1,170 (10.4%)	1,190 (1.7%)	880 (-26.1%)	-0.3%
6213	Castle Peak Road – Hung Shui Kiu	Tin Ha Road	Lam Tei Int	33,510	31,720 (-5.3%)	33,490 (5.6%)	34,140 (1.9%)	32,740 (-4.1%)	-0.6%
	Total			43,260	41,570 (-3.9%)	43,810 (5.4%)	44,340 (1.2%)	43,650 (-1.6%)	0.2%

Note: (1) Figures in bracket indicated the % increase/decrease between two years.

4.3.2 From **Table 4.2**, the adjacent station recorded growth between Year 2014 to Year 2018 with an annual growth rate of +0.2%.

Territorial Population and Employment Data Matrix Data

4.3.3 Reference was also made to the 2016 – based Territorial Population and Employment Data Matrix (TPEDM) published by the Planning Department (PlanD). The population and employment data of year 2016 and 2026 are summarized in **Table 4.3**.

Table 4.3 TPEDM Data – Tuen Mun

Year	Population	Employment	Total
2016	464,150	126,300	590,450
2026	534,600	140,550	675,150
	+1.35%		

- 4.3.4 As shown in **Table 4.3**, the average annual growth rate of population and employment number in Tuen Mun District is +1.35% between Year 2014 and Year 2026.
- 4.3.5 To produce a conservative estimation, the larger annual growth rate of +1.35% derived from TPDM has been adopted into the subsequent traffic forecast.

#### 4.4 Traffic Generation for the Proposed Training Ground Development

4.4.1 Trip rates for training ground are not documented in the Transport Planning and Design Manual (TPDM) published by the Transport Department, traffic generation surveys were conducted at two selected existing training grounds. The selection criteria consider the availability of public transport, and no. of users of the training ground. The results are presented in **Table 4.4**.

**AM Peak Hour PM Peak Hour** Unit/ No. of Site **Trainees** Content Total Gen. Att. Gen. Att. **Total** Kwun Tong - Wai 100(1) 2 pcu/hr 2 4 6 3 5 Lok Street 30<sup>(1)</sup> 2 2 Tin Yuet Road pcu/hr 1 3 1 1 **Derived Trip Rates** Kwun Tong - Wai pcu/hr/ 0.0200 0.0400 0.0300 0.0200 Lok Street trainee pcu/hr/ Tin Yuet Road 0.0333 0.0667 0.0333 0.0333 trainee Traffic Generation/ Attraction of the 400 pcu/hr 14 27 41 14 14 28 **Proposed Training Ground** 

Table 4.4 Proposed Training Ground Development Traffic Generation

Note: (1) The number of trainees during the surveyed periods are provided by the corresponding CIC training Centre

- 4.4.2 As shown in the results, a set of higher traffic generation rate is obtained at Tin Yuet Road Training Ground. Also, in view of the locational characteristic (approximate 1 km away from the railway station) of Tin Yuet Road Training Ground is similar to that of the proposed training ground, its derived trip rates are adopted to estimate the traffic generation of the proposed training ground.
- 4.4.3 The proposed training ground will induce an additional two-way traffic of 41 pcu/hour and 28 pcu/hour during both AM and PM peak hours, respectively. The development traffic is assigned onto the road network as shown in **Figure 4.1**.

## 4.5 2024 Reference and Design Flows

4.5.1 The 2024 Reference Flows, i.e. the traffic flows in the local road network without the additional traffic generated by the Site is estimated based on the following equation.

2024 Reference Flows = 2019 Observed Traffic Flows x  $(1 + 1.35\%)^5$  + Traffic Generated by the Adjacent Approved Development

- 4.5.2 The traffic arrangements for private car will be re-arranged in future scenario. The reference traffic flows are adjusted accordingly to reflect future base traffic flows.
- 4.5.3 The 2024 Design Flows, i.e. the traffic flows in the local road network with the additional traffic generated by the proposed training ground, were estimated based on the following equation:

2024 Design Flows = 2024 Reference Flows + Additional Development Traffic Flows

4.5.4 The 2024 Reference Flows and Design Flows are shown in **Figure 4.2** and **Figure 4.3**, respectively.

#### 4.6 Junction Capacity Assessment

4.6.1 Assessments of the junction performance were based on the 2024 reference and design flows. The assessment results are summarized in **Table 4.5** and the calculations sheets are attached in **Appendix B**.

Table 4.5 2024 Junction Capacity Assessment

Na	Junction	Type/	2029 Re	ference	2029 🛭	Design
No.	Junction	Capacity Index <sup>(1)</sup>	AM Peak	PM Peak	AM Peak	PM Peak
А	Castle Peak Road-Lam Tei/ Wong Kong Wai Road	Priority/DFC	0.07	0.07	0.08	0.09
В	Castle Peak Road-Lam Tei/ Fuk Hang Tsuen Road	Signals/RC	1%	3%	-1%	2%
С	Wong Kong Wai Road / Man Chat Road	Priority/DFC	0.05	0.07	0.08	0.09
D	Wong Kong Wai Road / Tat Fuk Road	Priority/DFC	0.03	0.04	0.03	0.04
E	Fuk Hang Tsuen Road / Tat Fuk Road	Priority/DFC	0.02	0.03	0.02	0.03

Note:

- (1) DFC = Design flow to capacity ratio for priority junction.
- (2) RC = Reserved capacity for signalized junction.
- 4.6.2 As shown in **Table 4.5**, junction A will operate satisfactorily in both the reference and design scenarios. For junction B at J/O Castle Peak Road Lam Tei/Fuk Hang Tsuen Road, it will operate near its capacity.
- 4.6.3 In association with the proposed widening of Fuk Hang Tsuen Road, a junction modification works at J/O Castle Peak Road Lam Tei/Fuk Hang Tsuen Road was being planned. The traffic situation discussed in **Table 4.5** would be an interim stage and will be improved upon the completion of the road works. Details of the junction improvement works will be discussed in the following section.

#### 4.7 Junction Improvement at J/O Castle Peak Road-Lam Tei/ Fuk Hang Tsuen Road

- 4.7.1 It is estimated that J/O Castle Peak Road Lam Tei/Fuk Hang Tsuen Road will be operating beyond its capacity during both AM and PM peak hour. Based on the public information available, it is understood that the existing 6.5m Fuk Hang Tsuen Road will be widened to 10.3m. Also, J/O Castle Peak Road Lam Tei/Fuk Hang Tsuen Road will be modified and a junction improvement scheme is formulated and presented in **Figure 5**.
- 4.7.2 The junction performance is re-assessed based on the improved junction layout. The results are presented in **Table 4.6** and detailed junction capacity calculation sheets are presented in **Appendix C**.

Table 4.6 Junction Capacity Assessment for Design Year 2024 with Junction Improvement)

			2024 Design								
No.	Junction Location	Type /Capacity	Without In	nprovement	With Improvement						
		Index <sup>(1)</sup>	AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour					
J1	Castle Peak Road – Lam Tei/Fuk Hang Tsuen Road	Signalized /RC	-1%	2%	3%	2%					

4.7.3 As shown in **Table 4.6**, the junction performance of J/O Castle Peak Road – Lam Tei/Fuk Hang Tsuen Road will be improved upon the completion of the junction modification works. Therefore, the proposed residential development is acceptable in traffic point of view.

## 4.8 Link Capacity Assessment

4.8.1 Being a single track access road, the Volume to Capacity (V/C) Ratios of Wong Kong Wai Road were assessed and the results are presented in **Table 4.7**.

Table 4.6 Link Capacity Assessments

		Capacity (veh/hr)	Pea	ak hour	Traffic F	low	V/C Ratio [B] / [A]		
Road	Direction		рсі	ı/hr	veh/h	ır [B]			
		[A]	AM Peak	PM Peak	AM Peak	PM Peak	AM Peak	PM Peak	
Wong Kong Wai Road (between Site Access and Castle Peak Rd)	2-way	100	107	106	90	90	0.9	0.9	

4.8.2 **Table 4.7** shows that the concerned section of Wong Kong Wai Road will be operating with spare capacities during both AM and PM peak hours.


#### 5 SUMMARY AND CONCLUSION


#### 5.1 Summary


- 5.1.1 The Construction Industry Council intends to develop a training ground at a vacant site underneath the Kong Sham Western Highway in Lam Tei, Tuen Mun.
- 5.1.2 The proposed training ground will accommodate a total of 400 nos. of students and 20 nos. of staff. The car parking spaces are solely reserved for staff use and no space is allowed for visitors and trainers. It will provide 8 car parking spaces and 2 additional motorcycle parking spaces for operation use. There is no regular loading/unloading demand at the proposed training ground. The minimal loading/unloading activities can be carried out along the internal access road and will not generate a traffic queue onto the public road.
- 5.1.3 Traffic count survey was conducted to establish the current traffic conditions at the concerned junctions during AM and PM peak periods at 07:30 09:30 and 16:30 18:30 of typical weekdays. Based on the existing traffic flows, the junction capacity and link capacity assessments show that all junctions and the concerned section of Wong Kong Wai Road are operating satisfactorily.
- 5.1.4 Based on the traffic generation survey results on two other existing training grounds, the proposed training ground is expected to induce minimal two-way traffic flows of 41 pcu/hr and 28 pcu/hr in the AM and PM peak hours, respectively. The increase in traffic was assigned onto the existing road network based on the observed traffic pattern.
- 5.1.5 Junction capacity assessments for the key junctions and link capacity assessment at Wong Kong Wai Road were carried out for both the reference and the design scenarios in 2024. The assessment results revealed that all junctions would perform satisfactorily in both scenarios, except Junction B J/O Castle Peak Road Lam Tei/Fuk Hang Tsuen Road which will operate at capacity.
- 5.1.6 In association with the proposed widening of Fuk Hang Tsuen Road, junction modification works at J/O Castle Peak Road Lam Tei/Fuk Hang Tsuen Road was being planned. The junction performance will be improved upon the completion of the junction modification works.


#### 5.2 Conclusion


5.2.1 The findings of the traffic impact assessment indicated that the adjacent road network would be able to cope with the traffic generated by the proposed training ground and it is considered acceptable in traffic viewpoint.






























# Appendix A

Junction Calculation Sheets
- Existing Scenario

LLA CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCU		INITIALS	DATE		
Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Ko	ng Institute of Construction, Construction Industry	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20
J/O Wong Kong Wai Road / Castle Peak Road-Lam Tei	2019 Existing AM	FILENAME :	J1_WKWR_CPRLT.xl	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	O.:	REVIEWED BY:	SLN	Feb-20




q b-c =

30 (pcu/hr)

```
NOTES: (GEOMETRIC INPUT DATA)
                 MAJOR ROAD WIDTH
     W cr =
                 CENTRAL RESERVE WIDTH
     W b-a =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
     W b-c =
     W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
     VIb-a =
                VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
     Vrb-a =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
     Vr b-c =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
     Vr c-b =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
                STREAM-SPECIFIC B-A
       E =
                STREAM-SPECIFIC B-C
       F = STREAM-SPECIFIC C-B
                (1-0.0345W)
```

ETRIC DETAILS:	GEOMETRIC FACTORS:	THE CAPACITY OF MOVEMENT :	COMPARISION OF DESIGN FLOW TO CAPACITY:		
MAJOR ROAD (ARM A)					
W = 11.2 (metres)	D = 0.9921	Q b-a = 368	DFC b-a	=	0.0000
W cr = 0.0 (metres)	E = 1.0820	*Q b-c = 476 Q b-c (O) = 476	DFC b-c	=	0.0630
q a-b = 49 (pcu/hr)	F = 1.3047	Q c-b = 629	DFC c-b	=	0.0000
q a-c = 1127 (pcu/hr)	Y = 0.6136	Q b-ac = 476			
	F for (Qb-ac) = 1.0000	TOTAL FLOW = 1206 (PCU/HR	)		
MINOR ROAD (ARM B)			CRITICAL DFC	=	0.06
W b-c = 5.5 (metres)					
Vr b-c = 33 (metres)					
q b-a = 0 (pcu/hr)					

<b>LLA</b> CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCU	INITIALS	DATE			
Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Ko	ng Institute of Construction, Construction Industry	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20
J/O Wong Kong Wai Road / Castle Peak Road-Lam Tei	2019 Existing PM	FILENAME :	J1_WKWR_CPRLT.xl	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	O.:	REVIEWED BY:	SLN	Feb-20



q b-a =

q b-c =

0 (pcu/hr) 31 (pcu/hr)

```
NOTES: (GEOMETRIC INPUT DATA)
                 MAJOR ROAD WIDTH
     W cr =
                 CENTRAL RESERVE WIDTH
     W b-a =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
     W b-c =
     W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
     VI b-a =
                VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
     Vrb-a =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
     Vr b-c =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
     Vr c-b =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
                STREAM-SPECIFIC B-A
       E =
                STREAM-SPECIFIC B-C
       F = STREAM-SPECIFIC C-B
                (1-0.0345W)
```

TRIC DETAIL	.S:		GEOMETRIC FA	CTORS :		THE CAPACITY OF MO	/EMENT :			COMPARISION OF DESIGN FLOT TO CAPACITY:	V	
MAJOR ROA	D (ARM A)											
W =	11.2	(metres)	D	=	0.9921	Q b-a =	368			DFC b-a	=	0.0000
W cr =	0.0	(metres)	E	=	1.0820	*Q b-c =	476	Q b-c (O) =	476	DFC b-c	=	0.0651
q a-b =	54	(pcu/hr)	F	=	1.3047	Q c-b =	628			DFC c-b	=	0.0000
q a-c =	1127	(pcu/hr)	Υ	=	0.6136	Q b-ac =	476					
			F for (Qb-	ac) =	1.0000	TOTAL FLOW	=	1212	(PCU/HR)			
MINOR ROAL	O (ARM B)									CRITICAL DFC	=	0.07
W b-c =	5.5	(metres)										
Vr b-c =	33	(metres)										

# **LLA** CONSULTANCY LIMITED

NOTE:


O - OPPOSING TRAFFIC

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

# 2019 Existing AM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Feb-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Feb-20
		Reviewed By:	SLN	Feb-20



Loss time		L =	25	sec
Total Flow		=	2705	pcu
Co	= (1.5*L+5)/(1-Y)	=	99.3	sec
Cm	= L/(1-Y)	=	58.4	sec
Yult		=	0.713	
R.C.ult	= (Yult-Y)/Y*100%	=	24.6	%
Ср	= 0.9 L/(0.9 Y)	=	68.6	sec
Ymax	= 1-L/C	=	0.792	
R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	25	0/



SG - STEADY GREEN

N - NEAR SIDE LANE

Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	13	9
P2	2.3	11.4	10	10	2	70	10

QUEUING LENGTH = AVERAGE QUEUE \* 6m

Move	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation		Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	Х	(m / lane)	(seconds)
																							25					
1	1	3.75	2				4260		798		798	0.00	4260							4260	0.187	0.187		31	31	0.723	57	40
1,2	1	3.60	1	10		N	1975	72	287		359	0.20	1917							1917	0.187			31	31	0.723	48	45
5	2	3.40	1	10			2095			192	192	1.00	1822							1822	0.105	0.105		18	18	0.723	30	60
6	1	3.40	3			N	6145		886		886	0.00	6145							6145	0.144			24	31	0.723	46	44
3,4	3	3.20	1	10		N	1935	294		176	470	1.00	1683							1683	0.279	0.279		46	46	0.723	54	35
	1																											
	1																											
	1	1		l	l	L		l .		l	l	l	1		l		l	L	l	l		1						

FG - FLASHING GREEN

PEDESTRAIN WALKING SPEED = 1.2m/s


# **LLA** CONSULTANCY LIMITED

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

## 2019 Existing PM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Feb-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Feb-20
1		Reviewed By:	SLN	Feb-20



R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	32	%
Ymax	= 1-L/C	=	0.792	
Ср	= 0.9*L/(0.9-Y)	=	62.4	sec
R.C.ult	= (Yult-Y)/Y*100%	=	32.0	%
Yult		=	0.713	
Cm	= L/(1-Y)	=	54.3	sec
Co	= (1.5*L+5)/(1-Y)	=	92.3	sec
Total Flow	•	=	2572	pcu
Loss time		L =	25	sec
Sum(y)		Y =	0.540	
Cycle time	•	C =	120	sec
No. of stag	ges per cycle	N =	3	



Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	20	9
P2	2.3	11.4	10	10	2	71	10

ment   Width   lane   m.   Ahead   Sat. Flow   pcu/h																													
m	Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
1     1     3.75     2       1,2     1     3.60     1     10     N     1975     66     209     275     0.24     1906       5     2     3.40     1     10     10     2095     261     261     261     1041     1041     1041     1041     1041     0.00     6145       6     1     3.40     3     3     0.169     0.169     0.169     0.169     0.169     0.169     0.169     0.169	ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
1     1     3.75     2       1,2     1     3.60     1     10     N     1975     66     209     275     0.24     1906       5     2     3.40     1     10     10     2095     261     261     261     1041     1041     1041     1041     1041     0.00     6145       6     1     3.40     3     3     0.169     0.169     0.169     0.169     0.169     0.169     0.169     0.169			m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	l m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	l x	(m / lane)	(seconds)
1     1     3.75     2       1,2     1     3.60     1     10     N     1975     66     209     275     0.24     1906       5     2     3.40     1     10     N     2095     261     261     261     1.00     1822       6     1     3.40     3     1     10     N     6145     1041     0.00     6145									F	P = = = =	F	p = =,		F		F		p		F = =,	F			25				(,	()
1,2     1     3.60     1     10     N     1975     66     209     275     0.24     1906       5     2     3.40     1     10     N     2095     261     261     1.00     1822       6     1     3.40     3     N     6145     1041     0.00     6145			0.75					4000		040		040	0.00	4000							4000	0.444		25	05	00	0.000	40	42
5 2 3.40 1 10 N 2095 N 6145 1041 261 261 1.00 1822 1822 0.143 0.143 25 25 0.682 36 48 0.169 0.16	1	1	1	2						1																			
6 1 3.40 3 N 6145 1041 1041 0.00 6145	1,2	1	3.60	1	10		N	1975	66	209		275	0.24	1906							1906	0.144			25	30	0.682	42	48
6 1 3.40 3 N 6145 1041 1041 0.00 6145																													
6 1 3.40 3 N 6145 1041 1041 0.00 6145	5	2	3.40	1	10			2095			261	261	1.00	1822							1822	0.143	0.143		25	25	0.682	36	48
	6	1	1	3			l N			1041													1						
3,4 3 3.20 1 10 N 1935 216 166 382 1.00 1683			0.40	ľ			''	0140		1041		10-11	0.00	0140							0140	0.100	0.100				0.002	<u> </u>	
3,4 3 3,20 1 10 N 1935 216 166 382 1.00 1683 1	l	_	l				l		l																			40	
	3,4	3	3.20	1	10		N	1935	216		166	382	1.00	1683							1683	0.227	0.227		40	40	0.682	48	37
									1																				
									1																				

NOTE:

O - OPPOSING TRAFFIC

N - NEAR SIDE LANE


SG - STEADY GREEN

FG - FLASHING GREEN

PEDESTRAIN WALKING SPEED = 1.2m/s

QUEUING LENGTH = AVERAGE QUEUE \* 6m


LLA CONSULTANCY LIMITED	PRIORITY JUNCTION CAL	CULATIO	N		INITIALS	DATE
Feasibility for Proposed Training Ground in Lam Tei for the Hong Ko	ng Institute of Construction, Construction Industry C	PROJECT NO.:	40624	PREPARED BY:	SKL	Feb-20
J/O Wong Kong Wai Road / Man Chat Road	2019 Existing AM	FILENAME :	J3_WKWR_MCR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	O.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                 MAJOR ROAD WIDTH
      W =
      W cr =
                 CENTRAL RESERVE WIDTH
      W b-a =
                 LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
      W b-c =
                 LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                 LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                 VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                 VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
                 VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vr c-b =
       D =
                 STREAM-SPECIFIC B-A
       E =
                 STREAM-SPECIFIC B-C
       F =
                 STREAM-SPECIFIC C-B
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                              GEOMETRIC FACTORS:
                                                                                           THE CAPACITY OF MOVEMENT:
                                                                                                                                                   COMPARISION OF DESIGN FLOW
                                                                                                                                                   TO CAPACITY:
      MAJOR ROAD (ARM A)
                    3.56 (metres)
                                                                        0.83974
                                                                                                  Q b-a =
                                                                                                                 503
                                                                                                                                                                 DFC b-a
                                                                                                                                                                                            0.0477
                                                         Ε
                                                                                                                 671 Q b-c (O) =
                                                                                                                                   663
                                                                                                                                                                 DFC b-c
                                                                                                                                                                                            0.0030
      W cr =
                         (metres)
                                                                        0.91257
                                                                                                 Q b-c =
       qa-b =
                         (pcu/hr)
                                                         F
                                                                        0.90230
                                                                                                 Q c-b =
                                                                                                                 662
                                                                                                                                                                 DFC c-b
                                                                                                                                                                                            0.0498
                                                         Υ
                                                                        0.87718
                                                                                                                                                                 DFC b-c (share lane) =
                                                                                                                                                                                            0.0039
      qa-c =
                     28 (pcu/hr)
                                                                                                 Q b-ac =
                                                                                                                 513
                                                     F for (Qb-ac) =
                                                                     0.07692308
                                                                                                 TOTAL FLOW = 111
                                                                                                                                  (PCU/HR)
      MAJOR ROAD (ARM C)
      W c-b =
                    3.56 (metres)
      Vr c-b =
                    20
                         (metres)
      q c-a =
                     16
                          (pcu/hr)
      q c-b =
                    33
                          (pcu/hr)
                                                                                                                                                   CRITICAL DFC
                                                                                                                                                                                     = 0.05
      MINOR ROAD (ARM B)
      W b-a =
                   3.68
                          (metres)
                   3.68
      W b-c =
                         (metres)
                         (metres)
      Vr b-a =
                         (metres)
      Vr b-c =
                          (metres)
      q b-a =
                     24 (pcu/hr)
      q b-c =
                     2 (pcu/hr)
```


LLA CONSULTANCY LIMITED	PRIORITY JUNCTION CAL	CULATIO	N		INITIALS	DATE
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kor	g Institute of Construction, Construction Industry C	PROJECT NO.:	40624	PREPARED BY:	SKL	Feb-20
J/O Wong Kong Wai Road / Man Chat Road	2019 Existing PM	FILENAME :	J3_WKWR_MCR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	D.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
     W =
                MAJOR ROAD WIDTH
                CENTRAL RESERVE WIDTH
     W cr =
     W b-a =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
     W b-c =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vr c-b =
       D =
                STREAM-SPECIFIC B-A
       E =
                STREAM-SPECIFIC B-C
       F =
                STREAM-SPECIFIC C-B
       Y = (1-0.0345W)
```

OMETRIC DETAILS	<b>3:</b>		GEOMETRIC FAC	TORS :		THE CAPACITY OF MOVI	MENT :	:		COMPARISION ( TO CAPACITY:	OF DESIGN FLOW		
MAJOR ROAD	(ARM A)												
W =	3.56	(metres)	D	=	0.83974	Q b-a =	501				DFC b-a	=	0.0659
W cr =	0	(metres)	E	=	0.91257	Q b-c =	670	Q b-c (O) =	659		DFC b-c	=	0.0015
q a-b =	13	(pcu/hr)	F	=	0.90230	Q c-b =	660				DFC c-b	=	0.0545
q a-c =	29	(pcu/hr)	Υ	=	0.87718	Q b-ac =	505				DFC b-c (share lane)	=	0.0020
MAJOR ROAD	(ARM C)		F for (Qb-	ac) =	0.02941176	TOTAL FLOW	=	130	(PCU/HR)				
W c-b =	3.56	(metres)											
Vr c-b =	20	(metres)											
q c-a =	18	(pcu/hr)											
q c-b =	36	(pcu/hr)											
										CRITICAL	DFC	=	0.07
MINOR ROAD	(ARM B)												
W b-a =	3.68	(metres)											
W b-c =	3.68	(metres)											
VI b-a =	17	(metres)											
Vr b-a =	20	(metres)											
Vr b-c =	20	(metres)											
q b-a =	33	(pcu/hr)											
q b-c =	1	(pcu/hr)											


LLA CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCUI	ATION			INITIALS	DATE
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kon	Institute of Construction, Construction Industry C	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20
J/O Wong Kong Wai Road / Tat Fuk Road	2019 Existing AM	FILENAME :	J4_WKWR_TFR.xls	CHECKED BY:	SLN	Feb-20
		REFERENCE N	O.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
                  CENTRAL RESERVE WIDTH
      W cr =
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W b-c =
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VIb-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vrc-b =
                  STREAM-SPECIFIC B-A
        D =
                  STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
        Y =
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                               GEOMETRIC FACTORS:
                                                                                               THE CAPACITY OF MOVEMENT:
                                                                                                                                                        COMPARISION OF DESIGN FLOW
                                                                                                                                                        TO CAPACITY:
      MAJOR ROAD (ARM A)
       W =
                                                          D
                                                                            0.7411
                                                                                                     Q b-a =
                                                                                                                      463
                                                                                                                                                                       DFC b-a
                                                                                                                                                                                                  0.0302
                    3.48
                          (metres)
                          (metres)
       W cr =
                    0.00
                                                          Ε
                                                                            0.6096
                                                                                                     Q b-c =
                                                                                                                      453
                                                                                                                           Q b-c (O) = 449.6
                                                                                                                                                                       DFC b-c
                                                                                                                                                                                                  0.0000
                     20
                          (pcu/hr)
                                                          F
                                                                 =
                                                                            0.9032
                                                                                                     Q c-b =
                                                                                                                      667
                                                                                                                                                                       DFC c-b
                                                                                                                                                                                                  0.0000
       qa-b =
                          (pcu/hr)
                                                                            0.8799
                                                                                                     Q b-ac =
                                                                                                                      463
                                                                                                                                                                       DFC b-ac (share lane)
                                                                                                                                                                                                  0.0000
      MAJOR ROAD (ARM C)
                                                      F for (Qb-ac) =
                                                                            0.0000
                                                                                                      TOTAL FLOW
                                                                                                                                       (PCU/HR)
      W c-b =
                   3.57
                          (metres)
      Vr c-b =
                     20
                          (metres)
                          (pcu/hr)
                     0
      q c-a =
      q c-b =
                          (pcu/hr)
                                                                                                                                                         CRITICAL DFC
                                                                                                                                                                                           = 0.03
      MINOR ROAD (ARM B)
                          (metres)
      W b-a =
                   2.05
      W b-c =
                   0.00
                          (metres)
      VI b-a =
                          (metres)
                          (metres)
      Vr b-c =
                          (metres)
                     14
                          (pcu/hr)
      q b-a =
      q b-c =
                          (pcu/hr)
```


LLA CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCUL	ATION			INITIALS	DATE
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kon	g Institute of Construction, Construction Industry C	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20
J/O Wong Kong Wai Road / Tat Fuk Road	2019 Existing PM	FILENAME :	J4_WKWR_TFR.xls	CHECKED BY:	SLN	Feb-20
		REFERENCE N	O.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
                  CENTRAL RESERVE WIDTH
      W cr =
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W b-c =
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VIb-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vrc-b =
                  STREAM-SPECIFIC B-A
        D =
                  STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
        Y =
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                               GEOMETRIC FACTORS:
                                                                                               THE CAPACITY OF MOVEMENT:
                                                                                                                                                        COMPARISION OF DESIGN FLOW
                                                                                                                                                        TO CAPACITY:
      MAJOR ROAD (ARM A)
       W =
                                                          D
                                                                            0.7411
                                                                                                     Q b-a =
                                                                                                                     463
                                                                                                                                                                      DFC b-a
                                                                                                                                                                                                  0.0324
                    3.48
                          (metres)
                          (metres)
       W cr =
                    0.00
                                                          Ε
                                                                            0.6096
                                                                                                     Q b-c =
                                                                                                                     453
                                                                                                                           Q b-c (O) = 449.3
                                                                                                                                                                      DFC b-c
                                                                                                                                                                                                  0.0000
                          (pcu/hr)
                                                          F
                                                                =
                                                                            0.9032
                                                                                                     Q c-b =
                                                                                                                     669
                                                                                                                                                                      DFC c-b
                                                                                                                                                                                                  0.0000
       qa-b =
                     15
                      0
                          (pcu/hr)
                                                                            0.8799
                                                                                                     Q b-ac =
                                                                                                                      463
                                                                                                                                                                      DFC b-ac (share lane)
                                                                                                                                                                                                  0.0000
      MAJOR ROAD (ARM C)
                                                      F for (Qb-ac) =
                                                                            0.0000
                                                                                                     TOTAL FLOW
                                                                                                                                       (PCU/HR)
      W c-b =
                   3.57
                          (metres)
      Vr c-b =
                     20
                          (metres)
                          (pcu/hr)
                     0
      q c-a =
      q c-b =
                          (pcu/hr)
                                                                                                                                                        CRITICAL DFC
                                                                                                                                                                                           = 0.03
      MINOR ROAD (ARM B)
                          (metres)
      W b-a =
                   2.05
      W b-c =
                   0.00
                          (metres)
      VI b-a =
                          (metres)
                          (metres)
      Vr b-c =
                          (metres)
                     15
                          (pcu/hr)
      q b-a =
      q b-c =
                          (pcu/hr)
```


LLA CONSULTANCY LIMITED	PRIORITY JUNCTION CAL	CULATIO	V		INITIALS	DATE
Feasibility for Proposed Training Ground in Lam Tei for the Hong Ko	ng Institute of Construction, Construction Industry (	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20
J/O Fuk Hang Tsuen Road / Tat Fuk Road	2019 Existing AM	FILENAME :	J5_FHTR_TFR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	D.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
      W cr =
                  CENTRAL RESERVE WIDTH
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
      W b-c =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
      Vr c-b =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
        D =
                  STREAM-SPECIFIC B-A
                 STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                              GEOMETRIC FACTORS:
                                                                                         THE CAPACITY OF MOVEMENT:
                                                                                                                                                COMPARISION OF DESIGN FLOW
                                                                                                                                                TO CAPACITY:
      MAJOR ROAD (ARM A)
                                                                      0.90579
                                                                                                Q b-a =
                                                                                                               511
                                                                                                                                                              DFC b-a
                                                                                                                                                                                         0.0215
                   7.36 (metres)
                                                        Ε
                                                                                                               435 Q b-c (O) = 432.7
                                                                                                                                                              DFC b-c
                                                                                                                                                                                        0.0069
      W cr =
                     0 (metres)
                                                                      0.61552
                                                                                               Q b-c =
      qa-b =
                    13 (pcu/hr)
                                                                      0.95534
                                                                                                Q c-b =
                                                                                                               674
                                                                                                                                                              DFC c-b
                                                                                                                                                                                        0.0104
                                                        Υ
                                                                                                               493
                                                                                                                                                                                        0.0061
      qa-c =
                    133 (pcu/hr)
                                                                      0.74608
                                                                                               Q b-ac =
                                                                                                                                                              DFC b-c (share lane) =
                                                    F for (Qb-ac) = 0.21428571
                                                                                               TOTAL FLOW
                                                                                                              = 299
                                                                                                                               (PCU/HR)
      MAJOR ROAD (ARM C)
      W c-b =
                   4.18 (metres)
                         (metres)
      Vr c-b =
                    20
      q c-a =
                   132
                         (pcu/hr)
      q c-b =
                    7
                         (pcu/hr)
                                                                                                                                                CRITICAL DFC
                                                                                                                                                                                  = 0.02
      MINOR ROAD (ARM B)
      W b-a =
                   3.62
                         (metres)
                   0.00
      W b-c =
                         (metres)
                         (metres)
      Vr b-a =
                   100
                         (metres)
      Vr b-c =
                         (metres)
      q b-a =
                    11 (pcu/hr)
      q b-c =
                     3 (pcu/hr)
```

LLA CONSULTANCY LIMITED	PRIORITY JUNCTION CAL	CULATIO	N		INITIALS	DATE
Feasibility for Proposed Training Ground in Lam Tei for the Hong Ko	ng Institute of Construction, Construction Industry (	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20
J/O Fuk Hang Tsuen Road / Tat Fuk Road	2019 Existing PM	FILENAME :	J5_FHTR_TFR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	D.:	REVIEWED BY:	SLN	Feb-20




```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
      W cr =
                  CENTRAL RESERVE WIDTH
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
      W b-c =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vr c-b =
        D =
                  STREAM-SPECIFIC B-A
                 STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                              GEOMETRIC FACTORS:
                                                                                         THE CAPACITY OF MOVEMENT:
                                                                                                                                                COMPARISION OF DESIGN FLOW
                                                                                                                                                TO CAPACITY:
      MAJOR ROAD (ARM A)
                                                                      0.90579
                                                                                               Q b-a =
                                                                                                              527
                                                                                                                                                              DFC b-a
                                                                                                                                                                                        0.0247
                   7.36 (metres)
                                                        Ε
                                                                                                              445 Q b-c (O) = 442.3
                                                                                                                                                              DFC b-c
                                                                                                                                                                                        0.0045
      W cr =
                     0 (metres)
                                                                      0.61552
                                                                                               Q b-c =
      qa-b =
                     8 (pcu/hr)
                                                                      0.95534
                                                                                               Q c-b =
                                                                                                               690
                                                                                                                                                              DFC c-b
                                                                                                                                                                                        0.0101
                                                        Υ
                                                                                                                                                              DFC b-c (share lane) =
                                                                                                                                                                                        0.0039
      qa-c =
                    76 (pcu/hr)
                                                                      0.74608
                                                                                               Q b-ac =
                                                                                                              514
                                                    F for (Qb-ac) = 0.13333333
                                                                                               TOTAL FLOW
                                                                                                             = 227
                                                                                                                               (PCU/HR)
      MAJOR ROAD (ARM C)
      W c-b =
                   4.18 (metres)
                         (metres)
      Vr c-b =
                    20
      q c-a =
                   121
                         (pcu/hr)
      q c-b =
                    7
                         (pcu/hr)
                                                                                                                                                CRITICAL DFC
                                                                                                                                                                                  = 0.02
      MINOR ROAD (ARM B)
      W b-a =
                   3.62
                         (metres)
                   0.00
      W b-c =
                         (metres)
                         (metres)
                         (metres)
      Vr b-a =
                   100
      Vr b-c =
                         (metres)
      q b-a =
                    13 (pcu/hr)
      q b-c =
                     2 (pcu/hr)
```

# Appendix B

Junction Calculation Sheets
- Reference and Design Scenario

LLA CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCU	LATION			INITIALS	DATE
Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Ko	ng Institute of Construction, Construction Industry	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20
J/O Wong Kong Wai Road / Castle Peak Road-Lam Tei	2024 Reference AM	FILENAME :	J1_WKWR_CPRLT.xl	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	O.:	REVIEWED BY:	SLN	Feb-20




(pcu/hr)

q b-c =

```
NOTES: (GEOMETRIC INPUT DATA)
                 MAJOR ROAD WIDTH
     W cr =
                 CENTRAL RESERVE WIDTH
     W b-a =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
     W b-c =
     W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
     VIb-a =
                VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
     Vrb-a =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
     Vr b-c =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
     Vr c-b =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
                STREAM-SPECIFIC B-A
       E =
                STREAM-SPECIFIC B-C
       F = STREAM-SPECIFIC C-B
                (1-0.0345W)
```

TRIC DETAILS			GEOMETRIC FA	CTORS :		THE CAPACITY OF MO	VEMENT :			COMPARISION OF DESIGN TO CAPACITY:	FLOW		
MAJOR ROAL	, ,												
W =	11.2	(metres)	D	=	0.9921	Q b-a =	368			DFC b-a	=	0.0000	
W cr =	0.0	(metres)	E	=	1.0820	*Q b-c =	476	Q b-c (O) =	476	DFC b-c	=	0.0693	
qa-b =	53	(pcu/hr)	F	=	1.3047	Q c-b =	628			DFC c-b	=	0.0000	
q a-c =	1127	(pcu/hr)	Υ	=	0.6136	Q b-ac =	476						
			F for (Qb-a	nc) =	1.0000	TOTAL FLOW	=	1213	(PCU/HR)				
MINOR ROAD	(ARM B)									CRITICAL DFC	=	0.07	
	( /												
W b-c =	5.5	(metres)											
Vr b-c =	33	(metres)											
VID-C -													

<b>LLA</b> CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCU	LATION			INITIALS	DATE
Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Ko	ng Institute of Construction, Construction Industry	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20
J/O Wong Kong Wai Road / Castle Peak Road-Lam Tei	2024 Reference PM	FILENAME :	J1_WKWR_CPRLT.xl	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	D.:	REVIEWED BY:	SLN	Feb-20




(pcu/hr)

q b-c =

```
NOTES: (GEOMETRIC INPUT DATA)
                 MAJOR ROAD WIDTH
     W cr =
                 CENTRAL RESERVE WIDTH
     W b-a =
                 LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
     W b-c =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
     W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
     VIb-a =
                VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
     Vrb-a =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
     Vr b-c =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
     Vr c-b =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
                STREAM-SPECIFIC B-A
       E =
                STREAM-SPECIFIC B-C
       F = STREAM-SPECIFIC C-B
                (1-0.0345W)
```

ETRIC DETAIL:	S:		GEOMETRIC FA	CTORS :		THE CAPACITY OF MO	/EMENT :			COMPARISION TO CAPACITY:	OF DESIGN FLOW		
MAJOR ROAL	. ,												
W =	11.2	(metres)	D	=	0.9921	Q b-a =	367				DFC b-a	=	0.0000
W cr =	0.0	(metres)	E	=	1.0820	*Q b-c =	475	Q b-c (O) =	475		DFC b-c	=	0.0716
q a-b =	58	(pcu/hr)	F	=	1.3047	Q c-b =	627				DFC c-b	=	0.0000
q a-c =	1127	(pcu/hr)	Υ	=	0.6136	Q b-ac =	475						
			F for (Qb-a	ac) =	1.0000	TOTAL FLOW	=,	1219	(PCU/HR)				
										CRITICAL	DEC	=	0.07
MINOR ROAD	(ARM B)									OKITIOAL		_	0.07
W b-c =	5.5	(metres)											
Vr b-c =	33	(metres)											
		(pcu/hr)											

LLA CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCU	LATION			INITIALS	DATE
Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Ko	ng Institute of Construction, Construction Industry	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20
J/O Wong Kong Wai Road / Castle Peak Road-Lam Tei	2024 Design AM	FILENAME :	J1_WKWR_CPRLT.xl	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	D.:	REVIEWED BY:	SLN	Feb-20




(pcu/hr)

q b-c =

```
NOTES: (GEOMETRIC INPUT DATA)
                 MAJOR ROAD WIDTH
     W cr =
                 CENTRAL RESERVE WIDTH
     W b-a =
                 LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
     W b-c =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
     W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
     VI b-a =
                 VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
     Vrb-a =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
     Vr b-c =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
     Vr c-b =
                 VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
                 STREAM-SPECIFIC B-A
       E =
                 STREAM-SPECIFIC B-C
       F = STREAM-SPECIFIC C-B
                (1-0.0345W)
```

TRIC DETAIL	S:		GEOMETRIC FA	CTORS :		THE CAPACITY OF MO	VEMENT :			COMPARISION OF DESI TO CAPACITY:	GN FLOW			
MAJOR ROA	. ,													
W =	11.2	(metres)	D	=	0.9921	Q b-a =	366			DFC b		=	0.0000	
W cr =	0.0	(metres)	E	=	1.0820	*Q b-c =	474	Q b-c (O) =	474	DFC b	-с	=	0.0844	
qa-b =	67	(pcu/hr)	F	=	1.3047	Q c-b =	624			DFC o	-b	=	0.0000	
q a-c =	1127	(pcu/hr)	Υ	=	0.6136	Q b-ac =	474							
			F for (Qb-a	ac) =	1.0000	TOTAL FLOW	=	1234	(PCU/HR)					
										CRITICAL DFO		=	0.08	
MINOR ROAD	(ARM B)													
W b-c =	5.5	(metres)												
Vr b-c =	33	(metres)												
	0	(pcu/hr)												

LLA CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCU	LATION			INITIALS	DATE
Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Ko	ng Institute of Construction, Construction Industry	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20
J/O Wong Kong Wai Road / Castle Peak Road-Lam Tei	2024 Design PM	FILENAME :	J1_WKWR_CPRLT.xl	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	D.:	REVIEWED BY:	SLN	Feb-20



q b-a =

q b-c =

0 (pcu/hr) 41 (pcu/hr) NOTES: (GEOMETRIC INPUT DATA) MAJOR ROAD WIDTH W cr = CENTRAL RESERVE WIDTH W b-a = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c W b-c = W c-b = LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b VI b-a = VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a Vrb-a = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a Vr b-c = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c Vr c-b = VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b STREAM-SPECIFIC B-A E = STREAM-SPECIFIC B-C F = STREAM-SPECIFIC C-B (1-0.0345W)

TRIC DETAIL			GEOMETRIC FA	CTORS:		THE CAPACITY OF MO	/EMENT			COMPARISION OF DESIGN FLOW TO CAPACITY:		
MAJOR ROA W =	D (ARM A) 11.2	(t)	D	=	0.9921	0.5 -	367			DFC b-a	=	0.0000
		(metres)				Q b-a =						0.0000
W cr =	0.0	(metres)	E	=	1.0820	*Q b-c =	475		475	DFC b-c	=	0.0863
qa-b =	65	(pcu/hr)	F	=	1.3047	Q c-b =	625			DFC c-b	=	0.0000
q a-c =	1127	(pcu/hr)	Υ	=	0.6136	Q b-ac =	475					
			F for (Qb-a	ac) =	1.0000	TOTAL FLOW	=	1233	(PCU/HR)			
MINOR ROAD	(ARM B)									CRITICAL DFC	=	0.09
W b-c =	5.5	(metres)										


Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning

# TRAFFIC SIGNAL CALCULATION

2024 Reference AM

#### 

Const	ruction, Construction Industry Council - TIA Study in Support of the Planning
J/O	Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei
1	



R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	1 %
Ymax	= 1-L/C	=	0.792
Ср	= 0.9*L/(0.9-Y)	=	116.8 sec
R.C.ult	= (Yult-Y)/Y*100%	=	0.7 %
Yult		=	0.713
Cm	= L/(1-Y)	=	85.4 sec
Co	= (1.5*L+5)/(1-Y)	=	145.2 sec
Total Flow		=	3323 pcu
Loss time		L =	25 sec
Sum(y)		Y =	0.707
Cycle time		C =	120 sec
No. of stage	es per cycle	N =	3

[6]	<b>—</b>	[1] [2]	[5]	<b>→ ‡</b>	P1] P2]	[4] [3]	<b>↑</b> [F	22]				
Stage 1	G=	31	Stage 2	G=	17	Stage 3	G=	44	Stage 4	G=	Stage 5	G=
	Int =	8		Int =	11		Int =	9		Int =		Int =

Stane	Width	Gree	n Time Re	nuired	Green Tim	e Provided
Otage					_	FG
	(111)	36	1 0	Delay	36	1 0
2	10.8	9	9	2	13	9
2.3	11.4	10	10	2	69	10
					l	
	_	(m) 2 10.8	(m) SG 2 10.8 9	(m) SG FG 2 10.8 9 9	(m) SG FG Delay 2 10.8 9 9 2	(m)         SG         FG         Delay         SG           2         10.8         9         9         2         13

Move-	Stage	Lane	No. of	Radius	О	ΙN	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	V	Greater	1	I	g	Degree of	Queue	Average
ment	Clage	Width	lane	m.	1	'`	Ahead		Straight		FLow	of Turning	Flow	Lane	Effect	Factor	l	%	Effect	Sat. Flow	y	V	sec	(required)	(input)	Saturation		Delay
ment			lane	111.			1		-	-				l		Factor	l	70	1 1			У	Sec	(required)			-	
		m.					Sat. Flow	pcu/n	pcu/h	pcu/n	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	Х	(m / lane)	(seconds)
																							25					
1	1	3.75	2				4260		1012		1012	0.00	4260							4260	0.238			32	32	0.893	78	45
1,2	1	3.60	1	10		N	1975	105	349		454	0.23	1909							1909	0.238	0.238		32	32	0.893	78	37
5	2	3.40	1	10			2095			249	249	1.00	1822							1822	0.137	0.137		18	18	0.893	54	46
6	1	3.40	3			l <sub>N</sub>	6145		1048		1048	0.00	6145							6145	0.171			23	32	0.893	58	55
"	'	3.40	ľ			'`	0143		1040		1040	0.00	0143							0143	0.171			20	32	0.055	30	
			١.			١	4005	0.45		0.45	500	4.00	4000							4000							0.4	00
3,4	3	3.20	1	10		N	1935	345		215	560	1.00	1683							1683	0.333	0.333		45	45	0.893	84	28
							1																					
							1																					
		1																										
	l			·										l	1		I											

NOTE:

O - OPPOSING TRAFFIC

N - NEAR SIDE LANE

SG - STEADY GREEN

FG - FLASHING GREEN


PEDESTRAIN WALKING SPEED = 1.2m/s

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

#### 2024 Reference PM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Feb-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Feb-20
1		Reviewed By:	SLN	Feb-20



R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	3 %
Ymax	= 1-L/C	=	0.792
Ср	= 0.9*L/(0.9-Y)	=	106.8 sec
R.C.ult	= (Yult-Y)/Y*100%	=	3.4 %
Yult		=	0.713
Cm	= L/(1-Y)	=	80.5 sec
Co	= (1.5*L+5)/(1-Y)	=	136.8 sec
Total Flow	1	=	3666 pcu
Loss time		L =	25 sec
Sum(y)		Y =	0.689
Cycle time	•	C =	120 sec
No. of staເ	ges per cycle	N =	3



Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	19	9
P2	2.3	11.4	10	10	2	69	10

Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		m.					Sat. Flow		-		pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	x	(m / lane)	(seconds)
							out. I low	pourm	pour	pourn	pourn	7 07 110 100	poun		pourm		pourm		pourm	pour			25	555			(1117 10110)	(eeeeinae)
																							23					
1	1	3.75	2				4260		1005		1005	0.00	4260							4260	0.236			33	33	0.871	75	44
1,2	1	3.60	1	10		N	1975	106	345		451	0.24	1908							1908	0.236	0.236		33	33	0.871	72	36
5	2	3.40	1 1	10			2095			314	314	1.00	1822							1822	0.172	0.172		24	24	0.871	60	42
6	1	3.40	3	"		l <sub>N</sub>	6145		1424	014	1424	0.00	6145							6145	0.232	0.172		32	33	0.871	70	53
0	'	3.40	3			l in	0145		1424		1424	0.00	0145							0145	0.232			32	33	0.071	70	55
3,4	3	3.20	1	10		N	1935	269		203	472	1.00	1683							1683	0.281	0.281		39	39	0.871	72	32
							1																					
							1																					
							1																					
			l	L	<u> </u>				<u> </u>	l			l	l	l							1	<u> </u>					

NOTE:

O - OPPOSING TRAFFIC

N - NEAR SIDE LANE

SG - STEADY GREEN

FG - FLASHING GREEN


PEDESTRAIN WALKING SPEED = 1.2m/s

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


## TRAFFIC SIGNAL CALCULATION

#### 2024 Design AM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Feb-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Feb-20
		Reviewed Bv:	SLN	Feb-20



R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	-1 %	
Ymax	= 1-1/10	=	0.792	
Ср	= 0.9*L/(0.9-Y) = 1-L/C	=	124.8 sec 0.792	:
R.C.ult	= (Yult-Y)/Y*100%	=	-1.0 %	
Yult		=	0.713	
Cm	= L/(1-Y)	=	89.2 sec	;
Co	= (1.5*L+5)/(1-Y)	=	151.6 sec	
Total Flow		=	3350 pcu	
Loss time		L =	25 sec	:
Sum(y)		Y =	0.720	
Cycle time		C =	120 sec	:
No. of stage	es per cycle	N =	3	



Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	14	9
P2	2.3	11.4	10	10	2	69	10

Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	X	(m / lane)	(seconds)
																							25				, , ,	
1	١ ,	2.75	_ ا				4000		1017		1017	0.00	4000							4000	0.000		20	20	22	0.000	81	45
1 .'.		3.75				l	4260				1017	0.00	4260							4260	0.239			32	32	0.909		
1,2	1	3.60	1	10		N	1975	105	351		456	0.23	1909							1909	0.239	0.239		32	32	0.909	84	37
5	2	3.40	1	10			2095			262	262	1.00	1822							1822	0.144	0.144		19	19	0.909	66	46
6	1	3.40	3			l N	6145		1048		1048	0.00	6145							6145	0.171			23	32	0.909	60	56
1 -	· ·		•																									
1 24	ا ا	2 20		10		l <sub>N</sub>	4005	245		222	567	4.00	4000							1683	0.227	0.227		44	44	0.000	90	28
3,4	3	3.20	1	10		l N	1935	345		222	567	1.00	1683							1683	0.337	0.337		44	44	0.909	90	28
														l				l										
							I .	l		l			l	l	l													

NOTE:

O - OPPOSING TRAFFIC

N - NEAR SIDE LANE

SG - STEADY GREEN

FG - FLASHING GREEN


PEDESTRAIN WALKING SPEED = 1.2m/s

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

#### 2024 Design PM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Feb-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Feb-20
		Reviewed By:	SLN	Feb-20



R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	2 %
Ymax	= 1-L/C	=	0.792
Ср	= 0.9*L/(0.9-Y)	=	111.5 sec
R.C.ult	= (Yult-Y)/Y*100%	=	2.0 %
Yult		=	0.713
Cm	= L/(1-Y)	=	82.8 sec
Co	= (1.5*L+5)/(1-Y)	=	140.8 sec
Total Flow		=	3687 pcu
Loss time		L =	25 sec
Sum(y)		Y =	0.698
Cycle time		C =	120 sec
No. of stage	es per cycle	N =	3



Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	19	9
P2	2.3	11.4	10	10	2	69	10

Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	Х	(m / lane)	(seconds)
-		<del></del>			<b>†</b>	<b>†</b>	Out. 1 low	pourn	poum	росии	pourm	7 07 110 100	pourn		pourm		pourm		pourm	pour			25	000		- ^ -	(1117 10110)	(occondo)
١.,	١,						4000		1,,,,		4044		4000							4000	0.007	0.007	23	00				45
1	1	3.75	2				4260		1011		1011	0.00	4260							4260	0.237	0.237		32	32	0.882	75	45
1,2	1	3.60	1	10		N	1975	106	346		452	0.23	1908							1908	0.237			32	32	0.882	78	37
5	2	3.40	1	10			2095			321	321	1.00	1822							1822	0.176	0.176		24	24	0.882	60	42
6	1	3.40	3			l <sub>N</sub>	6145		1424	02.	1424	0.00	6145							6145	0.232	00		32	32	0.882	70	54
"	'	3.40	٦			l in	0145		1424		1424	0.00	0145							0145	0.232			32	32	0.002	70	34
3,4	3	3.20	1	10		N	1935	269		210	479	1.00	1683							1683	0.285	0.285		39	39	0.882	72	32
							1	l																				
							1	l																				
							1	l																				
L	<u> </u>	<u> </u>	<u> </u>	L	<u> </u>			l	<u> </u>	l			l	l	l							1	<u> </u>					

NOTE:

O - OPPOSING TRAFFIC


N - NEAR SIDE LANE

SG - STEADY GREEN

FG - FLASHING GREEN

PEDESTRAIN WALKING SPEED = 1.2m/s


LLA CONSULTANCY LIMITED	PRIORITY JUNCTION CAL	CULATION	N		INITIALS	DATE
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kon	g Institute of Construction, Construction Industry Co	PROJECT NO.:	40624	PREPARED BY:	SKL	Feb-20
J/O Wong Kong Wai Road / Man Chat Road	2024 Reference AM	FILENAME :	J3_WKWR_MCR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	).:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
     W =
                MAJOR ROAD WIDTH
                CENTRAL RESERVE WIDTH
     W cr =
     W b-a =
               LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
     W b-c =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vr c-b =
       D =
                STREAM-SPECIFIC B-A
                STREAM-SPECIFIC B-C
       E =
       F =
                STREAM-SPECIFIC C-B
       Y = (1-0.0345W)
```

ETRIC DETAIL	.S:		GEOMETRIC FAC	TORS :		THE CAPACITY OF MOV	EMENT :			COMPARISION TO CAPACITY:	OF DESIGN FLOW		
MAJOR ROA	D (ARM A)												
W =	3.56	(metres)	D	=	0.83974	Q b-a =	501				DFC b-a	=	0.0519
W cr =	0	(metres)	E	=	0.91257	Q b-c =	670	Q b-c (O) =	661.3		DFC b-c	=	0.0045
q a-b =	9	(pcu/hr)	F	=	0.90230	Q c-b =	661				DFC c-b	=	0.0545
q a-c =	30	(pcu/hr)	Υ	=	0.87718	Q b-ac =	514				DFC b-c (share lane)	=	0.0058
MAJOR ROAL	D (ARM C)		F for (Qb-	ac) =	0.10344828	TOTAL FLOW	=	122	(PCU/HR)				
W c-b =	3.56	(metres)											
Vr c-b =	20	(metres)											
q c-a =	18	(pcu/hr)											
q c-b =	36	(pcu/hr)								CRITICAL	DEC	=	0.05
MINOR ROAD	(ARM B)									CINITICAL	- Di O	_	0.03
W b-a =	3.68	(metres)											
W b-c =	3.68	(metres)											
VI b-a =	17	(metres)											
Vr b-a =	20	(metres)											
Vr b-c =	20	(metres)											
q b-a =	26	(pcu/hr)											
q b-c =	3	(pcu/hr)											


LLA CONSULTANCY LIMITED	PRIORITY JUNCTION CAL	CULATION	N		INITIALS	DATE
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kon	g Institute of Construction, Construction Industry Co	PROJECT NO.:	40624	PREPARED BY:	SKL	Feb-20
J/O Wong Kong Wai Road / Man Chat Road	2024 Reference PM	FILENAME :	J3_WKWR_MCR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	).:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
     W =
                MAJOR ROAD WIDTH
                CENTRAL RESERVE WIDTH
     W cr =
     W b-a =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
     W b-c =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vr c-b =
       D =
                STREAM-SPECIFIC B-A
       E =
                STREAM-SPECIFIC B-C
       F =
                STREAM-SPECIFIC C-B
       Y = (1-0.0345W)
```

METRIC DETAILS	S:		GEOMETRIC F	ACTORS :		THE CAPACITY OF MOV	EMENT :			COMPARISION OF DESIGN FLOW TO CAPACITY:		
MAJOR ROAD	(ARM A)											
W =	3.56	(metres)	[	) =	0.83974	Q b-a =	498			DFC b-a	=	0.0723
W cr =	0	(metres)	E	=	0.91257	Q b-c =	669	Q b-c (O) =	656.9	DFC b-c	=	0.0030
qa-b =	14	(pcu/hr)	F	=	0.90230	Q c-b =	659			DFC c-b	=	0.0592
q a-c =	32	(pcu/hr)	١	<i>(</i> =	0.87718	Q b-ac =	505			DFC b-c (share lane)	=	0.0040
MAJOR ROAD	(ARM C)		F for (	Qb-ac) =	0.05263158	TOTAL FLOW	=	143	(PCU/HR)			
W c-b =	3.56	(metres)										
Vr c-b =	20	(metres)										
q c-a =	20	(pcu/hr)										
q c-b =	39	(pcu/hr)										
										CRITICAL DFC	=	0.07
MINOR ROAD	(ARM B)											
W b-a =	3.68	(metres)										
W b-c =	3.68	(metres)										
VI b-a =	17	(metres)										
Vr b-a =	20	(metres)										
Vr b-c =	20	(metres)										
q b-a =	36	(pcu/hr)										
q b-c =	2											


LLA CONSULTANCY LIMITED	PRIORITY JUNCTION CAL	CULATION	N		INITIALS	DATE
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kong	g Institute of Construction, Construction Industry Co	PROJECT NO.:	40624	PREPARED BY:	SKL	Feb-20
J/O Wong Kong Wai Road / Man Chat Road	2024 Design AM	FILENAME :	J3_WKWR_MCR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	).:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
     W =
                MAJOR ROAD WIDTH
                CENTRAL RESERVE WIDTH
     W cr =
     W b-a =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
     W b-c =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vr c-b =
       D =
                STREAM-SPECIFIC B-A
       E =
                STREAM-SPECIFIC B-C
       F =
                STREAM-SPECIFIC C-B
       Y = (1-0.0345W)
```

IETRIC DETAILS	<b>S</b> :		GEOMETRIC FA	ACTORS :		THE CAPACITY OF MOV	EMENT :	1		COMPARISION OF DESIGN FLOW TO CAPACITY:		
MAJOR ROAL	(ARM A)											
W =	3.56	(metres)	D	=	0.83974	Q b-a =	496			DFC b-a	=	0.0786
W cr =	0	(metres)	E	=	0.91257	Q b-c =	667	Q b-c (O) =	653.9	DFC b-c	=	0.0045
q a-b =	16	(pcu/hr)	F	=	0.90230	Q c-b =	657			DFC c-b	=	0.0548
q a-c =	37	(pcu/hr)	Υ	=	0.87718	Q b-ac =	505			DFC b-c (share lane)	=	0.0059
MAJOR ROAD	(ARM C)		F for (Q	b-ac) =	0.07142857	TOTAL FLOW	=	163	(PCU/HR)			
W c-b =	3.56	(metres)										
Vr c-b =	20	(metres)										
q c-a =	32	(pcu/hr)										
q c-b =	36	(pcu/hr)										
										CRITICAL DFC	=	0.08
MINOR ROAD	(ARM B)											
W b-a =	3.68	(metres)										
W b-c =	3.68	(metres)										
VI b-a =	17	(metres)										
Vr b-a =	20	(metres)										
Vr b-c =	20	(metres)										
q b-a =	39	(pcu/hr)										
q b-c =	3	(pcu/hr)										


LLA CONSULTANCY LIMITED	PRIORITY JUNCTION CAL	CULATION	N		INITIALS	DATE
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kong	g Institute of Construction, Construction Industry Co	PROJECT NO.:	40624	PREPARED BY:	SKL	Feb-20
J/O Wong Kong Wai Road / Man Chat Road	2024 Design PM	FILENAME :	J3_WKWR_MCR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	<b>)</b> .:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
     W =
                MAJOR ROAD WIDTH
                CENTRAL RESERVE WIDTH
     W cr =
     W b-a =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
     W b-c =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
                VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vr c-b =
       D =
                STREAM-SPECIFIC B-A
       E =
                STREAM-SPECIFIC B-C
       F =
                STREAM-SPECIFIC C-B
       Y = (1-0.0345W)
```

METRIC DETAILS	<b>3</b> :		GEOMETRIC FA	CTORS :		THE CAPACITY OF MOV	EMENT :			COMPARISION OF DESIGN TO CAPACITY:	FLOW		
MAJOR ROAD	(ARM A)												
W =	3.56	(metres)	D	=	0.83974	Q b-a =	494			DFC b-a		=	0.0870
W cr =	0	(metres)	E	=	0.91257	Q b-c =	666	Q b-c (O) =	651.5	DFC b-c		=	0.0030
q a-b =	21	(pcu/hr)	F	=	0.90230	Q c-b =	655			DFC c-b		=	0.0595
q a-c =	39	(pcu/hr)	Y	=	0.87718	Q b-ac =	500			DFC b-c (s	share lane)	=	0.0040
MAJOR ROAD	(ARM C)		F for (Q	b-ac) =	0.0444444	TOTAL FLOW	=	171	(PCU/HR)				
W c-b =	3.56	(metres)											
Vr c-b =	20	(metres)											
q c-a =	27	(pcu/hr)											
q c-b =	39	(pcu/hr)											
										CRITICAL DFC		=	0.09
MINOR ROAD	(ARM B)												
W b-a =	3.68	(metres)											
W b-c =	3.68	(metres)											
VI b-a =	17	(metres)											
Vr b-a =	20	(metres)											
Vr b-c =	20	(metres)											
q b-a =	43	(pcu/hr)											
q b-c =	2												


LLA CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCUL		INITIALS	DATE		
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kong	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20	
J/O Wong Kong Wai Road / Tat Fuk Road	2024 Reference AM	FILENAME :	J4_WKWR_TFR.xls	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	O.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
                  CENTRAL RESERVE WIDTH
      W cr =
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W b-c =
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VIb-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vrc-b =
                  STREAM-SPECIFIC B-A
        D =
                  STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
        Y =
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                               GEOMETRIC FACTORS:
                                                                                               THE CAPACITY OF MOVEMENT:
                                                                                                                                                        COMPARISION OF DESIGN FLOW
                                                                                                                                                        TO CAPACITY:
      MAJOR ROAD (ARM A)
       W =
                                                          D
                                                                            0.7411
                                                                                                     Q b-a =
                                                                                                                     463
                                                                                                                                                                       DFC b-a
                                                                                                                                                                                                  0.0324
                    3.48
                          (metres)
                          (metres)
       W cr =
                    0.00
                                                          Ε
                                                                            0.6096
                                                                                                     Q b-c =
                                                                                                                     452
                                                                                                                           Q b-c (O) = 448.3
                                                                                                                                                                       DFC b-c
                                                                                                                                                                                                  0.0000
                     22
                          (pcu/hr)
                                                          F
                                                                =
                                                                            0.9032
                                                                                                     Q c-b =
                                                                                                                     666
                                                                                                                                                                       DFC c-b
                                                                                                                                                                                                  0.0000
       qa-b =
                          (pcu/hr)
                                                                            0.8799
                                                                                                     Q b-ac =
                                                                                                                      463
                                                                                                                                                                       DFC b-ac (share lane)
                                                                                                                                                                                                  0.0000
      MAJOR ROAD (ARM C)
                                                      F for (Qb-ac) =
                                                                            0.0000
                                                                                                     TOTAL FLOW
                                                                                                                                       (PCU/HR)
      W c-b =
                   3.57
                          (metres)
      Vr c-b =
                     20
                          (metres)
                          (pcu/hr)
                     0
      q c-a =
      q c-b =
                          (pcu/hr)
                                                                                                                                                        CRITICAL DFC
                                                                                                                                                                                           = 0.03
      MINOR ROAD (ARM B)
                          (metres)
      W b-a =
                   2.05
      W b-c =
                   0.00
                          (metres)
      VI b-a =
                          (metres)
                          (metres)
      Vr b-c =
                          (metres)
                     15
                          (pcu/hr)
      q b-a =
      q b-c =
                          (pcu/hr)
```


LLA CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCUL		INITIALS	DATE		
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kong	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20	
J/O Wong Kong Wai Road / Tat Fuk Road	2024 Reference PM	FILENAME :	J4_WKWR_TFR.xls	CHECKED BY:	SLN	Feb-20
		REFERENCE N	0.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                 MAJOR ROAD WIDTH
      W =
                  CENTRAL RESERVE WIDTH
      W cr =
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W b-c =
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VIb-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vrc-b =
        D =
                  STREAM-SPECIFIC B-A
                 STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
        Y =
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                               GEOMETRIC FACTORS:
                                                                                              THE CAPACITY OF MOVEMENT:
                                                                                                                                                       COMPARISION OF DESIGN FLOW
                                                                                                                                                       TO CAPACITY:
      MAJOR ROAD (ARM A)
       W =
                    3.48
                                                          D
                                                                           0.7411
                                                                                                     Q b-a =
                                                                                                                     463
                                                                                                                                                                      DFC b-a
                                                                                                                                                                                                 0.0367
                          (metres)
       W cr =
                    0.00
                          (metres)
                                                          Ε
                                                                           0.6096
                                                                                                     Q b-c =
                                                                                                                     453
                                                                                                                          Q b-c (O) = 448.8
                                                                                                                                                                      DFC b-c
                                                                                                                                                                                                 0.0000
      qa-b =
                     17
                          (pcu/hr)
                                                          F
                                                                =
                                                                           0.9032
                                                                                                     Q c-b =
                                                                                                                     668
                                                                                                                                                                      DFC c-b
                                                                                                                                                                                                 0.0000
                                                                                                                     463
                      0
                          (pcu/hr)
                                                                           0.8799
                                                                                                     Q b-ac =
                                                                                                                                                                      DFC b-ac (share lane)
                                                                                                                                                                                                 0.0000
      MAJOR ROAD (ARM C)
                                                      F for (Qb-ac) =
                                                                           0.0000
                                                                                                     TOTAL FLOW
                                                                                                                                      (PCU/HR)
      W c-b =
                   3.57
                          (metres)
      Vr c-b =
                     20
                          (metres)
                     0
                          (pcu/hr)
      q c-a =
      q c-b =
                          (pcu/hr)
                                                                                                                                                       CRITICAL DFC
                                                                                                                                                                                          = 0.04
      MINOR ROAD (ARM B)
      W b-a =
                   2.05
                          (metres)
      W b-c =
                   0.00
                          (metres)
      VI b-a =
                          (metres)
                          (metres)
      Vr b-c =
                          (metres)
                     17
                          (pcu/hr)
      q b-a =
      q b-c =
                          (pcu/hr)
```


LLA CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCUL		INITIALS	DATE		
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kon	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20	
J/O Wong Kong Wai Road / Tat Fuk Road	2024 Design AM	FILENAME :	J4_WKWR_TFR.xls	CHECKED BY:	SLN	Feb-20
		REFERENCE N	O.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
                  CENTRAL RESERVE WIDTH
      W cr =
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W b-c =
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VIb-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vrc-b =
                  STREAM-SPECIFIC B-A
        D =
                  STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
        Y =
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                               GEOMETRIC FACTORS:
                                                                                               THE CAPACITY OF MOVEMENT:
                                                                                                                                                        COMPARISION OF DESIGN FLOW
                                                                                                                                                        TO CAPACITY:
      MAJOR ROAD (ARM A)
       W =
                                                          D
                                                                            0.7411
                                                                                                     Q b-a =
                                                                                                                     463
                                                                                                                                                                       DFC b-a
                                                                                                                                                                                                  0.0324
                    3.48
                          (metres)
                          (metres)
       W cr =
                    0.00
                                                          Ε
                                                                            0.6096
                                                                                                     Q b-c =
                                                                                                                     452
                                                                                                                           Q b-c (O) = 448.3
                                                                                                                                                                       DFC b-c
                                                                                                                                                                                                  0.0000
                     22
                          (pcu/hr)
                                                          F
                                                                =
                                                                            0.9032
                                                                                                     Q c-b =
                                                                                                                     666
                                                                                                                                                                       DFC c-b
                                                                                                                                                                                                  0.0000
       qa-b =
                          (pcu/hr)
                                                                            0.8799
                                                                                                     Q b-ac =
                                                                                                                      463
                                                                                                                                                                       DFC b-ac (share lane)
                                                                                                                                                                                                  0.0000
      MAJOR ROAD (ARM C)
                                                      F for (Qb-ac) =
                                                                            0.0000
                                                                                                     TOTAL FLOW
                                                                                                                                       (PCU/HR)
      W c-b =
                   3.57
                          (metres)
      Vr c-b =
                     20
                          (metres)
                          (pcu/hr)
                     0
      q c-a =
      q c-b =
                          (pcu/hr)
                                                                                                                                                        CRITICAL DFC
                                                                                                                                                                                           = 0.03
      MINOR ROAD (ARM B)
                          (metres)
      W b-a =
                   2.05
      W b-c =
                   0.00
                          (metres)
      VI b-a =
                          (metres)
                          (metres)
      Vr b-c =
                          (metres)
                     15
                          (pcu/hr)
      q b-a =
      q b-c =
                          (pcu/hr)
```


LLA CONSULTANCY LIMITED	TRAFFIC SIGNAL CALCUL		INITIALS	DATE		
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kong	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20	
J/O Wong Kong Wai Road / Tat Fuk Road	2024 Design PM	FILENAME :	J4_WKWR_TFR.xls	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	O.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
                  CENTRAL RESERVE WIDTH
      W cr =
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W b-c =
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VIb-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vrc-b =
                  STREAM-SPECIFIC B-A
        D =
                  STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
        Y =
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                               GEOMETRIC FACTORS:
                                                                                               THE CAPACITY OF MOVEMENT:
                                                                                                                                                        COMPARISION OF DESIGN FLOW
                                                                                                                                                        TO CAPACITY:
      MAJOR ROAD (ARM A)
       W =
                                                          D
                                                                            0.7411
                                                                                                     Q b-a =
                                                                                                                     463
                                                                                                                                                                      DFC b-a
                                                                                                                                                                                                  0.0367
                    3.48
                          (metres)
                          (metres)
       W cr =
                    0.00
                                                          Ε
                                                                            0.6096
                                                                                                     Q b-c =
                                                                                                                     453
                                                                                                                           Q b-c (O) = 448.8
                                                                                                                                                                      DFC b-c
                                                                                                                                                                                                  0.0000
                          (pcu/hr)
                                                                =
                                                                            0.9032
                                                                                                     Q c-b =
                                                                                                                     668
                                                                                                                                                                      DFC c-b
                                                                                                                                                                                                  0.0000
       qa-b =
                     17
                      0
                          (pcu/hr)
                                                                            0.8799
                                                                                                     Q b-ac =
                                                                                                                      463
                                                                                                                                                                      DFC b-ac (share lane)
                                                                                                                                                                                                  0.0000
      MAJOR ROAD (ARM C)
                                                      F for (Qb-ac) =
                                                                            0.0000
                                                                                                     TOTAL FLOW
                                                                                                                                      (PCU/HR)
      W c-b =
                   3.57
                          (metres)
      Vr c-b =
                     20
                          (metres)
                          (pcu/hr)
                     0
      q c-a =
      q c-b =
                          (pcu/hr)
                                                                                                                                                        CRITICAL DFC
                                                                                                                                                                                           = 0.04
      MINOR ROAD (ARM B)
      W b-a =
                   2.05
                          (metres)
      W b-c =
                   0.00
                          (metres)
                          (metres)
      VI b-a =
                          (metres)
                          (metres)
      Vr b-c =
                     17
                          (pcu/hr)
      q b-a =
      q b-c =
                          (pcu/hr)
```


LLA CONSULTANCY LIMITED	INITIALS	DATE				
Feasibility for Proposed Training Ground in Lam Tei for the Hong Ko	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20	
J/O Fuk Hang Tsuen Road / Tat Fuk Road	2024 Reference AM	FILENAME :	J5_FHTR_TFR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	O.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
      W cr =
                  CENTRAL RESERVE WIDTH
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
      W b-c =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
      Vr c-b =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
        D =
                  STREAM-SPECIFIC B-A
                 STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                              GEOMETRIC FACTORS:
                                                                                         THE CAPACITY OF MOVEMENT:
                                                                                                                                                COMPARISION OF DESIGN FLOW
                                                                                                                                                TO CAPACITY:
      MAJOR ROAD (ARM A)
                                                                      0.90579
                                                                                                Q b-a =
                                                                                                               507
                                                                                                                                                               DFC b-a
                                                                                                                                                                                         0.0237
                   7.36 (metres)
                                                        Ε
                                                                                                               434 Q b-c (O) = 431.4
                                                                                                                                                               DFC b-c
                                                                                                                                                                                         0.0092
      W cr =
                     0 (metres)
                                                                      0.61552
                                                                                                Q b-c =
                                                        F
      qa-b =
                    14 (pcu/hr)
                                                                      0.95534
                                                                                                Q c-b =
                                                                                                               671
                                                                                                                                                               DFC c-b
                                                                                                                                                                                         0.0119
                                                        Υ
                                                                                                               487
                                                                                                                                                               DFC b-c (share lane) =
                                                                                                                                                                                         0.0082
      qa-c =
                    143 (pcu/hr)
                                                                      0.74608
                                                                                               Q b-ac =
                                                    F for (Qb-ac) =
                                                                         0.25
                                                                                                TOTAL FLOW
                                                                                                             = 323
                                                                                                                                (PCU/HR)
      MAJOR ROAD (ARM C)
      W c-b =
                   4.18 (metres)
      Vr c-b =
                    20
                         (metres)
      q c-a =
                   142
                         (pcu/hr)
      q c-b =
                     8
                         (pcu/hr)
                                                                                                                                                 CRITICAL DFC
                                                                                                                                                                                  = 0.02
     MINOR ROAD (ARM B)
      W b-a =
                   3.62
                         (metres)
                   0.00
      W b-c =
                         (metres)
                         (metres)
                         (metres)
      Vr b-a =
      Vr b-c =
                         (metres)
      q b-a =
                    12 (pcu/hr)
      q b-c =
                     4 (pcu/hr)
```


LLA CONSULTANCY LIMITED	INITIALS	DATE				
Feasibility for Proposed Training Ground in Lam Tei for the Hong Kor	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20	
J/O Fuk Hang Tsuen Road / Tat Fuk Road	2024 Reference PM	FILENAME :	J5_FHTR_TFR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	D.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
      W cr =
                  CENTRAL RESERVE WIDTH
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
      W b-c =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vr c-b =
        D =
                  STREAM-SPECIFIC B-A
                 STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                              GEOMETRIC FACTORS:
                                                                                         THE CAPACITY OF MOVEMENT:
                                                                                                                                                COMPARISION OF DESIGN FLOW
                                                                                                                                                TO CAPACITY:
      MAJOR ROAD (ARM A)
                                                                      0.90579
                                                                                                Q b-a =
                                                                                                                                                               DFC b-a
                                                                                                                                                                                         0.0267
                   7.36 (metres)
                                                        Ε
                                                                                                               444 Q b-c (O) = 441
                                                                                                                                                               DFC b-c
                                                                                                                                                                                         0.0068
      W cr =
                     0 (metres)
                                                                      0.61552
                                                                                                Q b-c =
      qa-b =
                     9 (pcu/hr)
                                                                      0.95534
                                                                                                Q c-b =
                                                                                                               688
                                                                                                                                                               DFC c-b
                                                                                                                                                                                         0.0116
                                                        Υ
                                                                                                                                                                                         0.0059
      qa-c =
                    82 (pcu/hr)
                                                                      0.74608
                                                                                               Q b-ac =
                                                                                                               508
                                                                                                                                                               DFC b-c (share lane) =
                                                    F for (Qb-ac) = 0.17647059
                                                                                                TOTAL FLOW
                                                                                                              = 246
                                                                                                                                (PCU/HR)
      MAJOR ROAD (ARM C)
      W c-b =
                   4.18 (metres)
                         (metres)
      Vr c-b =
                    20
      q c-a =
                   130
                         (pcu/hr)
      q c-b =
                    8
                         (pcu/hr)
                                                                                                                                                 CRITICAL DFC
                                                                                                                                                                                  = 0.03
      MINOR ROAD (ARM B)
      W b-a =
                   3.62
                         (metres)
                   0.00
      W b-c =
                         (metres)
                         (metres)
                         (metres)
      Vr b-a =
                   100
      Vr b-c =
                         (metres)
      q b-a =
                    14 (pcu/hr)
      q b-c =
                     3 (pcu/hr)
```


LLA CONSULTANCY LIMITED	INITIALS	DATE				
Feasibility for Proposed Training Ground in Lam Tei for the Hong K	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20	
J/O Fuk Hang Tsuen Road / Tat Fuk Road	2024 Design AM	FILENAME :	J5_FHTR_TFR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	D.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
      W cr =
                  CENTRAL RESERVE WIDTH
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
      W b-c =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
      Vr c-b =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
        D =
                  STREAM-SPECIFIC B-A
                 STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                              GEOMETRIC FACTORS:
                                                                                         THE CAPACITY OF MOVEMENT:
                                                                                                                                                COMPARISION OF DESIGN FLOW
                                                                                                                                                TO CAPACITY:
      MAJOR ROAD (ARM A)
                                                                      0.90579
                                                                                                Q b-a =
                                                                                                               507
                                                                                                                                                               DFC b-a
                                                                                                                                                                                         0.0237
                   7.36 (metres)
                                                        Ε
                                                                                                               434 Q b-c (O) = 431.4
                                                                                                                                                               DFC b-c
                                                                                                                                                                                         0.0092
      W cr =
                     0 (metres)
                                                                      0.61552
                                                                                               Q b-c =
                                                        F
      qa-b =
                    14 (pcu/hr)
                                                                      0.95534
                                                                                                Q c-b =
                                                                                                               671
                                                                                                                                                               DFC c-b
                                                                                                                                                                                         0.0119
                                                        Υ
                                                                                                               487
                                                                                                                                                              DFC b-c (share lane) =
                                                                                                                                                                                         0.0082
      qa-c =
                    143 (pcu/hr)
                                                                      0.74608
                                                                                               Q b-ac =
                                                    F for (Qb-ac) =
                                                                         0.25
                                                                                               TOTAL FLOW
                                                                                                             = 323
                                                                                                                                (PCU/HR)
      MAJOR ROAD (ARM C)
      W c-b =
                   4.18 (metres)
      Vr c-b =
                    20
                         (metres)
      q c-a =
                   142
                         (pcu/hr)
      q c-b =
                     8
                         (pcu/hr)
                                                                                                                                                CRITICAL DFC
                                                                                                                                                                                  = 0.02
     MINOR ROAD (ARM B)
      W b-a =
                   3.62
                         (metres)
                   0.00
      W b-c =
                         (metres)
                         (metres)
      Vr b-a =
                   100
                         (metres)
      Vr b-c =
                         (metres)
      q b-a =
                    12 (pcu/hr)
      q b-c =
                     4 (pcu/hr)
```

LLA CONSULTANCY LIMITED	INITIALS	DATE				
Feasibility for Proposed Training Ground in Lam Tei for the Hong K	PROJECT NO.:	40624	PREPARED BY:	BSL	Feb-20	
J/O Fuk Hang Tsuen Road / Tat Fuk Road	2024 Design PM	FILENAME :	J5_FHTR_TFR.xlsx	CHECKED BY:	SLN	Feb-20
		REFERENCE NO	O.:	REVIEWED BY:	SLN	Feb-20



```
NOTES: (GEOMETRIC INPUT DATA)
                  MAJOR ROAD WIDTH
      W =
      W cr =
                  CENTRAL RESERVE WIDTH
      W b-a =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-a
      W b-c =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM b-c
      W c-b =
                  LANE WIDTH AVAILABLE TO VEHICLE WAITING IN STREAM c-b
                  VISIBILITY TO THE LEFT FOR VEHICLES WAITING IN STREAM b-a
      VI b-a =
      Vr b-a =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-a
      Vr b-c =
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM b-c
                  VISIBILITY TO THE RIGHT FOR VEHICLES WAITING IN STREAM c-b
      Vr c-b =
        D =
                  STREAM-SPECIFIC B-A
                 STREAM-SPECIFIC B-C
        E =
        F =
                  STREAM-SPECIFIC C-B
                 (1-0.0345W)
```

```
GEOMETRIC DETAILS:
                                              GEOMETRIC FACTORS:
                                                                                         THE CAPACITY OF MOVEMENT:
                                                                                                                                                COMPARISION OF DESIGN FLOW
                                                                                                                                                TO CAPACITY:
      MAJOR ROAD (ARM A)
                                                                      0.90579
                                                                                                Q b-a =
                                                                                                                                                               DFC b-a
                                                                                                                                                                                         0.0267
                   7.36 (metres)
                                                        Ε
                                                                                                               444 Q b-c (O) = 441
                                                                                                                                                               DFC b-c
                                                                                                                                                                                         0.0068
      W cr =
                     0 (metres)
                                                                      0.61552
                                                                                                Q b-c =
      qa-b =
                     9 (pcu/hr)
                                                                      0.95534
                                                                                                Q c-b =
                                                                                                               688
                                                                                                                                                               DFC c-b
                                                                                                                                                                                         0.0116
                                                        Υ
                                                                                                                                                                                         0.0059
      qa-c =
                    82 (pcu/hr)
                                                                      0.74608
                                                                                               Q b-ac =
                                                                                                               508
                                                                                                                                                               DFC b-c (share lane) =
                                                    F for (Qb-ac) = 0.17647059
                                                                                                TOTAL FLOW
                                                                                                              = 246
                                                                                                                                (PCU/HR)
      MAJOR ROAD (ARM C)
      W c-b =
                   4.18 (metres)
                         (metres)
      Vr c-b =
                    20
      q c-a =
                   130
                         (pcu/hr)
      q c-b =
                    8
                         (pcu/hr)
                                                                                                                                                 CRITICAL DFC
                                                                                                                                                                                  = 0.03
      MINOR ROAD (ARM B)
      W b-a =
                   3.62
                         (metres)
                   0.00
      W b-c =
                         (metres)
                         (metres)
                         (metres)
      Vr b-a =
                   100
      Vr b-c =
                         (metres)
      q b-a =
                    14 (pcu/hr)
      q b-c =
                     3 (pcu/hr)
```

# Appendix C

Junction Calculation Sheets
- 2024 Design Scenario (With Junction Improvement)

NOTE:


O - OPPOSING TRAFFIC

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


#### TRAFFIC SIGNAL CALCULATION

#### 2024 Design AM (IMP)

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Feb-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Feb-20
		Reviewed By:	SLN	Feb-20



	ges per cycle	N =	4	
Cycle time	е	C =	120 sec	
Sum(y)		Y =	0.536	
Loss time		L =	46 sec	
Total Flow	v	=	3350 pcu	
Co	= (1.5*L+5)/(1-Y)	=	159.6 sec	
Cm	= L/(1-Y)	=	99.2 sec	
Yult		=	0.555	
R.C.ult	= (Yult-Y)/Y*100%	=	3.5 %	
Ср	$= 0.9 \times L/(0.9 - Y)$	=	113.8 sec	
Ymax	= 1-L/C	=	0.617	
R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	3 %	



SG - STEADY GREEN

N - NEAR SIDE LANE

Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	5	9	3	12	9
P2	2,3	8	5	7	0	49	7
P3	4	10.3	5	9	2	13	9

QUEUING LENGTH = AVERAGE QUEUE \* 6m

Move-	Stage	Lane	No. of	Radius	0	l N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	V	Greater		I	g	Degree of	Queue	Average
ment	Clage	Width	lane	m.	l	'`	Ahead		Straight		FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow	y	V	sec	(required)	(input)	Saturation		Delay
ment		1	lane	111.			1		1 -	-						Factor		70	1 1			У	Sec	(required)			-	'
-		m.					Sat. Flow	pcu/n	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	Х	(m / lane)	(seconds)
																							46					
1	1	3.75	2				4260		1013		1013	0.00	4260							4260	0.238	0.238		33	33	0.870	75	44
1,2	1	3.75	1	12		N	1990	105	355		460	0.23	1935							1935	0.238			33	33	0.870	72	36
6	1,4	3.40	3			l N	6145		1048		1048	0.00	6145							6145	0.171			24	24	0.870	56	55
5	2	3.40	1	12			2095			262	262	1.00	1862							1862	0.141	0.141		19	19	0.870	54	45
"	~	0.40		'-			2000			202	202	1.00	1002							1002	0.171	0.141			10	0.010	<u> </u>	-10
		0.40		40			0005	70		000	004	4.00	4000							4000	0.450	0.450		00	00	0.070	co	44
3,4	3	3.40	1	12		l	2095	72		222	294	1.00	1862							1862	0.158	0.158		22	22	0.870	60	44
4	3	3.40	1	12		N	1955	273			273	1.00	1738							1738	0.157			22	22	0.870	54	44

FG - FLASHING GREEN


PEDESTRAIN WALKING SPEED = 1.2m/s

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


#### TRAFFIC SIGNAL CALCULATION

#### 2024 Design PM (IMP)

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Feb-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Feb-20
		Reviewed By:	SLN	Feb-20



Ymax	= 1-L/C	=	0.617
Ср	= 0.9 L/(0.9 Y)	=	115.6 sec
R.C.ult	= (Yult-Y)/Y*100%	=	2.4 %
Yult		=	0.555
Cm	= L/(1-Y)	=	100.4 sec
Co	= (1.5*L+5)/(1-Y)	=	161.5 sec
Total Flow		=	3687 pcu
Loss time		L =	46 sec
Sum(y)		Y =	0.542
Cycle time		C =	120 sec
No. of stag	ges per cycle	N =	4



Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	5	9	3	17	9
P2	2,3	8	5	7	0	50	7
P3	4	10.3	5	9	2	18	9

Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	×	(m / lane)	(seconds)
																							46					
1	4	3.75	ء ا				4260		1007		1007	0.00	4260							4260	0.236	0.236		32	32	0.879	75	45
'			4			١	1	400	I													0.230						
1,2	1	3.75	1	12		N	1990	106	350		456	0.23	1934							1934	0.236			32	32	0.879	78	37
							1																					
6	1,4	3.40	3			N	6145		1424		1424	0.00	6145							6145	0.232			32	32	0.879	70	54
5	2	3.40	1	12			2095			321	321	1.00	1862							1862	0.172	0.172		24	24	0.879	60	43
							1																					
3,4	3	3.40	1	12			2095	38		210	248	1.00	1862							1862	0.133	0.133		18	18	0.879	54	46
4	3	3.40	;	12		l <sub>N</sub>	1955	231		210	231	1.00	1738							1738	0.133	0.100		18	18	0.879	54	46
4	3	3.40	'	12		l in	1900	231			231	1.00	1730							1730	0.133			10	10	0.079	34	40
							1																					
							1																					
							1																					
							1																					
							1																					
							1																					
								1																				
		•	•		•	•		•	•	•	•		•		•				•									

NOTE:

O - OPPOSING TRAFFIC

N - NEAR SIDE LANE

SG - STEADY GREEN

FG - FLASHING GREEN

PEDESTRAIN WALKING SPEED = 1.2m/s

Suite 1710, Concordia Plaza, 1 Science Museum Road, Tsim Sha Tsui East, Kowloon, Hong Kong.

Kowloon, Hong Kong. Tel: (852) 2802-7203 Fax: (852) 2620-6022

E-mail: pac@planarch.com.hk

# PlanArch Consultants Ltd. 建港規劃顧問有限公司



TPB Ref.: A/TM-LTYY/398 Our Ref.: pa/tm.ltyy/1906605

By Hand and Email

Secretary
Town Planning Board
15/F., North Point Government Offices,
No. 333, Java Road, North Point, Hong Kong
(Attn.: Mr. Raymond KAN)

17 June 2020

Dear Sir,

S16 Application for Proposed Temporary Training Ground
(Hong Kong Institute of Construction, Construction Industry Council)
for a Period of 3 Years at Government Land under Kong Sham Western Highway
(next to Wong Kong Wai Road near Fuk Hang Tusen),

Lam Tei, Tuen Mun, New Territories

We refer to the captioned S16 application submitted to the Town Planning Board on 25.2.2020 and the subsequent comments from the Planning Department (PlanD) and Transport Department (TD).

#### 1. Temporary Use of the Proposed Development

The captioned application applies for a period of 3 years in order to provide sufficient flexibility for the proposed development. The proposed duration allows the temporary training ground to start as a pilot operation instead of a long-term development, and that the surrounding communities can observe and understand that the proposed training ground will not bring any negative impact to them and to the environment. Hence, their acceptance of the operation of the training ground at the site could be obtained.

It is intended that the operation of proposed temporary training ground at the application site will be reviewed after 3 years, and a more comprehensive development plan may be prepared to investigate the possibility of a long-term development.

#### 2. Road Widening Works and Link Capacity Assessment of Fuk Hang Tsuen Road

In addition to our submission of Further Information on 29.4.2020, we would like to further address the comments from TD on road widening works and link capacity assessment of Fuk

Z:\Project\Pjt605\tpb-170620-01.docx

Page 1 of 3



Hang Tsuen Road. Attached please find the revised pages to the Traffic Impact Assessment (TIA) for your consideration (Appendix A).

It is understood that there is no programme for Fuk Hang Tsuen Road widening works at this stage. So, it is anticipated that the proposed development will be operated before the completion of the road widening works.

Link capacity assessment at Fuk Hang Tsuen Road is conducted and presented in Table R2 of the revised TIA (**Appendix A**). The results show that Fuk Hang Tsuen Road will operate with capacity in both reference and design scenarios in 2024.

A sensitivity test is also conducted assuming the capacity of Fuk Hang Tsuen Road reduced to 800 veh/hr and the result is presented in Table R3 of the revised TIA (**Appendix A**). The results show that Fuk Hang Tsuen Road will operate over 0.85 in both reference and design scenarios in 2024. With Fuk Hang Tsuen Road widening works, the v/c ratios can be improved significantly to 0.36.

At the same time, an updated junction capacity assessment is carried out at J/O Cast Peak Road-Lam Tei / Fuk Hang Tsuen Road and presented in updated Table 4.6 of the revised TIA (Appendix A). The result shows that with the Fuk Hang Tsuen Road junction improvement works, the RCs can be improved to more than 15%. The calculations are also attached for reference.

The applicant, Construction Industry Council (CIC), is a statutory body established on 2007 under Cap. 587 Construction Industry Council Ordinance. The main function of CIC is to convey the needs and aspirations of the construction industry to the Hong Kong Government. It also serves as an advisory body advising the Government on construction-related matters. In particular, CIC is empowered to steer forward research and manpower development. It provides training courses for the construction industry and establish and maintain industrial training centres for the construction industry.

It is understood that the Fuk Hang Tsuen Road widening works will affect the basketball court of "Fuk Hang playground" and many private lots along Fuk Hang Tsuen Road. Land resumption will be involved and the project scale of such works is relatively large.

The application for the proposed training ground at Lam Tei under the captioned application is only for a temporary use for 3 years, it will have no funding / capacity / resources for the extensive scope of works involving land resumption, objections handling as well as civil engineering works for road widening and junction improvements.

The information serves as clarification of the background information of the application under the Section 5(b) of the TPB Guideline No. 32, and we would like to seek an exemption from Z:\Project\Pjt605\tpb-170620-01.docx Page 2 of 3

publication and recounting requirement. In case you decide that the above information in accepted but not exempted from publication and recounting requirement, we would like to proceed with the application with the further information.

Should you have any questions, please feel free to contact the undersigned.

Thank you for your kind attention.

Yours faithfully,
For and on behalf of
PlanArch Consultants Ltd.

w/e.

cc. Client

DPO/TMYLW, PlanD (Attn.: Mr. Keith FUNG)

C for T, TD (Attn.: Ms. WAN Mei Yin)

Car Parking Provisions of the Existing CIC Training Grounds – Bar Bending and Table 2.2 **Timber Formwork Training** 

Site	Name of Training Ground	Maximum Staff No.	Maximum Student No.	No. of Carparking Provision	No. of space / staff
1	Kwun Tong - Wai Lok Street	28	400	8	0.29
2	Tin Yuet Road	7	90	2	0.29
3	5-7 Wong Lung Hang Road, Tung Chung	6	70	2	0.33
4	Tung Chau Street, Sham Shui Po	4	60	0	0
5	Siu Lun Street, Tuen Mun	5	80	2	0.40

Table 4.5 **2024 Junction Capacity Assessment** 

No.	Junction	Type/	2024 Re	ference	2024 🛭	Design
NO.	Junction	Capacity Index <sup>(1)</sup>	AM Peak	PM Peak	AM Peak	PM Peak
А	Castle Peak Road-Lam Tei/ Wong Kong Wai Road	Priority/DFC	0.07	0.07	0.08	0.09
В	Castle Peak Road-Lam Tei/ Fuk Hang Tsuen Road	Signals/RC	3%	5%	1%	4%
С	Wong Kong Wai Road / Man Chat Road	Priority/DFC	0.05	0.07	0.08	0.09
D	Wong Kong Wai Road / Tat Fuk Road	Priority/DFC	0.03	0.04	0.03	0.04
Е	Fuk Hang Tsuen Road / Tat Fuk Road	Priority/DFC	0.02	0.03	0.02	0.03

(1) (2) Note:

DFC = Design flow to capacity ratio for priority junction. RC = Reserved capacity for signalized junction.

Table 4.6 **Junction Capacity Assessment for Design Year 2024 with Junction Improvement)** 

			2024 Design							
No.	Junction Location	Type /Capacity	Without In	nprovement	With Improvement					
		Index <sup>(1)</sup>	AM Peak Hour	PM Peak Hour	AM Peak Hour	PM Peak Hour				
В	Castle Peak Road – Lam Tei/Fuk Hang Tsuen Road	Signalized /RC	1%	4%	16%	15%				

Table R1 Level of Service (LOS) of the Surveyed Footpaths

Ref	Location	Actual Width	Effective Width	Peak Ho	our Flow d/hr)	Flow f	Rate <sup>(3)</sup> n [LOS]
		(m)	(m) <sup>(1)(2)</sup>	AM	PM	AM	PM
Existi	ng Scenario						
P1	Northern footpath of Wong Kong Wai Road (between Castle Peak Road – Hung Shui Kiu and Man Chat Road)	1.5	0.5	14	8	0.5 [A]	0.3 [A]
P2	Northern footpath of Wong Kong Wai Road (between Man Chat Road and local access road)	2.0	1.0	18	10	0.3 [A]	0.2 [A]
P3	Southern footpath of Wong Kong Wai Road (between local access road and the Proposed Site Access)	1.0	0.6	4	1	0.1 [A]	0.1 [A]
Futur	e Scenario (With the Proposed Development)						
P1	Northern footpath of Wong Kong Wai Road (between Castle Peak Road – Hung Shui Kiu and Man Chat Road)	1.5	0.5	415	409	13.8 [A]	13.6 [A]
P2	Northern footpath of Wong Kong Wai Road (between Man Chat Road and local access road)	2.0	1.0	419	411	7.0 [A]	6.9 [A]
P3	Southern footpath of Wong Kong Wai Road (between local access road and the Proposed Site Access)	1.0	0.6	400	400	11.1 [A]	11.1 [A]

Note:

- A clearance zone of 0.5m on side with obstruction was adopted for P1 and P2.
- A clearance zone of 0.2m on side with obstruction was adopted for P3.
- (2) (3) For LOS "C" or above, flow volumes should be less than 33 ped/m/min.

Link Capacity Assessment at Fuk Hang Tsuen Road (Between Castle Peak Road and Man Chat Road) Table R2


	Road	Capacity (veh/hr)	Peak Traffic (veh		V/C Ratio	
			AM	PM	АМ	PM
Existing Scenario		1,400	616	595	0.44	0.43
2024 Design Scanario	Without FHTR widening works	1,400	784	760	0.56	0.54
2024 Design Scenario	With FHTR widening works	2,200	704	760	0.36	0.35

Note: (1) The traffic flow is converted from pcu/hr to veh/hr by adopting the surveyed pcu factors.

Table R3 Link Capacity Assessment at Fuk Hang Tsuen Road (Between Castle Peak Road and Man Chat Road) – Sensitivity Test

<u>Scenarios</u>	Capacity (veh/hr)	Peak hour Traffic Flow <sup>(1</sup> (veh/hr)		V/C Ratio		
		<mark>AM</mark>	<mark>PM</mark>	<mark>AM</mark>	<mark>PM</mark>	
Existing Scenario	800	<mark>616</mark>	<mark>595</mark>	0.77	0.74	
2024 Reference Scenario	800	<mark>767</mark>	<mark>749</mark>	0.96	0.94	
2024 Design Scenario	800	<mark>784</mark>	<mark>760</mark>	0.98	0.95	

Note: (1) The traffic flow is converted from pcu/hr to veh/hr by adopting the surveyed pcu factors.




Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

### 2019 Existing AM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Jun-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Jun-20
		Reviewed By:	SLN	Jun-20



Sum(y) Loss time		L =	25 sec
Total Flow	•	=	2705 pcu
Co	= (1.5*L+5)/(1-Y)	=	97.1 sec
Cm	= L/(1-Y)	=	57.1 sec
Yult		=	0.713
R.C.ult	= (Yult-Y)/Y*100%	=	26.7 %
Ср	= 0.9 L/(0.9 Y)	=	66.6 sec
Ymax	= 1-L/C	=	0.792
R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	27 %



Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	12	9
P2	2.3	11.4	10	10	2	69	10

Move-ment   Move																													
m.   Sat. Flow   pcu/h   m.   pcu/hr	eue Average	Queue	Degree of	g	g	L	Greater	У	Revised	Gradient	Gradient	Site	Site	Flare	Flare	Sat.	Proportion	Total	nt	Moveme		Straight-	N	0	Radius	No. of	Lane	Stage	Move-
1     1     3.65     2       1,2     1     3.65     1       1,2     1     3.65     1       1     1     3.65     1       1,2     1     3.65     1       1     1     3.65     1       1     1     3.65       1     1       1     3.65       1     1       1     3.65       1     1       1     1       1     3.65       1     1       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.2       3.2     3.710       3.2     3.2       3.2     3.710       3.2     3.710       3.2     3.710       3.2     3.710       3.1     3.2       3.1     3.2       3.1     3.2       3.1     3.2       3.1     3.2 <td< th=""><th>ngth Delay</th><th>Length</th><th>Saturation</th><th>(input)</th><th>(required)</th><th>sec</th><th>у</th><th></th><th>Sat. Flow</th><th>Effect</th><th>%</th><th>Effect</th><th>Factor</th><th>Effect</th><th>Lane</th><th>Flow</th><th>of Turning</th><th>FLow</th><th>Right</th><th>Straight</th><th>Left</th><th>Ahead</th><th></th><th></th><th>m.</th><th>lane</th><th>Width</th><th></th><th>ment</th></td<>	ngth Delay	Length	Saturation	(input)	(required)	sec	у		Sat. Flow	Effect	%	Effect	Factor	Effect	Lane	Flow	of Turning	FLow	Right	Straight	Left	Ahead			m.	lane	Width		ment
1     1     3.65     2       1,2     1     3.65     1       1,2     1     3.65     1       1     1     3.65     2       1,2     1     3.65     1       1     1     3.65     2       1     1     3.65       1     1     3.65       1     1     3.65       1     1     3.65       1     1     3.65       1     1     3.65       1     3.65     1       1     3.65     1       1     3.65     1       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.65       1     3.20       3.1     3.2       3.2     3.710       3.2     3.710       3.2     3.710       3.2     3.710       3.2     3.710       3.2     3.710       3.2     3.710       3.1     3.2       3.710     3.10       3.1     3.2	lane) (seconds	(m / lane	1 x	sec	sec				pcu/h	pcu/hr		pcu/hr		pcu/hr	l m.	pcu/h	Vehicles	pcu/h	pcu/h	pcu/h	pcu/h	Sat. Flow					m.		
1     1     3.65     2       1,2     1     3.65     1       1,2     1     3.65       1     1       3.65     1       1     1       3.65     1       1     1       3.65     1       1     1       3.65     1       1     1       3.65     1       1     1       3.65     1       1     1       3.65     1       1     1       3.65     1       1     1 <th></th> <th></th> <th></th> <th></th> <th></th> <th>25</th> <th></th>						25																							
1,2     1     3.65     1     12     N     1980     72     287     359     0.20     1932       5     2     3.40     1     15     N     6145     192     192     192     1.00     1905     1905     0.101     0.101     0.101     17     17     17     0.710       6     1     3.40     3     3     886     0.00     6145     0.00     6145     0.144     0.101     0.101     0.710	7 39	57	0.740	22	20	-	0.400	0.400	4040							4040	0.00	700		700		4040				ا ا	2.05	4	1 ,
5 2 3.40 1 15 N 2095 N 6145 886 192 192 1.00 1905 6145 1							0.100	1	l									1		1		1	l			-		!	1 .'.
6 1 3.40 3 N 6145 886 886 0.00 6145 6145 0.144 24 32 0.710	8 44	48	0.710	32	31			0.186	1932							1932	0.20	359		287	72	1980	N		12	1	3.65	1	1,2
6 1 3.40 3 N 6145 886 886 0.00 6145 6145 0.144 24 32 0.710																													
	0 59	30	0.710	17	17		0.101	0.101	1905							1905	1.00	192	192			2095			15	1	3.40	2	5
	6 43	46	0.710	32	24			0.144	6145							6145	0.00	886		886		6145	ΙN			3	3.40	1	6
3,4 3 3.20 1 12 N 1935 294 176 470 1.00 1720 1720 1720 1720 1720 0.273 0.273 46 46 0.710																		***		***			''						"
3,4 3 3.20 1 12 N 1935 294 176 470 1.00 1720 1720 1720 0.273 0.273 46 46 0.710		54	0.740	40	40		0.070	0.070	4700							4700	4.00	470	470		004	4005	١.,		40	١,	0.00	•	1
	4 34	54	0.710	46	46		0.273	0.273	1720							1720	1.00	4/0	1/6		294	1935	I N		12	1	3.20	3	3,4
				1														1											
				1														1											
																					l	1							

NOTE:

O - OPPOSING TRAFFIC

N - NEAR SIDE LANE

SG - STEADY GREEN

FG - FLASHING GREEN

PEDESTRAIN WALKING SPEED = 1.2m/s

NOTE:


O - OPPOSING TRAFFIC

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

#### 2019 Existing PM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Jun-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Jun-20
		Reviewed By:	SLN	Jun-20



R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	35	%
Ymax	= 1-L/C	=	0.792	
Ср	= 0.9 L/(0.9 Y)	=	60.6	sec
R.C.ult	= (Yult-Y)/Y*100%	=	34.8	%
Yult		=	0.713	
Cm	= L/(1-Y)	=	53.0	sec
Co	= (1.5*L+5)/(1-Y)	=	90.1	sec
Total Flow	•	=	2572	pcu
Loss time		L =	25	sec
Sum(y)		Y =	0.529	
Cycle time	•	C =	120	sec
No. of staເ	ges per cycle	N =	3	



SG - STEADY GREEN

N - NEAR SIDE LANE

Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	20	9
P2	2.3	11.4	10	10	2	71	10

QUEUING LENGTH = AVERAGE QUEUE \* 6m

Move	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation		Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	Х	(m / lane)	(seconds)
																							25					
1	1	3.65	2				4240		613		613	0.00	4240							4240	0.145			26	30	0.668	48	42
1,2	1	3.65	1	12		N	1980	66	209		275	0.24	1922							1922	0.143			26	30	0.668	42	47
5	2	3.40	1	15			2095			261	261	1.00	1905							1905	0.137	0.137		25	25	0.668	36	48
6	1	3.40	3			N	6145		1041		1041	0.00	6145							6145	0.169	0.169		30	30	0.668	50	38
3,4	3	3.20	1	12		N	1935	216		166	382	1.00	1720							1720	0.222	0.222		40	40	0.668	48	37
		1	l				1	L					l		l					<u> </u>		l						

FG - FLASHING GREEN

NOTE:

O - OPPOSING TRAFFIC


N - NEAR SIDE LANE

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

#### 2024 Reference AM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Jun-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Jun-20
		Reviewed Bv:	SLN	Jun-20



	ges per cycle	N =	3
Cycle time		C =	120 sec
Sum(y)		Y =	0.694
Loss time		L =	25 sec
Total Flow	1	=	3323 pcu
Co	= (1.5*L+5)/(1-Y)	=	139.0 sec
Cm	= L/(1-Y)	=	81.8 sec
Yult		=	0.713
R.C.ult	= (Yult-Y)/Y*100%	=	2.6 %
Ср	= 0.9 L/(0.9-Y)	=	109.4 sec
Ymax	= 1-L/C	=	0.792
R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	3 %



SG - STEADY GREEN

Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	13	9
P2	2.3	11.4	10	10	2	69	10

QUEUING LENGTH = AVERAGE QUEUE \* 6m

Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	×	(m / lane)	(seconds)
																							25					
1	1	3.65	ر ا				4240		1008		1008	0.00	4240							4240	0.238			33	33	0.877	75	44
'		_	-	40		١		405														0.000						
1,2	1	3.65	1	12		N	1980	105	353		458	0.23	1925							1925	0.238	0.238		33	33	0.877	78	37
5	2	3.40	1	15			2095			249	249	1.00	1905							1905	0.131	0.131		18	18	0.877	54	47
6	1	3.40	3			N	6145		1048		1048	0.00	6145							6145	0.171			23	33	0.877	58	55
3,4	3	3.20	4	12		l <sub>N</sub>	1935	345		215	560	1.00	1720							1720	0.326	0.326		45	45	0.877	78	28
3,4	"	3.20	'	12		"	1933	343		213	300	1.00	1720							1720	0.320	0.320		45	40	0.077	70	20
		1																										
	l			l	I			L		L	L		L		l													

FG - FLASHING GREEN

NOTE:

O - OPPOSING TRAFFIC


N - NEAR SIDE LANE

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

#### 2024 Reference PM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Jun-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Jun-20
		Reviewed Bv:	SLN	Jun-20



	ges per cycle	N =	3
Cycle time	•	C =	120 sec
Sum(y)		Y =	0.676
Loss time		L =	25 sec
Total Flow	1	=	3666 pcu
Co	= (1.5*L+5)/(1-Y)	=	131.0 sec
Cm	= L/(1-Y)	=	77.1 sec
Yult		=	0.713
R.C.ult	= (Yult-Y)/Y*100%	=	5.5 %
Ср	= 0.9 L/(0.9-Y)	=	100.3 sec
Ymax	= 1-L/C	=	0.792
R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	5 %



SG - STEADY GREEN

Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	18	9
P2	2.3	11.4	10	10	2	68	10

QUEUING LENGTH = AVERAGE QUEUE \* 6m

Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	X	(m / lane)	(seconds)
								P	F = 1,11	F-1.,	F		P		F		F		F	F			25				(,)	()
Ι.	١.,	0.05					4040				4000		4040							40.40	0.000		25				70	40
1 1	1	3.65	2	_			4240		1002		1002	0.00	4240							4240	0.236	0.236		33	33	0.853	72	43
1,2	1	3.65	1	12		N	1980	106	348		454	0.23	1924							1924	0.236			33	33	0.853	72	36
							1																					
5	2	3.40	1	15			2095			314	314	1.00	1905							1905	0.165	0.165		23	23	0.853	60	43
6	1	3.40	3			l <sub>N</sub>	6145		1424		1424	0.00	6145							6145	0.232			33	33	0.853	68	53
ľ	l '	0.40	ľ			''	0140		1727		1727	0.00	0140							0140	0.202				00	0.000	•••	
		l		_																								
3,4	3	3.20	1	12		N	1935	269		203	472	1.00	1720							1720	0.274	0.274		39	39	0.853	72	32
							1																					
							1																					
							1																					
							1																					
							1																					
							1																					
							1																					
							1																					
							1																					
							1																					
								1																				
								1																				

FG - FLASHING GREEN

NOTE:


O - OPPOSING TRAFFIC

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

#### 2024 Design AM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Jun-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Jun-20
		Reviewed By:	SLN	Jun-20



	ges per cycle	N =	3
Cycle time	9	C =	120 sec
Sum(y)		Y =	0.706
Loss time		L =	25 sec
Total Flow	<i>I</i>	=	3350 pcu
Co	= (1.5*L+5)/(1-Y)	=	144.6 sec
Cm	= L/(1-Y)	=	85.1 sec
Yult		=	0.713
R.C.ult	= (Yult-Y)/Y*100%	=	0.9 %
Ср	= 0.9 L/(0.9-Y)	=	116.1 sec
Ymax	= 1-L/C	=	0.792
R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	1 %



SG - STEADY GREEN

N - NEAR SIDE LANE

Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	14	9
P2	2.3	11.4	10	10	2	69	10

QUEUING LENGTH = AVERAGE QUEUE \* 6m

Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	Х	(m / lane)	(seconds)
																							25					
1 4	١,	3.65	ا ا				4240		1013		1013	0.00	4240							4240	0.000			32	32	0.000	78	45
.'.		_	-			l															0.239					0.892		
1,2	1	3.65	1	12		N	1980	105	355		460	0.23	1925							1925	0.239	0.239		32	32	0.892	78	37
5	2	3.40	1	15			2095			262	262	1.00	1905							1905	0.138	0.138		19	19	0.892	60	46
6	1	3.40	3			N	6145		1048		1048	0.00	6145							6145	0.171			23	32	0.892	58	55
3,4	3	3.20	4	12		l <sub>N</sub>	1935	345		222	567	1.00	1720							1720	0.330	0.330		44	44	0.892	84	28
3,4	"	3.20	'	12		"	1933	343		222	307	1.00	1720							1720	0.550	0.550		44		0.032	04	20
	l			l	I	L		L		L	L				l								l					


FG - FLASHING GREEN

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

#### 2024 Design PM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Jun-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Jun-20
		Reviewed By:	SLN	Jun-20



R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	4	%
Ymax	= 1-L/C	=	0.792	
Ср	= 0.9*L/(0.9-Y)	=	104.4	sec
R.C.ult	= (Yult-Y)/Y*100%	=	4.1	%
Yult		=	0.713	
Cm	= L/(1-Y)	=	79.2	sec
Co	= (1.5*L+5)/(1-Y)	=	134.7	sec
Total Flow	•	=	3687	pcu
Loss time		L =	25	sec
Sum(y)		Y =	0.685	
Cycle time	•	C =	120	sec
No. of staເ	ges per cycle	N =	3	



Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided			
Phase		(m)	SG	FG	Delay	SG	FG			
P1	2	10.8	9	9	2	18	9			
P2	2.3	11.4	10	10	2	68 10				

Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	X	(m / lane)	(seconds)
								F	F = =,	F	F		F		F		p		F = =,	F			25				(,	()
	١,	0.05	_				4040		4007		4007	0.00	4040							4040	0.000	0.000	25	00	00	0.005	7.5	44
1	1	3.65	2	_			4240		1007		1007	0.00	4240							4240	0.238	0.238		33	33	0.865	75	44
1,2	1	3.65	1	12		N	1980	106	350		456	0.23	1924							1924	0.237			33	33	0.865	72	36
5	2	3.40	l 1	15			2095			321	321	1.00	1905							1905	0.169	0.169		23	23	0.865	60	43
6	1	3.40	3			l <sub>N</sub>	6145		1424		1424	0.00	6145							6145	0.232			32	33	0.865	68	53
"	l '	0.40	ľ			''	0140		1727		1727	0.00	0140							0140	0.202			02	00	0.000	•••	
1		l	Ι.			l																						
3,4	3	3.20	1	12		N	1935	269		210	479	1.00	1720							1720	0.278	0.278		39	39	0.865	72	32
							1	1																				
								1																				

NOTE:

O - OPPOSING TRAFFIC

N - NEAR SIDE LANE

SG - STEADY GREEN

FG - FLASHING GREEN

PEDESTRAIN WALKING SPEED = 1.2m/s


QUEUING LENGTH = AVERAGE QUEUE \* 6m

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

#### 2024 Design AM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Jun-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Jun-20
		Reviewed By:	SLN	Jun-20



TITICA	120		0.702
Ymax	= 1-L/C	=	0.792
Ср	$= 0.9 \times L/(0.9 - Y)$	=	116.1 sec
R.C.ult	= (Yult-Y)/Y*100%	=	0.9 %
Yult		=	0.713
Cm	= L/(1-Y)	=	85.1 sec
Co	= (1.5*L+5)/(1-Y)	=	144.6 sec
Total Flow	1	=	3350 pcu
Loss time		L =	25 sec
Sum(y)		Y =	0.706
Cycle time	•	C =	120 sec
No. of staເ	ges per cycle	N =	3



Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	14	9
P2	2.3	11.4	10	10	2	69	10

Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	X	(m / lane)	(seconds)
								F	F	F	F		F		F		P = =,		F	F			25				(,	()
	١.						4040		1,,,,		4040		4040							40.40	0.000		25				70	45
1	1	3.65	2				4240		1013		1013	0.00	4240							4240	0.239			32	32	0.892	78	45
1,2	1	3.65	1	12		N	1980	105	355		460	0.23	1925							1925	0.239	0.239		32	32	0.892	78	37
5	2	3.40	1	15			2095			262	262	1.00	1905							1905	0.138	0.138		19	19	0.892	60	46
6	1	3.40	3			l <sub>N</sub>	6145		1048		1048	0.00	6145							6145	0.171			23	32	0.892	58	55
"		0.40	ľ			''	0140		1040		1040	0.00	0140							0140	0.171			20	02	0.002	•••	
1																												
3,4	3	3.20	1	12		N	1935	345		222	567	1.00	1720							1720	0.330	0.330		44	44	0.892	84	28

NOTE:

O - OPPOSING TRAFFIC

N - NEAR SIDE LANE

SG - STEADY GREEN

FG - FLASHING GREEN

PEDESTRAIN WALKING SPEED = 1.2m/s

QUEUING LENGTH = AVERAGE QUEUE \* 6m

NOTE:

O - OPPOSING TRAFFIC


N - NEAR SIDE LANE

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


# TRAFFIC SIGNAL CALCULATION

#### 2024 Design PM

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Jun-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Jun-20
		Reviewed By:	SLN	Jun-20



Cp Ymax	= 0.9*L/(0.9-Y) = 1-L/C	=	104.4 sec 0.792
R.C.ult	= (Yult-Y)/Y*100%	=	4.1 %
Yult	_()	=	0.713
Cm	= L/(1-Y)	=	79.2 sec
Total Flow Co	, = (1.5*L+5)/(1-Y)	=	134.7 sec
Loss time Total Flow		L = =	25 sec 3687 pcu
Sum(y)		Y =	0.685
Cycle time	•	C =	120 sec
No. of staເ	ges per cycle	N =	3



SG - STEADY GREEN

Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	9	9	2	18	9
P2	2.3	11.4	10	10	2	68	10

QUEUING LENGTH = AVERAGE QUEUE \* 6m

Move- Stage Lane No. of Radius O Width lane m. m.		Left Strain	ht Right	1	Proportion of Turning	Sat. Flow	Flare Lane	Flare Effect	Site		Gradient		Revised	у	Greater	L	g	g	Degree of	Queue	Average
m.	Sat. Flov	1 1	_	1	of Turning	Flow	Lane	Effoot													,
		pcu/h pcu	h pcu/h	//-			Lanc	Ellect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		F		pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	Х	(m / lane)	(seconds)
	4040			p = =,		F-44.1		P = =		F,		P = =,	F			25				(,)	(22221)
			,	4007	0.00	4040							4040	0.000	0.000	20	00	00	0.005	75	
1 1 3.65 2	4240	100		1007	0.00	4240							4240	0.238	0.238		33	33	0.865	75	44
1,2 1 3.65 1 1 12	N 1980	106 350	1	456	0.23	1924							1924	0.237			33	33	0.865	72	36
																					(
5 2 3.40 1 15	2095		321	321	1.00	1905							1905	0.169	0.169		23	23	0.865	60	43
6 1 3.40 3	N 6145	142	1	1424	0.00	6145							6145	0.232			32	33	0.865	68	53
	1 0140		'	1727	0.00	0140							0140	0.202			02	•••	0.000	•••	
		1																			
3,4 3 3.20 1 12	N 1935	269	210	479	1.00	1720							1720	0.278	0.278		39	39	0.865	72	32
		1 1																			
		1 1																			
		1 1																			
		1 1																			
																					(
		1 1																			
		1 1																			
		1 1																			
		1 1																			
		1 1																			
		1 1																			
		1 1																			

FG - FLASHING GREEN

NOTE:

O - OPPOSING TRAFFIC


N - NEAR SIDE LANE

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


#### TRAFFIC SIGNAL CALCULATION

#### 2024 Design AM (IMP)

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Jun-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Jun-20
		Reviewed Bv:	SLN	Jun-20



No. of sta	ges per cycle	N =	4
Cycle time	e	C =	120 sec
Sum(y)		Y =	0.534
Loss time		L =	37 sec
Total Flow	v	=	3350 pcu
Co	= (1.5*L+5)/(1-Y)	=	129.9 sec
Cm	= L/(1-Y)	=	79.5 sec
Yult		=	0.623
R.C.ult	= (Yult-Y)/Y*100%	=	16.5 %
Ср	$= 0.9 \times L/(0.9 - Y)$	=	91.1 sec
Ymax	= 1-L/C	=	0.692
R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	16 %



SG - STEADY GREEN

Pedestrian	Stage	Width	Gree	n Time Re	auired	Green Tim	e Provided
Phase		(m)	SG	FG	Delay	SG	FG
P1	2	10.8	5	9	3	14	9
P2	2,3	8	5	7	0	54	7
P3	4	10.3	5	5	2	19	5

QUEUING LENGTH = AVERAGE QUEUE \* 6m

Move-	Stage	Lane	No. of	Radius	0	N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	У	Greater	L	g	g	Degree of	Queue	Average
ment		Width	lane	m.			Ahead	Left	Straight	Right	FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow		у	sec	(required)	(input)	Saturation	Length	Delay
		m.					Sat. Flow	pcu/h	pcu/h	pcu/h	pcu/h	Vehicles	pcu/h	l m.	pcu/hr		pcu/hr		pcu/hr	pcu/h				sec	sec	l x	(m / lane)	(seconds
		1																					37					`
1 ,	,	3.65					4240		1013		1013	0.00	4240							4240	0.239	0.239	0,	37	37	0.773	69	38
'.			'	۱.,		١	1	405					_									0.239						
1,2	1	3.65	1	12		N	1980	105	355		460	0.23	1925							1925	0.239			37	37	0.773	60	43
							1																					
6	1,4	3.40	3			N	6145		1048		1048	0.00	6145							6145	0.171			26	26	0.773	54	44
5	2	3.40	1	15			2095			262	262	1.00	1905							1905	0.138	0.138		21	21	0.773	42	59
3,4	3	3.40	1	12			2095	72		222	294	1.00	1862							1862	0.158	0.158		25	25	0.773	48	55
3,4	1						1			222			1									0.130						
4	3	3.40	1	12		N	1955	273			273	1.00	1738							1738	0.157			24	25	0.773	42	56
							1																					
							1																					
							1																					
							1																					
							1																					
							1																					
							1																					
							1																					
	<u> </u>		<u> </u>	<u> </u>	l			l	1	1	l .	l .	l		ı			l										


FG - FLASHING GREEN

Feasibility for Proposed Ttraining Ground in Lam Tei for the Hong Kong Institute of Construction, Construction Industry Council - TIA Study in Support of the Planning J/O Fuk Hang Tsuen Road/Castle Peak Road-Lam Tei


#### TRAFFIC SIGNAL CALCULATION

#### 2024 Design PM (IMP)

			INITIALS	DATE
PROJECT NO.:	40624	Prepared By:	BSL	Jun-20
FILENAME :	J2_FHTR_CPRLT.xlsx	Checked By:	SLN	Jun-20
		Reviewed Bv:	SLN	Jun-20



No. of stag	ges per cycle	N =	4	
Cycle time	9	C =	120 sec	
Sum(y)		Y =	0.539	
Loss time		L =	37 sec	
Total Flow	<i>I</i>	=	3687 pcu	
Co	= (1.5*L+5)/(1-Y)	=	131.3 sec	
Cm	= L/(1-Y)	=	80.3 sec	
Yult		=	0.623	
R.C.ult	= (Yult-Y)/Y*100%	=	15.4 %	
Ср	= 0.9 L/(0.9-Y)	=	92.3 sec	
Ymax	= 1-L/C	=	0.692	
R.C.(C)	= (0.9*Ymax-Y)/Y*100%	=	15 %	



Pedestrian	Stage	Width	Gree	n Time Re	quired	Green Tim	e Provided
Phase	_	(m)	SG	FG	Delay	SG	FG
P1	2	10.8	5	9	3	19	9
P2	2,3	8	5	7	0	54	7
P3	4	10.3	5	5	2	24	5

Move-	Stage	Lane	No. of	Radius	0	l N	Straight-		Movemer	nt	Total	Proportion	Sat.	Flare	Flare	Site	Site	Gradient	Gradient	Revised	V	Greater	L	l a l	g	Degree of	Queue	Average
ment		Width	lane	m.		``	Ahead		Straight		FLow	of Turning	Flow	Lane	Effect	Factor	Effect	%	Effect	Sat. Flow	,	v	sec	(required)	(input)	Saturation		Delay
		m.					Sat. Flow		pcu/h	-	pcu/h	Vehicles	pcu/h	m.	pcu/hr		pcu/hr	~	pcu/hr	pcu/h		,		sec	sec		(m / lane)	1 .
-	<u> </u>	+ '''-					Out. 1 low	pou/ii	pou/ii	роции	pou/ii	Vernoice	pod/11		pou/m		pou/iii		pou/iii	роции			37	500	500		(III / Idilo)	(SCOOTIGS)
1	4	3.65	ر ا				4240		1007		1007	0.00	4240							4240	0.238	0.238	31	37	37	0.780	69	39
'		1	4	40		١.,	1	400														0.236						
1,2	1	3.65	1	12		N	1980	106	350		456	0.23	1924							1924	0.237			36	37	0.780	60	44
6	1,4	3.40	3			N	6145		1424		1424	0.00	6145							6145	0.232			36	36	0.780	66	38
5	2	3.40	1	15			2095			321	321	1.00	1905							1905	0.169	0.169		26	26	0.780	48	54
3,4	3	3.40	1	12			2095	38		210	248	1.00	1862							1862	0.133	0.133		20	20	0.780	42	61
4	3	3.40	1	12		N	1955	231			231	1.00	1738							1738	0.133			20	20	0.780	42	62

NOTE:

O - OPPOSING TRAFFIC

N - NEAR SIDE LANE

SG - STEADY GREEN

FG - FLASHING GREEN

PEDESTRAIN WALKING SPEED = 1.2m/s

QUEUING LENGTH = AVERAGE QUEUE \* 6m

# Appendix Ie of RNTPC Paper No. A/TM-LTYY/456



RE: Planning Application No. A/TM-LTYY/456 - Departmental Comments16/06/2023

12:14

From:

To: "tpbpd@pland.gov.hk" <tpbpd@pland.gov.hk>

, "ekytam@pland.gov.hk"

<ekytam@pland.gov.hk>, "dhhng@pland.gov.hk" <dhhng@pland.gov.hk>

2 Attachments





20230210 LTTG FS251.pdf 20230616 LTTG FS251.pdf

Dear Sir/Madam,

We refer to your email dated 7 June 2023.

We enclosed the full set of valid FS251 for your perusal.

Best regards, Ferrero YIP

#### **Ferrero Yip**

Assistant Manager - Estates Office

**CONSTRUCTION INDUSTRY COUNCIL** 

Tel: Email: Construction INDUSTRY COUNCIL 建造業議會

Follow us







Mi

建造業議會可持續建築大獎2023 | 立即報名 | 展示專業的可持續作業

CIC Sustainable Construction Award 2023 | Apply Now | Play a leading role in sustainable development!

The contents of this email are intended for the named addressee(s) only and may contain confidential information and/or copyrighted materials. If you are not the intended recipient or received it in error, please notify the sender immediately and then delete it. Any unauthorised use, disclosure, reproduction, copying, distribution, or other forms of dissemination of the contents is expressly prohibited. We also take no responsibility for any potential malware and viruses that might be transferred through this email.

From: dhhng@pland.gov.hk <dhhng@pland.gov.hk>

Sent: Wednesday, June 7, 2023 10:40 AM

To:

cc: ; ekytam@pland.gov.hk

Subject: Planning Application No. A/TM-LTYY/456 - Departmental Comments

**EXTERNAL EMAIL**: Do not click any links or open any attachments unless you trust the sender and know the content is safe.

Our Reference: ( ) in TPB/A/TM-LTYY/456

Dear Ferrero.

# Application No. A/TM-LTYY/456 under s.16 of the Town Planning Ordinance

We spoke. Please find attached comments of Director of Fire Services on the captioned application.

- (i) The type and numbers of FSIs listed on the FS251 should be tally with the FSIs listed on the previously submitted FSI proposal.
- (ii) Full set of <u>valid</u>FS251 covering all the FSIs implemented on the application site shall be submitted.

Should you wish to submit further information in response to the above, please do so preferably as soon as possible in writing to Secretary of the Town Planning Board (Address: 15/F, North Point Government Offices, 333 Java Road, North Point, Hong Kong; Fax: 2877 0245) with a copy to us. In submitting the further information, reference should be made to the TPB Guidelines No. 32A on the Submission of Further Information in Relation to Applications for Amendment of Plan, Planning Permission and Review.

Alternatively, you can request the TPB to defer the consideration of the application in order to allow more time to prepare the further information. For details, please refer to the TPB Guidelines No. 33A on Deferment of Decision on Representations, Comments, Further Representations and Applications. Both guidelines could be retrieved from the TPB website: <a href="http://www.info.gov.hk/tpb/en/forms/guideline.html">http://www.info.gov.hk/tpb/en/forms/guideline.html</a>.

Regards,
Danny NG
for District Planning Officer/Tuen Mun and Yuen Long West
Planning Department
Tel: 2158 6201

#### FIRE SERVICE (INSTALLATIONS AND EQUIPMENT) REGULATIONS


消防 (裝置及設備) 規例 (Regulation 9(1)) (第九條(1)款)

30216032673

#### FSD Ref .: 消防處檔號


	CER	TIFICATE OF FIRE SERVIO 消防駐	CE ÌNSTALLAT 置及設備證書	TON AND EQUIPM	MENT	
	Client 顧客姓名	Swe wi	且从以附加自			
	ction Industry Council - Lam Te	Training Ground		- Ve		回線開始然回
Address		CC 125 8 CC 226)				
	nent Land (STT no. MX 18030 : 0		500 Sec. 1		1	
Kong Sh	am Western Highway,Wong Ko	ng Wai Road, Lam Tei, Tue	n Mun, NT			
Type of Bu	ilding 樓宇類型: Industrial 工業	Commercial 商業 Domestic	住宅 Composit	te 綜合 Licensed pr	remises 持牌處所	Institutional 社團
	ONLY or equip	rdance with Regulation 8(b) of the F oment which is installed in any prem once in every 12 months. 根據消防 名註冊承辦商檢查該等消防裝置或設	ises shall have suc (裝置及設備)規例第	h fire service installation	or equipment inspect	ed by a registered contractor
Code 編碼 (1-35)	Code 這時 Type of FSI 裝置類型 Location(s)位置 Comment on Condition 狀况評述 完成日期 (DD/MM/YY)				Completion Date 完成日期 (DD/MM/YYYY)	下次到期日
24	34 nos. x 5 kg CO2 F.E.	STT No. MX 18030 : CS-225 & CS-226	Conforms w requiremen		16/06/2023	15/06/2024
25	4 nos. x sand bucket	Ditto	Ditto 16/06/2			15/06/2024
Part 2 第	写二部 Installation / Modification /	Repair / Inspection works 裝	· 是置/改裝/修理/k	<u></u> 僉查工作		
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置	Nature of V	Vork Carried out 之工作內容	Comment on Con 狀況評述	Completion Date 完成日期 (DD/MM/YYYY)
Part 3 第	三部 Defects 損壞事項					
Code		1 / 1 / 1 PR			(HL) EL	Comment on Defects
編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置	Ou	itstanding Defects 未	<b>修缺點</b>	缺點評述
						1
				For and 美利	on behalf of 堅消防工程	有限公司
Remark (	苗計			AMERICAN Authorized	FIRE ENGINEESHING	COMPANY LIMITED
	11111444			Signature: 受權人簽署 Name:		For FSD use only
working or Equipment	oy certify that the above installations/equip rder in accordance with the Codes of Pr t and Inspection, Testing and Maintenan e by the Director of Fire Services. Defects	ractice for Minimum Fire Service I ice of Installations and Equipment	nstallations and	姓名 ESD/PC No:	3 / 0216 RC	Inspected
本人藉此語	e by the Director of Fire Services, Defects 證明以上之消防裝置及設備經試驗,證明性 讀守則與裝置及設備之檢查測試及保養守則	能良好,符合消防處處長不時公佈的	最低限度之消防(	Company Name: 公司名稱		Key-in
Thio	如證書涉及年檢事項 處所當眼處以供 certificate should be displayed at	消防處人員查核	ilding or	₩ 格 單 話	941455	Verified
prer	nises for FSD's inspection if any a	nnual maintenance work is ir	volved.	Date: 日期 16	5/06/2023	

1b48-66a6-fb0e-9e84-664f-2125-e841-e65f



Name of Client 顧客姓名

Construction Industry Council - Lam Tei Training Ground





# FIRE SERVICE (INSTALLATIONS AND EQUIPMENT) REGULATIONS 消防(裝置及設備)規例

(Regulation 9(1))

(第九條(1)款)

i	Serial Number
	10259015063

Name of Cl	lient 顧客姓名	TIFICATE OF FIRE SERVIC 消防裝	置及設備證書	· ·	IPIVIENI		
	tion Industry Council - Lam Tei	Training Ground				P-11.00	. v r. 2 2 <del></del>
Address 地	<u> </u>						
Governme	ent Land (STT no. MX 18030 : C	S-225 & CS-226),	_				
Kong Shar	m Western Highway,Wong Kor	ng Wai Road, Lam Tei, Tuer	n Mun, NT				
Type of Build	ding 櫻宇類型: Industrial 工業	Commercial 商業 Domestic (	生宅 Compo	osite 綜合 License	d premises 持牌處所	Institutio	nal 社團
	ONLY or equip	dance with Regulation 8(b) of the F ment which is installed in any prem once in every 12 months. 根據消防 註冊承辦商檢查該等消防裝置或設	ises shall have s (裝置及設備)規例	such fire service installa	ation or equipment inspe	cted by a re	gistered contractor
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置	Comment o	n Condition 狀況評議	Completion Da 走 完成日期 (DD/MM/YYY)		ext Due Date 下次到期日 D/MM/YYYY)
13 N	MFA System	STT No. MX 18030 : CS-225 & CS-226	Conforms requireme		08/02/2023	3 (	7/02/2024
23 H	Hose Reel	Ditto Ditto			08/02/2023	3 (	07/02/2024
Part 2 第二	二部 Installation / Modification / F	Repair / Inspection works 裝	置/改裝/修理				
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置	Nature of Work Carried out Comment of		Comment on Co 狀況評述	mailion	Completion Date 完成日期 DD/MM/YYYY)
Part 3 第三	三部 Defects 損壞事項						
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置	Outstanding Defects 未修缺點			Comment on Defects 缺點評述	
				For a 美	md on behalf of 利堅消防工物	有限	<b>∤</b> ৱা
Remark 備註 Authorized Signature: 受權人簽署					CAN FIRE ENGINEERING	Congrainy	For FSD use only
working order Equipment a time to time to 本人藉此證明	certify that the above installations/equiper in accordance with the Codes of Prand Indianal Inspection, Testing and Maintenand by the Director of Fire Services, Defects  月以上之消防裝置及設備經試驗,證明性能 守則與裝置及設備之檢查測試及保養守則	nstallations and published from	E00/00 N	RC1 / 0259 RC	2 / 0405	Inspected	
This c	如證書涉及年檢事項 如證書涉及年檢事項 處所當眼處以供剂 certificate should be displayed at ises for FSD's inspection if any an	,應張貼於大廈或 肖防處人員查核 prominent location of the bu		公司右稱 Telephone: 聯絡電話 Date: 日期	23941455 10/02/2023		Verified

F.S. 251 (Rev. 01/2012) bab9-fc6f-8694-418a-cf03-864e-19ff-1f49

FSD Ref.:

消防處檔號



Name of Client 顧客姓名


Construction Industry Council - Lam Tei Training Ground


# Part 1 Annual Maintenance ONLY


第一部 只適用於年檢事項


In accordance with Regulation 8(b) of the Fire Service (Installations and Equipment) Regulations, the owner of any fire service installation or equipment which is installed in any premises shall have such fire service installation or equipment inspected by a registered contractor at least once in every 12 months. 根據消防(裝置及設備)規例第八條(b)款,擁有裝置在任何處所內的任何消防裝置或設備的人, 須每12個月由一名註冊承辦商檢查該等消防裝置或設備至少一次。


	71日 日に同かが同以直めず行例表直外に研ェクー外							
Code 編碼 (1-35)	Type of FSI 裝置類型	Location(s)位置	Comment on Condition 狀況評述	Completion Date 完成日期 (DD/MM/YYYY)	Next Due Date 下次到期日 (DD/MM/YYYY)			
11	Emergency Lighting System	STT No. MX 18030 : CS-225 & CS-226	Conforms with FSD requirements	08/02/2023	07/02/2024			
12	Exit Signs	Ditto	Ditto	08/02/2023	07/02/2024			
		į						




















RE: Planning Application No. A/TM-LTYY/456 - Departmental Comments19/06/2023

17:19 From:

To: "tpbpd@pland.gov.hk" <tpbpd@pland.gov.hk>

Cc: "dhhng@pland.gov.hk" <dhhng@pland.gov.hk>, "ekytam@pland.gov.hk"

<ekytam@pland.gov.hk>,

5 Attachments











RtoC for TD\_20230619.pdf Figure 2.2.pdf Figure 2.3 to 2.5.pdf Section 2.4.pdf Table 4.4.pdf

Dear Sir/Madam,

For responding to comments from Commissioner for Transport dated 1 June 2023, we would like to submit the following with attachments to replace the previous submission dated 5 June 2023 for your consideration.

There was no substantial change of the traffic volume in vicinity to the proposed development in the past three years, and the current traffic generation and attraction arising from the proposed development would be maintained. Moreover, there will be no large development at the site surroundings in upcoming 3 years which will affect the traffic condition of Wong Kong Wai Road. Therefore, the proposed renewal would not cause adverse traffic impact to the existing road network.

Best Regards, Ferrero YIP



Assistant Manager - Estates Office

**CONSTRUCTION INDUSTRY COUNCIL** 











建造業議會可持續建築大獎2023 | 立即報名 | 展示專業的可持續作業

CIC Sustainable Construction Award 2023 | Apply Now | Play a leading role in sustainable development!


The contents of this email are intended for the named addressee(s) only and may contain confidential information and/or copyrighted materials. If you are not the intended recipient or received it in error, please notify the sender immediately and then delete it. Any unauthorised use, disclosure, reproduction, copying, distribution, or other forms of dissemination of the contents is expressly prohibited. We also take no responsibility for any potential malware and viruses that might be transferred through this email.


# Application No. A/TM-LTYY/456 under s.16 of the Town Planning Ordinance


# **Summary of Responses to Comments (19 June 2023)**


	Comments	Responses
	Comments from Commissioner for Transport via PlanD'	s email dated 1 June 2023
a.	Please advise the number of vehicular and pedestrian	Please refer to Table 4.4
	trip generation and attraction by the subject site.	
b.	Please clarify if any shuttle service will be provided by	No shuttle service will be provided.
	the subject site.	
c.	Please clarify the size of proposed private car and	Please refer to Figure 2.2
	motorcycle parking spaces and their locations as they	Parking space of private car: 5m x 2.5m
	are not easily readable on the layout plan	Parking space of motorcycle: 2.4m x 1m
d.	Please clarify the width of the proposed two vehicular	About 6m width.
	accesses and the internal driveways of the subject	
	site.	
e.	Please supplement the swept path analysis showing	Please refer to Figure 2.3 to 2.5
	the vehicles (i) using the private car and motorcycle	
	parking spaces, (ii) manoeuvring within the internal	
	driveway, and (iii) entering and leaving the site from	
	Wong Kong Wai Road through the proposed vehicular	
	accesses.	

f.	Please justify that the proposed parking provisions are sufficient to cater for the parking demand due to	Please refer to Section 2.4
	the proposed use.	
g.	It is noted that internal driveways are reserved within the subject site. Please ensure that no queuing and / or waiting of motor vehicles from the subject site onto public roads would occur and no motor vehicles shall be permitted to reverse into and out of the subject site onto adjacent public roads or Government Land.	Noted.









#### 2.4 Proposed Car parking and Loading/unloading Provisions

2.4.1 There is no specific guideline set in the Hong Kong Planning Standards and Guidelines for training grounds, the proposed car parking provision will be based on the existing provisions of other CIC training grounds as well as meeting the operational needs. **Table 2.2** listed out the existing car parking provisions at the five existing training grounds operated by CIC.

Table 2.2 Car Parking Provisions of the Existing CIC Training Grounds – Bar Bending and Timber Formwork Training

Site	Name of Training Ground	Maximum Staff No.	Maximum Student No.	No. of Carparking Provision	No. of space / staff
1	Kwun Tong - Wai Lok Street	28	400	8	0.29
2	Tin Yuet Road	7	90	2	0.29
3	5-7 Wong Lung Hang Road, Tung Chung	6	70	2	0.33
4	Tung Chau Street, Sham Shui Po	4	60	0	0
5	Siu Lun Street, Tuen Mun	5	80	2	0.40

- 2.4.2 For all the existing CIC training grounds, the car parking spaces are solely reserved for staff use and no space is allowed for visitors and trainers. Having considered the provision rate per staff at the five existing training grounds, it is suggested to provide 8 car parking spaces, which is equivalent to the rate of 0.4 space/staff, for the proposed training ground. Also, two additional motorcycle parking spaces will also be provided to serve the possible demand.
- 2.4.3 There is no regular loading/unloading demand at the proposed training ground. The minimal loading/unloading activities can be carried out along the internal access road and will not generate a traffic queue onto the public road.
- 2.4.4 Existing carpark provision is enough, no additional parking space is required.


Table 4.4 Proposed Training Ground Development Traffic Generation

Site	No. of Unit/		AM Peak Hour			PM Peak Hour		
Site	Trainees	Content	Gen.	Att.	Total	Gen.	Att.	Total
Kwun Tong - Wai Lok Street	100 <sup>(1)</sup>	pcu/hr	2	4	6	3	2	5
Tin Yuet Road	30 <sup>(1)</sup>	pcu/hr	1	2	3	1	1	2
Derived Trip Rates	Derived Trip Rates							
Kwun Tong - Wai Lok Street	-	pcu/hr/ trainee	0.0200	0.0400	-	0.0300	0.0200	-
Tin Yuet Road	-	pcu/hr/ trainee	0.0333	0.0667	-	0.0333	0.0333	-
Traffic Generation/ Attraction of the Proposed Training Ground	400	pcu/hr	14	27	41	14	14	28

Note: (1) The number of trainees during the surveyed periods are provided by the corresponding CIC training Centre.

所根據資料來源為繪圖所示 EXTRACT PLAN PREPARED ON 12/6/2020 BASED ON SOURCE AS SHOWN IN THE DRAWING

SCALE 1:1,500



SCALE 1:1,500

EXTRACT PLAN PREPARED ON 12/6/2020 BASED ON SOURCE AS SHOWN IN THE DRAWING

APPLICATION SITE (BOUNDARY FOR IDENTIFICATION ONLY) 申請地點(界線只作識別用)

■例 LEGEND 申請セ點 (界線只作識別用) APPLICATION SITE (BOUNDARY FOR IDENTIFICATION ONLY)

本摘要圖於2020年6月18號擬備, 所根據資料來源為繪圖所示 EXTRACT PLAN PREPARED ON 18/6/2020 BASED ON SOURCE AS SHOWN IN THE DRAWING

# Appendix III of RNTPC Paper No. A/TM-LTYY/456

# Relevant Extracts of Town Planning Board Guidelines on "Renewal of Planning Approval and Extension of Time for Compliance with Planning Conditions for Temporary Use or Development" (TPB-PG No. 34D)

- 1. The criteria for assessing applications for renewal of planning approval include:
  - (a) whether there has been any material change in planning circumstances since the previous temporary approval was granted (such as a change in the planning policy/land-use zoning for the area) or a change in the land uses of the surrounding areas;
  - (b) whether there are any adverse planning implications arising from the renewal of the planning approval (such as pre-emption of planned permanent development);
  - (c) whether the planning conditions under previous approval have been complied with to the satisfaction of relevant Government departments within the specified time limits;
  - (d) whether the approval period sought is reasonable; and
  - (e) any other relevant considerations.
- 2. Under normal circumstances, the approval period for renewal should not be longer than the original validity period of the temporary approval. In general, the Board is unlikely to grant an approval period exceeding three years unless there are strong justifications and the period is allowed for under the relevant statutory plans. Depending on the circumstances of each case, the Board could determine the appropriate approval period, which may be shorter than the time under request.

# Appendix IV of RNTPC Paper No. A/TM-LTYY/456

# **Previous Application covering the Application Site**

# **Approved Application**

	Application <u>No.</u>	Proposed Use(s)	Date of Consideration (RNTPC)
1	A/TM-LTYY/398	Proposed Temporary Training Ground (Hong Kong Institute of Construction, Construction Industry Council) for a Period of 3 Years	26.6.2020

#### **Government Departments' General Comments**

#### 1. Land Administration

Comments of the District Lands Officer/Tuen Mun, Lands Department (DLO/TM, LandsD):

No comment on the application.

#### 2. Traffic

(a) Comments of the Commissioner for Transport (C for T):

No adverse comment on the application.

(b) Comments of the Chief Highway Engineer/New Territories West, Highways Department (CHE/NTW, HyD):

No adverse comment on the application.

#### 3. Environment

Comments of the Director of Environmental Protection (DEP):

- no objection to the application; and
- no environmental complaint concerning the Site received in the past three years.

#### 4. Drainage

Comments of the Chief Engineer/Mainland North, Drainage Services Department (CE/MN, DSD):

- no objection in principle to the application; and
- should the application be approved, conditions should be included to request the applicant to submit condition records of the existing drainage facilities of the Site and to maintain the existing drainage facilities properly as per the drainage proposal to ensure that it will not cause adverse drainage impact to the adjacent area.

#### 5. Fire Safety

Comments of the Director of Fire Services (D of FS):

No in-principle objection to the renewal application subject to the existing fire service installations implemented on the Site being maintained in efficient working order at all times.

#### 6. Water Supplies

Comments of the Chief Engineer/Construction, Water Supplies Department (CE/C, WSD):

No objection to the application.

#### 7. **Building Matters**

Comments of the Chief Building Surveyor/New Territories West, Buildings Department (CBS/NTW, BD):

- no in-principle objection to the application subject to the following condition:
- it is mentioned in the proposal that the existing footpath between two pieces of site (i.e. CS225 and CS226) will be retained. If it is the case and the footpath is remained as Government Land, the development intensity and site areas of the two pieces of site shall be separately considered. Otherwise, if the case of existing footpath is to be included in the site areas and required to be retained as part of any street under the Building (Planning) Regulation (B(P)R) 2, it may be deducted from the site area for the purpose of plot ratio and site coverage calculations under the B(P)R 23 (2) (a).

#### 8. Long Term Development

Comments of the Project Manager (West), Civil Engineering and Development Department (PM(W), CEDD):

No comment on the application.

#### 9. Landscape

Comments of the Chief Town Planner, Urban Design and Landscape Section, Planning Department (CTP/UD&L, PlanD);

No adverse comment on the application.

#### 10. District Officer's Comments

Comments of the District Officer (Tuen Mun), Home Affairs Department (DO(TM), HAD):

No comment from departmental point of view.

#### 11. Other Departments

The following departments have no comment on the application:

- Director of Electrical and Mechanical Services (DEMS);
- Director of Agriculture, Fisheries and Conservation (DAFC); and
- Commissioner of Police (C of P).

#### **Recommended Advisory Clauses**

- (a) to note the comments of the District Lands Officer/ Tuen Mun, Lands Department (DLO/TM, LandsD) that;
  - as noted from the planning statement of the current renewal application, there is no change in layout, use and development parameters as compared with the previous one, which conform with the tenancy agreement of the Site held under STT No. STTTM0012;
- (b) to note the comments of the Director of Environmental Protection (DEP) that:
  - (i) the project is subject to control by Water Pollution Control Ordinance (Cap. 358) and its Technical Memorandum. The applicant should make reference to the good practices stated in ProPECC PN 1/94 "Construction Site Drainage" and ProPECC PN 5/93 "Drainage Plan to be commented by the Environmental Protection Department" to minimize water quality impacts to its watercourse nearby; and
  - (ii) regarding the proposed adoption of chemical toilet and portable shower rooms for sewage and wastewater disposal on-site, adequate capacity of wastewater/sewage storage should be implemented. Besides, licensed sewage collector should be employed to regularly collect and dispose wastewater. The applicant should also regularly arrange wastewater collection on-site to minimise the nuisance and hygiene issues due to the wastewater generated in operation phase;
- (c) to note the comments of the Commissioner for Transport (C for T) that:
  - no queuing and / or waiting of motor vehicles from the application site (the Site) onto public roads would occur and no motor vehicles shall be permitted to reverse into and out of the Site onto adjacent public roads or Government Land;
- (d) to note the comments of the Chief Town Planner/Urban Design and Landscape, Planning Department (CTP/UD&L, PlanD) that:
  - the applicant should note that approval of the s.16 application by the Town Planning Board does not imply approval of tree works such as pruning, transplanting and/or felling under lease. The applicant is reminded to approach relevant authority/government department(s) direct to obtain necessary approval on tree works, where appropriate;
- (e) to note the comments of the Chief Building Surveyor/New Territories West, Buildings Department (CBS/NTW, BD) that:
  - (i) if the existing structures are erected on leased land without approval of the Buildings Department (BD) (not being a New Territories Exempted House), they are unauthorized under the Buildings Ordinance (BO) and should not be designated for any approved use under the captioned application;
  - (ii) before any new building works (including shelters, containers and structures as temporary buildings) are to be carried out on the application site (the Site), the prior approval and consent of the BD should be obtained, otherwise they are unauthorized building works (UBW). An Authorized Person (AP) should be

- appointed as the coordinator for the proposed building works in accordance with the BO;
- (iii) for UBW erected on leased land, enforcement action may be taken by the BD to effect their removal in accordance with BD's enforcement policy against UBW as and when necessary. The granting of any planning approval should not be construed as an acceptance of any existing building works or UBW on the Site under the BO;
- (iv) in connection with (ii) above, the Site shall be provided with means of obtaining access thereto from a street and emergency vehicular access in accordance with Regulations 5 and 41D of the Building (Planning) Regulations (B(P)R) respectively;
- (v) if the Site does not abut on a specified street of not less than 4.5m wide, its permitted development intensity shall be determined under Regulation 19(3) of the B(P)R at the building plan submission stage;
- (vi) sanitary fitment and BFA facilities shall be provided to the development; and
- (vii) detailed comments will be provided at the building plan submission stage;
- (f) to note the comments of the Chief Engineer/Construction, Water Supplies Department (CE/C, WSD) that:
  - (i) existing water mains will be affected. The cost of any necessary diversion shall be borne by the development;
  - (ii) in case it is not feasible to divert the affected water mains, a waterworks reserve within 1.5 metres from the centre line of the water main shall be provided to his office. No structure shall be built or materials stored within this waterworks reserve. Free access shall be made available at all times for staff of the Director of Water Supplies or their contractor to carry out construction, inspection, operation, maintenance and repair works;
  - (iii) no trees or shrubs with penetrating roots may be planted within the Waterworks Reserve or in the vicinity of the water main; and
  - (iv) Government shall not be liable to any damage whatsoever and however caused arising from burst or leakage of the public water mains within and in close vicinity of the Site.

☐ Urgent	☐ Return Receipt Requested ☐ Sign ☐ Encrypt ☐ Mark Subject Restricted ☐ Expand	d personal&publi
	A/TM-LTYY/456 Fuk Hang Tsuen Highway HK Inst Const 28/05/2023 03:15	
From: To: File Ref:	tpbpd <tpbpd@pland.gov.hk></tpbpd@pland.gov.hk>	
Dear TPB N	Members,	
•	sing to note that even The Construction Industry Council, a statutory ars to have failed to fulfill conditions. Seven Extensions of Time	
•	embers could question if it has finally decided to demonstrate its support vaunted lawful society we are told we now live in by ticking all the	
Mary Mulvih	nill	. •
Date: Thu Subject: I	<tpbpd@pland.gov.hk> irsday, 28 May 2020 3:36 AM CST Re: A/TM-LTYY/398 Fuk Hang Tsuen Highway HK Inst Const</tpbpd@pland.gov.hk>	
Dear TPB	Members,	
Regrettab public.	ly much information you are provided with is not shared with the general	
Responses to	comments of the Antiquities and Monuments Office.	
	are also issues of heritage involved that were not included in the original n of the plans.	
Hopefully	you will raise questions on this matter also.	
Mary Mulv	vihill	
Sent: Mor	d" <tpbpd@pland.gov.hk> nday, April 20, 2020 3:52:32 AM A/TM-LTYY/398 Fuk Hang Tsuen Highway HK Inst Const</tpbpd@pland.gov.hk>	

A/TM-LTYY/398

Government Land under Kong Sham Western Highway (next to Wong Kong Wai

Road near Fuk Hang Tsuen), Lam Tei, Tuen Mun Site area: About 10,300sq.m Government Land

Zoning: 'Road'

Applied use: Training Ground (Hong Kong Institute of Construction / 8 Vehicle

Parking (10)

Dear TPB Members,

While supporting the use of the vast quantities of land currently wasted under highways – West Kowloon is an appalling example – Application mentions intention to provide a rest garden. Can members please ask PlanD to provide details on the current population and the provision of OS and recreational in the district.

We now have a new breed of district councilors who take far greater interest in the provision of community facilities than their predecessors.

Mary Mulvihill

# 致城市規劃委員會秘書:

專人送遞或郵遞:香港北角渣華道 333 號北角政府合署 15 樓

傳真:2877 0245 或 2522 8426

電郵: tpbpd@pland.gov.hk

To: Secretary, Town Planning Board

By hand or post: 15/F, North Point Government Offices, 333 Java Road, North Point, Hong Kong

By Fax: 2877 0245 or 2522 8426 By e-mail: tpbpd@pland.gov.hk

有關的規劃申請編號 The application no. to which the comment relates

A/TM-LTYY/456

意見詳情 (如有需要,請另頁說明)

Details of the Comment (use separate sheet if necessary)

以不影響	附近居	民為大前	提下	同意申請。	<b>AL</b>
				25 AB	

「提意見人」姓名/名稱 Name of person/company making this comment 内的 第 7 18

簽署 Signature / 1993

日期 Date