2022年 4月 2 8日 .

此文件在 只个"全学所有必要的资料及文件很才正式確認收到

The Council is received on Z 8 APR 2022

The form Plorning Board will formally acknowledge the dree of receipt of the application only upon receipt of all the required information and documents.

Form No. S16-I 表格第 S16-I 號

APPLICATION FOR PERMISSION UNDER SECTION 16 OF THE TOWN PLANNING ORDINANCE (CAP.131)

根據《城市規劃條例》(第131章) 第16條遞交的許可申請

Applicable to proposals not involving or not only involving: 適用於建議不涉及或不祇涉及:

(i) Construction of "New Territories Exempted House(s)";興建「新界豁免管制屋宇」;

(ii) Temporary use/development of land and/or building not exceeding 3 years in rural areas; and 位於鄉郊地區土地上及/或建築物內進行為期不超過三年的臨時用途/發展;及

(iii) Renewal of permission for temporary use or development in rural areas 位於鄉郊地區的臨時用途或發展的許可續期

Applicant who would like to publish the <u>notice of application</u> in local newspapers to meet one of the Town Planning Board's requirements of taking reasonable steps to obtain consent of or give notification to the current land owner, please refer to the following link regarding publishing the notice in the designated newspapers: https://www.info.gov.hk/tpb/en/plan application/apply.html

申請人如欲在本地報章刊登申請通知,以採取城市規劃委員會就取得現行土地擁有人的同意或通知現行土地擁有人所指定的其中一項合理步驟,請瀏覽以下網址有關在指定的報章刊登通知: https://www.info.gov.hk/tpb/tc/plan_application/apply.html

General Note and Annotation for the Form 填寫表格的一般指引及註解

- "Current land owner" means any person whose name is registered in the Land Registry as that of an owner of the land to which the application relates, as at 6 weeks before the application is made 「現行土地擁有人」指在提出申請前六星期,其姓名或名稱已在土地註冊處註冊為該申請所關乎的土地的擁有人的人
- E Please attach documentary proof 請夾附證明文件
- ^ Please insert number where appropriate 請在適當地方註明編號

Please use separate sheets if the space provided is insufficient 如所提供的空間不足,請另頁說明

Please insert a 「レ」 at the appropriate box 請在適當的方格内上加上「レ」號

1, 14 2 (89)

				
For Official Use Only 請勿填寫此欄	Application No. 申請编號	A/YC-5[/618	,	
	Date Received 收到日期	2 8-APR 2022	· ·	•

- The completed form and supporting documents (if any) should be sent to the Secretary, Town Planning Board (the Board), ISIR, North Point Government Offices, 333 Java Road, North Point, Hong Kong.
 申請人須把填妥的申請表格及其他支持申請的文件(倘有),送交香港北角渣轉道 333 號北角政府合署 15 楼城市規制委員會(下稱「委員會」)秘書收。
- 3. This form can be downloaded from the Board's website, and obtained from the Secretariat of the Board and the Planning Enquiry Counters of the Planning Department. The form should be typed or completed in block letters. The processing of the application may be refused if the required information or the required copies are incomplete. 此表格可從委員會的網頁下載,亦可向委員會秘書處及規劃署的規劃資料查詢處索取。申請人須以打印方式或以正楷填寫表格。如果申請人所提交的資料或文件副本不齊全,委員會可拒絕處理有關申請。

I. Name of Applicant 申請人姓名/名稱

(□Mr. 先生 /□Mrs. 夫人 /□Miss 小姐 /□Ms. 女士 /回Company 公司 /□Organisation 機構)

CLP Power Hong Kong Limited

2. Name of Authorised Agent (if applicable) 獲授權代理人姓名/名稱(如適用)

(□Mr. 先生 /□Mrs. 夫人 /□Miss 小姐 /□Ms. 女士 /回Company 公司 /□Organisation 機構)

Kum Shing Engineering Company Limited

3.	Application Site 申請地點	· · · · · · · · · · · · · · · · · · ·
(a)	Full address / location / demarcation district and lot number (if applicable) 詳細地址/地點/丈量約份及地段號碼(如適用)	Government land in DD96 (Near DD96 Lot 1808 - 1813) Lok Ma Chau Tsuen, YL
(b)	Site area and/or gross floor area involved 涉及的地盤面積及/或總樓面面 積	☑Site area 地盤面積 42.5 sq.m 平方米☑About 约 □Gross floor area 總樓面面積 sq.m 平方米□About 約
(c)	Area of Government land included (if any) 所包括的政府土地面積(倘有)	

1							
(d)	Name and number of the statutory plan(s) 有關法定圖則的名称及編號	S/YL-ST/8					
(e)	Land use zone(s) involved 涉及的土地用途地帶	Conservation Area, Green Belt					
(f)	Current use(s) 現時用途	Local Track					
		(If there are any Government, institution or community facilities, please illustrate of plan and specify the use and gross floor area) (如有任何政府、機構或补區解析,諸在關則上顯示,並註明用途及總越而面積					
4.	"Current Land Owner	of Application Site 申請地點的「現行土地擁有人」					
The	applicant 申請人 -						
	is the sole "current land owne 是唯一的「現行土地擁有人	'& (please proceed to Part 6 and attach documentary proof of ownership). *** (諸继續填寫第 6 部分,並夾附業權證明文件)。					
	is not a "current land owner". 並不是「現行土地擁有人」"。						
M	The application site is entirely 申請地點完全位於政府土地	n Government land (please proceed to Part 6). (請继續填寫第6部分)。					
5.	Statement on Owner's	insept/Notification					
•		通知土地擁有人的陳述					
(a)	According to the record(s) of the Land Registry as at						
	根據土地註冊處藏至	··················· 在 ········					
	涉 名「現	土地擁有人」。					
(b)	The applicant 申請人 -						
		"current land owner(s)".					
	已取得	名「現行土地擁有人」"的同意。					
	Details of consent of "c	ent land owner(s)" obtained 取得「現行土地擁有人」"同意的詳情					
	No. of 'Current Land Owner(s)' 「田伝上神経古	mber/address of premises as shown in the record of the Land y where consent(s) has/have been obtained 地柱师處記錄已經得同案的地段錄碼/成所地址 取得同意的日期					
	, , , , , , , , , , , , , , , , , , ,	(日/月/年)					
,	(Please use separate sheets i	nc space of any box above is insufficient. 如上列任何方格的空間不足,請另頁說明)					
	•						

1 27 1

		De	tails of the "cu	rrent land owner(s)"	# notified	已疫通知「現行		的詳細資料
		La	o. of 'Current nd Owner(s)' 現行土地擁 人」數目	Lot number/addres Land Registry who 根據土地註冊處記	ere notificat	ion(s) has/have b	een given .	Date of notification given (DD/MM/YYYY) 通知日期(日/月/年)
	•		•				•	
					•	•	•	
				,	.,,,			
		(Plea	ise use separate si	heets if the space of ar	y box above	is insufficient. 如	上列任何方格的3	[] [] [] [] [] [] [] [] [] []
				e steps to obtain con 取得土地擁有人的				
		Reas	sonable Steps to	Obtain Consent of	Owner(s)	取得土地擁有人	的同意所採取	的合理步骤
			sent request fo	r consent to the "cu (日/月/年	· rrent land o)向每一名	wner(s)" on 「現行土地擁有	人」"郵遞要求	(DD/MM/YYYY) ^{II&} 引意奋 ^{&}
		Reas		Give Notification t				
			published noti	ces in local newspay (日/月/年	pers on)在指定報:	革 就中請刊登一	(DD/MM/Y) 次通知 ^{&}	YY) ^{&}
•				n a prominent posit		ear application sit	e/premises on	
			於	(日/月/年)在申請地	點/申請處所或	 们近的顧明位置	ILL I II 於該申請的通知
	•		office(s) or run	ral committee on (日/月/年		(DD/M	M/YYYY) ^{&}	committee(s)/managemer 委員會/互助委員會或管理
		<u>Oth</u>	ars 其他	•				
			others (please 其他(誵指明					
		-		• •		•	··· ·	
		-					·····	
		-	<u>.</u>		·			
•								,

6.	Type(s)	of Applicatio	n 申讃	類別				
	Type (i) 第(i)類		within exist	ting building or p	earl thereof			
Ø	Type (ii)				lling of land / filling of	pond as r	equired !	under Notes of Statutory
ļ.,	第(ii)類	rian(s) .			/ 这一/ 填 土/ 填土/ 填			
V	Type (iii) 第(iii)類	Public utility in 公用事業設施	istallation / 1 装置/私人的	Utility installatio 發展計創的公用詞	on for private project 設施裝置			
ο.	Type (iv) 第(iv)類	Minor relaxatio	on of stated o		triction(s) as provided	under No	otes of St	fatutory Plan(s)
i			nent other the	nan (i) to (iii) abov				
Note:	1: May insen : 可在多於- 2: For Develope	more than one「~ 一個方格內加上「	√」. 「✓」 ‰ mbarium use. nl	picase complete the to	able in the Appendix.			
Ø.	For Ivp	e (1) applicati	on 供第(類用語		36.50		
	Potal floo Involved 步及的總複面					sq.n	n 平方》	**************************************
								•
u	Proposed ise(s)/develop 疑賊用途/發展	ment 民	ine use and	gross Hoor area)	institution or community G設施・請在圖列上數7			· ustrate on plan and specify 總製面面移)
	Number of sto 步及層數	oreys involved			Number of units inv 涉及單位數目			The last star are to be
		-	Domestic _I	part 住用部分 .	(*104)***********************************	sq.m भ्	方米	□ About 約
	Proposed floor 民談樓面面程		Non-dome	stic part 非住用?	部分	sq.m 靬	² 方米	□About 約
_	·		Total 總計	• • • • • • • • • • • • • • • • • • • •	*1*************	sq.m SP	 ² 方米	□About 约
(e) P	roposed use	s of different	Floor(s) 被層	Current u	se(s) 現時用途	Pr	roposed	use(s) 擬餓用途
ብ ች	loors (if appli 下同极層的據	icable) 疑餓用途(如遜	.!					
(P sp	pace provided is	rate sheets (f. the insufficient)]不足・遊男真故						
朔		No.						

(ii) Koi Type (ii) applic	ation 供第(ii)類电話
	Diversion of stream 河道改道
	□ Filling of pond 填塘 Area of filling 填塘面積
(a) Operation involved 涉及工程	☑ Filling of land 填土 Area of filling 填土面積 42.5 sq.m 平方米 ☑About 約 Depth of filling 填土厚度 1.8 m米 □About 約
•	 ☑ Excavation of land 挖土 Area of excavation 挖土面積
	(Please indicate on site plan the boundary of concerned land/pond(s), and particulars of stream diversion, the extent of filling of land/pond(s) and/or excavation of land) (蔣門國則顯示有關土地/池坳界線,以及河道改道、填魁、填土及/或挖土的細節及/或範閱))
(b) Intended use/development 有意進行的用途/發展	Public utility installation (Pole & Pole Stay Erection) Filling and Excavation of land
(gib) Province (lib) apoliti	autons供用funi類用單位。
B 250.03F parameters and a second a second and a second a	☑ Public utility installation 公用事業設施裝置
	Utility installation for private project 私人發展計劃的公用設施裝置 Please specify the type and number of utility to be provided as well as the dimensions of each building/structure, where appropriate 諸註明有關裝置的性質及數量,包括每座建築物/構築物(倘有)的長度、高度和闊度
	Please specify the type and number of utility to be provided as well as the dimensions of
(a) Nature and scale 性質及規模	Please specify the type and number of utility to be provided as well as the dimensions of each building/structure, where appropriate 講註明有關裝置的性質及數量,包括每座建築物/構築物(倘有)的長度、高度和闊度 Number of provision
	Please specify the type and number of utility to be provided as well as the dimensions of each building/structure, where appropriate is is each building/structure, where appropriate is each building/structure, where appropriate is each building/structure (m) (by a building/st
	Please specify the type and number of utility to be provided as well as the dimensions of each building/structure, where appropriate is in the provision with the pr

(iv)	For Type (iv) application (第(iv)類申讀		
(B)	Please specify the proposed	minor relaxation of state	d development restriction(s) and	also fill in the
	proposed use/development a	<u>nd development particul</u>	ars in part (v) below	
	调为的对摊融哈局 从鬼的贺茂	限制 <u>亚琪妥於第(v)部分</u> 的	勺凝鐵用途/發展及發展細節 —	
	Plot ratio restriction 地秘比率限制	From 由	to 至	
	Gross floor area restriction 總被面面積限制	From 由sq. m	平方米 to 至sq. m 平方	*
	Site coverage restriction 上蓋面被限制	From 由	.% to 至%	
	Building helght restriction 建築物高度限制 -		m米 to 至m米	
		From 曲	mPD 米 (主水平基準上) to 至	•
	•	***********	mPD 米 (主水平基準上)	
		From 由	. storeys 層 to 至store	ys 暦
	Non-building area restriction 非建築用地限制		.m to 至m	
	Others (please specify) 其他(諧註明)	***********************************		
		<u> </u>	· · · · · · · · · · · · · · · · · · ·	
(i) <u>I</u>	Oi Type (v). application 供	第0)類用語。		
				<u>. 19</u> - 10 - 10 - 10 - 10 - 10 - 10 - 10 - 1
<i>(</i>) n				
	posed (s)/development 義用途/發展			٠
<u> </u>	(Please	illustrate the details of the propo	sal on a layout plan 請用平面區說明建議	詳情)
(b) <u>De</u> r	velopment Schedule 發展細節表			
	posed gross floor area (GFA) 擬	翰總樓面面積	sq.m 平方米	□About 約
	posed plot ratio 擬讓地稱比率		*******************	□About 約
	posed site coverage 擬議上蓋面和	· ·	%	□About 約
	posed no. of blocks 擬議座數		***************	l
Pro	posed no. of storeys of each block	:每座建築物的擬談層數	storeys 層	
~			☐ include 包括storeys of basem	
			□ exclude 不包括storeys of bas	ements 層地雕
Pro	posed building height of each blo	ck每座建築物的擬識高度	mPD 米(主水平基準上)□About約
:		·	m 米	□About約

Domestic par		· .	,	
GFA 總	桦面面積	•	sq. m 平方米	DAbout 約
number	of Units 單位數目		I > + + + + + + + + + + + + + + + + + +	
average	unit size 單位平均面	頹	sq. m 平方米	□A:bout 約
estimate	d number of resident	s估計住客数目	.****************************	•
☐ Non-domestic	c part 非住用部分		GFA 總模面面	徴
	iace 食肆	•	sq. m 平方米	· □About約
□ hotel 泗		•	·sq. m 平方米	□About約 .
· · · · · · · · · · · · · · · · · · ·	•		(please specify the number of rooms 請註明房間數目)	
□ office 辦	公 定		sq. m 平方米	□About 約
	l scrvices 商店及服	经行数	sq. m 平方米	□About 約
	, on 1,000 (50)E35011864	31 3 5K	,	, ,,
☐ Governm	nent, institution or co	mmunity facilities	(please specify the use(s) and	concerned land
政府、杭	股構或社區設施 .		area(s)/GFA(s) 說註明用途及有關的 機面面稅)	的地面面積/總
•			*******************************	
	•			

			•	
other(s)	其他		(please specify the use(s) and area(s)/GFA(s) 請註明用途及有關的 搜面面積)	
			.,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
* ^	•	•	,	

☐ Open space 衍	k憩用地 ·		(please specify land area(s) 讀註明:	也面面積)
	pen space 私人休憩	用地	sq. m 平方米 口 Not !	ess than 不少於
— ·	en space 公眾休憩		sq. m 平方米 口 Not l	
		pie) 各機屬的用途 (如		
		AND TO THE PROPERTY OF THE PARTY OF THE PART	[Proposed use(s)]	
[Block number]	[Floor(s)]		[擬織用途]	·
[座數]	[屠数]		[环底积 713 2至]	
!! ***********				
*************	4,01,010,010,014,011,0			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
*************	************	********************		
	41.41.41.41.41.41.41.41	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	, ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	********
.,,	1444441111111111111	****************		
(d) Proposed use(s)	of uncovered area (i	fany) 驚天地方(倘存		
(a) 1.0pooda doo(b)				
		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		******
****************	Perlandandandan () - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 -	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
***************************************	P-1944 534 140 54 141 444 44	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,		
	444444444444		,,.,.	
,				

7. Anticipated Completion Time of the Development Proposal 擬議發展計劃的預計完成時間							
Anticipated completion time (in month and year) of the development proposal (by phase (if any)) (e.g. June 2023) 接鐵發展計劃預期完成的年份及月份 (分期 (倘有)) (例: 2023 年 6 月) (Separate anticipated completion times (in month and year) should be provided for the proposed public open space and Government, institution or community facilities (if any)) (申請人須就接職的公眾休憩用地及政府、機構或社區設施(倘有)提供個別擬緻完成的年份及月份)							
Target Complete Date	: Befor	e Sep 2022 (About 3 weeks)					
III							
*******************************	**********	***************************************					
8. Vehicular Access Arr 擬識發展計劃的行	angemer 車通道	of the Development Proposal 安排					
Any vehicular access to the site/subject building? 是否有草路通往地盤/有關 建築物?	Yes是	 ✓ There is an existing access. (please indicate the street name, where appropriate) 有一條現有車路。(講註明車路名稱(如適用)) Lok Ma Chau Road via local road □ There is a proposed access. (please illustrate on plan and specify the width) 有一條擬議車路。(講在圖則顯示,並註明車路的閱度) 					
	No 否	<u> </u>					
Any provision of parking space for the proposed use(s)? 是否有為擬談用途提供停車位?	Yes是	□ (Please specify type(s) and number(s) and illustrate on plan)					
	№否	<u> </u>					
Any provision of loading/unloading space for the proposed use(s)? 是否有為擬議用途提供上落客 貨車位?	Yes 是 _,	□ (Please specify type(s) and number(s) and illustrate on plan) 請註明租類及數目並於圖則上顯示) Taxi Spaces 的士車位 Coach Spaces 旅遊巴車位 Light Goods Vehicle Spaces 輕型货車車位 Medium Goods Vehicle Spaces 中型貨車車位 Heavy Goods Vehicle Spaces 重型货車車位 Others (Please Specify) 其他 (請列明)					
	№ 否	<u> </u>					

9. Impacts of De	evelopme	ent Proposal 擬議發展計劃的影響
justifications/reasons for	or not prov	sheets to indicate the proposed measures to minimise possible adverse impacts or give iding such measures. 最減少可能出現不良影響的措施,否則請提供理緣/理由。
	Yes 是	□ Please provide details 請提供詳情
Does the development proposal involve		
alteration of existing		101.101.111.111.111.1111.1111.1111.1111.1111.1111
building?		,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,
操機發展計劃是否包括現有建築物的		
改動?) },,, ****	
	No 否 Yes 是	[V] [Please indicate on site plan the boundary of concerned land/pond(s), and particulars of stream diversion,
i '	ISE	the extent of filling of land/pond(s) and/or excavation of land)
Does the development		(請用地盤平面圈廣示有關土地/池樂界線,以及河追改道、填塊、填出及/或控土的細節及/或範
proposal involve the	1	(湖)
operation on the		□ Diversion of stream 河道改道
right? 擬蔽發展是否涉及		□ Filling of pond 缜塘
右列的工程?		Area of filling 填塘面積sq,m 平方米 口About 約
(Note: where Type (ii) application is the		Depth of filling 填塘深度 m 米 □About 約
subject of application,		☐ Filling of land 填土
please skip this		Area of filling 填土面积sq:m 平方米 □About 约
section. 註:如申請涉及第		Depth of filling 填土厚度 in 米 □About 约
(ii)類申請,謝跳至下		□ Excavation of land 接士
一條問題。)		Area of excavation 挖土面積sq.m 平方米 口About 约
,		Depth of excavation 挖土深度
·	No否	
		onment 對環境 Yes 會 No 不會 日 s 對交通 Yes 會 No 不會 日
	On traffic	っ 對交通 Yes 會 □ No 不會 □ supply 對供水 Yes 會 □ No 不會 □
	On drains	age 對排水 Yes 會 No 不會 日
		s 對斜坡 Yes 會 □ No 不會 回 by slones 受斜坡影響 Yes 會 □ No 不會 回
,		by slopes 受斜坡影響 Yes 會 □ No 不會 □ □ be Impact 構成景観影響 Yes 會 □ No 不會 □
	Tree Fell	ing 砍伐樹木 Yes 會 🗌 No 不會 🗐
·	Visual In	npact 構成視燈影響 Yes 會 □ No 不會 □ Please Specify) 其他 (請列明) Yes 會 □ No 不會 □
Would the	Others (r	rease aposity) 条(图 (图7世列)
development	*	· ·
proposal cause any adverse impacts?	Please st	ate measure(s) to minimise the impact(s). For tree felling, please state the number,
擬議發展計劃會否	diameter	at breast height and species of the affected trees (if possible)
造成不良影響?		建減少影響的措施 。如涉及砍伐樹木,謂說明受影響樹木的數目、及胸高度的樹幹
	且徑 及占	· 插(倘可)
		•
,		

10. Justifications 理由						
The applicant is invited to provide justifications in support of the application. Use separate sheets if necessary. 現語申討人提供申請理由及支持其申銷的資料。如有需要,前另頁說明。						
CLP received a new application for electricity supply.						

111212244114114114141414141414141414141						
, the second						

',		Form No. S16-I 麦格第 S16-1 號
11. Declaration 聲明	4.	
I hereby declare that the particulars giv本人誕此聲明,本人就追宗申請提到	ren in this application are correct and t 医的資料,據本人所知及所信,均屬	rue to the best of my knowledge and belief. 真質無誤。
I hereby grant a permission to the Boar to the Board's website for browsing an 黃會酌情將本人就此申請所提交的戶	I downloading by the public free-of-c	this application and/or to upload such materials harge at the Board's discretion. 本人現准許委 5,供公眾免費瀏覽或下載。
Signature 簽署	☐ Applicant	申請人 / M Authorised Agent 獲授權代理人
· Au Hin V	Vah Se	nior Project Engineer
Name in Blo 姓名(讃以江		Position (if applicable) 職位 (如適用)
專業資格 □ □ □ RP	HKIS 香港測量節學會 / □ HK	IA 香港建築師學會 / IE 香港工程師學會 / IUD 香港城市設計學會
10.00	Engineering Co. Ltd.	33.
☑ Company 公司 / □	Organisation Name and Chop (if app	licable)被稱名稱及蓋諱(如適用)
Date 日期 12/04/2022	(DD/MM/Y	(YY 日/月/年)
	Remark 備註	
materials would also be uploaded to the considers appropriate.	e Board's website for browsing and fi 申請資料和委員會對申請所作的決	plication would be disclosed to the public. Such ee downloading by the public where the Board 定。在委員會認為合適的假況下,有關申請
•	Warning 警告	<u></u>
Any person who knowingly or wilfully which is false in any material particular	makes any statement or furnish any i , shall be liable to an offence under th	nformation in connection with this application, e Crimes Ordinance.

任何人在明知或故意的情况下,就這宗申請提出在任何要項上是虛假的陳述或資料,即屬違反《刑事罪行條例》

Statement on Personal Data 個人資料的聲明

- The personal data submitted to the Board in this application will be used by the Secretary of the Board and Government departments for the following purposes: 委員會就這宗申請所收到的個人資料會交給委員會秘書及政府部門,以根據《城市規劃條例》及相關的城市規劃委員會規劃指引的規定作以下用途:
 - (a) the processing of this application which includes making available the name of the applicant for public inspection when making available this application for public inspection; and
 - facilitating communication between the applicant and the Secretary of the Board/Government departments. 方便申請人與委員會秘書及政府部門之間進行聯絡。
- 2. The personal data provided by the applicant in this application may also be disclosed to other persons for the purposes mentioned in paragraph I above. 申鶕人就這宗申鶕提供的個人資料,或亦會向其他人士披露,以作上述第1段提及的用途。
- 3. An applicant has a right of access and correction with respect to his/her personal data as provided under the Personal Data (Privacy) Ordinance (Cap. 486). Request for personal data access and correction should be addressed to the Secretary of the Board at 15/F, North Point Government Offices, 333 Java Road, North Point, Hong Kong. 根據《個人資料(私)(級)條例》(第 486 章)的規定,申請人有權查閱及更正其個人資料。如欲查閱及更正個人資料 您向委員會秘書提出有關要求,其地址為香港北角渣鞋道 333 號北角政府合署 15 樓。

For Developments involving Columbarium Use, please also complete the 如發展涉及靈灰安置所用途,請另外填妥以下資料:	following:
Ash interment capacity 骨灰安放容量®	
Maximum number of sets of ashes that may be interred in the niches 在爺位內最多可安放母灰的數量 Maximum number of sets of ashes that may be interred other than in niches 在非爺位的範國內最多可安放母灰的數盘	
Total number of niches 實位總数	
Total number of single niches 單人爺位總數	
Number of single niches (sold and occupied) 單人龕位數目 (已售並佔用) Number of single niches (sold but unoccupied) 單人龕位數目 (已售但未佔用) Number of single niches (residual for sale) 單人龕位數目 (待售)	
Total number of double niches 雙人愈位總數	
Number of double niches (sold and fully occupied) 雙人確位數目(已售並全部佔用) Number of double niches (sold and partially occupied) 雙人爺位數目(已售並部分佔用) Number of double niches (sold but unoccupied) 雙人爺位數目(已售但未佔用) Number of double niches (residual for sale) 雙人爺位數目(符售)	
Total no. of niches other than single or double niches (please specify type) 除單人及雙人耷位外的其他畬位總數 (請列明頻別)	
Number. of niches (sold and fully occupied) 充位数目 (已售並全部佔用) Number of niches (sold and partially occupied) 充位数目 (已售並部分佔用) Number of niches (sold but unoccupied) 充位数目 (已售但未佔用) Number of niches (residual for sale)	
和位数目 (特售)	· · ·
Proposed operating hours 擬緻蒼運時間	
 Ash interment capacity in relation to a columbarium means – 款茲灰安亞所而言。骨灰安放容量指: the maximum number of containers of ashes that may be interred in each niche in the columbarium; 每個商位內可受放的骨灰容器的最高數目: the maximum number of sets of ashes that may be interred other than in niches in any area in the columbarium 在該暨灰安亞所並非愈位的範圍內,總共派多可安放多少份骨灰;以及 the total number of sets of ashes that may be interred in the columbarium. 在該骨灰安亞所內,總共戰多可安放多少份骨灰。 	nbarium; and

Gist of Application 申請摘要					
(Please provide details in both English and Chinese as far as possible. This part will be circulated to relevant consultees, uploaded to the Town Planning Board's Website for browsing and free downloading by the public and available at the Planning Enquiry Counters of the Planning Department for general information.) (調整量以英文及中文填寫。此部分將會發送予相關諮詢人士、上戰至城市規劃委員會網頁供公眾免費瀏覽及下戰及於規劃署規劃資料查詢處供一般參閱。) Application No. (For Official Use Only) (請勿填寫此欄)					
Application No. 申請編號	(,	
Location/address 位置/地址	Go	Government land in DD96			
, , , , , , , , , , , , , , , , , , ,	(Near DD96 Lot 1808 - 1813)				
	Lok Ma Chau Tsuen, YL				
Site area 地盤面積		42.5		sq. m 平力	了米 🗹 About 約
中心然在1917 有	(includ		of包括政府土地 42.5	sq. m 平力	7米 ☑About 約)
Plan 圖則 ·	S/Y	L-ST/8			
Zoning 地帶	Conservation Area, Green Belt				
Applied use/ development 申請用途/發展	elopment 1. Public utility installation (Pole & Pole Stay Electron			tay Erection)	
.			•		
i) Gross floor are and/or plot rati			sq.m 平方米		Ratio 地積比率
總模面面積及 地積比率	/或	Domestic 住用	□ About □ Not mor 不多於		□About 約 □Not more than 不多於
·		Non-domestic 非住用	□ About (□ Not mor 不多於		□About 約 □Not more than 不多於
ii) No. of block 憶數		Domestic 住用	,	•	
		Non-domestic 非住用			
•		Composite 綜合用途			

(iii)	Building height/No.	Domestic	
	of storeys 建築物高度/層數	住用	m 米 口 (Not more than 不多於)
			mPD 米(主水平基準上) 口 (Not more than 不多於)
			Storeys(s) 屬 □ (Not more than 不多於)
			(□Include 包括(□ Exclude 不包括 □ Carport 停車間 □ Basement 地庫 □ Refuge Floor 防火層 □ Podium 平台)
		Non-domestic 非住用	m 米□ (Not more than 不多於)
		·	mPD 米(主水平基準上)□ (Not more than 不多於)
			Storeys(s) 層 □ (Not more than 不多於)
			(□Include 包括/□ Exclude 不包括 □ Carport 停車間 □ Basement 地庫 □ Refuge Floor 防火層 □ Podium 平台)
		Composite 綜合用途	m 米□ (Not more than 不多於)
			mPD 米(主水平基準上) □ (Not more than 不多於)
	;		Storeys(s) 層 (Not more than 不多於)
-			(□Include 包括/□ Exclude 不包括 □ Carport 停車間 □ Basement 地庫 □ Refuge Floor 防火層 □ Podium 平台)
(iv)	Site coverage 上蓋面穫		% □ About 約
(v)	No. of units 單位數目		
(vi)	Open space 休憩用地	Private 私人	sq.m 平方米 口 Not less than 不少於
	;	Public 公眾	sq.m 平方米 口 Not less than 不少於

(vii) No. of parking spaces and loading / unloading spaces 停車位及上落客貨 車位數目	Total no. of vehicle parking spaces 停車位總數 Private Car Parking Spaces 私家車車位 Motorcycle Parking Spaces 電單車車位 Light Goods Vehicle Parking Spaces 輕型貨車泊車位 Medium Goods Vehicle Parking Spaces 中型貨車泊車位 Heavy Goods Vehicle Parking Spaces 重型貨車泊車位 Others (Please Specify) 其他(講列明)	
	Total no. of vehicle loading/unloading bays/lay-bys 上落客貨車位/停車處總數 Taxi Spaces 的士車位 Coach Spaces 旅遊巴車位 Light Goods Vehicle Spaces 輕型貨車車位 Medium Goods Vehicle Spaces 中型貨車位 Heavy Goods Vehicle Spaces 重型貨車位 Others (Please Specify) 其他 (講列明)	

	<u>Chinese</u>	English
tuned best bound J. A. Draft	中文	英文
Plans and Drawings 圖則及繪圖	_	_
Master layout plan(s)/Layout plan(s) 總綱發展藍圖/布局設計圖	Ä	<u></u>
Block plan(s) 楔字位置圖	<u>.</u>	
Floor plan(s) 模字平面圖	□	
Sectional plan(s) 截視圖		ſΆ
Elevation(s) 立視圈	. □	
Photomontage(s) showing the proposed development 顯示擬議發展的合成照片		
Master landscape plan(s)/Landscape plan(s) 國境設計總圖/國境設計圖		
Others (please specify). 其他(請註明)		☑′
Location plan, Vehicular road access plan		
,		
Reports 報告書		
Planning Statement/Justifications 規劃綱領/理據		
Environmental assessment (noise, air and/or water pollutions)		
環境評估(噪音、空氣及/或水的污染)		
Traffic impact assessment (on vehicles) 就車輛的交通影響評估		
Traffic impact assessment (on pedestrians) 就行人的交通影響評估		
Visual impact assessment 視覺影響評估		
Landscape impact assessment 景觀影響評估		
Tree Survey 樹木調查		
Geotechnical impact assessment 土力影響評估		
Drainage impact assessment 排水影響評估		
Sewerage impact assessment 排污影響評估		
Risk Assessment 風險評估		
Others (please specify) 其他(講註明)		. 🗆
And the state of t	•	


Note: The information in the Gist of Application above is provided by the applicant for easy reference of the general public. Under no circumstances will the Town Planning Board accept any liabilities for the use of the information nor any inaccuracies or discrepancies of the information provided. In case of doubt, reference should always be made to the submission of the applicant.


註: 上述申銷摘要的資料是由申請人提供以方便市民大眾參考。對於所能資料在使用上的問題及文裁上的歧異,被市規創委員


會概不負責·若有任何疑問·應查閱申請人提交的文件·


此為空白頁。

This is a blank page.









- 1,防盜。
- 2,抽排放雨水。
- 3、安裝太陽能發电。
- 4 · 農耕用途。
- 5、照明。


簽名:




4/5/2022

TOWN PLANTING BOARD

10 July 100 July 1533





Appendix Ia of RNTPC
Paper No. A/YL-ST/618B

Remarks

Superseded by the revised GPRR in Encl. (b) at **Appendix Ib**

Kum Shing Engineering Co. Ltd.

17 August 2022

Town Planning Board
15/F., North Point Government Offices
333 Java Road, North Point,
Hong Kong

Attn.: CHAN Cheuk Lee, Cherry

Dear Sir/Madam,

Proposed Public Utility Installation (Pole and Pole Stay Erection) and associated Filling and Excavation of Land in "Conservation Area" and "Green Belt" Zones, Government Land in D.D.96, San Tin, Yuen Long

I refer to the committee meeting dated 15.6.2022.

The attachment are 4 hard copies of further representation, geotechnical planning review report for installation of proposed public utility installation and associated filling and excavation of land; for paper no. A/YL-ST/618.

Should you require further information on the above, please feel free to contact the undersigned Mr. Au Hin Wah at

Yours faithfully

(Cathy CHENG)

Assistant Engineer, Kum Shing Eng.

1011 AUG 18 A 10:54

Appendix Ib of RNTPC Paper No. A/YL-ST/618B

Town Planning Board Secretariat

15/F, North Point Government Offices 333 Java Road, North Point, Hong Kong, RECEIVED

2077, DEC 14 P 3: 19

TOWN PLANNING BOARD

<u>PlanD Planning Application No. A/YL-ST/618 Further Information</u>
I'm writing to provide the FI the planning application No. A/YL/618 to address the following items:

- i) Comments from H(GEO), CEDD dated on 21.9.2022 in the latest GPRR;
- ii) Comments from EPD dated on 30.5.2022;
- iii) Purpose for electricity supply;

Thank you for your kind assistance.

Yours Faithfully,



Ivan Au 14/Dec/2022

Encls:

- a. Comments from EPD dated on 30.5.2022;
- b. A full revised GPRR;
- c. Purpose for electricity supply;
- d.20221007 (FHK to PlanD) RtC B190011.05;
- e.20221007 (FHK to PlanD) RtC B190011.051 (Fig and Appendices

Encl. (a)

- (i) Departmental Comments (EPD) for s.16 Planning Application A/YL-ST/618
- i. The mitigation measures to be implemented during construction phase to handle non-point source and point source pollution, such as runoff and sewage from construction site workers, etc.
- Debris and rubbish generated on-site will be collected, handled and disposed of properly to avoid entering the nearby stormwater drains and open drainage channels. The refuse collection point will be properly constructed with covers and will be bunded and drained to the CLP sewerage system.
- Open storm water drains and culverts near the works area will be covered to block the entrance of large debris and refuse.
- 3. Oil leakage or spillage will be contained and cleaned up immediately. Waste oil should be collected and stored for recycling or disposal, in accordance with the Waste Disposal Ordinance. The Contractors will prepare guidelines and procedures for immediate clean-up actions following any spillages of oil, fuel or chemicals.
- ii. Please state the compliance with relevant regulations, best practices and guidelines, such as WPCO, ProPECC PN 1/94 "Construction Site Drainage", etc.;
- In order to minimize the impacts of wastewater/ runoff generated on site to the nearby WSRs, mitigation measures and good site practices will be adopted during the construction site and operation phases of the Project based on the ProPECC PN 1/94 and WPCO.
- Please confirm if the works area would be reinstated and there would not be any discharge during operation phase.
- 1. We are ensure the works area would be reinstated and there would bot be any discharge during operation phase.

TOTAL P.003

4-DEC-2022 15.02

1 050 0500 0400

Encl. (b) (revised GPRR full Report)



Geotechnical Planning Review Report for Installation of Proposed Public Utility Installation and Associated Filling and Excavation of Land (OHL Pole & Stay Erection)

Geotechnical Planning Review | Government Land in D.D. 96, San Tin, Yuen Long

B190011.051.01 | 8 August 2022

BD Ref.: N/A

CLP Power Hong Kong Limited

Executive Summary

This geotechnical planning review report is prepared on behalf of the Applicant, CLP Power Hong Kong Limited, to seek approval from the Town Planning Board under Section 16 of the Town Planning Ordinance for installation of 5 electricity poles with 10 pole stays for low voltage overhead line cable.

The proposed public utilities installation includes erection of 5 electricity poles and 10 pole stays for low voltage overhead line cable. To facilitate the foundation construction for OHL pole and pole stays, pit excavation of 1.8m deep is required.

After completion of the foundation, the OHL poles and pole stay are to be erected, pits will be backfilled and the ground will be reinstated to its original situation.

Based on available geotechnical information, the effect of proposed utility installation works including pit excavation and the erection of OHL poles, that may affect or be affected by natural terrain or manmade slopes, is addressed in this report. In view of failure of the man-made slopes would affect the OHL poles at the slope toe, stability analysis is proposed to be carried out. The proposed development would not comprise any critical facilities (i.e. facilities under Group 1-3 in Table 2.2 of GEO Report No. 138), hence a Natural Terrain Hazard Study is **not** necessary.

The geotechnical assessment concludes that the proposed utility installation works including pit excavation and the erection of OHL poles are geotechnically feasible.

Contents

Executive Summary		2
Contents		
1.	Introduction	5
1.1	Background	5
1.2	Description of the Works	5
1.3	The Report	6
1.4	Client	6
1.5	Geotechnical Engineer	6
2.	Description of Site Conditions	7
2.1	Site Topography	7
2.2	The Proposed Development	9
3.	Desk Study	9
3.1	Topography	9
3.2	Geology	9
3.3	Hydrology	9
3.4	Man-made Slopes	9
3.5	Available Ground Investigation	10
4.	Geotechnical Assessment	11
4.1	Man-made Slopes	11
4.2	Natural Terrain Hazard	11
4.3	Excavation Works	12
5.	Recommendation	13
6.	References	14

Tables

- 1 Summary of Registered Man-made Slopes
- 2 Summary of Previous Ground Investigations

Figures

Figure 1

Location plan

Figure 2

Site plan For Proposed Cable Circuits

Figure 3

Geological Map

Appendices

Appendix A

Table 2.2 of GEO Report No. 138

Assessment of Natural Terrain Hazard

Natural Terrain Plan

Sections

Inventory Plan

Natural Terrain Landslide Inventory Plan

Boulder Inventory

Features and Sections

Feature Layout Plan

Sections

Appendix B

Slope Location Plan

General View of Registered Man-made Slopes

Basic Data of Slope downloaded from SIS

Slope Maintenance Responsibility Report Downloaded from SMRIS

Appendix C

Location Plan of Existing Boreholes

Summary of Measured Groundwater level Existing Ground Investigation Records

Appendix D

Drg. No. 01 – A and 01 G A Detail of Pole and Pole Stay

Photo Illustration for the Pole and Pole Stay

Introduction

1.1 Background

Fugro (Hong Kong) Limited was appointed by CLP Power Hong Kong Limited as the Engineering Consultant for the preparation of a Geotechnical Planning Review Report for proposed public utilities installation of 5 electricity poles and 10 pole stays for low voltage overhead line cable as shown in Figure 1 – Site Location Plan and Figure 2 – Site Plan.

The proposed public utilities installation includes erection of 5 electricity poles and 10 pole stays for low voltage overhead line cable. To facilitate the foundation construction for OHL pole and pole stays, pit excavation of 1.8m deep is required.

After completion of the foundation, the OHL poles and pole stays are to be erected, pits will be backfilled and the ground will be reinstated to its original situation.

Based on available geotechnical information, the proposed utility installation works including pit excavation and the erection of OHL poles that may affect or be affected by natural terrain or man-made slopes is addressed in this report and geotechnical feasibility of proposed utility installation works is also recommended.

1.2 Description of the Works

There are 5 groups of pole and pole stay (one group consists of one pole and two pole stay) in the application, which are illustrated on the photo in Appendix D.

The height of the proposed pole and pole stay (including the above ground portion) with illustration on drawings (Drg. No. 01 - A and 01 G A) and photos in.

The proposed works with supporting drawings and photo illustrations (in Appendix D) as follows:

According to the applicant, the proposed installation is for providing electricity to support the agricultural use at Lot 1808 in D.D. 96 (Plan A-2). The proposal involves erection of five poles of dimension 2m (L) x 2m (W) x 10m (H)) and ten pole stays of dimension 1.5m (L) x 1.5m (W) x 5m (H) for low voltage overhead line (OHL) cable with associated excavation of about 42.5 m2 (1.5m to 2m in length and width) and about 1.8m in depth. Each group of the installation set involves one pole stand which will be supported by two pole stays (Drg. No. 01 – A and 01 G A) and photo in Appendix D. Upon erection of the OHL poles and pole stays, the pits will be backfilled and the ground will be reinstated to its original situation. All the pole stay wire are located at the outer side of the road such that no pedestrian or traffic will be obstructed after completion of the installation. The location plan is shown in Figures 1 and 2 and the sections are shown

in Appendix A and the vehicular access plan is Figures 1 and 2. The installation works will be carried out only from 8 am to 5 pm.

The location and disposition of the Site for erection of the OHL will minimise the filling and excavation of land and slope maintenance required for the proposed works and avoid encroachment onto private land. The proposed works will not cause adverse impacts on geotechnical safety, traffic, landscape, environment, sewerage, drainage and water supply. The applicant shall minimise the disturbance to the nearby vegetation during the land excavation/filling works.

The existing local road will not be obstructed. All vehicles are allowed to use the existing roads during construction period.

1.3 The Report

This Geotechnical Planning Review Report is prepared in support of a Section 16 planning application (Application No. A/YL-ST/618).

1.4 Client

CLP Power Hong Kong Limited

1.5 Geotechnical Engineer

Fugro (Hong Kong) Limited


2. Description of Site Conditions

2.1 Site Topography


The site is situated northeast of San Tin in the North West New Territories. The site is along a road with low vehicular traffic density. Beyond the road to the northwest are numerous estuaric ponds and then Shenzhen River.

The natural hillside (see Figure 1) above the proposed site is located at the southeast, which is elevated from the man-made slopes 2SE-B/C296 and 2SE-B/C305 (+11mPD) along the site towards the southeast direction (+49mPD max).

For the proposed public utility installation, 5 OHL poles with approximate height of 10m will be installed in the specified areas along a local road. General views along with the photo plan of the application site are shown in the Plates below. The road gradients is quite gentle and all poles are located at +6.0 mPD to +8.0 mPD approximately.




JGRO



Location refers to figure 2

P1: General View 1 of the Site with Approximate Location of a Pole & Pole Stays (looking Southwest)



Location refers to figure 2

P2: General View 2 of the Site with Approximate Location of a Pole & Pole Stays (looking Northeast)

2.2 The Proposed Development

The proposed public utilities installation includes erection of 5 electricity poles and 10 pole stays for low voltage overhead line cable. To facilitate the foundation construction for OHL pole and pole stays, pit excavation of 1.8m deep is required.

After completion of the foundation, the OHL poles and pole stay are to be erected, pits will be backfilled and the ground will be reinstated to its original situation.

3. Desk Study

3.1 Topography

The 1:1000 topographical survey maps of the Site and the area of the adjacent natural terrains obtained from the Lands Department are used as the base map for this geotechnical assessment. With reference to the topographical survey maps, sections showing man-made slopes and hillsides of natural terrain are prepared and presented in Appendix A.

3.2 Geology

Sheet 2 of the Hong Kong Geology Survey 1:20,000 scale map series HGM20 (Geological Map is shown in Figure 3) indicates that the site is underlain by superficial deposit, which is Qd – unsorted sand, gravel, cobbles and boulders; Clay/Silt matrix (Debris Flow Deposits). Underlying the superficial deposits are different compositions of rocks including metasiltstone with metasandstone, granite and quartzite.

3.3 Hydrology

The site is surrounded with ponds, which affect the groundwater levels under the existing flatland.

Based on the available groundwater monitoring records (summarized in Appendix C), groundwater levels are at 0.25 m to 1.5 m below the existing ground, which match with the water levels of adjacent rivers and ponds.

3.4 Man-made Slopes

There are 2 registered man-made slopes within the site area affecting / being affected by the proposed installation works. Features locations are shown in Appendix A. These slope characteristics are summarised in Table 1 and their locations are indicated on the plan in Appendix B. Details of the man-made slopes downloaded from the Slope Information

System along with SMRIS information are presented in same Appendix. Both man-made slopes are cut slopes with 6m in height at 45° slope angle. Both cut slopes are located at the southwest of the site. The general views of the slopes are also shown in Appendix B.

Table 1_ Summary of Registered Man-made Slopes

Feature No.	Slope height (m)	Slope Angle (degree)	Upgrading works	Site formation works	Drawings / record plans	Related GI borehole	Responsible Party
2SE-B/C296	6	45	-	post- 1977	*	NIL	Lands Department
2SE-B/C305	6	45	æ	post- 1977	=:	SBF/DH10	Lands Department

3.5 Available Ground Investigation

Lok Ma Chau area was previously used for fishery activities, with water channels, oyster beds and fish ponds. Based on the available ground investigation information and as summarized in Table 2, the superficial deposits mainly comprise fill (1 to 2m thick), pond deposits / alluvium (1 to 7m thick). The in-situ soil / rock of meta-siltstone / granite/ quartzite is encountered at 1m to 9m below the existing ground level. Geotechnical Sections are shown in Appendix A.

A plan showing the locations of previous ground investigation works carried out in the vicinity of the site area is presented in Appendix C. The relevant GI records are enclosed in same Appendix and summarized in Table 2.

Table 2_Summary of Previous Ground Investigations

Borehole	Ground Level (mPD)	Total Depth (m)	Thickness (m)					H.G.W.L	L.G.W.L	Related
			Fill	Pond Deposit	Alluvium	Grade V/IV	Grade III or above		ow ground vel	Slope/ Section
LMCT- BH1	3.95	10	2	1.1	2.5	4.4	-	1.11	1.27	=
LMCT- BH2	3.98	49.05	1.5	2	3.1	28.37	14.08	0.25	0.48	= :
SBF/DH10	6.74	3.03	0.8	-	-	12	2.23	-	-	Section 4-4
SBF/DH11	4.86	14.15	2	-	7	5.15	-	-	-	Section 6-6
SBF/TP40	6.44	2	1.65	=	-	0.35	:=	=	-	=:
BH-5	53.19	45.10	÷	-		22.40	22.70	Ħ	=	

Geotechnical Assessment

4.1 Man-made Slopes

There are 2 registered man-made slopes in the vicinity affecting / being affected by the proposed utility installation. Features locations are shown in Appendix A. It can be inferred that 2 registered slopes, which maintenance responsible party is Lands Department, are the cut slopes formed during the previous road construction works. Slope information shown in Appendix B and slope characteristic is summarized in Table 1.

The proposed poles will be installed along the existing road at the toe of the cut slopes by pit excavation method. After pit excavation and installation of poles and pole stays, the excavation will be reinstated to its original situation, Hence, the construction effect of the proposed utility installation on the cut slopes is insignificant.

These 2 registered man-made slopes are cut slopes with 6m in height at 45° slope angle. In view of failure of the man-made slopes would affect the OHL ploes at the slope toe, stability analysis is proposed to be carried out.

4.2 Natural Terrain Hazard


A natural hillside (shown in Appendix A) near proposed poles location is located to the southeast. The hillside is elevated from the man-made slopes 2SE-B/C296 and 2SE-B/C305 (+11mPD) along the site towards the southeast direction (+49mPD max). Sections 1, 2 & 3 (in the same Appendix) shows that the proposed pole locations are within the angular elevation of 20° and thus the locations of proposed poles likely meet alert criteria of natural terrain hazard. However, the proposed development would not comprise any critical facilities (i.e. facilities under Group 1-3 in Table 2.2 of GEO Report No. 138) (refer to the table below), a Natural Terrain Hazard Study is not necessary. Table 2.2 of GEO Report No. 138 is attached in Appendix A.

Group No.	Table 2.2 GEO Report No. 138	The proposed development	Conclusion
1(a) 2(a)	Buildings	The proposed development comprise the erection of poles	The proposed development does not compirse the critical facilities in Group No. 1(a) and 2(a).
1(b) 2(b) 3	Road with heavy / moderate traffic density	Along the toe of the proposed poles is "road with low traffic density"	The proposed development does not compirse the critical facilities in Group No. 1(b), 2(b) and 3.

Based on the ENTLI Inventory Plan and Boulder Inventory Plan (shown in Appendix A) extracted from GIU of GEO, there are no records of landslides and boulders within the natural terrain area above the proposed pole locations.

4.3 Excavation Works

The foundation of the proposed OHL poles and pole stays will be constructed by pit excavation method. The pit will be 1.5m to 2m wide and 1.8m deep approximately. It is proposed that the pit will be supported by planking and struts as shown in the figure below.



B190011.051.01 | Geotechnical Planning Review Report for Installation of Proposed Public Utility Installation and Associated Filling and Excavation of Land (OHL Pole & Stay Erection)
Page 12 of 14

In the design of excavation and lateral support works, attention should be paid to the excavation and strutting sequence and to the standard workmanship in order to limit loss of ground due to the inward movement of the temporary planking. Earth load, water load and surcharge should be taken into consideration. It was recorded that the water level of the site is approximately 1.2m below the existing ground, sufficient water pumps shall be provided to ensure that the pits are not submerged during the construction of foundation.

Since the pit excavation works involves excavation of depth 1.8m only, excavation effects on the adjacent slopes and change of ground profile should be minimal.

After excavation and installation of poles, the pits will be backfilled and the ground will be reinstated to its original situation. Hence, the construction effect of proposed pit excavation on adjacent ground / slopes is insignificant.

Recommendation

- 1. The proposed utility installation works including pit excavation and the erection of 5 electricity poles and 10 pole stays is geotechnically feasible.
- 2. In the design of excavation and lateral support works for the pits, attention should be paid to the excavation and strutting sequence and earth load, water load and surcharge should be taken into consideration. During excavation works, sufficient water pump shall be provided to ensure that the pits are not submerged.
- 3. Proposed pit excavation works for erecting the poles will involve installation of planking with temporary strutting systems during the construction stage. Since the pit excavation works involves excavation of depth 1.8m only, excavation effects on the adjacent ground / slopes and change of ground profile should be minimal.
- 4. The proposed OHL poles and stay poles will be installed at the toe of the existing slopes. After pit excavation and installation of poles, the pits will be reinstated to its original situation. Hence, the construction effect of proposed utilities installation at the toe of slopes on the adjacent slope is insignificant.
- 5. Two registered man-made slopes are cut slopes with 6m in height at 45° slope angle. In view of failure of the man-made slopes would affect the OHL ploes at the slope toe, stability analysis is proposed to be carried out.
- 6. There are no records of landslides and boulders within the natural terrain area above the proposed pole locations. The proposed development would not comprise any critical facilities (i.e. facilities under Group 1-3 in Table 2.2 of GEO Report No. 138), a Natural Terrain Hazard Study is **not** necessary.

B190011.051.01 | Geotechnical Planning Review Report for Installation of Proposed Public Utility Installation and Associated Filling and Excavation of Land (OHL Pole & Stay Erection)








- 7. The location and disposition of the Site for erection of the OHL will minimise the filling and excavation of land and slope maintenance required for the proposed works and avoid encroachment onto private land. The proposed works will not cause adverse impacts on geotechnical safety, traffic, landscape, environment, sewerage, drainage and water supply. The applicant shall minimise the disturbance to the nearby vegetation during the land excavation/filling works.
- 8. The existing local road will not be obstructed. All vehicles are allowed to use the existing roads during construction period.

References

- 1. GEO (2007), GEO Advice Note for Planning Applications under Town Planning Ordinance (Cap.131), Geotechnical Engineering Office, Hong Kong.
- 2. Geotechnical Control Office (1989). "Solid and Superficial Geology. Hong Kong Geological Survey HGM20, Edition 1, Sheet No. 2, 1:20,000 scale". Government Press, Hong Kong.
- 3. Manusell Fugro Scott Wilson (2005). "Enhanced Natural Terrain Landslide Inventory". Geotechnical Engineering Office, Hong Kong.
- 4. Geotechnical Control Office (1988). "GEO Report No. 138 Guidelines for Natural Terrain Hazard Studies". Geotechnical Engineering Office, Hong Kong.
- 5. The Buildings Department. "Practice Note for Authorized Person and Registered Structural Engineer, PNAP APP 24".








Appendix A

Assessment of Natural Terrain Hazard

GEO Report No. 138

Table 2.2 Grouping of Facilities (adapted from Wong, 1998)

Group No.	Facilities					
	(a) Buildings - any residential building, commercial office, store and shop, hotel, factory, school, power station, ambulance depot, market, hospital/polyclinic/ clinic, welfare centre					
1	(b) Others - bus shelter, railway platform and other sheltered public waiting area - cottage, licensed and squatter area - dangerous goods storage site (e.g. petrol station) - road with very heavy vehicular or pedestrian traffic density					
2	(a) Buildings - built-up area (e.g. indoor car park, building within barracks, abattoir, incinerator, indoor games' sport hall, sewage treatment plant, refuse transfer station, church, temple, monastery, civic centre, manned substation)					
	(b) Others - road with heavy vehicular or pedestrian traffic density - major infrastructure facility (e.g. railway, tramway, flyover, subway, tunnel portal, service reservoir)					
3	 densely-used open space and public waiting area (e.g. densely-used playground, open car park, densely-used sitting out area, horticultural garden) quarry road with moderate vehicular or pedestrian traffic density 					



Comparing Figure 2.5 and Section 1, the site for proposed OHL Pole meets alert criteria of natural terrain hazard.





Figure 2.5 Application of Alert Criteria

Comparing Figure 2.5 and Section 2, the site for proposed OHL Pole meets alert criteria of natural terrain hazard.






Figure 2.5 Application of Alert Criteria

Pole meets alert criteria of natural terrain hazard. Comparing Figure 2.5 and Section 3, the site for proposed OHL






Figure 2.5 Application of Alert Criteria

Appendix A(Cont'd)


Inventory Plan







Appendix A(Cont'd)


Features and Sections







Appendix B
Slope Location Plan



General Views of Registered Man-made Slopes




Photo 1: General View of 2SE-B/C296




Photo 2: General View of 2SE-B/C305

Appendix B(Cont'd)

Basic Data of Slope Downloaded from SIS

BASIC INFORMATION

Location:

BORDER FENCE ROAD Adjoining Border Rd opposite DD96 Lot1811

Registration Date:

12-05-1998

Ranking Score (NPRS):

0 (EI)

Date of Formation:

post-1977

Date of Construction/

Modification:

Data Source:

EI(HyD)

Approximate Coordinates:

Easting: 826564

Northing: 841830

CONSEQUENCE-TO-LIFE CATEGORY

Facility at Crest:

Undeveloped green belt

Distance of Facility from Crest (m):

Facility at Toe:

Road/footpath with very low traffic density

Distance of Facility from Toe (m):

Consequence-to-life Category:

.

Remarks:

SLOPE PART

(1) Max. Height (m): 6

Length (m): 140

0

3

N/A

Average Angle (deg): 45

WALL PART

N/A

MAINTENANCE RESPONSIBILITY

(1) Sub Div.: O Government Feature Party: Lands D Agent: Lands D Land Cat.: 5b(vi) Reason Code: 62 MR Endorsement Date: 29-11-2013

DETAILS OF SLOPE / RETAINING WALL

Date of Inspection:

10-06-2014

Data Source:

EI(HyD)

Slope Part Drainage:

(1) Position: On slope

Size(mm): 300

Wall Part Drainage:

N/A

SLOPE PART

Slope Part (1)

Surface Protection (%):

Bare: 50 Veg

Vegetated: 50 Ch

Chunam: 0 Shotcrete: 0

Other Cover: 0

Material Description:

Material type: Soil

Geology: N/A

Berm:

No. of Berms: $\ensuremath{\text{N}}\xspace/\ensuremath{\text{A}}\xspace$

Min. Berm Width (m): N/A

Weepholes:

Size (mm): N/A

Spacing (m): N/A

WALL PART

N/A

SERVICES

N/A

CHECKING STATUS INFORMATION

Tagmark: 14810_0_5 Part: 0 Checking Status: No checking records Checking Certificate No.: N/A

BACKGROUND INFORMATION

GIU Cell Ref.:

2SE3B2

Map Sheet Reference (1:1000):

2SE- 3B

Aerial Photos:

51439 (1983), 51440 (1983)

Nearest Rainguage Station

(Station Number):

Sheung Shui Water Treatment Plant, Fu Tei Au Road(N34)

Data Collected On:

10-06-2014

Date of Construction, Subsequent

Modification: Constructed Before: 1979 After: 1975

Modification and Demolition:

Modification: Modified Before: 1983 After: 1979

Related Reports/Files or Documents:

File/Report: PWDC Ref. No.: GC 4/1/2-3 f(34) pt III

File/Report: PWDC

Ref. No.: GC 4/1/2-3 f(34) pt III

Remarks: N/A

Follow Up Actions:

N/A

DH-Order (To Be Confirmed None with Buildings Department):

Advisory Letter (To Be Confirmed None with Buildings Department):

LPMIS: None

ENHANCED MAINTENANCE INFORMATION

From Maintenance Department: (Last Updated Date: 26/05/2022)

STAGE 1 STUDY REPORT

Inspected On:

Weather:

District: MW

Section No:

1-1

Height(m):

Type of Toe Facility:

Road/footpath with very low traffic density

Distance from Toe(m):

. . .

Type of Crest Facility:

Undeveloped green belt

Distance from Crest(m):

Consequence Category:

Engineering Judgement:

Section No:

2-2

Type of Toe Facility:

Distance from Toe(m):

Type of Crest Facility:

Distance from Crest(m):

Consequence Category:

Engineering Judgement:

Sign of Seepage:

Criterion A satisfied:

Sign of Distress:

Criterion D satisfied:

Non-routine maintenance required:

Note:

Masonry wall/Masonry facing:

Note:

Consequence category (for critical section):

Observations:

N/A

Emergency Action Required:

Action By: N/A

ACTION TO INITIATE PREVENTIVE WORKS

Criterion A/Criterion D:

N/A

Action By:

N/A

Further Study:

Action By:

N/A

OTHER EXTERNAL ACTION

Check / repair Services:

Action By:

N/A

Non-routine Maintenance:

Action By:

N/A




<u> PHOTO</u>











BASIC INFORMATION

Location:

Border Fence Road

Registration Date:

12-05-1998

Ranking Score (NPRS):

0 (EI)

Date of Formation:

post-1977

Date of Construction/

Modification:

Data Source:

EI(Lands D)

Approximate Coordinates:

Easting : 826687

Northing: 841952

CONSEQUENCE-TO-LIFE CATEGORY

Facility at Crest:

Undeveloped green belt

Distance of Facility from Crest (m):

0

Facility at Toe:

Road/footpath with low traffic density

Distance of Facility from Toe (m):

0

Consequence-to-life Category:

3

Remarks:

N/A

SLOPE PART

(2) Max. Height (m): 6

Length (m): 218

Average Angle (deg): 45

WALL PART

N/A

MAINTENANCE RESPONSIBILITY

Agent: Lands D Land Cat.: 1,5b(vi),7 (1) Sub Div.: 1 Mixed Feature Party: Lands D Reason Code: 62 MR Endorsement Date: 29-11-2013 Party: DD96 LOT 1750RP Agent: N/A Land Cat.: 1,5b(vi),7 Reason Code: 1 MR Endorsement Date: 29-11-2013 (2) Sub Div.: 2 Mixed Feature Land Cat.: 1,5b(vi),7 MR Endorsement Date: 29-11-2013 Reason Code: 1 (3) Sub Div.: 3 Mixed Feature Party: DD96 LOT 1746RP Agent: N/A Reason Code: 1 Party: DD96 LOT 1745 Agent: N/A Land Cat.: 1,5b(vi),7 MR Endorsement Date: 29-11-2013 (4) Sub Div.: 4 Mixed Feature

DETAILS OF SLOPE / RETAINING WALL

Date of Inspection: 05-11-2018

Data Source: EI(Lands D)

Slope Part Drainage: N/A

Wall Part Drainage: N/A

SLOPE PART

Slope Part (1)

Surface Protection (%): Bare: 0 Vegetated: 100 Chunam: 0 Shotcrete: 0 Other Cover: 0

Material Description: Material type: Soil Geology: N/A

Berm: No. of Berms: N/A Min. Berm Width (m): N/A

Weepholes: Size (mm): N/A Spacing (m): N/A



Feature No. 2SE-B/C 305

WALL PART

N/A

SERVICES

N/A

CHECKING STATUS INFORMATION

Checking Status: No checking records Checking Certificate No.: N/A Tagmark: 14813_1_5 Part: 1

BACKGROUND INFORMATION

GIU Cell Ref.:

2SE3B2

Map Sheet Reference (1:1000):

2SE- 3B

Aerial Photos:

51439 (1983), 51440 (1983)

Nearest Rainguage Station

(Station Number):

Sheung Shui Water Treatment Plant, Fu Tei Au Road(N34)

Data Collected On:

05-11-2018

Date of Construction, Subsequent

Modification and Demolition:

Modification: Constructed Before: 1979 After: 1975

Modification: Modified Before: 1983 After: 1979

Related Reports/Files or Documents:

File/Report: PWDC

Ref. No.: GC 4/1/2-3 f(34) pt III

File/Report: PWDC

Ref. No.: GC 4/1/2-3 f(34) pt III

Remarks: N/A

Follow Up Actions:

N/A

DH-Order (To Be Confirmed None with Buildings Department):

Advisory Letter (To Be Confirmed None with Buildings Department):

LPMIS: None

ENHANCED MAINTENANCE INFORMATION

From Maintenance Department: (Last Updated Date: 26/05/2022)

STAGE 1 STUDY REPORT

Inspected On:

Weather:

District: MW

Section No:

1-1

Height(m):

Type of Toe Facility:

Road/footpath with low traffic density

Distance from Toe(m):

Type of Crest Facility:

Undeveloped green belt

Distance from Crest(m):

Consequence Category:

Engineering Judgement:

Section No:

2-2

Type of Toe Facility:

Distance from Toe(m):

Type of Crest Facility:

Distance from Crest(m):

Consequence Category:

Engineering Judgement:

Sign of Seepage:

Criterion A satisfied:

Sign of Distress:

Criterion D satisfied:

Non-routine maintenance required:

Note:

Masonry wall/Masonry facing:

Note:

Consequence category (for critical section):

Observations:

N/A

Emergency Action Required:

Action By:

N/A

ACTION TO INITIATE PREVENTIVE WORKS

Criterion A/Criterion D:

N/A

Action By:

N/A

Further Study:

Action By:

N/A

OTHER EXTERNAL ACTION

Check / repair Services:

Action By:

N/A

Non-routine Maintenance:

Action By:

N/A

PHOTO











Feature No. 2SE-B/C 305 +44 826 650E 826 700E 842 050N 842 050N PO 16 826 700E 842 000N 3.6 PO 826 650E 841 950N 841,950N 841 950N 841-950N PO 30 26 841 900N 841 900N 841 900N 841 900N 38 12 38 40 42 46 20 18.4 750E 826 700E SE-B/C 296 826 36. 841 850N 841 850N 841 850N 841 850N 56 53 53.0 59.4 49.8

Appendix B(Cont'd)

Slope Maintenance Responsibility Report
Downloaded from SMRIS

Slope Maintenance Responsibility Report

(2SE-B/C296)



List of Slope Maintenance Responsibility Area(s)

1	2SE-B/C296		Sub-Division	Not Applicable						
	Location	ADJOINING BORDER ROAD OPPOSITE DD96 LOT 1811								
	Responsible Lot/Party	Lands Department	Maintenance Agent	Lands Department						
	Remarks	For enquiries about the maintenance of this slope / sub-division of the slope, please contact the Maintenance Agent directly.								

- End of Report -

Notes:


- (i) The location plan in Annex is for identification purposes of slope(s) only.
- (ii) The slope(s) as listed in the Slope Maintenance Responsibility Report may not be shown on the location plan in Annex.

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at http://www.slope.landsd.gov.hk/smris/disclaimer. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

Search Criteria: 2SE-B/C296

Annex

Location Plan



Legend

Slope Area(s)

---- Search Location

Slope(s) Maintained by Government

Slope(s) Maintained by Private Party/Parties

Slope(s) Maintained by Government and Private Party/Parties



ESTATE MANAGEMENT SECTION LANDS DEPARTMENT

This Plan is **NOT TO SCALE** and intended for **IDENTIFICATION** only. All information shown on this plan **MUST** be verified by field survey.

Printed on: 01/08/2022

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at http://www.slope.landsd.gov.hk/smris/disclaimer. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

Slope Maintenance Responsibility Report

(2SE-B/C305)



List of Slope Maintenance Responsibility Area(s)

1	2SE-B/C305		Sub-Division	1							
	Location	ADJOINING BORDER ROAD & WITHIN DD96 LOT 1750RP, 1746RP & 1745 NEAR SPOT LEVEL 11.2									
	Responsible Lot/Party	Lands Department Maintenance Agent Lands Department									
	Remarks	2	For enquiries about the maintenance of this slope / sub-division of the slope, please contact the Maintenance Agent directly.								

- End of Report -

Notes:

- (i) The location plan in Annex is for identification purposes of slope(s) only.
- (ii) The slope(s) as listed in the Slope Maintenance Responsibility Report may not be shown on the location plan in Annex.


The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at http://www.slope.landsd.gov.hk/smris/disclaimer. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

1

Search Criteria: 2SE-B/C305

Annex

Location Plan



Legend

Slope Area(s)

Search Location

Slope(s) Maintained by Government

Slope(s) Maintained by Private Party/Parties

Slope(s) Maintained by Government and Private Party/Parties



ESTATE MANAGEMENT SECTION LANDS DEPARTMENT

This Plan is **NOT TO SCALE** and intended for **IDENTIFICATION** only. All information shown on this plan **MUST** be verified by field survey.

2

Printed on: 01/08/2022


The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at http://www.slope.landsd.gov.hk/smris/disclaimer. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

Search Criteria: 2SE-B/C305



Appendix C

Location Plan of Existing Borehole



Appendix C(Cont'd)

Measured Groundwater Record

GROUNDWATER MONITORING RECORD VIBRO (H.K.) LIMITED Drillhole No.: LMCT-BH 1 Contractor: GE/2015/29 Date of Installation: 19/09/2017 Contract No.: GE/2015/29.2 Pipe Top Level: +4.10 mPD Task Order No.: Co-ordinates: E 826249.35 N 841664.70 Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Project: Drainage Improvement Works at North District - Package B - Investigation Location: San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau Sheet 1 of 1 Piezometer Tip Level: - 4.55 mPD Checked By: Y. M. Leung Buckets (If any) Depth: From 0.05m 2.55m, Spacing @ 0.50m to HIGHEST BUCKET WITH ENTRAPPED WATER (if any) GROUNDWATER LEVEL (FROM TOP OF PIPE) REMARKS TIME REPORTED BY DATE ELEVATION (mPD) ELEVATION (mPD) DEPTH (m) (m) 22/09/2017 09:10 Y. T. Chow 1.26 +2.84 23/09/2017 10:25 Y. T. Chow +2.83 1.27 25/09/2017 10:00 Y. T. Chow 1.26 +2.84 26/09/2017 Y. T. Chow 1.28 +2.82 13:16 27/09/2017 Y. T. Chow 1.28 +2.82 13:20 28/09/2017 11:21 Y. T. Chow 1.30 +2.80 29/09/2017 14:16 Y. T. Chow 1.30 +2.80

GROUNDWATER MONITORING RECORD VIBRO (H.K.) LIMITED Drillhole No.: LMCT-BH 1 Contract No.: GE/2015/29 Date of Installation: 19/09/2017 GE/2015/29.2 Task Order No.: Pipe Top Level: +4.10 mPD Co-ordinates: Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau E 826249.35 N 841664.70 Project: Sheet 1 of 1 Standpipe Tip Level: - 1.55 mPD to 2.55m, Spacing @ 0.50m Buckets (If any) Depth: From 0.05m Checked By: Y. M. Leung GROUNDWATER LEVEL (FROM TOP OF PIPE) HIGHEST BUCKET WITH ENTRAPPED WATER (if any) DATE TIME REPORTED BY REMARKS **ELEVATION** DEPTH **ELEVATION** (m) (mPD) (m) 22/09/2017 09:10 Y. T. Chow 1.40 +2.70 23/09/2017 10:25 Y. T. Chow 1.41 +2.69 25/09/2017 10:00 Y. T. Chow 1.36 +2.74 26/09/2017 13:16 Y. T. Chow 1.40 +2.70 27/09/2017 13:20 Y. T. Chow 1.41 +2.69 28/09/2017 11:21 Y. T. Chow 1.42 +2.68 29/09/2017 14:16 Y. T. Chow 1.41 +2.69

GROUNDWATER MONITORING RECORD LMCT-BH 2 Drillhole No. : Contractor: VIBRO (H.K.) LIMITED Date of Installation: 13/10/2017 GE/2015/29 Contract No.: Pipe Top Level: +4.13 mPD Task Order No.: GE/2015/29.2 Co-ordinates: Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Project: Drainage Improvement Works at North District - Package B - Investigation Location: San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau E 826149.30 N 841498.38 Sheet of 1 Piezometer Tip Level: - 34.02 mPD Buckets (If any) Depth: From 0.08m 2.58m, Spacing @ 0.50m Checked By: Y. M. Leung to GROUNDWATER LEVEL (FROM TOP OF PIPE) HIGHEST BUCKET WITH ENTRAPPED WATER (if any) DATE TIME REPORTED BY REMARKS ELEVATION (mPD) DEPTH **ELEVATION** (mPD) (m) (m) 16/10/2017 09:40 Y. T. Chow 0.40 +3.73 17/10/2017 10:08 Y. T. Chow 0.47 +3.66 +3.65 18/10/2017 11:00 Y. T. Chow 0.48 19/10/2017 13:21 Y. T. Chow 0.48 +3.65 20/10/2017 Y. T. Chow 0.42 +3.71 14:16 21/10/2017 10:41 Y. T. Chow 0.40 +3.73 Y, T, Chow 23/10/2017 0.45 +3.68 09:04

GROUNDWATER MONITORING RECORD VIBRO (H.K.) LIMITED Drillhole No.: LMCT-BH 2 Contractor: GE/2015/29 Contract No.: Date of Installation: 13/10/2017 Task Order No.: GE/2015/29.2 Pipe Top Level: +4.13 mPD Co-ordinates: Ground Investigation - New Territories West Project: Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location: San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau E 826149.30 N 841498.38 Sheet 1 of 1 Piezometer Tip Level: - 20.42 mPD Buckets (If any) Depth: From 0.08m 2.58m, Spacing @ 0.50m to Checked By: Y. M. Leung HIGHEST BUCKET WITH ENTRAPPED WATER (if any) GROUNDWATER LEVEL (FROM TOP OF PIPE) DATE TIME REPORTED BY REMARKS ELEVATION (mPD) DEPTH ELEVATION (mPD) (m) (m) 16/10/2017 09:40 Y. T. Chow 0.56 +3.57 17/10/2017 10:08 Y. T. Chow 0.63 +3.50 18/10/2017 11:00 Y. T. Chow 0.60 +3.53 19/10/2017 13:21 Y. T. Chow 0.58 +3.55 20/10/2017 14:16 Y. T. Chow 0.51 +3.62 21/10/2017 Y. T. Chow 10:41 0.50 +3.63 23/10/2017 09:04 Y. T. Chow 0.53 +3.60

Appendix C(Cont'd)

Existing Ground Investigation Records



HOLE NO.

LMCT-BH 1

CONTRACT NO.:

GE/2015/29

SHEET 1

OF 1

PROJECT

Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau

METHOD F	Rotary CO-ORDI	INATES		TASK ORDER NO. GE/2015/29.2	
MACHINE & NO. V	/BM52 E 826249	9.35	N 841664.70		DATE: 15/09/2017 to 18/09/2017
FLUSHING MEDIUM	Water ORIENTA	ATION	Vertical		GROUND LEVEL + 3.95 mPD
Start S F	R Q D % Lests Lests	Samples No. Type Depth	Reduced Level (m)	Grade	Description
15/09/2017 SW		A Id 0.50 B 1.00 C 1.35	+2.60 - 1.35		Brown (7.5YR 5/4), mottled reddish brown, spotted white, slightly clayey silty fine to coarse SAND with some angular to subangular fine to coarse gravel sized rock fragments. (FILL)
SW 2.00 PW		S W	+1.95 2.00		Reddish brown (2.5YR 5/4), locally light brownish grey, angular COBBLE sized moderately decomposed Metasandstone with some angular medium to coarse gravel sized rock fragments, (FILL)
80 98		2 3.00	+0.85		Firm, dark grey (N 4), mottled black, clayey slightly sandy SILT with occasional decayed wood pieces. (POND DEPOSIT)
	3.10 1,1, 1,1,1,1 N=4	3 3.20 4 3.50 3.55	- 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		Soft, brown, slightly clayey sandy SILT with occasional subrounded fine to medium gravel sized rock fragments. (ALLUVIUM)
0.50m	5.65 x 10 ⁻⁶ m/sec	5.00			Reddish brown (2.5YR 5/4), mottled light yellowish brown, spotted white, sandy subangular to subrounded fine to coarse GRAVEL sized quartz and rock fragments. (ALLUVIUM)
15/09/2017 18:00 1.20m at 08:00 1.21m at 18:00 1.21m at 18:00 1.21m at 18:00 1.31m at 18:00 1.31m at 08:00	5.60 3,1, 1,2,3,3 N=9 6.0s	5.55 7 5.60 8 6.00 6.05	1.65 5.60 0 0 0	V	Extremely weak, light grey (N 7), streaked reddish brown and light brown, completely decomposed METASILTSTONE. (Slightly sandy SILT)
80 40	8.50	7,10	-3.15 7.10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	V	Extremely weak to very weak, reddish brown (2.5YR 5/4), dappled yellow and red, occasional mottled light grey, completely decomposed METASILTSTONE. (Slightly sandy SILT with some subangular fine to coarse gravel)
80 95 PW at at 18/09/2017/10.00 18:00	9.30 2.5, 5.9.17.22 N=53	12 9.20 9.30 13 9.40 14 9.70 9.75	- 11 10 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1		End of Investigation Hole at 10.00m.
Disturbed sample Piston sample	Standard penetration test In-situ vane shear test Permeability test	LOGGED		specti	on pit was excavated to 1.35m.
Split spoon sample U76 undisturbed sample	Pressuremeter test Packer Test	DATE 1	3. A sta	ndpipe	head permeability test was carried out from 4.10m to 5.60m. • was installed to 5.50m. •r was installed at 8.50m.
U100 undisturbed sample Mazier sample SPT liner sample	Acoustic or optical televiewer survey Piezometer tip Standpipe Groundwater Sampling Well	CHECKED Y	5. Piezo to 2.5	meter	er was installed at o.50m. buckets were installed in standpipe and piezometer from 0.05m pth at 0.50m intervals below ground level.
Water sample	Vibrating wire piezometer Impression packer test	DATE2	21/09/2017		J201617e



VIBRO

惠保(香港)有限公司 VIBRO (H.K.) LIMITED 新創建集團成員 Member of NWS Holdings

•	ລ	
1	N	
1	2	
	5	
1	ŭ	
1	II	
1	Ö	
2	Ξ.	
	ö	
2000	Ž	
	+	
	ac	
	ĭ	
	E	
	ò	

Contract Title: Ground Investigation - New Territories West


Task Order No.: **GE/2015/29.2**

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

- Investigation

0.00m

10.00 to Ε Date of Photograph : 31-10-2017 LMCT-BH1 0.00 Hole No.: Box No.: Depth:





GE/2015/29

HOLE NO.

LMCT-BH 2

CONTRACT NO. :

SHEET 1 OF 5

PROJECT

Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau

METHOD	METHOD Rotary					1	CO-ORDINATES								TASK ORDER NO. GE/2015/29.2	
MACHINE	& NO.			VB	M52		1	E 826149	9.3	0		N 84	1498.	.38		DATE: 21/09/2017 to 10/10/2017
FLUSHING		IUM		W	ater		(ORIENTA	TI	ON		Verti	cal			GROUND LEVEL + 3.98 mPD
Drilling Progress Casing Depth/Size	Water Level (m) Shift start / end	Flush Returns %	TCR%	SCR%	RQD%	Н	Depth of FI / Test	Tests		Sampl No. Type		A Reduced	o Depth (m)	Legend	Grade	Description
21/09/2017 SW										NSPECTION PIT	0.50	+2.98	- - - - - - - - - - - - - -			Brown (7.5YR 5/4), mottled reddish brown, silty sandy subangular fine to coarse GRAVEL sized rock fragments. (FILL)
		80	36							T2101	1.50	+2.48	- - - - 1.50			Light grey (N 7), locally light brown, slightly silty angular medium to coarse GRAVEL sized rock fragments. (FILL)
2 .		80	90							2	2.50 2.60	+1.38	- - - - - - - - 2.60	19 1 - 0 1 - 0 - 1 - 0 1 - 1 - 0 1 - 1 - 1 - 0 1 - 1 - 1 - 1 - 1		Firm to stiff, dark greyish brown (10YR 4/2), spotted dark grey, clayey slightly sandy SILT with occasional subrounded fine to medium gravel sized rock fragments. (ALLUVIUM)
321/09/2017 22/09/2017	0.10m at 18:00 0.40m at 08:00						3.05	1,1, 1,1,1,1 N=4 23.24 kN/n	m²	3	2.70 3.00 3.05	+1.38	2.50 			Soft, dark grey (N 4), spotted dark brown, clayey slightly sandy SILT. (POND DEPOSIT)
4 22/09/2017	0.25m at 18:00	112	0							6	3.60 4.55 4.60	-0.62	- 4.60			From 3.60m to 4.60m : No recovery.
23/09/2017 5	1.03m at 08:00		56				5.10 5.55	28 bls 2,3, 3,3,5,8 N=19 1.30 x 10 ⁻⁷ m/sec		9 10	5.05 5.10 5.20 5.50 5.55					Stiff, yellowish brown (10YR 5/4), mottled reddish brown, occasional mottled white, clayey slightly sandy SILT with occasional subrounded fine to medium gravel sized rock fragments. (ALLUVIUM)
7.		80	98					1	-	13	7.60 7.70	-2.62	6.60	6 1	>	Extremely weak, brown (7.5YR 5/4), streaked reddish brown, completely decomposed METASILTSTONE. (Sandy SILT with some subangular fine to medium gravel)
B SW 23/09/2017 8.15 25/09/2017 PW	0.22m at 18:00 0.53m at 08:00						8.15	5,7, 6,10,20,16 N=52		14 15	7.80 8.10 8.15			(a)	\ 	Extremely weak to very weak, light reddish brown (2.5YR 7/3), spotted and mottled reddish brown, completely decomposed METASILTSTONE. (Sandy SILT with much subangular fine to medium gravel)
9 - - - - 25/09/2017 26/09/2017	0.27m at 18:00 0.80m	60	95				9.70	9.17 x 10 ⁻⁷ m/sec	k:	17	9.60 9.70			0		4
Disturbed sa	at						netration	17,7,8,9 n test	П	18	9.80			REMA	RKS	
Piston sample Split spoon sa U76 undisturt	e ample	ole	3		Permea Pressu Packer	ability remet Test	ter test	ear test st test DATE				S. C. Law 1. An inspecti 2. An in-situ v				
U100 undistu Mazier sampl	SPT liner sample Standpipe Groundwater S					optical urvey			/. M. Lei	4. Piezometers were installed at 24.40m and 38.00m. 5. Piezometer buckets were installed in piezometers from 0.08m to 2.58 at 0.50m intervals below ground level.						
TANK TO SEE THE SECOND	Water sample N Environmental Sample Vibrating wire pi Impression pad					e piezon	neter	D.	ATE		20/10/20)17			J201617e	



GE/2015/29

HOLE NO. LMCT-BH 2

2

SHEET

5 OF

PROJECT

Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau

CONTRACT NO.:

METHOD				otary		100	CO-ORDIN	IATES						TASK ORDER NO. GE/2015/29.2
MACHINE	& NO.		VE	3M52			E 826149.	30		N 84	11498.	.38		DATE: 21/09/2017 to 10/10/2017
FLUSHING	MED	IUM	W	ater			ORIENTAT	TION		Verti	cal	90		GROUND LEVEL + 3.98 mPD
Drilling Progress Casing Depth/Size	Water Level (m) Shift start / end	Flush Returns % T C R %	2	RQD%	Ы	Depth of FI / Test	Tests	Sampl No. Type		A Reduced	Depth (m)	Legend	Grade	Description
26/09/2017 PW 27/09/2017 1111 1111 112 112 112 112 112 112 112	/end 08:00 0.28m at 18:00 0.81m at 08:00	60 88				10.1	13.3. 5,6,7,9 5,=27	20 21 22 23 24 24 24	10.10 10.15 10.60 11.60 11.70 11.80 12.10 12.15	-6.62 -6.62	10.60	0,,	V	Extremely weak, brown (7.5YR 5/4), occasional spotted white, completely decomposed METASILTSTONE. (Slightly sandy SILT) Extremely weak, reddish brown (2.5YR 5/4), streaked light grey, completely decomposed METASILTSTONE. (Slightly sandy SILT with occasional subangular fine to medium gravel)
14 27/09/2017 = 28/09/2017 = 15	0.25m at 18:00 0.95m at 08:00	60 95				14.1	a 3,8, 12,19,22,33 N=86	25 26 27 28 28 29 30 31 31	13.60 13.70 14.10 14.15 14.50 15.60 15.70 15.80 16.10 16.15	-12.62				gravery
117 	0.55m at 18:00 1.12m at 08:00	60 95				17.J 18.4 19.3	14,28,32,24 N=98	32 33 34 35 36	17.60 17.70 17.80 18.10 18.15		17.70		IV IV	Very weak, reddish brown (2.5YR 5/4), streaked and mottled light grey, highly decomposed METASANDSTONE. (Silty sandy subangular fine to medium GRAVEL) Very weak, brown (7.5YR 5/4), spotted white, highly decomposed METASANDSTONE. (Subangular fine to medium GRAVEL) Very weak, reddish brown (2.5YR 5/4), streaked and mottled brown, highly decomposed METASANDSTONE. (Silty sandy subangular fine to medium GRAVEL)
Piston samp Split spoon: U76 undistu U100 undist Mazier samp SPT liner sa Water samp	Disturbed sample Piston sample Split spoon sample U76 undisturbed sample U100 undisturbed sample Mazier sample SPT liner sample Standard pe In-situ vanie Permeability Pressureme Accustic or televiewer si televiewer si Standpipe Groundwate						t t t t t t t t t t t t t t t t t t t	LOGGED DATE CHECKE	- :D _	S. C. I 11/10/2 Y. M. Lo 20/10/2	2017 eung	REMA		J201617e



HOLE NO.

LMCT-BH 2

CONTRACT NO. :

GE/2015/29

SHEET 3 OF

PROJECT

Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau

	METHOD Rotary								0	CO-ORDI	NATES					TASK ORDER NO. GE/2015/29.2	
	MACH	INE	& NO.	e e		VB	M52	!		E 826149	.30		N 84	11498	.38		DATE: 21/09/2017 to 10/10/2017
	FLUSH	_		IUM	į.	W	ater			ORIENTA	TION		Verti	cal			GROUND LEVEL + 3.98 mPD
	Drilling Progress	Casing Depth/Size	Water Level (m) Shift start / end	Flush Returns %	TCR%	SCR%	RQD%	Œ	Depth of FI / Test	Tests	Samples	eptn	Reduced 16.02	(m) 20.00	Legend	Grade	Description
21 22 23 24 24	29/09/2017 30/09/2017	HW	0.42m at 18:00 0.92m at 08:00	60	95			9.4	22.15	\$ 12, 14,18,30,32 N=94 N=94 100/60mm (100/60mm)	39	20.10 (20.15) (20.16)	-16.02 -18.62	22.60			Very weak to weak, light grey (N 7), streaked brown, highly decomposed METASILTSTONE. (Slightly silty subangular fine to coarse GRAVEL) Moderately strong, greyish brown, dappled brown, moderately decomposed METASILTSTONE.
26 	30/09/2017 03/10/2017		0.31m at 18:00 1.00m at 08:00	60	100	49	0 15	>20 12.5 >20 10.9	25.49 25.59 26.07 26.07		T2101		-24.52	28.50		V	Joints are very closely to closely spaced, locally medium spaced, occasional slickensided planar, extremely narrow to very narrow, iron and manganese oxide stained, dipping 10° to 20°, 20° to 30°, 40° to 50°, 60° to 70° and 70° to 80°. At 26.97m: Fractured, quartz vein up to 40mm thick, dipping 20° to 30°.
300 E	Piston : Split sp U76 un U100 u Mazier SPT lin	sample noon sindisturi undisturi sample sampler sample	e ample bed samp rbed sam le nple	nple	<u> </u>		Standa n-situ Permea Pressu Packer Cousti Eleviev Piezom Standp Ground	rd pee vane bbility remet Test c or o ver su eter t ipe water	netration shear te test er test ptical rvey ip	ing Well meter	LOGGED DATE CHECKED DATE		M. Lei	aw D17	REMAR	RKS	J201617e



GE/2015/29

HOLE NO.

SHEET

LMCT-BH 2

OF 5

PROJECT

Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau

CONTRACT NO.:

ME	тно	OD				Ro	tary		T	CO-ORDIN	ATES					TASK ORDER NO. GE/2015/29.2
MA	ACHI	INE	& NO.			VB	M52	9	T F	E 826149.	30	N 84	11498.	38		DATE: 21/09/2017 to 10/10/2017
FL	USH	IING	MED	IUM		Wa	ater		(ORIENTAT	ION	Verti	cal			GROUND LEVEL + 3.98 mPD
Drilling	Progress	Casing Depth/Size	Water Level (m) Shift start / end	Flush Returns %	TCR%	SCR%	RQD%	H	Depth of FI / Test	Tests	Samples No. Type Depth	Reduced 76.02	00.00 (m)	Legend	Grade	Description
31 		HW	0.90m	85	160	89	43	4.5 12.0 >20	31.13 31.63 32.13		T2 O 30.22 T2 O T2 O T2 O	-28.15	32.13		III V	From 32.13m to 32.59m: No recovery, inferred to be completely decomposed METASILTSTONE.
	10/2017 10/2017		at 18:00 1.10m at 08:00	85	96	31	16	NA 14.2 >20	32.59 32.79 33.00 33.20		32.59 T2 IOI 	-28.61 -28.80 -29.22	Γ'		III	Moderately weak to moderately strong, reddish brown, spotted white, moderately decomposed METASANDSTONE. Joints are very closely to closely spaced, locally extremely closely spaced, rough planar and rough stepped, extremely narrow to very narrow, iron and manganese oxide stained, dipping 20° to 30°, 40° to 50° and 50° to 60°. From 32.59m to 32.78m: Moderately weak, reddish brown (2.5YR 5/4), spotted white, highly decomposed METASANDSTONE. (Sandy subangular fine to coarse
35 04/ - 06/	10/2017 10/2017		0.90m at 18:00 1.05m at 08:00	85	95	0	0	NA	35.10 35.20 36.20 36.30	50/70mm, 99,10/5mm (100/80mm)	T2 IOI 51 35.10 52 36.10 54 36.20 54 36.60 36.60 36.60 36.60 36.60	-31.12	35.10		IV	GRAVEL) Very weak to weak, reddish brown (2.5YR 5/4), streaked dark greyish brown, highly decomposed METASANDSTONE. (Silty sandy subangular fine to coarse GRAVEL) Moderately weak, brown (7.5YR 5/4), dappled brown, highly decomposed METASANDSTONE. (Slightly silty sandy subangular fine to coarse GRAVEL with some subangular cobbles) Extremely weak to very weak, brown, streaked black, completely decomposed METASANDSTONE. (Silty fine to medium SAND with much subangular fine to medium gravel)
37 	/10/2017 /10/2017		0.65m at 18:00 0.90m at 08:00	80	95			NA 13.0	38.4 38.90 39.13	0 (20,30/65mm, 19100/70mm (100/70mm)	55 37.10 56 38.10 57 58 38.30 38.90	-34.92 -35.15	38.90	0 0 0 0		Moderately weak to moderately strong, brown, streaked black, moderately decomposed METASILTSTONE. Joints are very closely to closely spaced, locally extremely
- - - - - - 40	io Disturbed si		ample	80	98		15 Stand	NA	39.36 39.99 enetratio	on test	T2101	-36.01	39.36	P di	9	closely spaced, occasional slickensided planar, extremely narrow to very narrow, iron and manganese oxide stained, dipping 0° to 10°, 20° to 30°, 40° to 50°, 50° to 60° and 60° to 70°.
	Piston sample Piston sample Split spoon sample U76 undisturbed sample U100 undisturbed sample Mazier sample SPT liner sample V In-situ vane Permeability Pressureme Acoustic or televiewer si Plezometer Standpie Groundwate						vane eability urement or Tes tic or ewer s meter pipe odwate ing wi	e shear to y test eter test t optical survey tip er Samp ire piezo	bling Well	LOGGED _ DATE _ CHECKED _ DATE _	S. C. I 11/10/2 Y. M. L 20/10/2	2017 eung	-		J201617	



GE/2015/29

HOLE NO.

LMCT-BH 2

CONTRACT NO.:

SHEET

OF

PROJECT

Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau

METH	ETHOD Rotary			//	CO-ORDINATES						TASK ORDER NO. GE/2015/29.2				
MACH	INE	& NO			VE	3M52	2		E 826149.	30	N 84	41498	.38		DATE: 21/09/2017 to 10/10/2017
FLUSH	IING			1	W	ater	8		ORIENTAT	ION	Verti	cal			GROUND LEVEL + 3.98 mPD
Drilling Progress	Casing Depth/Size	Water Level (m) Shift start / end	Flush Retirns %	TCR%	SCR%	RQD%	Е	Depth of FI / Test	Tests	Samples No. Type Depth	Reduced So Level	00.00 (m)	Legend	Grade	Description
	HW		80	69	40	32	NR	.40.16 .40.65 .41.08		T2101	-36.18 -36.67	- 40.16 - 40.65 - 41.08		III IV	From 38.90m to 39.13m: Moderately weak, brown (7.5YR 5/4), streaked black, highly decomposed METASANDSTONE. (Slightly silty sandy subangular fine to coarse GRAVEL with occasional subangular cobbles) From 39.36m to 39.99m: Weak to moderately weak, brown (7.5YR 5/4), streaked black, highly decomposed METASILTSTONE. (Silty slightly sandy subangular fine to coarse GRAVEL with occasional subangular cobbles)
42			80	99	46	30	9.0	41.57		T2101		- 41.57 	10 8V.	111	From 40.16m to 40.65m: No recovery, inferred to be completely decomposed METASILTSTONE. From 41.08m to 41.57m: Weak to moderately weak, brown (7.5YR 5/4), streaked black, highly decomposed METASILTSTONE. (Silty slightly sandy subangular fine to coarse GRAVEL with occasional subangular cobbles)
43			80	78	15	0	NA 17.1	42.77 43.18		42.58 T2101	-38.79 -39.20	42.77		111	From 42.24m to 42.77m: Weak to moderately weak, brown (7.5YR 5/4), streaked black, highly decomposed METASILTSTONE. (Silty slightly sandy subangular fine to coarse GRAVEL with occasional subangular cobbles) From 43.18m to 43.58m: Weak to moderately weak, brown
07/10/2017 44 09/10/2017		0.65m at 18:00 0.95m at 08:00	60	0			NA NR	43.58 43.97	,	59 43.86 43.89 43.91	-39.88 -39.93	43.58 - 43.86 - 43.91	000	V IV	(7.5YR 5/4), streaked black, highly decomposed METASILTSTONE. (Silty slightly sandy subangular fine to coarse GRAVEL with occasional subangular cobbles) From 43.58m to 43.86m: No recovery, inferred to be completely decomposed METASILTSTONE. Weak to moderately weak, greyish brown (2.5Y 5/2),
45 	HW 45.34		60	100	100	94	3.1			T2101					streaked brown (7.5YR 5/4), highly decomposed METASILTSTONE. (Slightly sandy angular to subangular fine to coarse GRAVEL) Strong, grey, occasional streaked dark brown, slightly decomposed METASILTSTONE. Joints are medium spaced, locally closely spaced, occasional rough stepped, extremely narrow, iron and manganese oxide stained, dipping 10° to 20°, 40° to 50°, 50° to 60° and 60° to 70°.
46 			60	100	98	89		46.51		T2101	-42.39	- - - - - - - - 46.37		111	Moderately strong, brown, streaked white and dark brown,
47 	_	0.28m at 18:00	60	100	16	0	18.2	46.83 47.17 47.28 47.50		46.83 T2101 47.50					moderately decomposed METASANDSTONE. Joints are closely to medium spaced, locally very closely spaced, rough planar and rough stepped, occasional slickensided planar, extremely narrow, iron and manganese oxide stained, dipping 20° to 30°, 30° to 40°, 40° to 50°, 50° to 60° and 60° to 70°.
- - - - - - -		at 08:00	60	100	89	66	9.8	48.42 48.56		T2101					From 47.54m to 48.29m : With some quartz veins up to 10mm thick, dipping 30° to 40°.
49 10/10/2017		0.52m at 18:00	60	100	70	43	4.0	48.81 49.05		T2101	-45.07	- - - - - - - - -			End of Investigation Hole at 49.05m.
Piston : Split sp U76 un U100 u Mazier SPT lin Water	Piston sample Piston sample Split spoon sample U76 undisturbed sample U100 undisturbed sample Mazier sample SPT liner sample Piston sample Groundwater Sar		test ter test optical urvey tip r Samp	ar test est DATE 11/10/20 al y CHECKED Y. M. Let mpling Well ezometer DATE 20/10/20			017 ung	REMAI	RKS						



惠保(香港)有限公司 VIBRO (H.K.) LIMITED 新島語集團成员 Member of NWS Holdings

Contract No.: GE/2015/29

Contract Title: Ground Investigation - New Territories West

Task Order No.: **GE/2015/29.2**

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

Investigation

11.70 10 9 Ε Date of Photograph : 31-10-2017 LMCT-BH2 0.00 Hole No.: Box No.: Depth:

0/:11

2/3

00.1

hc 00'0

CONTO



VIBRO

惠保(香港)有限公司 VIBRO (H.K.) LIMITED 新創建集團成員 Member of NWS Holdings

Contract No.: GE/2015/29

Contract Title: Ground Investigation - New Territories West

Task Order No.: GE/2015/29.2

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

Investigation

0.00m

Date of Photograph : 31-10-2017

24.96

9 Ε

10

of

LMCT-BH2

Hole No.:

Box No.:





惠保(香港)有限公司 VIBRO (H.K.) LIMITED

	6
	N
	10
	5
	2
	H
	G
	٠:
	0
	z
	to
	ä
ĺ	幸
	0
	-

Contract Title: Ground Investigation - New Territories West

Task Order No.: **GE/2015/29.2**

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

- Investigation

3 Box No.:

o

Hole No.:

LMCT-BH2

E 24.96

27.55 9

Date of Photograph : 31-10-2017

CONTO

0.00m



D CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

Z BRO

惠保(香港)有限公司 VIBRO (H.K.) LIMITED

Contract No.: GE/2015/29


Contract Title: Ground Investigation - New Territories West


Task Order No.: **GE/2015/29.2**

Agreement No. CE78/2014(DS) Drainage Improvement Works at North District - Package B

- Investigation

0.00m







CEDD CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

VIBRO (H.K.) LIMITED 惠保一番

0	53
1	5
9	202
1	GF
	.:
	Z
	rac
	Sint
	Х

Contract Title: Ground Investigation - New Territories West

Task Order No.: GE/2015/29.2

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

- Investigation

(32.99)10 9 Ε Date of Photograph : 31-10-2017 LMCT-BH2 30.22 S Hole No.: Box No.:

(82,99)



EDD CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

惠保(香港)有限公司 VIBRO (H.K.) LIMITED

Contract No.: GE/2015/29

Contract Title: Ground Investigation - New Territories West


Task Order No.: **GE/2015/29.2**

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

- Investigation

0.00m

39.90 10 Kodak Color Control Patches 9 Ε of Date of Photograph : 31-10-2017 LMCT-BH2 (32.99)9 Hole No.: Box No.: Depth:






RTMENT A GEOTECHNICAL ENGINEERING DEELCE

惠保(香港)有限公司 VIBRO (H.K.) LIMITED

0.00m







CEDD GEOTECHNICAL ENGINEERING OFFICE CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

V BRO

惠保(香港)有限公司 VIBRO (H.K.) LIMITED 新島建集團成員 Member of NWS Holdings

6
/29
2
-
20
S
Ш
GE/
٠:
0
S
ract
2
in
4
0

Contract Title: Ground Investigation - New Territories West

Task Order No.: GE/2015/29.2

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

Investigation

0.00m

500

45.34 10 9 Date of Photograph : 31-10-2017 LMCT-BH2 42.58 00 Hole No.: Box No.: Depth:

HE 40

98'Et

CONTO



CEDD GIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

VIBRO

VIBRO (H.K.) LIMITED 新創建集團成員 Member of NWS Holdings

/29
5
/201
Ш
G
٠:
0
Z
ct
ä
ᆂ
ont
0

Contract Title: Ground Investigation - New Territories West

Task Order No.: GE/2015/29.2

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

- Investigation

45.34 0 Box No.: Depth:

LMCT-BH2


Hole No.:

10

48.12)

Date of Photograph : 31-10-2017

0.00m





CEDD GEOTECHNICAL ENGINEERING OFFICE CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

LMCT-BH2

Hole No.:

惠保(香港)有限公司 VIBRO (H.K.) LIMITED 新創建集團成員 Member of NWS Holdings

Contract No.: GE/2015/29

Contract Title: Ground Investigation - New Territories West

Task Order No.: GE/2015/29.2

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

- Investigation

0.00m

Date of Photograph : 31-10-2017 (48.12)10 Box No.: Depth:

49.05

2 E

10

of

Georg		1.00m
3000		
white		
Wagersa		
Green Yestow Red		
Yelow		
Green		
Cyan		
Bloe		





BOX SITE: CONSTRUCTION OF A SECONDARY BOUNDARY FENCE - STAGE W.O. NO .: ASD 010414 AL GEOTECHNICS & CONCRETE ENGG (HK) LTD 0.00 MTO TERM CONTRACT FOR GROUND INVESTIGATION ARCHITECTURAL SERVICES DEPARTMENT 3.03 0.5m HOLE NO .: CONTRACT NO. TC N307 24-5-2005 DHIO

0.0m





PISTON SAMPLE

PACKER TEST

GEOTECHNICS & CONCRETE ENGG. (H.K.) LTD. **GROUND INVESTIGATION DEPARTMENT**

HOLE NO. SBF/DH10

SHEET

OF

DRILLHOLE RECORD CONTRACT NO. TC N307 PROJECT Construction of A Secondary Boundary Fence - Stage 1 METHOD **Rotary Cored** WORKS ORDER NO. ASD 010414 E 826647.23 MACHINE & NO. DR113 DATE FROM 20/04/2005 TO 20/04/2005 N 841934.82 mPD FLUSHING MEDIUM Water ORIENTATION Vertical **GROUND LEVEL** 6.74 Water level (m) & Time Casing size Total core Recovery 9 Solid core Recovery 9 Reduced Samples Legend Description R.Q.D. Depth (m) Grade Tests 20/04/2005 НХ Yellowish red (5YR 5/8), silty fine to medium SAND with some angular to subangular fine to coarse gravel sized moderately strong rock fragments. (FILL) 0.50 Moderately strong, reddish brown, moderately decomposed meta-SANDSTONE. Joints are closely spaced, occasional very closely 91 8.7 99 . . . HX 1.26 1,26 • 14.9 98 0 and medium spaced, rough and smooth planar, rough undulating, extremely narrow to occasional very narrow, limonite, iron and manganese oxide stained, dipping at 0 to 10, 20 to 30 and 30 to 40. 1,60 56 92 From 1.71m to 1.98m : Subvertical joint. 20 12,1 T2101 3.03 Hole completed at 3.03m. REMARKS SMALL DISTURBED SAMPLE △ WATER SAMPLE LOGGED Y.K. Lee LARGE DISTURBED SAMPLE PIEZOMETER TIP SPT LINER SAMPLE \triangle STANDPIPE DATE 21/04/2005 STANDARD PENETRATION TEST U76 UNDISTURBED SAMPLE PERMEABILITY TEST U100 UNDISTURBED SAMPLE CHECKED Tom Lo II IMPRESSION PACKER TEST MAZIER SAMPLE IN-SITU VANE SHEAR TEST 22/04/2005 DATE



GEOTECHNICS & CONCRETE ENGG. (H.K.) LTD. **GROUND INVESTIGATION DEPARTMENT**

HOLE NO. SBF/DH11

SHEET 1 OF 2

DRILLHOLE RECORD

CONTRACT NO. TC N307

PROJE	CT	Constru	ction of	A Second	dary E	Bound	ary Fence -	- Stage 1							
METHO	D		R	otary C	ore	d		CO-ORDIN	NATES 82638	6.01			WORKS ORDER NO. ASD 010414		
MACHI	NE & N	١٥.	D	R129					84175				DATE FROM 24/04/2005 TO 26/04/2005		
FLUSH	ING M	EDIUM	w	ater				ORIENTAT	ION	Ver	tical		GROUND LEVEL 4.86 mPI		
Drilling Progress	Casing size	Water level (m) & Time	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced %Level	Depth (m)	Legend	Grade	Description		
24/04/2005	PX							NSPECTION PIT	3,36				Firm, yellowish brown (10YR 5/8), dappled grey, sandy clayey SILT with some angular to subangular fine to coarse gravel sized moderately weak to moderately strong rock fragments. (FILL)		
24/04/2005 25/04/2005		Dry at 18:00 Dry at	/89/					D	2,86	2,00	-9		Yellowish brown (10YR 5/8), clayey silty fine to coarse SAND with much angular fine to medium gravel sized rock fragments. (FILL) Greyish brown (2.5Y 5/2), clayey silty fine to coarse		
3		08:00						2	1,76	3,10			SAND with much angular to subangular fine to coarse gravel sized moderately strong and strong rock and quartz fragments. (ALLUVIUM)		
	PX 4,00						1,1 1,1,1,2 N=5	3 4 •	0,86	3.55			Loose, dark grey (7.5YR 4/1), clayey silty fine to coarse SAND. (ALLUVIUM)		
5 25/04/2005	нх	0.60m at 18:00	Ø5					5	-0,24	- - - - - - - - - - - - - - - - - - -	- ф - ф - ф - о		Brownish yellow (10YR 6/8), slightly clayey silty fine to coarse SAND with some subangular fine to medium gravel sized moderately strong rock fragments. (ALLUVIUM)		
26/04/2005		1.50m at 08:00	0					,	-1,34	6,20	0 0 0 0		Dark yellowish brown (10YR 3/6), silty fine to medium SAND with much subangular fine to coarse gravel sized moderately strong and strong rock and quartz fragments. (ALLUVIUM)		
,							3,2 2,2,3,3 N=10	8 •	-2,24	6.65			Loose to medium dense, yellowish brown (10YR 5/8), sandy subangular fine to medium GRAVEL sized moderately strong rock and quartz fragments. (ALLUVIUM)		
99 1.)5 					T2101 T2101 T2101		7.60			Yellowish brown (10YR 5/8), slightly sandy subangular medium to coarse GRAVEL with some cobble sized, moderately decomposed, meta-sandstone and occasional quartz fragments. (ALLUVIUM)		
0			30				3,9 11,11,14,18 N=54	9 10 11	-4.14 -4.64	9,00	9	V	Extremely weak, brownish yellow (10YR 6/8), completely decomposed, meta-SANDSTONE. (Very silty fine SAND) Extremely weak, dark yellowish brown, dappled grey (10YR 3/6), completely decomposed, meta-CONGLOMERATE / meta-SILTSTONE.		
• SMAL		BED SAMPL		WATER S				LOGGED	Y.K	. Lee			IARKS ater sample was taken at a depth of 14.15m.		
SPT L U76 U	INER SAN		LE I	STANDAR STANDAR PERMEAN	PE RD PEN BILITY	ETRATI TEST		DATE	27/	04/2009 n Lo	5				
4	ER SAMPL		II V	IMPRESS IN-SITU V PACKER	ANE S		0472.0	DATE		04/200	5				



GEOTECHNICS & CONCRETE ENGG. (H.K.) LTD. GROUND INVESTIGATION DEPARTMENT

HOLE NO. SBF/DH11

TC N307

SHEET CONTRACT NO.

OF 2

DRILLHOLE RECORD

PROJECT Construction of A Secondary Boundary Fence - Stage 1 CO-ORDINATES METHOD **Rotary Cored** WORKS ORDER NO. ASD 010414 E 826386.01 MACHINE & NO. DR129 DATE FROM 24/04/2005 TO 26/04/2005 N 841754.65 FLUSHING MEDIUM Water ORIENTATION Vertical 4.86 mPD **GROUND LEVEL** Water level (m) & Time Casing size Total core Recovery 9 Solid core Recovery 9 Drilling Progress Reduced Level Fracture Samples Description R.Q.D. Legend Grade Depth (m) Tests HX (Silty fine SAND with much subangular fine to medium coarse gravel sized moderately strong rock and qartz fragments) 12 13 Extremely weak, yellowish red (5YR 5/8), completely decomposed, meta-SILTSTONE. (Very stiff, sandy SILT) 14 Extremely weak, brownish yellow (10YR 6/8), completely decomposed, meta-SANDSTONE. (Very silty fine SAND) 4,7 9,18,26,40 N93 12.15 HX 12,60 17 Extremely weak, yellowish brown (10YR 5/8), dappled grey, completely decomposed, meta-CONGLOMERATE / meta-SILTSTONE. (Clayey silty fine to medium SAND with much subangular fine to medium gravel sized moderately strong rock and qartz fragments) -8.84 13,70 Extremely weak, brownish yellow (10YR 6/8), completely decomposed, meta-SILTSTONE. (Very stiff, sandy SILT)
Hole completed at 14.15m. 5,8 11,19,29,43 N#02 0.80m at 18:00 -9.29 - 14.15 21

SMALL DISTURBED SAMPLE
LARGE DISTURBED SAMPLE
SPT LINER SAMPLE
U76 UNDISTURBED SAMPLE
U100 UNDISTURBED SAMPLE
MAZIER SAMPLE
PISTON SAMPLE

△ WATER SAMPLE
 PIEZOMETER TIP
 STANDPIPE
 STANDARD PENETRATION TEST
 PERMEABILITY TEST
 IMPRESSION PACKER TEST

IN-SITU VANE SHEAR TEST

PACKER TEST

 LOGGED
 Y.K. Lee

 DATE
 27/04/2005

 CHECKED
 Tom Lo


 DATE
 28/04/2005


REMARKS


DEPTH SITE: CONSTRUCTION OF A SECONDARY BOUNDARY FENCE - STAGE GEOTECHNICS & CONCRETE ENGG (HK) LTD 1: ASD 010414 0.00 MTO TERM CONTRACT FOR GROUND INVESTIGATION ARCHITECTURAL SERVICES DEPARTMENT 9.50 0.5m HOLE NO.: DATE: CONTRACT NO. TC N307 24-5-2005 DH -

































CONTR	ACT	NO. C	C/85	/09				د ،					-533		W.O. NO. PW7/2/16.75
								ORIL	LHO	LE I	RECC	ORD			HOLE NOBH5
Lam	Ge	otec	hnic	s Lin	nited	ı									SHEET of 5
							_		-					-	DATE from 5.11.86 to 11.11.86
PROJEC	T B	te Inv orrow	estiga Area	tion — at Mt.	Vehici Luard	ular	Bord	ier Link	< -						
METHO	R	otary				· ·	C		DINATES			_			ROCK COREBIT T2. TNW
MACHIN	IE & N		ong \ 0-49	oar ·					_	6828 1746		3 12	7		HOLE DIA. 140mm to 114mm to 89mm
FLUSHII	NG ME	DIUM	Wa	ter			C	DRIENTA	NOITA						GROUND LEVEL 53.19 mPD
Drilling Progress	Casing depth/size	Water level/ time/ date	ster overy	Total core Recovery	Solid core Recovery	R.Q.D.	Fracture	Tests	Samples	Reduced	Depth (m.)	Legend	Grade	Zone	Description
Prog	Ca	time/ date	Rec	Tota Rec	Solid	ж.	P. c.	, <u>e</u>	San	Red	9,5	, Le	5	76	ouseliption.
5/11	Р		ВO								0.00				
											Ē	××			Medium dense, yellowish brown
45										34	1.00	×.	XW		and brown, slightly silty fine SAND, relict texture
							**				Ē	××			(Extremely weathered SANDSTONE)
				75							Ē	. ×. ×.			(Extremely wedthered SANDSTONE)
				\vdash	-			ĺ	1/2.	51.19	2.00	××			
٠.											Ē	. ×. ×			8 ° a
								ž			Ē	××			Very dense to weak, brown and
i.	i,	ł		-	1						=_3.00	.×. ×	XW		reddish brown, silty fine SAND
				100							E	××	to DW		(Extremely to distinctly weathered
*								i.			4.00	. ×. ×			SANDSTONE)
	4.53				1			į.			= 7.00	××			<u> </u>
	H			\vdash	\vdash				4	48.6	4.5	. * *.			
	"			70	6	0	*				E5.00	::::	DW		Moderately weak to moderately strong, light grey and reddish brown,
					\perp	_					5.30		nino XW		distinctly weathered SANDSTONE with
				8							E	1::::	to DW	-	layers of extremely to distinctly weathered SANDSTONE
-				100	28	1,1	6			47.2	5,90	1			
											E 6.45				Moderately strong, reddish brown
								E			E	1::::	DW		and white, distinctly weathered SANDSTONE, joints are irregular,
-				82	54	33	4				7.00	1::::			mainly closely spaced, dip sub-horizontally
					-	-			T2	45,7	F 7.45				
ki ki							_				8.00]:::::			Moderately strong to strong,
				94	82	42	5				=	::::	DW	ī	light grey and white, distinctly to
				+	++	-		1			8.45	1::::	to SW		slightly weathered fine SANDSTONE, joints are closely spaced, planner
- 1				100	0	0	*				=_9.00				with limonite staining
										43.9		1		_	
		-		65		0		1			= 3.45	1::::	DW		See sheet 2 of 5
5/11	Н		40	45	٦	u	Ĺ				10.00	<u> </u>			
		ed sample	A	Water sair							Vinale	REM	ARKS	5	
	disturbe	d sample ple	¥.	Water Lev Standard					LOGGET		1.86	1. *	: 0	ann	ot be determined
		ed sampl		Permeabil	ity 1831	×			DATE_	NA	7/20	2. 1	IR:	No	Recovery
Man.		bed samp		In titu van					CHECK		1.00				
PS Pino				shoor test					DATE_	18.1	T'90				,


CONTRA	ACT	NO. G	C/85	5/09	9						2007						W.O. NOPW7/2/16.75
· ·								ı	DRIL	LH	10	LE	RECO	ORD			HOLE NO. BH5
Lam	Ge	otecl	hnic	s l	_in	nited	ł										SHEET of 5
DDC IFO	- Si	te Inve	estigo	tion	_	Vehic	ılor	Bore	der lin	V -				-			DATE from5.11.86to11.11.8
PROJECT		rrow /											-				
METHOD	Ro	tary						(CO-OR								ROCK COREBIT T2. TNW
MACHINE	& N		ong ` -49	rear						E N		6828 1746	à	*			HOLE DIA. 140mm to 114mm to 89r
FLUSHIN			-	ter				(ORIENT	ИОПА	4		,				GROUND LEVEL 53.19 mPD
Drilling Progress	Casing depth/size	Water level/ time/ date	Water	Total core	Kecovery 7	Solid core Recovery	R.Q.D.	Fracture Index	Tests		Samples	Reduced	Depth (m.)	Legend	Grade	Zone	Description
5/11	Н		40		1					Ť			= 10.00	::::			
	*			4	0	12	0	*					11.00		DW		Moderately strong, pale brown and brownish grey, fine to medium grained, distinctly weathered quartzitic SANDSTONE, a layer of fine sandy silt at 10.35m to 10.65m,
				1	9	0	0	*		T2	2		12.00				minor schistorcity at 10.65m to 12.80m, joints are very closely spaced to shattered, rock with abundant incipient joints
		-		N	R	+	-				27	40.34	12.85 13.00 13.20	::::x	XIY		Layer of brown, silty SAND
				_ N	R						⊿.	39.95	13.20	× ×	/DW		(Extremely to distinctly weathered SANDSTONE)
				4	0	9	0	*		T2	2		<u> 1</u> 4.00				<u>1</u>
					R	+							14.70 15.00 15.15				Strong to very strong, light grey
				П	2	9	0			T2	- 1000				DW to SW		fine grained, distinctly to slightly weathered SANDSTONE, thin layers of soil at 15.00m to 15.45m and 16.00m to 16.22m, rocks are under minor
		11.20m		N	R					Ż	Ī.		- 16.00 - 16.22			I	metamorphism
	L6.72	at 19;00		7	0	þ	0	*					E 16,72				
5/11 6/11		13.25m at 7:00		9	o	82	11	*	'			35.79	17.00				·
		10.80m at		10	סס	53	0	•		T2	<u>)</u>	34.99	17.72 18.00 18.20		DW to SW		Strong, light grey and white, medium grained, distinctly to slightly weathered quartzitic SANDSTONE, joints are planner and closely spaced some recrystallized quartz crystal
6/11		19:00 16.20m		Н		-						34.57	18.62	2.0	XW		Layer of red, reddish brown.
		at 7:00		g	o	53	0						<u>1</u> 9.00		DW to	000	silty fine SAND (Extremely weathered fine SANDSTONE
				H									19.72		SW		See sheet 3 of 5
- 7/11 • Small d	N		40	L				_		*	_		F 20.00		_		*
Large di	ıslurbed	sample	Y	Water Water Standa	Level					Logo	GED	<u>K.Y.</u>	1 2000	REMA	ARKS	i	
1 U16 und	disturbe	d sample		peneti Peimei						DATE	Ε_	12.11					
Mariar 1		ed sample	V	Pieron In Iilu	vane	Uр				CHEC	CKE	85	770				8
P.S Pillon				111401 1	***					DATE	E	18.11	1.86				


CONTR				/09 S Lin	nited	ſ	C	DRILI	LHC	LE I	RECC	RD			W.O. NO. PW7/2/16.75 HOLE NO. BH5 SHEET 3 of 5 DATE from 5.11.86 to 11.11.86
PROJEC						ılar	Bord	er Link	_						DATE HOIL
METHOD MACHIN FLUSHIN	Ro E & N	otary IO. D	ong Y -49		Luard			O-ORDI	82	6828 1746	N.		4		ROCK COREBIT T2. TNW HOLE DIA. 140mm to 114mm to 89mm P to H to N GROUND LEVEL 53.19 mPD
			Wat		T.		1,	RIENTA	IION	T					GROUND LEVEL 53.19 mPD
Drilling Progress	Casing depth/size	Water level/ time/ date	Water Recovery	Total core Recovery	Solid core Recovery	R.Q.D.	Fracture	Tests	Samples	Reduced	Depth (m.)	Legend	Grade	Zone	Description
7/11	И		40	100	92	0	*				20.00	::::	DW		Moderately strong to strong, white and light grey, fine to medium grained, distinctly to slightly weathered quartzitic
		3		94	55	21	*			31.54	21.00 21.65		to SW		SANDSTONE, joints are closely spaced, minor limonite, rocks are rich in incipient joints, sheared joints at 19.45m to 19.50m
				100	95	44	*		T2		22.00 E				
7/11 8/11		12.30m at 19:00		100	100	27	*				22.65 23.00 23.32				
	24.50	21.65m at 7:00		65	10	0	*				23.80 24.00		,		, ,
	N			59	25	0	•				24.50 - 25.00	::::			Strong, light grey and white, fine to medium grained, slightly
. '				1.00	45	0	*				25.32 25.65	1			weathered quartzitic SANDSTONE, joints are closely to moderately
				98	58	28	*				26.00		SW		spaced from 21.70m to 23.20m, closely spaced from 23.20m to 37.00m joints are irregular, rough with Iron staining, dip mainly 25, 65
				100	85	0	*	ı	TNW		26.85 27:00				and sub-vertically, minor joint fault zone at 28.50m to 28.90m some recrystallized quartz crystal
•				57	63	0	*				27,45	::::			, in the second
•		18.10m at		55	0	0	*	11			28.00				
8/11 10/11		19:00 26.30m at 7:00		92	0	0	*				28,95				
10/11 • Sm•ll	disturbe	d sample	40_	Water Marin	pie.				+	 	30.00	1000000000			
\$ Large SPT II	disturbei iner samp indisturbe undisturl	elqmei t	+	Water Levi Standard penatration Permeabili Pierometer	n lest ly lest tip			ı	OGGET DATE _ CHECKI	1		KEM	ARKS	•	


am Geotechnics Limited	DRILLHOLE RECORD	W.O. NO. PW7/2/16.75 HOLE NO. BH5 SHEET 4 of 5 DATE from 5.11.86 to 11.11.86
OJECT Site Investigation — Vehicular Bor Borrow Area at Mt. Luard	CO-ORDINATES	T ====================================
THOD Rotary	E 826828	ROCK COREBIT T2. TNW
ACHINE & NO. Long Year D-49	N 841746	HOLE DIA. P to H to N
USHING MEDIUM Water	ORIENTATION I	GROUND LEVEL 53.19 mPD
Casing depth size apply the progress of the pr	Tests Samples Reduced Level Depth (m.)	Description
.0/11 40 -	30.00	
73 77 55	. E	
93 79 10	* 32.00	
	32,25	Strong, light grey and white,
g8 45 0	* 33.00	fine to medium grained, slightly weathered quartzitic SANDSTONE, joints are closely to moderately spaced from 21.70m to 23.20m,
	Sw	closely spaced from 23.20m to 37.00m, joints are irregular, rough with
91 86 0	*	iron staining, dip mainly 25, 65 and sub—vertically, minor joint fault zone at 28.50m to 28.90m some
*	34.60	recrystallized quartz crystal —
80 79 0	* TNW = 35.00	
	35.80	
1970- 100 100 40	5 - 36.00	
at	16.1 36.85	
10/11 19:00 26.25m at 7:00 82 69 0	* = 37.00 · · · · DW	Moderately strong, yellowish brown, fine to medium grained, distinctly
68 36 0	* 58.00 DW	weathered and distinctly to slightly weathered SANDSTONE some thin layers of weathered soil minor schistorcity
52 0 0	• = 5	rocks are under low-graded metamorphism
	14.1年 39.00	
100 40 18	* = 39.70 : : : SW	See sheet 5 of 5
• Small disturbed sample Water sample	- 40.00	5
Large disturbed sample Water Level	LOGGED K.Y.Kwok	


Lam	Ģe	otec	hnic	s Lir						OLE	RECO	DRD)		W.O. NO. PW7/2/16.75 HOLE NO. BH5 SHEET 5 of 5 DATE from 5.11.86 to 11.11.86
ROJEC		te Inv					Bord	er Lin	k –	*					
ETHO	R	otary		4				:O-OR	DINATE	s 26828					ROCK COREBIT T2. TNW
ACHIN	E & 1		ong Y 0-49	ear						41746					HOLE DIA. 140mm to 114mm to 89mm
LUSHII	IG ME	DIUM	Wat	er			C	RIENT	ИОПА					GROUND LEVEL 53.19 mPD	
Drilling Progress	Casing depth/size	Water level/ time/ date	Water Recovery	Total core Recovery	Solid core Recovery	R.Q.D.	Fracture	Tests	Samples	Reduced	Depth (m.)	Legend	Grade	Zone	Description
11/11			40	100	73	14	•				40.00		SW		Strong, light grey, fine to medium grained, slightly weathered SANDSTONE, joints are mainly planner, closely spaced, dip at 15-25', rocks with minor limonite staining,
*		2%		76	68	0					41.50 E LS 42.00	× ×	XW/		Very dense to very weak, brown and greyish brown, silty fine SAND
				90	85	0			TNW		= 42.20 =				(Extremely to distinctly weathered SANDSTONE)
×				100							43.00 43,30 - 44.00		DW to		Moderately strong to strong. light grey and brownish grey, distinctly to slightly weathered SANDSTONE, Joints are closely to
11/11	•	18.90m at 19:00		93	79	21	*	×		8.0	44.30		SW		moderately spaced, mainly planner, dlp sub-vertically, joint planner with limonite staining
		-						·			47.00				End of Investigation hole at 45.10m
											49.00				
SPT 1	disturbed ner sampl ndisturbe undisturb sample	semple	¥ 3 8 8 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Vater samp Vater Leve Handard Henetration armeabilit Hezometer Tistu vane	l Hest y lest Lip	v			LOGGE DATE _ CHECK DATE _	12.1 ED V	1.86 1.86	REM.	ARKS	i	































Appendix A

Assessment of Natural Terrain Hazard




Comparing Figure 2.5 and Section 1, the site for proposed OHL Pole meets alert criteria of natural terrain hazard.



Angular elevation of Within 50m of ground Alert Criteria natural terrain >20° sloping at >15° yes Yes Yes Yes No No No No Site B ground slope >15° A ground slope <15° ground slope <15°

Figure 2.5 Application of Alert Criteria

Comparing Figure 2.5 and Section 2, the site for proposed OHL Pole meets alert criteria of natural terrain hazard.






Figure 2.5 Application of Alert Criteria

Pole meets alert criteria of natural terrain hazard. Comparing Figure 2.5 and Section 3, the site for proposed OHL






Figure 2.5 Application of Alert Criteria

Appendix A(Cont'd)


Inventory Plan







Appendix A(Cont'd)


Features and Sections











General Views of Registered Man-made Slopes




Photo 1: General View of 2SE-B/C296




Photo 2: General View of 2SE-B/C305

Appendix B(Cont'd)

Basic Data of Slope Downloaded from SIS



BASIC INFORMATION

Location:

BORDER FENCE ROAD Adjoining Border Rd opposite DD96 Lot1811

Registration Date:

12-05-1998

Ranking Score (NPRS):

0 (EI)

Date of Formation:

post-1977

Date of Construction/

Modification:

Data Source:

EI(HyD)

Approximate Coordinates:

Easting: 826564 Northing: 841830

CONSEQUENCE-TO-LIFE CATEGORY

Facility at Crest:

Undeveloped green belt

Distance of Facility from Crest (m):

Facility at Toe:

Road/footpath with very low traffic density

Distance of Facility from Toe (m):

Consequence-to-life Category:

Remarks:

3 N/A

0

SLOPE PART

(1) Max. Height (m): 6

Length (m): 140

Average Angle (deg): 45

WALL PART

MAINTENANCE RESPONSIBILITY

(1) Sub Div.: O Government Feature Party: Lands D Agent: Lands D Land Cat.: 5b(vi) Reason Code: 62 MR Endorsement Date: 29-11-2013

DETAILS OF SLOPE / RETAINING WALL

Date of Inspection:

10-06-2014

Data Source:

EI(HyD)

N/A

Slope Part Drainage:

(1) Position: On slope

Size(mm): 300

Wall Part Drainage:

SLOPE PART

Slope Part (1)

Surface Protection (%):

Bare: 50

Vegetated: 50

Chunam: 0

Shotcrete: 0

Other Cover: 0

Material Description:

Material type: Soil

Geology: N/A

Weepholes:

Berm:

No. of Berms: N/A

Min. Berm Width (m): N/A

Size (mm): N/A

nm): N/A Spacing (m): N/A

Feature No. 2SE-B/C 296

WALL PART

N/A

SERVICES

CHECKING STATUS INFORMATION

Tagmark: 14810_0_5 Part: 0 Checking Status: No checking records Checking Certificate No.: N/A

BACKGROUND INFORMATION

GIU Cell Ref.:

2SE3B2

Map Sheet Reference (1:1000):

2SE- 3B

Aerial Photos:

51439 (1983), 51440 (1983)

Nearest Rainguage Station

(Station Number):

Sheung Shui Water Treatment Plant, Fu Tei Au Road(N34)

Data Collected On:

10-06-2014

Date of Construction, Subsequent

Modification and Demolition:

Modification: Constructed

Before: 1979 After: 1975

Modification: Modified

Before: 1983 After: 1979

Related Reports/Files or Documents:

File/Report: PWDC

Ref. No.: GC 4/1/2-3 f(34) pt III

File/Report: PWDC

Ref. No.: GC 4/1/2-3 f(34) pt III

Remarks:

N/A

Follow Up Actions:

DH-Order (To Be Confirmed with Buildings Department):

None

Advisory Letter (To Be Confirmed with Buildings Department):

LPMIS: None

ENHANCED MAINTENANCE INFORMATION

From Maintenance Department: (Last Updated Date: 26/05/2022)

STAGE 1 STUDY REPORT

Inspected On:

Weather:

District: MW

Section No:

1-1

Height(m):

Type of Toe Facility:

Road/footpath with very low traffic density

Distance from Toe(m):

2-2

Type of Crest Facility:

Undeveloped green belt

Distance from Crest(m):

Consequence Category:

Engineering Judgement:

Section No:

Type of Toe Facility:

Distance from Toe(m):

Type of Crest Facility:

Distance from Crest(m):

Consequence Category:

Engineering Judgement:

Sign of Seepage:

Criterion A satisfied:

Sign of Distress:

Criterion D satisfied:

Non-routine maintenance required:

Note:

Masonry wall/Masonry facing:

Note:

Consequence category (for critical section):

Observations:

Emergency Action Required:

Action By: N/A

ACTION TO INITIATE PREVENTIVE WORKS

Criterion A/Criterion D:

N/A

N/A

Action By:

N/A

N/A

Further Study:

Action By:

OTHER EXTERNAL ACTION

Check / repair Services:

Action By:

N/A

Non-routine Maintenance:

Action By:

PHOTO












Feature No. 2SE-B/C 296



BASIC INFORMATION

Location:

Border Fence Road

Registration Date:

12-05-1998

Ranking Score (NPRS):

0 (EI)

Date of Formation:

post-1977

Date of Construction/

Modification:

Data Source:

EI(Lands D)

Approximate Coordinates:

Easting: 826687 Northing: 841952

CONSEQUENCE-TO-LIFE CATEGORY

Facility at Crest:

Undeveloped green belt

Distance of Facility from Crest (m):

Facility at Toe:

Road/footpath with low traffic density

Distance of Facility from Toe (m): 0

Consequence-to-life Category: 3

Remarks: N/A

SLOPE PART

(2) Max. Height (m): 6

Length (m): 218

Average Angle (deg): 45

WALL PART

MAINTENANCE RESPONSIBILITY

(1) Sub Div.: 1 Mixed Feature Party: Lands D Agent: Lands D Land Cat.: 1,5b(vi),7 Reason Code: 62 MR Endorsement Date: 29-11-2013 (2) Sub Div.: 2 Party: DD96 LOT 1750RP Mixed Feature Agent: N/A Land Cat.: 1,5b(vi),7 Reason Code: 1 MR Endorsement Date: 29-11-2013 Party: DD96 LOT 1746RP Land Cat.: 1,5b(vi),7 (3) Sub Div.: 3 Mixed Feature Agent: N/A Reason Code: 1 MR Endorsement Date: 29-11-2013 (4) Sub Div.: 4 Mixed Feature Party: DD96 LOT 1745 Agent: N/A Land Cat.: 1,5b(vi),7 Reason Code: 1 MR Endorsement Date: 29-11-2013

DETAILS OF SLOPE / RETAINING WALL

Date of Inspection: 05-11-2018

Data Source: EI(Lands D)

Slope Part Drainage: N/A

Wall Part Drainage: N/A

SLOPE PART

Slope Part (1)

Surface Protection (%): Bare: 0 Vegetated: 100 Chunam: 0 Shotcrete: 0 Other Cover: 0

Material Description: Material type: Soil Geology: N/A

Berm: No. of Berms: N/A Min. Berm Width (m): N/A

Weepholes: Size (mm): N/A Spacing (m): N/A

WALL PART

N/A

SERVICES



CHECKING STATUS INFORMATION

Tagmark: 14813_1_5 Part: 1 Checking Status: No checking records Checking Certificate No.: N/A

BACKGROUND INFORMATION

GIU Cell Ref.:

2SE3B2

Map Sheet Reference (1:1000):

2SE- 3B

Aerial Photos:

51439 (1983), 51440 (1983)

Nearest Rainguage Station

(Station Number):

Sheung Shui Water Treatment Plant, Fu Tei Au Road(N34)

Data Collected On:

05-11-2018

Date of Construction, Subsequent

Modification: Constructed B

Before: 1979 After: 1975

Modification and Demolition:

Modification: Modified Before: 1983 After: 1979

Related Reports/Files or Documents:

File/Report: PWDC

Ref. No.: GC 4/1/2-3 f(34) pt III

File/Report: PWDC

Ref. No.: GC 4/1/2-3 f(34) pt III

Remarks: N/A

Follow Up Actions:

DH-Order (To Be Confirmed None with Buildings Department):

Advisory Letter (To Be Confirmed None with Buildings Department):

LPMIS: None

ENHANCED MAINTENANCE INFORMATION

From Maintenance Department: (Last Updated Date: 26/05/2022)

STAGE 1 STUDY REPORT

Inspected On:

Weather:

District: MW

Section No:

1-1

Height(m):

Type of Toe Facility:

Road/footpath with low traffic density

Distance from Toe(m):

): 0

Type of Crest Facility:

Undeveloped green belt

Distance from Crest(m):

0

Consequence Category:

Engineering Judgement:

Section No:

2-2

Type of Toe Facility:

Distance from Toe(m):

Type of Crest Facility:

Distance from Crest(m):

Consequence Category:

Engineering Judgement:

Sign of Seepage:

Criterion A satisfied:

Sign of Distress:

Criterion D satisfied:

Non-routine maintenance required:

Note:

Masonry wall/Masonry facing:

Note:

Consequence category (for critical section):

Observations:

N/A

Emergency Action Required:

Action By:

N/A

ACTION TO INITIATE PREVENTIVE WORKS

Criterion A/Criterion D:

N/A

N/A

Action By:

N/A

Further Study:

Action By:

OTHER EXTERNAL ACTION

Check / repair Services:

Action By:


N/A

Non-routine Maintenance:


Action By:



<u>PHOTO</u>










Feature No. 2SE-B/C 305



Appendix B(Cont'd)

Slope Maintenance Responsibility Report Downloaded from SMRIS

Slope Maintenance Responsibility Report

(2SE-B/C296)



List of Slope Maintenance Responsibility Area(s)

1	2SE-B/C296		Sub-Division	Not Applicable
	Location	ADJOINING BORDER ROAD OPPOSITE DD96 LOT 1811		
	Responsible Lot/Party	Lands Department	Maintenance Agent	Lands Department
	Remarks	For enquiries about the maintenance of this slope / sub-division of the slope, please contact the		
		Maintenance Agent directly.		


- End of Report -

Notes:

- (i) The location plan in Annex is for identification purposes of slope(s) only.
- (ii) The slope(s) as listed in the Slope Maintenance Responsibility Report may not be shown on the location plan in Annex.

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at http://www.slope.landsd.gov.hk/smris/disclaimer. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

Search Criteria: 2SE-B/C296



Slope(s) Maintained by Government

Slope(s) Maintained by Private Party/Parties

Slope(s) Maintained by Government and Private Party/Parties



ESTATE MANAGEMENT SECTION LANDS DEPARTMENT

This Plan is **NOT TO SCALE** and intended for **IDENTIFICATION** only. All information shown on this plan **MUST** be verified by field survey.

Printed on: 01/08/2022

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at http://www.slope.landsd.gov.hk/smris/disclaimer. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

Search Criteria: 2SE-B/C296

Slope Maintenance Responsibility Report

(2SE-B/C305)



List of Slope Maintenance Responsibility Area(s)

1	2SE-B/C305		Sub-Division	1
	Location	ADJOINING BORDER ROAD & WITHIN DD96 LOT 1750RP, 1746RP & 1745 NEAR SPOT LEVEL 11.2		
	Responsible Lot/Party	Lands Department	Maintenance Agent	Lands Department
	Remarks	For enquiries about the maintenance of this slope / sub-division of the slope, please contact the Maintenance Agent directly.		


- End of Report -

Notes:

- (i) The location plan in Annex is for identification purposes of slope(s) only.
- (ii) The slope(s) as listed in the Slope Maintenance Responsibility Report may not be shown on the location plan in Annex.

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at http://www.slope.landsd.gov.hk/smris/disclaimer. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

Search Criteria: 2SE-B/C305



Slope(s) Maintained by Government Slope(s) Maintained by Private Party/Parties Slope(s) Maintained by Government and Private Party/Parties This Plan is NOT TO SCALE



Search Criteria: 2SE-B/C305

ESTATE MANAGEMENT SECTION LANDS DEPARTMENT

This Plan is **NOT TO SCALE** and intended for **IDENTIFICATION** only. All information shown on this plan **MUST** be verified by field survey.


2

Printed on: 01/08/2022

The use of this report and plan is subject to the terms and conditions set out under the respective Disclaimers, Copyright Notice and Privacy Policy displayed on the Slope Maintenance Responsibility Information System webpage at http://www.slope.landsd.gov.hk/smris/disclaimer. The contents of this report and plan, including but not limited to all text, graphics, drawings, diagrams and compilation of data or other materials are protected by copyright. The users of this report and plan acknowledge that the Government of the Hong Kong Special Administrative Region is the owner of all copyright works contained in this report and plan. Any reproduction, adaptation, distribution, dissemination or making available of any copyright works contained in this report and plan to the public is strictly prohibited unless prior written authorization is obtained from the Lands Department.

Appendix C

Location Plan of Existing Borehole



Appendix C(Cont'd)

Measured Groundwater Record

GROUNDWATER MONITORING RECORD VIBRO (H.K.) LIMITED Drillhole No. : LMCT-BH 1 Contract No.: GE/2015/29 Date of Installation: 19/09/2017 GE/2015/29.2 Task Order No.: Pipe Top Level: +4.10 mPD Co-ordinates: Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau E 826249.35 N 841664.70 Project: Sheet 1 of 1 Piezometer Tip Level: - 4.55 mPD Buckets (If any) Depth: From 0.05m 2.55m, Spacing @ 0.50m Checked By: Y. M. Leung GROUNDWATER LEVEL (FROM TOP OF PIPE) HIGHEST BUCKET WITH ENTRAPPED WATER (if any) DATE TIME REPORTED BY REMARKS DEPTH ELEVATION (mPD) ELEVATION (mPD) DEPTH (m) (m) 22/09/2017 09:10 Y. T. Chow 1.26 +2.84 23/09/2017 10:25 Y. T. Chow +2.83 1.27 25/09/2017 10:00 Y. T. Chow 1.26 +2.84 26/09/2017 13:16 Y. T. Chow 1.28 +2.82 27/09/2017 13:20 Y. T. Chow 1.28 +2.82 28/09/2017 11:21 Y. T. Chow 1.30 +2.80 29/09/2017 14:16 Y. T. Chow 1.30 +2.80

GROUNDWATER MONITORING RECORD VIBRO (H.K.) LIMITED Drillhole No.: LMCT-BH 1 19/09/2017 GE/2015/29 Date of Installation: Contract No.: GE/2015/29.2 mPD Pipe Top Level: +4.10 Task Order No.: Co-ordinates: Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau E 826249.35 N 841664.70 Project: Sheet of Standpipe Tip Level: - 1.55 mPD Checked By: Y. M. Leung Buckets (If any) Depth: From 0.05m to 2.55m, Spacing @ 0.50m GROUNDWATER LEVEL (FROM TOP OF PIPE) HIGHEST BUCKET WITH **ENTRAPPED WATER (if any)** DATE TIME REPORTED BY REMARKS ELEVATION (mPD) DEPTH DEPTH **ELEVATION** (m) (m) 22/09/2017 09:10 Y. T. Chow 1.40 +2.70 23/09/2017 10:25 Y. T. Chow 1.41 +2.69 25/09/2017 10:00 Y. T. Chow 1.36 +2.74 26/09/2017 +2.70 13:16 Y. T. Chow 1.40 27/09/2017 13:20 Y. T. Chow 1.41 +2.69 28/09/2017 11:21 Y. T. Chow 1.42 +2.68 29/09/2017 14:16 Y. T. Chow 1.41 +2.69

GROUNDWATER MONITORING RECORD Contractor: VIBRO (H.K.) LIMITED Drillhole No. : LMCT-BH 2 Contract No. : GE/2015/29 Date of Installation: 13/10/2017 Task Order No.: GE/2015/29.2 mPD Pipe Top Level: +4.13 Co-ordinates: Ground Investigation - New Territories West Project: Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location: San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau E 826149.30 N 841498.38 Sheet 1 of Piezometer Tip Level: - 34.02 mPD Buckets (If any) Depth: From 0.08m Checked By: 2.58m, Spacing @ 0.50m Y. M. Leung GROUNDWATER LEVEL (FROM TOP OF PIPE) HIGHEST BUCKET WITH ENTRAPPED WATER (if any) DATE TIME REPORTED BY REMARKS ELEVATION (mPD) ELEVATION (mPD) DEPTH **DEPTH** (m) (m) 16/10/2017 09:40 Y. T. Chow 0.40 +3.73 17/10/2017 10:08 Y. T. Chow 0.47 +3.66 18/10/2017 11:00 Y. T. Chow 0.48 +3.65 19/10/2017 13:21 Y. T. Chow 0.48 +3.65 20/10/2017 14:16 Y. T. Chow 0.42 +3.71 21/10/2017 10:41 Y. T. Chow 0.40 +3.73 23/10/2017 09:04 Y. T. Chow 0.45 +3.68

GROUNDWATER MONITORING RECORD VIBRO (H.K.) LIMITED Drillhole No.: LMCT-BH 2 GE/2015/29 Date of Installation: 13/10/2017 Contract No.: GE/2015/29.2 Pipe Top Level: +4.13 mPD Task Order No.: Co-ordinates: Ground Investigation - New Territories West Project: Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location: San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau E 826149.30 N 841498.38 Sheet 1 of 1 Piezometer Tip Level: - 20.42 mPD Buckets (If any) Depth: From 0.08m 2.58m, Spacing @ 0.50m Checked By: Y. M. Leung GROUNDWATER LEVEL (FROM TOP OF PIPE) HIGHEST BUCKET WITH ENTRAPPED WATER (if any) DATE TIME REPORTED BY REMARKS ELEVATION (mPD) ELEVATION (mPD) DEPTH DEPTH (m) (m) 16/10/2017 09:40 Y. T. Chow 0.56 +3.57 17/10/2017 Y. T. Chow +3.50 10:08 0.63 18/10/2017 11:00 Y. T. Chow 0.60 +3.53 19/10/2017 Y. T. Chow +3.55 13:21 0.58 20/10/2017 Y. T. Chow +3.62 14:16 0.51 21/10/2017 10:41 Y. T. Chow 0.50 +3.63 23/10/2017 09:04 Y. T. Chow 0.53 +3.60

Appendix C(Cont'd)

Existing Ground Investigation Records



GE/2015/29

HOLE NO.

LMCT-BH 1

1

SHEET OF

PROJECT

Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau

CONTRACT NO.:

METHOD Rotary									CO-ORDINATES						TASK ORDER NO. GE/2015/29.2	
MACH					VB	M52		+	E 826249.35 N 841664.70						DATE: 15/09/2017 to 18/09/2017	
FLUSH	_	MED Water	IUM		Wa	ater			ORIENTATION Vertical							GROUND LEVEL + 3.95 mPD
Drilling Progress	Casing Depth/Size	Level (m) Shift start / end	Flush Returns %	TCR%	SCR%	RQD%	E	Depth of FI / Test	Tests	Samples No. Type De		Reduced 26 Level	S Depth	Legend	Grade	Description
15/09/2017	7 SW									INSPECTION 1	1.00	+2.60	- 1,35			Brown (7.5YR 5/4), mottled reddish brown, spotted white, slightly clayey silty fine to coarse SAND with some angular to subangular fine to coarse gravel sized rock fragments. (FILL)
	SW 2.00		80	46						SW	2.00	+1.95	- - - - - - - 2.00			Reddish brown (2.5YR 5/4), locally light brownish grey, angular COBBLE sized moderately decomposed Metasandstone with some angular medium to coarse grave sized rock fragments. (FILL)
	PW		80	90							3.00	+0.85	- - - - - - - - - - - - - - - - - - -			Firm, dark grey (N 4), mottled black, clayey slightly sandy SILT with occasional decayed wood pieces. (POND DEPOSIT)
								3.1	1,1,1,1 N=4	3	3.20 3.50 3.55 4.00	-0.05	4.00			Soft, brown, slightly clayey sandy SILT with occasional subrounded fine to medium gravel sized rock fragments. (ALLUVIUM)
			80	0					5.65 x 10 ⁻⁶ m/sec		5.00 5.10			000		Reddish brown (2.5YR 5/4), mottled light yellowish brown, spotted white, sandy subangular to subrounded fine to coarse GRAVEL sized quartz and rock fragments. (ALLUVIUM)
15/09/2017 16/09/2017	77	0.50m at 18:00 1.20m at 08:00		0				5.5 5.6		6	5.55 5.60 5.70	-1.65	5.60	00.0	d	Extremely weak, light grey (N 7), streaked reddish brown
16/09/2017 18/09/2017		1.21m at 18:00 1.13m at 08:00	ſ					6.0	N=9	8 🖟	6.00 6.05					and light brown, completely decomposed METASILTSTONE. (Slightly sandy SILT)
				40				8.5	🛕		7.10 8.10 8.20	-3.15	7.10 		V	Extremely weak to very weak, reddish brown (2.5YR 5/4), dappled yellow and red, occasional mottled light grey, completely decomposed METASILTSTONE. (Slightly sand SILT with some subangular fine to coarse gravel)
18/09/2017	PW 710.00	0.58m at 18:00	80	95				9.3 9.7	5,9,17,22 N=53	13	9.20 9.30 9.40 9.70 9.75	-6.05	10.00			End of Investigation Hole at 10.00m.
Disturbed sample Piston sample Disturbed sample V In-situ var Permeabil				vane eability ureme er Test	shear y test eter test t	test	LOGGED	_	S. C. L	2. A co 3. A st 4. A pi	nspectonstan andpip ezome	tion pit was excavated to 1.35m. t head permeability test was carried out from 4.10m to 5.60m. be was installed to 5.50m. ter was installed at 8.50m.				
U100 undisturbed sample Mazier sample ` Piezometer lij SPT liner sample † Groundwater					tip er Samp	otical vey						er buckets were installed in standpipe and piezometer from 0.05n lepth at 0.50m intervals below ground level.				
	Water sample								DATE		21/09/2	017	-		J2016	



CEDD GEOTECHNICAL ENGINEERING OFFICE CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

VIBRO

惠保(香港)有限公司 VIBRO (H.K.) LIMITED 新創建集團成員 Member of NWS Holdings

000	23
I	S
-	502
1	GE/C
	No.:
	tract
	Son

Contract Title: Ground Investigation - New Territories West

Task Order No.: **GE/2015/29.2**


Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

Investigation

0.00m

10.00 Kodak Color Control Patches 2 Ε Date of Photograph : 31-10-2017 LMCT-BH1 0.00 Hole No.: Box No.: Depth:

Ε





GE/2015/29

HOLE NO.

LMCT-BH 2

5

OF

CONTRACT NO.:

SHEET 1

PROJECT

METHOD Rotary							_	CO-ORDINATES							TASK ORDER NO. GE/2015/29.2		
MACHINE & NO. VBM52								'	E 826149.30 N 841498.38					38	DATE: 21/09/2017 to 10/10/2017		
FLUSHI	_		UM		Wa	ater			ORIENTATION Vertical						1	GROUND LEVEL + 3.98 mPD	
	Depth/Size	Water Level (m) Shift start / end	Flush Returns %	TCR%	SCR%	RQD%	ᇤ	Depth of FI / Test	Tests	Samples No. Type Dep	oth	# Reduced	S Depth (m)	Legend	Grade	Description	
21/09/2017 \$	SW									A NOSECTION PIT		+2.98	- - - - - - - 1.00			Brown (7.5YR 5/4), mottled reddish brown, silty sandy subangular fine to coarse GRAVEL sized rock fragments. (FILL)	
			80	36						T2101		+2.48	- - - - 1.50			Light grey (N 7), locally light brown, slightly silty angular medium to coarse GRAVEL sized rock fragments. (FILL)	
			80	90										q		Firm to stiff, dark greyish brown (10YR 4/2), spotted dark grey, clayey slightly sandy SILT with occasional subrounder fine to medium gravel sized rock fragments. (ALLUVIUM)	
21/09/2017 22/09/2017		0.10m at 18:00 0.40m at 08:00						3.0	1,1,1,1 N=4	2 2.6 3 2.6 4 3.6 2 5 3.6	70 00 05	+1.38	2.60			Soft, dark grey (N 4), spotted dark brown, clayey slightly sandy SILT. (POND DEPOSIT)	
		0.25m at		0					v	3.0	60	Wood				From 3.60m to 4.60m : No recovery.	
22/09/2017 23/09/2017	-	18:00 1.03m at 08:00		56				5.1 5.5	3,3,5,8 N=19	8 51 55 55 10 6 6 6	05 10 20 60 55	-0.62	4.60			Stiff, yellowish brown (10YR 5/4), mottled reddish brown, occasional mottled white, clayey slightly sandy SILT with occasional subrounded fine to medium gravel sized rock fragments. (ALLUVIUM)	
			80	98				1120	1	12 6.0		-2.62	- 6.60 			Extremely weak, brown (7.5YR 5/4), streaked reddish brown, completely decomposed METASILTSTONE. (Sand SILT with some subangular fine to medium gravel)	
23/09/2017 25/09/2017	SW 8.15 PW	0.22m at 18:00 0.53m at 08:00		,,				8.1	6,10,20,16 N=52	14 7. 15 8. 8.			<u>-</u> - -			Extremely weak to very weak, light reddish brown (2.5YR 7/3), spotted and mottled reddish brown, completely decomposed METASILTSTONE. (Sandy SILT with much subangular fine to medium gravel)	
25/09/2017 26/09/2017		0.27m at 18:00	60	95				9.7	9.17 x 10 ⁻⁷ m/sec	17	.60 .70						
Disturb	ed sa	at		į.	<u> </u>			enetrati			.80		Ė		ARKS		
Piston sample Split spoon sample U76 undisturbed sample U100 undisturbed sample Mazier sample Mazier sample				Permi Press Packe Acous televie	u vane shear test eability test curemeter test er Test stic or optical ewer survey meter tip loipe			DATE CHECKED	_1	S. C. Law 11/10/2017 Y. M. Leung		2. An 3. Co 8.7 4. Pie 5. Pie	in-situ nstant 0m to 1 ezomete ezomete	tion pit was excavated to 1.00m. vane shear test was carried out at 3.55m. head permeability tests were carried out from 5.10m to 6.60m an 10.20m. ers were installed at 24.40m and 38.00m. er buckets were installed in plezometers from 0.08m to 2.58m dej ntervals below ground level.			
Water s	Groundwater						ire piez					10/2017					



HOLE NO.

LMCT-BH 2

CONTRACT NO.:

GE/2015/29

SHEET 2 OF 5

PROJECT

METHOD R	totary CO-ORDII	NATES		TASK ORDER NO. GE/2015/29.2
MACHINE & NO. V	BM52 E 826149	.30	N 841498.38	DATE: 21/09/2017 to 10/10/2017
LE STERMENT PROPERTIES AND PROPERTIES AND STERMENT SHOWS AND STERMENT	Vater ORIENTA	TION	Vertical	GROUND LEVEL + 3.98 mPD
Progresss Arguer Progresss Progresss Progresss Progresss Progress	A Depth Lests	Samples	Reduced Level (m) (m) Coron Carade	
26/09/2017 0.28m 27/09/2017 at 18:00	10.15 VN=31	19 10.10	- []\[\dag{1} \] \[\dag{1} \]	See sheet 1 of 5
111 60 888 60 88 60 88 60 88 60 60 88 60 60 88 60 60 60 60 60 60 60 60 60 60 60 60 60	11.70 3.3, 5.6,7.9 12.16 N=27	20 10.60 10.60 21 11.60 11.70 22 11.80 12.15	-6.62 - 10.60	Extremely weak, brown (7.5YR 5/4), occasional spotted white, completely decomposed METASILTSTONE. (Slightly sandy SILT)
13 60 95	13.76 6.8. 12.17.25.30 14.18	24 12.60 25 13.60 26 13.70 26 13.80 27 14.10	-9.62 12.60 1 1 1 V	Extremely weak, reddish brown (2.5YR 5/4), streaked light grey, completely decomposed METASILTSTONE. (Slightly sandy SILT with occasional subangular fine to medium gravel)
60 95	15.7e 3.8, 12,19,22,33 N=86	28 14.60 29 15.60 15.70 30 15.80 31 16.10		
17 60 95		32 16.60 - 17.60 -	12.62	mottled light grey, highly decomposed METASANDSTONE. (Silty sandy subangular fine to medium GRAVEL)
18 - 0.55m PW at 28/09/2017 18.50 18:00	17.70 10.12, 14.28,32,24 N=98	34 17.80 35 18.10 18.15	- 00 0 C IV	decomposed METASANDSTONE. (Subangular fine to medium GRAVEL)
29/09/2017 HW 1.12m at 08:00 60 95	^{19,70} 16,13, 13,16,30,36	36 18.60 ° 19.60 ° 19.70 38 19.80	14.62 18.60 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0	Very weak, reddish brown (2.5YR 5/4), streaked and mottled brown, highly decomposed METASANDSTONE. (Silty sandy subangular fine to medium GRAVEL)
Disturbed sample	Standard penetration test In-situ vane shear test	LOGGED	S. C. Law	S
Piston sample	Permeability test Pressuremeter test	<u> </u>		
U76 undisturbed sample U100 undisturbed sample Mazier sample SPT liner sample	Packer Test Acoustic or optical televiewer survey Piezometer tip Standpipe Groundwater Sampling Well		11/10/2017 (. M. Leung	
Water sample	Vibrating wire piezometer Impression packer test	DATE	20/10/2017	J201617e



GE/2015/29

LMCT-BH 2 HOLE NO.

CONTRACT NO.:

SHEET 3 OF 5

PROJECT

METHOD Rotary								VI .		CO-ORDIN	ATES				TASK ORDER NO. GE/2015/29.2	
0010000			& NO.				M52		_	E 826149.30 N 841498.38						DATE: 21/09/2017 to 10/10/2017
	FLUSHING MEDIUM Water									ORIENTATION Vertical						GROUND LEVEL + 3.98 mPD
Drilling	Progress	Casing Depth/Size	11	Flush Returns %	TCR%	SCR%	RQD%	E	Depth of FI / Test	Tests	Samples No. Type Depth	Reduced 16.02	00.00 (m)	Legend	Grade	Description
21		HW		60	95					8.12. 14.18.30,32 14.18.30,32	20.50 40 20.50 41 21.60 21.70 42 21.80 43 22.16	-18.62	22.60			See sheet 2 of 5
	9/2017 9/2017		0.42m at 18:00 0.92m at 08:00	60	95				23.70 23.83 24.40	50/70mm 700/60mm (100/60mm)	44 22.60 45 23.60 46 22.70 47 23.83 48 24.60 49 24.86 49 24.86 49 24.86		22.80			Very weak to weak, light grey (N 7), streaked brown, highly decomposed METASILTSTONE. (Slightly silty subangular fine to coarse GRAVEL)
25 - - - - - - - - - - - - - - - - - - -				60	100	82	33	9.4 >20 12.5 >20	25.49 25.59		T2101				.111	Moderately strong, greyish brown, dappled brown, moderately decomposed METASILTSTONE. Joints are very closely to closely spaced, locally medium spaced, occasional slickensided planar, extremely narrow to very narrow, iron and manganese oxide stained, dipping 10° to 20°, 20° to 30°, 40° to 50°, 60° to 70° and 70° to 80°.
- 30/09	9/2017 0/2017		0.31m at 18:00 1.00m at 08:00	60	63	49	15	10.9	20.73		T2101					At 26.97m : Fractured, quartz vein up to 40mm thick, dipping 20° to 30°.
								NR	28.50		29.05	-24.52 -25.07			V	From 28.50m to 29.05m: No recovery, inferred to be completely decomposed METASILTSTONE.
- - - - - 30	Distur	hed e	ample	85	100	1			enetratio		T2101		-	REMA	RKS	
	Piston sample Split spoon sample U76 undisturbed sample U100 undisturbed sample Mazier sample SPT liner sample V In-situ vane st Permeability te Pressuremete Packer Test Acoustic or opt televiewer surv Plezometer tip Standpipe Groundwater s Groundwater s					e shear t y test eter test t optical eurvey tip er Samp ire piezo	est ding Well meter	DATE CHECKED DATE	S. C. L 11/10/2 Y. M. Le 20/10/2	017 eung						

GE/2015/29

HOLE NO. LMCT-BH 2

SHEET 4 OF 5

PROJECT

Ground Investigation - New Territories West Agreement No. CE 78/2014 (DS) Drainage Improvement Works at North District - Package B - Investigation Location : San Tin Eastern Main Channel, Lok Ma Chau Tsuen and Hang Tau

CONTRACT NO.:

METHOD CO-ORDINATES Rotary TASK ORDER NO. GE/2015/29.2 E 826149.30 MACHINE & NO. N 841498.38 VBM52 DATE: 21/09/2017 10/10/2017 to **FLUSHING MEDIUM** Water ORIENTATION Vertical **GROUND LEVEL** +3.98mPD Casing Depth/Size Level Grade (m) Shift SCR Depth (m) 正 Tests Samples Description start No. Type Dept / end HW T2|101 30.22 See sheet 3 of 5 85 100 89 43 4.5 T2101 12.0 31.63 >20 32 85 5 5 0 32.13 T2101 From 32.13m to 32.59m : No recovery, inferred to be completely decomposed METASILTSTONE. NR 18:00 03/10/2017 -28.61 32.59 32.59 32.59 0.000 NA 32.79 Moderately weak to moderately strong, reddish brown, spotted white, moderately decomposed 32.78 at 08:00 -28.80 14.2 90 31 16 85 T2101 METASANDSTONE. >20 33.20 Joints are very closely to closely spaced, locally extremely closely spaced, rough planar and rough stepped, extremely 33 2 00000 narrow to very narrow, iron and manganese oxide stained, dipping 20° to 30°, 40° to 50° and 50° to 60°. From 32.59m to 32.78m: Moderately weak, reddish brown (2.5YR 5/4), spotted white, highly decomposed 0 65 34.00 34.10 METASANDSTONE. (Sandy subangular fine to coarse 000 34.10 GRAVEL) Very weak to weak, reddish brown (2.5YR 5/4), streaked dark greyish brown, highly decomposed
METASANDSTONE. (Silty sandy subangular fine to coarse 85 91 0 0 T2101 GRAVEL)
Moderately weak, brown (7.5YR 5/4), dappled brown, highly decomposed METASANDSTONE. (Slightly silty sandy 0.90m 04/10/2017 subangular fine to coarse GRAVEL with some subangular Extremely weak to very weak, brown, streaked black 80 95 . completely decomposed METASANDSTONE. (Silty fine to medium SAND with much subangular fine to medium 36.10 52 9 36.20 50/70mm, 36.35 90,10/5mm (100/80mm) 53 54 36.60 36.65 o. 37 55 37.10 95 9 38.10 9 38.20 20,30/65mm, 38.41 100/70mm (100/70mm) 58 38.36 0.65m at 06/10/2017 39 07/10/2017 18:00 0.90m Moderately weak to moderately strong, brown, streaked black, moderately decomposed METASILTSTONE.

Joints are very closely to closely spaced, locally extremely 200 \$ 0 NA 39.13 -35.15 39.13 at 08:00 III 13.0 80 98 T2101 21 15 000 closely spaced, occasional slickensided planar, extremely narrow to very narrow, iron and manganese oxide stained, dipping 0° to 10°, 20° to 30°, 40° to 50°, 50° to 60° and 60° Standard penetration test REMARKS Disturbed sample LOGGED S. C. Law In-situ vane shear test Piston sample Permeability test Split spoon sample Pressuremeter test Packer Test Acoustic or optica televiewer survey 11/10/2017 DATE U76 undisturbed sample U100 undisturbed sample Piezometer tip Mazier sample CHECKED Y. M. Leung Standpipe SPT liner sample Groundwater Sampling Well Water sample Vibrating wire piezometer Impression packer test DATE 20/10/2017 En Environmental Sample



GE/2015/29

HOLE NO.

LMCT-BH 2

CONTRACT NO.:

SHEET

5

OF 5

PROJECT

METHO	METHOD Rotary CO-ORDINATI						IATES					TASK ORDER NO. GE/2015/29.2			
MACHI	NE	& NO.			VB	M52		ا [E 826149.	30	N 84	1498.	38		DATE: 21/09/2017 to 10/10/2017
FLUSH			IUM		Wa	ater		-	ORIENTATION Vertica					GROUND LEVEL + 3.98 mPD	
Drilling Progress	Casing Depth/Size	Water Level (m) Shift start / end	Flush Returns %	TCR%	SCR%	RQD%	H	Depth of FI / Test	Tests	Samples No. Type Depth	Reduced So Level	Depth (m)	Legend	Grade	Description
- - - - - - - - -	HW		80	69	40	32	17.6 NR 11.6	40.16 40.65 41.08		T2101	-36.18 -36.67	- 40.16 	. 69 0.0	III V	From 38.90m to 39.13m: Moderately weak, brown (7.5YR 5/4), streaked black, highly decomposed METASANDSTONE. (Slightly silty sandy subangular fine to coarse GRAVEL with occasional subangular cobbles) From 39.36m to 39.99m: Weak to moderately weak, brown (7.5YR 5/4), streaked black, highly decomposed METASILTSTONE. (Silty slightly sandy subangular fine to coarse GRAVEL with occasional subangular cobbles)
- - - - - - 4 2			80	99	46	30	9.0	41.57 42.24		T2101	-37.59 -38.26	- 41.57 - 41.57 42.24	o 6	Ш	From 40.16m to 40.65m: No recovery, inferred to be completely decomposed METASILTSTONE. From 41.08m to 41.57m: Weak to moderately weak, brown (7.5YR 5/4), streaked black, highly decomposed METASILTSTONE. (Silty slightly sandy subangular fine to coarse GRAVEL with occasional subangular cobbles)
i3			80	78	15	0	NA 17.1	42.77		42.58 T2101	-38.79	- 42.77 - 43.18			From 42.24m to 42.77m: Weak to moderately weak, brown (7.5YR 5/4), streaked black, highly decomposed METASILTSTONE. (Silty slightly sandy subangular fine to coarse GRAVEL with occasional subangular cobbles) From 43.18m to 43.58m: Weak to moderately weak, brown
- - - - 07/10/2017 44 09/10/2017		0.65m at 18:00 0.95m at 08:00	-60				NA NR	43.58 143.89		59 43.86 43.89 43.91	-39.60 -39.88 39.93	- 43.58 - 43.86 - 43.91	ره م ا	V IV II	(7.5YR 5/4), streaked black, highly decomposed METASILTSTONE. (Silty slightly sandy subangular fine to coarse GRAVEL with occasional subangular cobbles) From 43.58m to 43.86m : No recovery, inferred to be completely decomposed METASILTSTONE. Weak to moderately weak, greyish brown (2.5Y 5/2),
	HW 45.34		60	160	100	94	3.1			T2101					streaked brown (7.5YR 5/4), highly decomposed METASILTSTONE. (Slightly sandy angular to subangular fine to coarse GRAVEL) Strong, grey, occasional streaked dark brown, slightly decomposed METASILTSTONE. Joints are medium spaced, locally closely spaced, occasional rough stepped, extremely narrow, iron and manganese oxide stained, dipping 10° to 20°, 40° to 50°,
- - - - - -			60	100	98	89		46.51		T2101	-42.39			111	50° to 60° and 60° to 70°. Moderately strong, brown, streaked white and dark brown,
- - - - - - - - - 09/10/2017 10/10/2017		0.28m at 18:00 1.21m at	60	100	16	0	9.4 >20 18.2 >20	1		46.83 T2101 47.50					moderately decomposed METASANDSTONE. Joints are closely to medium spaced, locally very closely spaced, rough planar and rough stepped, occasional slickensided planar, extremely narrow, iron and manganese oxide stained, dipping 20° to 30°, 30° to 40°, 40° to 50°, 50° to 60° and 60° to 70°. From 47.54m to 48.29m: With some quartz veins up to
- IB - - - -		08:00		100		66	>20	48.42 48.56		T2101					10mm thick, dipping 30° to 40°.
49 10/10/2017 - - - -	,	0.52m at 18:00	60	100	70	43	12.5	48.81 49.05		T2101	-45.07	-49.05			End of Investigation Hole at 49.05m.
Piston Split s U76 u U100 Mazie SPT li	Disturbed sample Piston sample Split spoon sample U76 undisturbed sample U100 undisturbed sample Mazier sample SPT liner sample					In-situ Perme Pressi Packe Acous televie Piezoi Stand Groun Vibrat	vane eabilit urem er Tes tic or ewer s meter pipe idwat ing w	eter test t optical survey tip	test t pling Well pometer	LOGGED DATE CHECKED DATE	S. C. I 11/10/2 Y. M. L 20/10/2	2017 eung	REMA	ARKS	



CEDD CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

VIBRO (H.K.) LIMITED 新數建集圖成員 Member of NWS Holdings 栖

Contract No.: GE/2015/29

Contract Title: Ground Investigation - New Territories West

Task Order No.: GE/2015/29.2

Agreement No. CE78/2014(DS) Drainage Improvement Works at North District - Package B - Investigation

0.00ш

00.1

hc 00.0

11.70 10 Q Ε Date of Photograph : 31-10-2017 LMCT-BH2 0.00 Hole No.: Box No.: Depth:

1.00m

0/:11

CONTO



CEDD GEOTECHNICAL ENGINEERING OFFICE CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

VIBRO

惠保(香港)有限公司 VIBRO (H.K.) LIMITED

Contract No.: GE/2015/29


Contract Title: Ground Investigation - New Territories West

Task Order No.: GE/2015/29.2

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B - Investigation

24.96 10 p Ε of Date of Photograph : 31-10-2017 LMCT-BH2 11.70 S Hole No.: Box No.: Depth:

Ε





CEDD GEOTECHNICAL ENGINEERING OFFICE CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

香港)有限公司 VIBRO (H.K.) LIMITED 新創建集團成員 Member of NWS Holdings

29	
15/	
/20	
GE	
10:	
ct	
tra	
On	

Contract Title: Ground Investigation - New Territories West

Task Order No.: **GE/2015/29.2**

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

Investigation

0.00m

COKI

27.55 10 2 E of Date of Photograph : 31-10-2017 LMCT-BH2 24.96 3 Hole No.: Box No.: Depth:

1.00m

CONTO



CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT CEDD GIVIL ENGINEERING OFFICE

VIBRO

惠保(香港)有限公司 VIBRO (H.K.) LIMITED

Contract No.: GE/2015/29

Contract Title: Ground Investigation - New Territories West

Task Order No.: **GE/2015/29.2**

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

 Investigation 0.00m

CONTO

5922

30.22 10 p Ε of Date of Photograph : 31-10-2017 LMCT-BH2 27.55 4 Hole No.: Box No.: Depth:

CONTO

30.22



EDD CIVIL ENGINEERING OFFICE CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

惠保(香港)有限公司 VIBRO (H.K.) LIMITED

29
S
/201
E E
٠:
9
_
Ct
ra 2
E
0

Contract Title: Ground Investigation - New Territories West

Task Order No.: GE/2015/29.2

Agreement No. CE78/2014(DS)
Drainage Improvement Works
at North District - Package B

- Investigation

0.00m

Hole No.: 5 of 10

Box No.: 30.22 m to (32.99)

Date of Photograph: 31-10-2017

(Bb'ZE)



CEDD CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

惠保(香港)有限公司 VIBRO (H.K.) LIMITED

Contract No.: GE/2015/29


Contract Title: Ground Investigation - New Territories West


Task Order No.: **GE/2015/29.2**

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

Investigation

0.00m







CEDD GEOTECHNICAL ENGINEERING OFFICE CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

新島建集團成員 Member of NWS Holdings

Hole No.: Contract Title: Ground Investigation - New Territories West Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B Task Order No.: GE/2015/29.2 Contract No.: GE/2015/29

- Investigation

0.00m

42.58 9 Ε ō Date of Photograph : 31-10-2017 LMCT-BH2 39,90 Box No.:





CEDD CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

VIBRO

LMCT-BH2

Hole No.: _

惠保(香港)有限公司 VIBRO (H.K.) LIMITED 新自建集圖長員 Member of NWS Holdings

29
-
Ŋ
Ξ
0
CA
Ш
5
٠:
0
Ž
to
ĕ
-
=
=
Q
\circ

Contract Title: Ground Investigation - New Territories West

Task Order No.: GE/2015/29.2

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

- Investigation

16:87

98°E+

45.34 10 2 Date of Photograph : 31-10-2017 42.58 00 Box No.: Depth:

CONTO



CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT CEDD GIVIL ENGINEERING OFFICE

惠保(香港)有限公司 VIBRO (H.K.) LIMITED 新創建集團成員 Member of NWS Holdings

Contract No.: GE/2015/29

Contract Title: Ground Investigation - New Territories West

Task Order No.: **GE/2015/29.2**

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

- Investigation 0.00m

CONTO

(48.12)10 2 Ε of Date of Photograph : 31-10-2017 LMCT-BH2 45.34 0 Hole No.: Box No.:

1.00m

(h (71.84)

CONTO



CEDD GEOTECHNICAL ENGINEERING OFFICE CIVIL ENGINEERING AND DEVELOPMENT DEPARTMENT

VIBRO

惠保(香港)有限公司 VIBRO (H.K.) LIMITED 新劇運集圖成員 Member of NWS Holdings

/29
5
/201
GE
 No.:
ıtract
ō

Contract Title: Ground Investigation - New Territories West

Task Order No.: GE/2015/29.2

Agreement No. CE78/2014(DS) **Drainage Improvement Works** at North District - Package B

Investigation

49.05 9 Ε oţ Date of Photograph : 31-10-2017 LMCT-BH2 (48.12)10 Hole No.: Box No.:

Depth:



49.05

1.00m



GEOTECHNICS & CONCRETE ENGG. (H.K.) LTD. **GROUND INVESTIGATION DEPARTMENT**

HOLE NO. SBF/DH10

SHEET DRILLHOLE RECORD CONTRACT NO. TC N307 PROJECT Construction of A Secondary Boundary Fence - Stage 1 CO-ORDINATES METHOD **Rotary Cored** WORKS ORDER NO. ASD 010414 E 826647.23 DR113 MACHINE & NO. DATE FROM 20/04/2005 TO 20/04/2005 N 841934.82 FLUSHING MEDIUM Water ORIENTATION Vertical mPD **GROUND LEVEL** 6.74 Water level (m) & Time Total core Recovery 9 Solid core Recovery 9 Drilling Progress Fracture Index Samples Description R.Q.D. Grade Tests Depth (m) НХ INSPECTION PIT Yellowish red (5YR 5/8), silty fine to medium SAND with some angular to subangular fine to coarse gravel sized moderately strong rock fragments. (FILL) 0.50 Moderately strong, reddish brown, moderately decomposed meta-SANDSTONE.

Joints are closely spaced, occasional very closely and medium spaced, rough and smooth planar, rough undulating, extremely narrow to occasional very narrow, limonite, iron and manganese oxide stained, dipping at 0% o 10% 20% o 30% and 30% o 40% 91 8.7 HX 1,26 1,26 149 0 1.60 56 From 1.71m to 1.98m : Subvertical pint. 90 T2101 1.23m at 18:00 3.71 3.03 Hole completed at 3.03m. REMARKS SMALL DISTURBED SAMPLE WATER SAMPLE LOGGED Y.K. Lee 1 LARGE DISTURBED SAMPLE PIEZOMETER TIP SPT LINER SAMPLE STANDPIPE DATE 21/04/2005 STANDARD PENETRATION TEST U76 UNDISTURBED SAMPLE PERMEABILITY TEST CHECKED Tom Lo II IMPRESSION PACKER TEST MAZIER SAMPLE

22/04/2005

DATE

IN-SITU VANE SHEAR TEST

PISTON SAMPLE

AL GEOTECHNICS & CONCRETE ENGG (HK) LTD TERM CONTRACT FOR GROUND INVESTIGATION ARCHITECTURAL SERVICES DEPARTMENT CONTRACT NO. TC N307

0.0m BOX SITE: CONSTRUCTION OF A SECONDARY BOUNDARY FENCE - STAGE W.O. NO : ASD 0104 14 DEPTH: 0.00 MTO 3,03 0.5m HOLE NO.: 24-5-2005 DHIO





GEOTECHNICS & CONCRETE ENGG. (H.K.) LTD. GROUND INVESTIGATION DEPARTMENT

HOLE NO. SBF/DH11

SHEET

OF 2

DRILLHOLE RECORD

CONTRACT NO. TC N307

						D	RILLHO	DLE REC	ORD				CONTRACT NO. TC N307		
PROJE	CT	Constru	iction of	A Second	dary I	Bound	lary Fence	- Stage 1							
METHO	DD		R	otary C	ore	d		CO-ORDI	NATES 82638	6.01			WORKS ORDER NO. ASD 010414		
MACHI	NE & 1	٧٥.	D	R129					84175				DATE FROM 24/04/2005 TO 26/04/2005		
FLUSH	ING M	EDIUM	v	/ater				ORIENTAT	TION	Ve	rtical		GROUND LEVEL 4.86 mPI		
^o Drilling Progress	Casing size	Water level (m) & Time	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced BLevel	Depth (m)	Legend	Grade	Description		
24/04/2005	PX							NSPECTION PIT	3,36	0.50 - - - - - - - - - - - - - - - - - - -			Firm, yellowish brown (10YR 5/8), dappled grey, sandy clayey SILT with some angular to subangular fine to coarse gravel sized moderately weak to moderately strong rock fragments. (FILL)		
2 24/04/2005 25/04/2005 3		Dry at 18:00 Dry at 08:00	80					1	2.86	2,00	9		Yellowish brown (10YR 5/8), clayey silty fine to coarse SAND with much angular fine to medium gravel sized rock fragments. (FILL) Greyish brown (2.5Y 5/2), clayey silty fine to coarse SAND with much angular to subangular fine to coarse gravel sized moderately strong and strong rock and quartz fragments. (ALLUVIUM)		
4	PX 4.00		7.04	Ð			1.1 1.1,1,2 N=5	3 4 • 5 7	0.86	- 3.55 - 4.00			Loose, dark grey (7.5YR 4/1), clayey silty fine to coarse SAND. (ALLUVIUM)		
5 25/04/2005	нх	0.60m at 18:00	05					6	-0,24	5,10	9 0		Brownish yellow (10YR 6/8), slightly clayey silty fine to coarse SAND with some subangular fine to medium gravel sized moderately strong rock fragments. (ALLUVIUM)		
26/04/2005 6		1.50m at 08:00	0					7	-1,34	6.20	0		Dark yellowish brown (10YR 3/6), slity fine to medium SAND with much subangular fine to coarse gravel sized moderately strong and strong rock and quartz fragments. (ALLUVIUM)		
			/ ab A				3,2 2,2,3,3 N=10	8	-2.24	- - - 6.65 - - - - 7,10	000000000000000000000000000000000000000		Loose to medium dense, yellowish brown (10YR 5/8), sandy subangular fine to medium GRAVEL sized moderately strong rock and quartz fragments. (ALLUVIUM)		
			5 5					T2101		7.60			Yellowish brown (10YR 5/8), slightly sandy subangular medium to coarse GRAVEL with some cobble sized, moderately decomposed, meta-sandstone and occasional quartz fragments. (ALLUVIUM)		
9	II II		30				3,9 11,11,14,18 N=54	9 H	-4.14 -4.64	9,00	0.0	V	Extremely weak, brownish yellow (10YR 6/8), completely decomposed, meta-SANDSTONE. (Very silty fine SAND) Extremely weak, dark yellowish brown, dappled grey (10YR 3/6), completely decomposed, meta-CONGLOMERATE / meta-SILTSTONE.		
SMALL DISTURBED SAMPLE LARGE DISTURBED SAMPLE SPT LINER SAMPLE STANOPIPE STANOPIPE STANOPIPE								LOGGED	Y.K	. Lee		REMA 1. Wat	ARKS ter sample was taken at a depth of 14.15m.		
U76 UI	BED SAMPLI	LE I	STANDAR STANDAR PERMEAE IMPRESSI	D PENI	EST CKER T	EST	DATE 27/04/2005 CHECKED Tom Lo			i					
#	V IN-SITU VANE SHEAR TEST PISTON SAMPLE PACKER TEST							DATE 28/04/2005							



GEOTECHNICS & CONCRETE ENGG. (H.K.) LTD. **GROUND INVESTIGATION DEPARTMENT**

HOLE NO. SBF/DH11

SHEET 2 OF 2


DRILLHOLE RECORD


CONTRACT NO. TC N307


000 000 e.c. (400)	Proservice					וט	KILLIIC	DLE REC	UKD				CONTRACT NO. 10 N307		
PROJE	СТ	Constru	ction of A	Second	dary E	Bound	ary Fence -								
METHO	DD		R	otary C	orec	i		CO-ORDII	NATES 82638				WORKS ORDER NO. ASD 010414		
MACH	NE & N	10.	DI	R129					84175		-		DATE FROM 24/04/2005 TO 26/04/2005		
FLUSH	ING M	EDIUM	w	ater				ORIENTAT	ION	Ver	tical		GROUND LEVEL 4.86 mP		
⁵ Drilling Progress	Casing size	Water level (m) & Time	Total core Recovery %	Solid core Recovery %	R.Q.D.	Fracture Index	Tests	Samples	Reduced Level	Depth (m)	Legend	Grade	Description		
	нх		700/					12	-5.74	10.60	9 1	V	(Silty fine SAND with much subangular fine to medium coarse gravel sized moderately strong rock and qartz fragments)		
11								13	-6,84	11,70		V	Extremely weak, yellowish red (5YR 5/8), completely decomposed, meta-SILTSTONE. (Very stiff, sandy SILT)		
12	HX 12,60						4,7 9,18,26,40 N93	15 16 •	-7,74	12.15		V	Extremely weak, brownish yellow (10YR 6/8), completely decomposed, meta-SANDSTONE. (Very silty fine SAND)		
13			90					17	-8.84	13,70	0 0	V	Extremely weak, yellowish brown (10YR 5/8), dappled grey, completely decomposed, meta-CONGLOMERATE / meta-SILTSTONE. (Clayey silty fine to medium SAND with much subangular fine to medium gravel sized moderately strong rock and qartz fragments)		
14 26/04/2005		0.80m at 18:00					5,8 11,19,29,43 N#02	18 19 20 A 8 21	-9,29	13,70		V	Extremely weak, brownish yellow (10YR 6/8), completely decomposed, meta-SILTSTONE. (Very stiff, sandy SILT) Hole completed at 14.15m.		
										andana and a manada					
SMAI							ON TEST	LOGGED Y.K. Le				REM	ARKS		
U100	U100 UNDISTURBED SAMPLE T. PERMEABILITY TEST						SECOND SECOND	DATE <u>27/04/2005</u> CHECKED <u>Tom Lo</u>					•		
Ħ	MAZIER SAMPLE V IN-SITU VANE SHEAR TEST PISTON SAMPLE PACKER TEST							DATE	28/	04/200	5				


0.00 7.10 0.0m BOX SITE : CONSTRUCTION OF W.O. NO.: ASD 010414 AL GEOTECHNICS & CONCRETE ENGG (HK) LTD 8.40 TERM CONTRACT FOR GROUND INVESTIGATION ARCHITECTURAL SERVICES DEPARTMENT A SECONDARY BOUNDARY TENCE - STAGE 0.5m 60 HOLE NO.: CONTRACTNO. TC N307 24-5-2005 DH II 9.50





















-










ONTRACT NO. GC/85/09 Lam Geotechnics Limited	DRILLHOLE RECORD	W.O. NO. PW7/2/16.75 HOLE NO. BH5 SHEET 1 of 5 DATE from 5.11.86 to 11.11.86
ROJECT Site Investigation — Vehicular Borrow Area at Mt. Luard	lorder Link —	
ETHOD- Rotary	CO-ORDINATES	ROCK COREBIT T2. TNW
ACHINE & NO. Long Year D-49	E 826828 N 841746	HOLE DIA. 140mm to 114mm to 89mm
USHING MEDIUM Water	ORIENTATION	GROUND LEVEL 53.19 mPD
Draing Progress Casing A depth/size Recovery	Tests Samples Samples Reduced Level (m.) Legend Grade	Description
75 100 4.53 P H 70 0 0 100 28 1.1 98 54 33 94 82 42 100 0 0	51.15 2.00 × × × × × × × × × × × × × × × × × ×	Medlum dense, yellowish brown and brown, slightly silty fine SAND, relict texture (Extremely weathered SANDSTONE) Very dense to weak, brown and reddish brown, silty fine SAND (Extremely to distinctly weathered SANDSTONE) Moderately weak to moderately strong, light grey and reddish brown, distinctly weathered SANDSTONE with layers of extremely to distinctly weathered SANDSTONE Moderately strong, reddish brown and white, distinctly weathered SANDSTONE Moderately strong, reddish brown and white, distinctly weathered SANDSTONE, joints are Irregular, mainly closely spaced, dip sub—horizontally Moderately strong to strong, light grey and white, distinctly to slightly weathered fine SANDSTONE, joints are closely spaced, planner with limonite staining
5/11 H 40 65 0 0	* <u>1</u> 0.00 DW	Sea sueer 7 01 2
Simil disturbed sample Large disturbed sample SPT liner sample U/6 undisturbed sample U100 undisturbed sample Mazier Level Seandard penstration test permeatishing test Permeatishing test Mazier sample Mazier sample V In situ vane sheer test	12.11.86	o Recovery


CONTR	RACT	NO. G	C/85	/09											W.O. NO. PW7/2/16.75
*							[DRIL	LHC	LE	RECO	ORD			HOLE NO. BH5
Lam	Ge	otech	nnics	s Li	mite	d							SHEET of 5		
													DATE from5.11.86to11.11.8		
PROJEC		orrow A					Boro	der Link	-						
METHO) Re	atary					(CO-ORD		*	L.				ROCK COREBIT T2. TNW
MACHIN	E & N		ong Y -49	'ear				E		6828 1746					HOLE DIA. 140mm to 114mm to 89m
FLUSHI		and a	Wat				(ORIENTA	MOIT	-			GROUND LEVEL 53.19 mPD		
Orilling Progress	Casing depth/size	Water level/ time/ date	Water Recovery	Total core Recovery	Solid core Recovery	R.Q.D.	Fracture	Tests	Samples	Reduced	Depth (m.)	Legend	Grade	Zone	Description
5/11	Н		40	IT	T				İΤ		= 10.00 = 10.35				
	¥.	_		40	12	0	*				11.00				Moderately strong, pale brown and brownish grey, fine to medium grained, distinctly weathered quartzitic SANDSTONE, a layer of
				19	0	0	*		T2		12.00		DW		fine sandy silt at 10.35m to 10.65m, minor schistorcity at 10.65m to 12.80m, Joints are very closely spaced to shattered, rock with abundant incipient joints
				NB	\perp					40.34	12.85 13.00	::::	V		
=				NR NR	11			ŀ	፟.	39.99	13.20		DW		Layer of brown, silty SAND (Extremely to distinctly weathered
									١Î		E				SANDSTÓNE)
				40	9	0			T2		<u>= 1</u> 4.00				
] 								x 1			= 14.70				
Ē				NR NR					₺.		= 15.00 = 15.15	::::			Strong to very strong, light grey fine grained, distinctly to slightly
				62	9	0			T2		E		to SW		weathered SANDSTONE, thin layers of soil at 15.00m to 15.45m and 16.00 to 16.22m, rocks are under minor
_		11.20m		NR	\pm	+		1	abla		- 16.00 - 16.22				metamorphism
5/11	16.72	at 19:00		70		0	*		1		E 16.72				
6/11	N	13.25m at 7:00		90	82	11		1		35.79	17.00				
										33.73	17.40		DW		Strong, light grey and white,
	H [®]	10.80m at		100	53	0			T2	34.99	= 18.00 = 18.20 =	0.00	to SW		medium grained, distinctly to slightly weathered quartzitic SANDSTONE, joints are planner and closely spaced some recrystallized quartz crystal
6/11 7/11		19:00 16.20m		+	+			1		34.57	E		A11	-	Layer of red, reddish brown.
		at 7:00		90	53	0	*				19.00		DW to		silty fine SAND (Extremely weathered fine SANDSTONE
7/11	N		40			-	-				19.72		SW		See sheet 3 of 5
		rd sample	A 1	Water san	npie		1		1		1 20.00				
Large	disturbe	d sample	Y	Water Le				, l	LOGGET	K.Y	Kwok	REM.	ARKS	5	74
_	iner samp	ole ed sample	* ,	Standard penetration Parmaatii				ι	DATE_	12.1	1.86				
1 U100	undistur	bed sample	À /	Piezameli	er tip			(CHECKE	6 A	200				
Marie	n sample		V :	n silu var				1	DATE_	18.1	1.86				8


Lam			•		nited	s	[ORILI	LHC	DLE I	RECC	RD		2000	W.O. NO. PW7/2/16.75 HOLE NO. BH5 SHEET 3 of 5 DATE from 5.11.86 to 11.11.86		
PROJEC	T Si	te Inv	estigat	ion – t Mt.	Vehic	ılar	Bord	ler Link	_						DATE HOIN		
METHOD	Ro	otary .	ong Y		Lugra			o-ordi	82	6 26828 41746					ROCK COREBIT T2. TNW		
		. D	-49				+	1	<u> </u>	+1/40					P to H to N		
FLUSHIN			Wat	-	Trans			RIENTA	IION		-	10 100			GROUND LEVEL 53.19 mPD		
Drilling Progress	Casing depth/size	Water level/ time/ date	Water Recovery	Total care Recovery	Solid core Recovery	R.Q.D.	Fracture Index	Tests	Samples	Reduced	Depth (m.)	Legend	Grade	Zone	Description		
7/11	N		40	100	92	٥	*	in			20.00		DW		Moderately strong to strong, white and light grey, fine to medium grained, distinctly to slightly weathered quartzitic		
-				94	55	21	*		T2	31.54	21.00 - - 21.65		to SW		SANDSTONE, joints are closely spaced, minor limonite, rocks are rich in incipient joints, sheared joints at 19.45m to 19.50m		
- 91				100	95	44	*				22.00 2 2 2 22.65				-		
- 7/11 8/11		12,30m at 19:00 21,65m		100	100		*	×			23.00				-		
_	24.50	at 7:00		65 42	10	0	*				23.80 24.00				, <u>, , , , , , , , , , , , , , , , , , </u>		
uř.	N N			59	25	0		· ·			24.50 - 25.00				Strong, light grey and white,		
	¥0			100	45	0	*				25,32				fine to medium grained, slightly weathered quartzitic SANDSTONE, joints are closely to moderately		
-				98	58	28	*			3	25.65 26.00		SW		spaced from 21.70m to 23.20m, closely spaced from 23.20m to 37.00m, joints are irregular, rough with		
				100	85	0	*		TNW		26.32				iron staining, dip mainly 25°, 65° and sub—vertically, minor joint fault zone at 28.50m to 28.90m some		
2 S				57	63	0	*				26.85 27.00 27.45				recrystallized quartz crystal		
- - 244	ū.	18.10m at		55	0	0	*	9			28.00				-		
8/11 10/11 10/11		19:00 26.30m at 7:00	40	92	0	0	*				28,95 - - - 30.00				-		
Small Large SPT II	disturbed disturbed ner samp ndisturbe	l sample	¥ 5 p	Vater Lamp Vater Leve Tandard enatration ermeabilit	(1611 1611			0	ATE_	12.11	Kwok86	REMA	ARKS	•			


ROJECT	. Sit	techi e Inves	tigati	on - \	/ehicul	ar B	order	Link	-			-			DATE from5.11.86to11.11.86
ETHOD	Bo	rrow Ar tary	ea at	Mt. L	uard			-ORDII			- 1				ROCK COREBIT T2. TNW
IACHIN	E & N		ng Ye	ear	6			E		6828 1746			HOLE DIA. 140mm to 114mm to 89m		
LUSHIN		υ-	-49 Wate	 er			OR	IENTA	пом						GROUND LEVEL 53.19 mPD
Drilling Progress	Casing depth/size	Water level/ time/ date	Recovery %	Total core Racovery %	Solid core Recovery	R.Q.D.	Index	Tests	Samples	Reduced	Depth (m.)	Legend	Grade	Zone	Description
10/11			40	•			T		1		30.00				
				73	77	55	*				31.0] :::::			
															2
				93	79	10	*				32.0	California Inchigation			· · ·
					+						32,2	5 : : : : : : :			Strong, light grey and white, fine to medium grained, slightly
				98	45	0	*				33.0	0			weathered quartzitic SANDSTONE, joints are closely to moderately
							-				= 33,5	0 : : :	sw		spaced from 21.70m to 23.20m, closely spaced from 23.20m to 37.00 joints are irregular, rough with
-			1	91	86	0	*				34.0	0 : : :			iron staining, dip mainly 25°, 65° and sub-vertically, minor joint fault
u.					\vdash			s (90)			34.6				zone at 28.50m to 28.90m some recrystallized quartz crystal
<u>-</u>				80	79	0			TNW		<u>- 3</u> 5.0	00			
											- 35.8 - 36.0				*
		18.20m		100	100	40	5				<u></u>				
10/1 -11/1	1	at 19:00 26.25n		1	\vdash			1		1.6	36.8		<u>: </u> _		
		at 7: 00		82	69	0	*				37.0	1:::	DV		Moderately strong, yellowish brown, fine to medium grained, distinctly
				68	36	0	*				= 38.0 = 38.0		DV to	٧	weathered and distinctly to slightly weathered SANDSTONE some thin lay of weathered soil minor schistorcity
				52	0	0				ļ	E		SV	'	rocks are under low—graded metamorphism
				100	40	18				1.	1.19 39. E	00	+	-	
11/1			40			-	-				= 39,		: SV		See sheet 5 of 5
e Sir	sall distor	bed sample	<u></u>	Water sar		1	T		1000	NED.	K.Y.Kwok	7	MARI	KS.	
Ø SP	T lines sai		▼	Standard penetrati	an 1+11						2.11.86				
M UI		rbed sampli urbed samp	7	Prezomet	er tip	94			CHEC	× .	A 11.86	-			


Lam		NO. G		-51		nited	ł	ı	DRII	LLI	нО	LE	RECO	DRD	W.O. NO. PW7/2/16.75 HOLE NO. BH5 SHEET 5 of 5 DATE from 5.11.86 to 11.11.86		
PROJEC	T B	ite Inv orraw	estigo Area	atic at	on – Mt.	Vehic Luard	ular	Bor	der Lir	nk –	•	7.60		3)			The state of the s
METHOD	R	otary							CO-OF	RDIN				****			ROCK COREBIT T2. TNW
MACHIN	E&I		ong 0-49		ar					N		6828 1746			HOLE DIA. 140mm to 114mm to 89mi		
FLUSHII	IG ME	DIUM	Wo	ater	r			,	ORIENT	ΓΑΊΙ	DИ			- North	GROUND LEVEL 53.19 mPD		
Drilling Progress	Casing depth/size	Water level/ time/ date	Recovery Rec						Tests		Samples	Reduced	Depth (m.)	Legend	Grade	Zone	Description
11/11			40		100	73	14	•					40.00 - - - 40.95		SW		Strong, light grey, fine to medium grained, slightly weathered SANDSTONE, joints are mainly planner, closely spaced, dip at 15"—25",
					76	68	0	٠			•		41.50 - 42.00	× ×	XW/ SW		rocks with minor limonite staining, and abundant incipient joints Very dense to very weak, brown and greyish brown, silty fine SAND
s _r					90	85	0			TI.	w		2.20 2 2 43.00				(Extremely to distinctly weathered SANDSTONE)
250					100	82	31	*					43,30		DW to SW		Moderately strong to strong, light grey and brownish grey, distinctly to slightly weathered SANDSTONE, Joints are closely to moderately spaced, mainly planner, dip sub-vertically, Joint planner
-11/11		18,90m at 19:00			93	79	21	*	. 16			8.09	44.30				with limonite staining
		je:							•				47.00			٠	End of investigation hole at 45.10m
	8												48.00				
• Small			The second second		ier sampi					1			<u>- 5</u> 0.00	REMA	RKS		
SPT 1	ndisturb		÷ A	Star peni Parn Pier	ier Level ndard atration meability ometer t itu vane ir lest	1011	ī			DAT		12.11	- 1	50000000000000000000000000000000000000	549355 7		



















Appendix D has been added


Appendix D


Drg No. 01-A and 01 G A Detail of Pole Stay Photo Illustration for the Pole and Pole Stay








Location Plan of the Pole and Pole Stay














(iii) Purpose for electricity supply

CLP received a submission requesting 60A three phase power supply from applicant Mr. Ko for CCTV, dewater system and fish-farm planned to be used at DD96 Lot 1808 located in Conservation Area (CA) and abut onto Green Blet (GB) on its southern in Lok Ma Chau.

It is inevitable that the supply network, either underground cable or overhead line to be built, must run into CA and GB.

We, CLP, carefully considered several factors such as environment, the load demanded by applicant, capacity of current network possible to meet the demand loading in designing the work plan.

The Overhead Line will be adopted for this power supply as they will have less impact on environment with less volume of excavation than underground cabling.

尊贵的閥下:

本人《高舜鹏》農地編號:DD96 地段 1808 地主·申請用電·用途如下:

- 1、安裝保安用監控。
- 2,抽水,排水(雨水及山洪)雨天時山水及路面水直沖入本地段,需及時排水。
- 3, 養魚 (需抽水過濾水,水池打氧氣。)
- 4、太陽能發电。

註:申請用電背景及目的。

- ① 做好保安,防止犯罪行為發生。
- ② 解決兩水及洪水氾濫、防止雨水及洪水對公眾、个人,安全及財物造等成損失。
- ③ 創造就業機會,配合政府政策,解決就業商位。
- ④ 支持政府環保策略、發展環保能源。

結語:

請賣公司盡快為我申請地段安裝電設施。本人申請至今3年有多,因到現在還沒有得到費 公司電設施的連接。使本人,相関人士及相関公司沒法在本地段開展合法的工作,令全部工作 停止,方法開展工作。三年多的損失巨大。懇話愛公司盡快落實工作。

申請人:高舜鵬

申請人簽名: 高

8 11 2022

	2-Year Outline Agreement No. 4600006281 for Provision of Geotechnical Consultancy Services
Project Title:	For Slope Improvement Works and Other Geotechnical Works at HKSAR & Shenzhen

COMMENTS RESPONSE SHEET

For CLP Power (Hong Kong) Limited

N/A Feature Ref .:

Installation and Associated Filling and Excavation of Land (OHL Pole & Stay Erection) Geotechnical Planning Review Report for Installation of Proposed Public Utility

Submitted on:

8 Aug 2022

Planning Department (Plan D) Commented by:

Subject:

3 Oct 2022 Provided on:

Email

Responded by:

3 Oct 2022

Letter Ref.:

Provided on: Fugro (Hong Kong) Limited

Comments/Inputs/Concerns

Ref. No.

The height of the proposed pole is 10m and pole stay is 5m above ground as shown Remark/Responses ij


on drawings (Drg. No. 01 – A and 01 G A) and photos in Appendix D in the revised GPRR 5 Clarifications of the dimensions, in particular, the height of the proposed pole and pole stay (including the above clarification on which group of the pole and stays are being referred to in P1 and P2 on p.7 of the GPRR as there ground portion) with illustration on drawings (attached) and photos ij 7

The pole and stays in P1 and P2 on P.7 are group A and group B. Location refer to Figure 2 in the GPRR.

Please provide

illustration for each of the 5 groups for clarify sake

are 5 such groups in the application.






According to the applicant, the proposed installation is for providing electricity to support the agricultural use at Lot 1808 in D.D. 96 (Plan A-2). The proposal involves erection of two pole stays (Drg. No. 01 – A and 01 G A) and photo in Appendix D. Upon erection of the OHL poles and pole stays, the pits will be backfilled and the ground will be reinstated to its no pedestrian or traffic will be obstructed after completion of the installation. The location plan is shown in Figures 1 and 2 and the sections are shown in Appendix A and the The location and disposition of the Site for erection of the OHL will minimise the filling and excavation of land and slope maintenance required for the proposed works and avoid The applicant shall minimise the disturbance to the nearby vegetation during the land The existing local road will not be obstructed. All vehicles are allowed to use the existing five poles of dimension 2m (L) x 2m (W) x 10m (H)) and ten pole stays of dimension 1.5m (L) x 1.5m (W) x 5m (H) for low voltage overhead line (OHL) cable with associated excavation of about 42.5 m2 (1.5m to 2m in length and width) and about 1.8m in depth. Each group of the installation set involves one pole stand which will be supported by original situation. All the pole stay wire are located at the outer side of the road such that vehicular access plan is Figures 1 and 2. The installation works will be carried out only encroaching onto private land. The proposed works will not cause adverse impacts on geotechnical safety, traffic, landscape, environment, sewerage, drainage and water supply. The proposed works with supporting drawings and photo illustrations (in Appendix D) roads during construction period. excavation/filling works. from 8 am to 5 pm.




COMMENTS RESPONSE SHEET



(Noted and presented in item 7 of recommendation in the GPRR (Item 7 of (Noted and presented in item 8 of recommendation in the GPRR (Item 8 of The existing local road will not be obstructed. All vehicles are allowed to use the existing vegetation during the land excavation/filling works. are allowed to use the existing roads during construction | roads during construction period. recommendation is attached)) recommendation is attached)) the disturbance to the nearby vegetation during the land The existing local road will not be obstructed. All vehicles sewerage, drainage and water supply. The applicant shall minimise safety, traffic, landscape, environment, COMMENTS RESPONSE SHEET excavation/filling works period







CAD Reference: X:WORKING:190011_051/GENEERAL PLANNING REVIEW REPORT/190011.051 FIG02 (P02) (GPRR).DWG Date & Time: 27-07-22 (11:34:09AM) Plotted By: LNGAN

Appendix A(Cont'd)

Features and Sections







Appendix D has been added

Appendix D

Drg No. 01-A and 01 G A Detail of Pole Stay Photo Illustration for the Pole and Pole Stay








INFORMATION CLASS: PROPRIETARY


ALL RIGHTS RESERVED AND REPRODUCTION IN ANY FORM MUST BE APPROVED BY CLP POWER


Location Plan of the Pole and Pole Stay














- 2. In the design of excavation and lateral support works for the pits, attention should be paid to the excavation and strutting sequence and earth load, water load and surcharge should be taken into consideration. During excavation works, sufficient water pump shall be provided to ensure that the pits are not submerged.
- 3. Proposed pit excavation works for erecting the poles will involve installation of planking with temporary strutting systems during the construction stage. Since the pit excavation works involves excavation of depth 1.8m only, excavation effects on the adjacent ground / slopes and change of ground profile should be minimal.
- 4. The proposed OHL poles and stay poles will be installed at the toe of the existing slopes. After pit excavation and installation of poles, the pits will be reinstated to its original situation. Hence, the construction effect of proposed utilities installation at the toe of slopes on the adjacent slope is insignificant.
- 5. Two registered man-made slopes are cut slopes with 6m in height at 45° slope angle. In view of failure of the man-made slopes would affect the OHL ploes at the slope toe, stability analysis is proposed to be carried out.
- 6. There are no records of landslides and boulders within the natural terrain area above the proposed pole locations. On the another hand, the locations of proposed poles & pole stays at the toe of hillside likely meet alert criteria of natural terrain hazard. Hence, natural terrain hazard study is recommended to determine the necessity mitigation works for natural terrain hazard.
- 7. The location and disposition of the Site for erection of the OHL will minimise the filling and excavation of land and slope maintenance required for the proposed works and avoid encroachment onto private land. The proposed works will not cause adverse impacts on geotechnical safety, traffic, landscape, environment, sewerage, drainage and water supply. The applicant shall minimise the disturbance to the nearby vegetation during the land excavation/filling works.
- 8. The existing local road will not be obstructed. All vehicles are allowed to use the existing roads during construction period.

References

 GEO (2007), GEO Advice Note for Planning Applications under Town Planning Ordinance (Cap.131), Geotechnical Engineering Office, Hong Kong.

and the second s



Planning Application No. A/YL-ST/618 Further Information - clarification2023/01/30 16:59

From: "AU, Ivan Hin Wah" <

To: "tpbpd@pland.gov.hk" <tpbpd@pland.gov.hk>

Cc: "ayycheung@pland.gov.hk" <ayycheung@pland.gov.hk>,

"jamesso(c

jamesso@

>, "Yik, Yau Fuk

(yk02597(

yk02597@

Sent by: prvs=3872a9e67=ivan.au@

4 Attachments



Purpose for electricity supply applicant.3.jpeg



Purpose for electricity supply applicant.1.jpeg



Purpose for electricity supply applicant.2.jpeg



FI for s.16 Planning Application AYL-ST618.pdf

Dear Sir,

Attached with the FI for the S.16 Planning Application AYL-ST618.

Best regards,

Ivan, Au Hin Wah

Senior Project Engineer
Power Systems Department – Overhead Line

T

Kum Shing Group 金城營造集團

集團通訊《城訊》KUM SHING NEWS | www.kumshing.com.hk

Disclaimer: This e-mail and its attachment(s) are confidential and may be subject to legal professional privilege and copyright. If you are not the intended addressee, you are hereby notified that any disclosure, usage, retention, dissemination is strictly prohibited. If you have received this mail in error, please contact the sender by returning this email. Thereafter, proceed to delete the entire e-mail from your computer immediately and permanently.

Town Planning Board Secretariat

15/F, North Point Government Offices 333 Java Road, North Point, Hong Kong,

<u>PlanD Planning Application No. A/YL-ST/618 Further Information</u>
I'm writing to provide the FI for the planning application No. A/YL/618 to address the following items:

- i) The duration of works for about 2 weeks after the approval of works, the installation of the poles & pole stays are 5 and 5 respectively;
- ii) The working hours is 8 a.m. to 5 p.m, working hours are daily;
- iii) The date of completion proposed on Q4 2023;
- iv) The updated Purpose for electricity supply by applicants.

Thank you for your kind assistance.

Yours Faithfully,

Ivan Au

30/Jan/2023

Encls:

a. Purpose for electricity supply applicant.

本人高舜鹏 Lot No.1808 in D.D.No.96, Yuen Long, NT 地主。申請安裝電表主要用于:

- 1,上述地段农业(養魚),本地段一边的山邊馬路比較高,本地段不能掘地做魚塘,魚池只能用木框做支架,帆布做魚池(如圖),魚池高 60cm,長 2 米,寬 1 米。由 2 个連成,連接處用 30cm 圓通相接。其中一个安裝循環進水,另一水池循環出水,組成 1 套循環活水。水循環主要用電驅動方式,整套養魚設備,需要穩定的供電設施。 所以必須要中電提供連續穩定的供電。全部設施不需掘地,填泥,平整土地。只需放在地面就可以。部分地方绿化,需要电泵泵水灌溉。下雨天排洪(山水漫过公路涌向本上述地段,下雨天需要排洪。1807號地段魚塘主已投訴多年。)
- 2,太陽能發电。是響應政府的呼籲,也回應有環保及保育知識的人士提供的建議。為綠色地球,環保出一份力。因太陽能供電是不可能連續穩定,所以必需要以中電并网,在雨天及沒有太陽能供電時,中電可以保証供電正常。
- 注:本人申請用電已3年有多,至今還沒通電,對本人及相関的公司影響非常大,也非常困擾, 沒法理解申請用電需時這麼多這麼久。香港是現代都市,正常申請用電需時3年多還沒有 著點,令人費解及不能接受。希相関部門加快審批。為環保及,綠色地球,可持續發展, 共同出一份力。


18,1,2023





=

3/2023



循環供水圖。

18,1,2023

Relevant Extracts of Town Planning Board Guidelines

The Site falls within an area partly zoned "Conservation Area" ("CA") and partly zoned "Green Belt" ("GB") on the approved San Tin OZP and also within the Wetland Buffer Area (WBA) of the Deep Bay area. The following Town Planning Board Guidelines are relevant.

Town Planning Board Guidelines for Application for Developments within Deep Bay Area under Section 16 of the Town Planning Ordinance (TPB PG-No. 12C)

All five groups fall within the WBA of the Deep Bay area under TPB PG-No. 12C. The key assessment criteria are summarised as follows:

WBA

- (a) the intention of the WBA is to protect the ecological integrity of the fish ponds and wetland within the Wetland Conservation Area (WCA) and prevent development that would have a negative off-site disturbance impact on the ecological value of fish ponds; and
- (b) within the WBA, for development or redevelopment which requires planning permission, an ecological impact assessment (EcoIA) would need to be submitted. Some local (including public utility installation of electricity mast, lamp pole, pipeline and telephone booth) and minor uses (including temporary uses) are however exempted from the requirement of EcoIA.

Town Planning Board Guidelines for Application for Development within "GB" Zone under Section 16 of the Town Planning Ordinance (TPB PG-No. 10)

Three groups are within "GB" zone. TPB PG-No. 10 is relevant and the assessment criteria are summarised as follows:

- (a) there is a general presumption against development (other than redevelopment) in "GB" zone;
- (b) an application for new development in a "GB" zone will only be considered in exceptional circumstances and must be justified with very strong planning grounds;
- (c) the design and layout of any proposed development should be compatible with the surrounding area. The development should not involve extensive clearance of existing natural vegetation, affect the existing natural landscape, or cause any adverse visual impact on the surrounding environment;
- (d) the proposed development should not overstrain the capacity of existing and planned infrastructure such as sewerage, roads and water supply. It should not adversely affect drainage or aggravate flooding in the area;
- (e) the proposed development should not be susceptible to adverse environmental effects from pollution sources nearby such as traffic noise, unless adequate mitigating measures are provided, and it should not itself be the source of pollution; and
- (f) any proposed development on a slope or hillside should not adversely affect slope stability.

Government Departments' General Comments

1. Traffic

Comments of the Chief Highway Engineer/New Territories West, Highways Department (CHE/NTW, HyD);

- the proposed access arrangement to the Site should be agreed by Transport Department;
- HyD shall not be responsible for maintenance of any access connecting the Site and Lok Ma Chau Road;
- Excavation Permit on GL should be obtained from DLO/YL, LandsD prior to commencement of excavation works; and
- adequate drainage measures should be provided to prevent surface water running from the Site to the nearby public roads and drains.

2. Environment

Comments of the Director of Environmental Protection (DEP):

- according to Appendix Ib, the applicant advised that during the construction phase, mitigation measures (such as collection of debris and rubbish on site with provision of refuse collection point with covers, covering of open storm water drains and culverts near the works area to block entrance of large debris and refuse, disposal of waste oil in accordance with the Waste Disposal Ordinance) will be implemented to handle non-point source and point source pollution. Also, the applicant will ensure compliance with relevant regulations, best practices and guidelines, such as Water Pollution Control Ordinance, Professional Persons Environmental Consultative Committee Practice Notes (ProPECC PN) 1/94 "Construction Site Drainage", etc.; and the works area would be reinstated and there would not be any discharge during operation phase;
- based on the above, DEP has no objection to the planning application; and
- no environmental complaint pertaining to the Site has been received over the past 3 years.

3. Landscaping

Comments of the Chief Town Planner/Urban Design and Landscape, Planning Department (CTP/UD&L, PlanD):

- she has no objection on the application from landscape planning perspective;
- with reference to the aerial photo of 2019, the Site is situated in an area of rural landscape character comprising fish ponds, small houses, temporary structures and scattered tree groups. According to the site photos taken in May 2022, the Site is mainly vacant with self-seeded vegetation and existing trees are observed near to some part of the Site. No detailed information on landscape resources within/adjacent to the Site and proposed landscape treatment is provided. Nevertheless, given the scale and nature

of the works, significant adverse impact on the existing landscape character and resource due to the proposed utility installation and excavation works is not anticipated;

- in consideration that there is limited space for meaningful landscaping within the Site, it is considered not necessary to impose any landscape-related condition should the application be approved by the Board; and
- her advisory comments are at **Appendix IV**.

4. Nature Conservation

Comments of the Director of Agriculture, Fisheries and Conservation (DAFC):

- the Site falls within the "CA" and "GB" zones and also within the WBA. He has no strong view on the application given that the construction time is short and no wetland habitat will be directly impacted; and
- given the applicant's claim that there is no excavation of land/pond filling as part of the application, he has no strong view on the application from a fisheries perspective. Notwithstanding, under the terms and conditions of land grant, a farmer who wishes to construct agricultural structures (e.g. greenhouses, livestock sheds, hatcheries, fish ponds, store rooms etc.) on leasehold agricultural land must apply to the Lands Department for a Letter of Approval ("LoA") for Agricultural Structures. More details can be located at the following link for reference:

https://www.afcd.gov.hk/english/agriculture/agr hk/agr hk app/agr hk app.html

5. Geotechnical Aspect

Comments of the Head of the Geotechnical Engineering Office, Civil Engineering and Development Department (H(GEO), CEDD):

- as noted in Sections 4.2 and 5.6 of the revised Geotechnical Planning Review Report (GPRR) at Appendix Ib, the applicant has clarified that the proposed development would not comprise any critical facilities (i.e. facilities under Group 1-3 in Table 2.2 of GEO Report No. 138 in Appendix A of the GPRR Report) and has concluded that Natural Terrain Hazard Study is not required for the proposed development. As such, he has no further comment on the GPRR for the captioned application; and
- his advisory comments are at **Appendix IV**.

6. Drainage

Comments of the Chief Engineer/Mainland North, Drainage Services Department (CE/MN, DSD):

he has no objection in principle to the application from drainage operation and maintenance point of view, subject to the following:

the proposed works should not affect/damage DSD's assets in the vicinity. Should such
damage occur, the applicant is requested to inform DSD immediately and carry out
remedial works so required to DSD's satisfaction; and

• since the applicant proposes filling and excavation of land on the Site, the applicant shall ensure that there will be no adverse drainage impact to the adjoining areas and drainage facilities in the vicinity.

7. Other Departments

The following government departments have no objection to or no comment on the application and their advisory comments are at **Appendix IV** where appropriate:

- (a) District Lands Officer/Yuen Long, Lands Department;
- (b) Commissioner for Transport;
- (c) Commissioner of Police;
- (d) Chief Engineer/Railway Development 2-2, Railway Development Office, Highways Department;
- (e) Project Manager (West), West Development Office, Civil Engineering and Development Department (CEDD);
- (f) Director of Fire Services;
- (g) Director of Electrical and Mechanical Services;
- (h) Chief Building Surveyor/New Territories West, Buildings Department;
- (i) Chief Engineer/Construction, Water Supplies Department; and
- (j) District Officer (Yuen Long).

Recommended Advisory Clauses

- (a) To note the comments of the District Lands Officer/Yuen Long, Lands Department (DLO/YL, LandsD) that the applicant has to apply for excavation permit(s) before commencement of works. However, there is no guarantee at this stage that the excavation permit(s) would be approved. Such application will be dealt with by LandsD acting in the capacity of the landlord at the discretion of LandsD, and if it is approved under such discretion, the approval would be subject to such terms and conditions including amongst others, the payment of administrative fee as may be imposed by LandsD;
- (b) to note the comments of the Commissioner for Transport (C for T) that no vehicle is allowed to queue back to or reverse onto/from public road at any time during the construction period;
- (c) to note the comments of the Chief Highway Engineer/New Territories West, Highways Department (CHE/NTW, HyD) that HyD shall not be responsible for maintenance of any access connecting the Site and Lok Ma Chau Road. Excavation Permit on GL should be obtained from DLO/YL, LandsD prior to commencement of excavation works. Adequate drainage measures should be provided at the Site to prevent surface water running from the Site to nearby public roads and drains;
- (d) to note the comments of the Chief Engineer/Railway Development 2-2, Railway Development Office, Highways Department (CE/RD 2-2, RDO, HyD) that the Site is in close proximity to the Northern Line (NOL) Spur Line alignment which is under development by MTRCL. The applicant is required to consult MTRCL with respect to the design and construction of the proposed works, whether it would affect the NOL Spur Line. Deep foundation such as piling is not permitted at the Site unless MTRCL's agreement is sought;
- (e) to note the comments of the Director of Environmental Protection (DEP) that during construction phase, mitigation measures should be implemented to handle non-point source and point source pollution and the applicant should ensure compliance with relevant regulations, best practices and guidelines (Water Pollution Control Ordinance (WPCO), Professional Persons Environmental Consultative Committee Practice Notes (ProPECC PN) 1/94 "Construction Site Drainage", etc.); and the works area should be reinstated and there should not be any discharge during operation phase;
- (f) to note the comments of the Chief Town Planner/Urban Design and Landscape, Planning Department (CTP/UD&L, PlanD) that:
 - (i) excavation of land should be carried out away from the Tree Protection Zone and trenching of roots should be avoided. Proper tree preservation measures should be carried out to avoid damage to existing trees during excavation. The applicant shall refer to the guidelines promulgated by the Development Bureau on Tree Preservation during Construction; and
 - (ii) approval of the application does not imply approval of tree works such as pruning, transplanting and felling under lease. The applicant shall seek approval for any proposed tree works from the maintenance parties and relevant departments prior to commencement of the works;

- (g) to note the comments of the Head of the Geotechnical Engineering Office, Civil Engineering and Development Department (H(GEO), CEDD) that based on Sections 4.2 and 5.6 of the revised Geotechnical Planning Review Report (GPRR) at Appendix Ib (Encl. (b)), the applicant has clarified that the proposed development would not comprise any critical facilities (i.e. facilities under Group 1-3 in Table 2.2 of GEO Report No. 138 in Appendix A of the GPRR Report) and has concluded that Natural Terrain Hazard Study is not required for the proposed development. The applicant should refer to the latest specification and standard given in Section 6 of the General Specifications for Civil Engineering Works (2020 Edition) for backfilling of trench/pit with fine fill material, and to refer to the Guide to Trench Excavation (Shoring Support and Drainage Measures) jointly published by HyD and CEDD which provides good technical guidelines on trench excavation;
- (h) to note the comments of the Chief Engineer/Mainland North, Drainage Services Department (CE/MN, DSD) that:
 - (i) the proposed works should not affect/damage DSD's assets in the vicinity. Should such damage occur, the applicant is requested to inform DSD immediately and carry out remedial works so required to DSD's satisfaction; and
 - (ii) since the applicant proposes filling and excavation of land on the site, the applicant shall ensure that there will be no adverse drainage impact to the adjoining areas and drainage facilities in the vicinity; and
- (i) to note the comments of the Director of Electrical and Mechanical Services (DEMS) that in the interests of public safety and ensuring the continuity of electricity supply, the applicant (i.e. CLP Power Hong Kong Limited) with planning, designing, organising and supervising any activity near the underground cable or overhead line under the mentioned works under the current applicant should check all relevant cable plans (and overhead line alignment drawings, where applicable) to find out whether there is any underground cable and/or overhead line within and/or in the vicinity of the Site. The applicant should also be reminded to observe the Electricity Supply Lines (Protection) Regulation and the "Code of Practice on Working near Electricity Supply Lines" established under the Regulation when carrying out works in the vicinity of the electricity supply lines.

Appendix V of RNTPC Paper No. A/YL-ST/618B

致城市規劃委員會秘書:

專人送遞或郵遞:香港儿角渣華道 333 號北角政府合署 15 樓

傳資: 2877 0245 或 2522 8426

電郵: tpbpd@pland.gov.hk

To : Secretary, Town Planning Board

By hand or post: 15/F, North Point Government Offices, 333 Java Road, North Point, Hong Kong

By Fax: 2877 0245 or 2522 8426 By e-mail: tpbpd@pland.gov.hk

有關的規劃申讀編號 The application no. to which the comment relates A/YL-ST/618

意見評情 (如有需要· 箭另頁說明)

Details of the Comment (use separate sheet if necessary)

		946
, , ,		
		0.65 • • •
1.		

「提意見人」姓名/名稱 Name of person/company making this comment

☐ Urgent	Return Receipt Requested	☐ Sign	☐ Encrypt	☐ Mark Su	bject Restr	icted	Expar	nd persona	al&publ
	A/YL-ST/618 DD 96 S 31/05/2022 02:12	an Tin Cl	LP Conser	vation	- 15		4		
				ş — — — — — — — — — — — — — — — — — — —				×	
From:				307 To					
To:	tpbpd <tpbpd@pland.gov.hk></tpbpd@pland.gov.hk>							~	

A/YL-ST/618 CLP

File Ref:

Government Land in D.D. 96, San Tin

Site area: About 42.5sq.m

Zoning: "Conservation Area" and "Green Belt"

Applied development: Public Utility Installation / Filling and Excavation of Land

Dear TPB Members,

Objection. Failure to provide justification for excavation of government land at sensitive location.

Once again it should be incumbent upon CLP to state what the intention of the installation is. This is Government Land and Conservation zoned. Ponds on one side of the road and the other side is GB.

So why would power supply be required on this road?

Mary Mulvihill

☐ Urgent	Return Receipt Requested	☐ Sign ☐ Encrypt	☐ Mark Subject Restricted	Expand personal&publi
(2)	規劃反對書 14/09/2022 19:44			e
From: To: File Ref:	tpbpd@pland.gov.nk		· ·	ar ar
8 attachme	nts		I . Do minoraminosors.	
201d22945640	53b9.jpg3b34a6c5a3eca982.jpg	315714d4ef79b2a2.jpg	7cdb7c5c2fe2cb12.ipg	
	365 ing20ft ha25909a3746 ing-6			

本人反對元朗新田落馬洲丈量約份第96約地段的政府土地申請編號為A/YL-ST/618的規劃申請書,本人認為此規劃在此地段是不合理的,此地段為自然保育區和綠化地帶,時常會有不同的候鳥在此休息,如果當此規劃實現後,會因規劃而帶來的工程影響附近居民的日常生活,以及填土及挖土工程這對於自然保護區和綠化地帶來說,是一種極大的破壞,並且由該規劃帶來的行人,會極度影響附近生活的村民,破壞他們的日常生活,因該規劃而帶來的行人,可能會亂拋垃圾,留下沒人清潔的昂髒物品,對於附近生活的村民來說,是一種非常討厭的行為,而且,現在還有疫情,並不知道因該規劃而來的行人,是否患上新冠肺炎,如有,對附近的村民則會產生麻煩,而且附近村民有老者,有幼童,一旦患上,後果很嚴重,還有,因之前有在此地段曾被破壞,現在還要面臨因該規劃而帶來的各種負面後果,因此,本人非常反對此規劃申請,誠請將此規劃申請取消。

附上申請規劃地段圖,可見這個非法建造的場所已經侵害了政府土地,而且用來表示 征服土地的鐵網已經倒了。

















☐ Urgent	Return Receipt Requested	☐ Sign ☐ Encrypt	☐ Mark Subject Restricted	☐ Expand p	ersonal&publi
(E)	規劃反對申請書 15/09/2022 20:29			(F)	
From:					
To: File Ref:	tpbpd@pland.gov.hk				
8 attachme	nts 2012.jpg201d2294564053b9.jpg	21571444670b222 ing3	th3/4665930ca982 ing		
- -	of c.jpg20f1ba25909a3746.jpg-6			e s	

















Urgent	Return Receipt Requested	☐ Sign [_ Encrypt	☐ Mark Subject	Restricted	Expand person	al&publi
	規劃反對申请書 15/09/2022 21:15		34		z a		
From:							
To: File Ref:	трорациріана.доч.тік						
8 attachme			Ø 81. ³⁷ 1				
SW 51	-WA0012.jpgIMG-20220915-WA0		1			•	
IMG-20220915	-WA0013.jpgIMG-20220915-WA0	J009.jpgIMG	-20220915	-WA0008.jpgIMG	-20220915-\	WA0010.jpg	

















☐ Urgent	Return Receipt Requested	☐ Sign	☐ Encrypt ☐ Mark Su	bject Restricted	Expand personal&publi
	規劃反對申請書 15/09/2022 20:50		8		
From:	tohod/shiond gov.bl/		Tayl de la		
To: File Ref:	tpbpd@pland.gov.hk				
8 attachme		0010 ingl	AC 20220015 WA0004 inc	10 20220015 V	VA0008 inc
4.1	WA0006.jpgIMG-20220915-WA	73 31	a a graph	* * * * * * * * * * * * * * * * * * *	
C LULLOO 10		Jpg		, = ======	

















☐ Urgent ☐ Return Receipt Requested ☐ Sign ☐ Encrypt ☐ Mark Subject Restricted ☐ Exp	pand personal&publi
規劃反對申請書 15/09/2022 20:30	
From:	v.
To: tpbpd@pland.gov.hk	
File Ref:	
8 attachments 7cdb7c5c2fe2cb12.jpg315714d4ef79b2a2.jpg201d2294564053b9.jpg3b34a6c5a3eca982.jpg 20f1ba25909a3746.jpg1ee64f53f47ec06c.jpg-6481522ba6e18382.jpg-62c8f4a0b8d9db55.jpg	

















☐ Urgent ☐ Return Receipt Requested ☐ Sign ☐ Encrypt ☐ Mark Subject Restricted ☐ Expand personal&p	publi
規劃反對申請書 15/09/2022 20:22	
From:	
To: tpbpd@pland.gov.hk File Ref:	
8 attachments	
IMG-20220915-WA0003.jpgIMG-20220915-WA0005.jpgIMG-20220915-WA0001.jpgIMG-20220915-WA0004.jpg	
IMG-20220915-WA0006.jpgIMG-20220915-WA0007.jpgIMG-20220730-WA0012.jpgIMG-20220915-WA0002.jpg	

















Urgent	Return Receipt Requested Sign	n 🗌 Encrypt 🔲 Mark Subject I	Restricted Expand personal&publi
	規劃反對申請書 14/09/2022 20:49		∞ •
			= 5
From:	· · · · · · · · · · · · · · · · · · ·		
To:	tpbpd@pland.gov.hk		
File Ref:			
8 attachme	AND THE STATE OF T		
	WA0000.jpgIMG-20220914-WA0001.jpgI	MG-20220914-WA0002.jpgIMG-2	20220914-WA0003.jpg
IMC-20220914	WA0004 inglMG-20220914-WA0005 ingl	MG-20220914-WA0006 ipgIMG-	20220914-WA0007 ing

















☐ Urgent ☐ Return Receipt Requested ☐ Sign ☐ Encrypt ☐ Mark Subject Restricted ☐ Expand personal&publi
A/YL-ST/618 DD 96 San Tin Wetlands CLP 15/09/2022 02:47
From: To: tpbpd <tpbpd@pland.gov.hk> File Ref:</tpbpd@pland.gov.hk>
Dear TPB Members,
609 withdrawn, some minor amendments to data.
Previous objections pertinent and upheld. CLP must provide information with regard to the end use of energy supply.
Mary Mulvihill
From: To: tpbpd <tpbpd@pland.gov.hk> Date: Tuesday, 25 January 2022 2:55 AM CST Subject: A/YL-ST/609 DD 96 San Tin Wetlands CLP</tpbpd@pland.gov.hk>
A/YL-ST/609
Government Land in D.D. 96, San Tin CLP
Site area : About 42sq.m
Zoning : "Conservation Area"
Applied development: LV Cable Laving / Filling and Excavation of Land

Dear TPB Members,

What is the purpose? This is alongside the wetland ponds. The birds, flora and fauna do not need electricity. On the contrary such installations indicate development that will have a negative impact on the natural environment.

Members must question the need of this.

Mary Mulvihill